

PolaRx5TR Reference Guide

Applicable to version 5.5.0 of the Firmware





PolaRx5TR Reference Guide

2022-08-19

Applicable to version 5.5.0 of the Firmware

© Copyright 2000-2022-08-19 Septentrio NV/SA. All rights reserved.

Septentrio NV Greenhill Campus, Interleuvenlaan 15i 3001 Leuven, Belgium

http://www.septentrio.com Phone: +32 16 300 800 Fax: +32 16 221 640 Septentrio





List of Contents

	Cont	ents	/
	Scop	e	8
	List	of Acronyms	ç
1	How	То	13
	1.1	Connect to the Receiver 1.1.1 Via COM Ports 1.1.2 Via USB 1.1.3 Via a TCP/IP Port 1.1.3.1 Ethernet 1.1.3.2 WiFi 1.1.3.2.1 Receiver as WiFi Access Point 1.1.3.2.2 Receiver as WiFi Client 1.1.3.3 Ethernet-over-USB 1.1.3.4 Point-to-Point Link 1.1.4 Via a Web Browser 1.1.5 Connection Descriptors	12 12 15 15 15 16 16
	1.2	Understand the Output of the Receiver 1.2.1 Proprietary Binary Output (SBF) 1.2.2 BINEX 1.2.3 NMEA 1.2.4 RTCM and CMR	18 18 18
	1.3	Define an SBF Output Stream	20
	1.4	Define a BINEX Output Stream	21
	1.5	Save the Configuration in Non-Volatile Memory	22
	1.6	Configure the Receiver in DGPS/RTK-Base Mode	
	1.7	Configure the Receiver in DGPS/RTK-Rover Mode	25
	1.8	Use the SECORX Services	26
	1.9	Configure the Receiver in NTRIP Server Mode	27
	1.10	Configure the Receiver in NTRIP Client Mode	28
	1.11	Use the Built-In NTRIP Caster	29
	1,12	Configure an IP Server Port	31



1.13	Configure an IP Receive Port	32
1.14	Manage Power Saving Mode	33
1.15	Manage Log Sessions	34
1.16	Log SBF Files	35
1.17	Log RINEX Files	36
1.18	Log RTCM-MSM Files	37
1.19	Log BINEX Files	38
1.20	Log NMEA Files	39
1.21	Estimate the Size of the Log Files	40
1.22	Log CGGTTS Files	41
1.23	Download Log Files from the Receiver	42
1.24	Cloudit Workflow (beta) 1.24.1 Introduction 1.24.2 Server Setup 1.24.2.1 Authentication Server Setup 1.24.2.2 Resource Server Setup 1.24.3 Receiver Configuration of Cloudit 1.24.4 File Upload.	44 44 45 45
1.25	FTP Push Log files	47
1.26	Communicate with External Equipment	48
1.27	Generate a "Pulse Per Second" Signal	49
1.28	Time Tag External Events	50
1.29	Monitor the RF Spectrum	51
1.30	Use Galileo OSNMA	52
1.31	Manage Users	53
1.32	Upgrade the Receiver	54
1.33	Check the Capabilities of your Receiver	55
1.34	Check or Change the Permission File	56
Oper	ration Details	57
2.1	Channel Allocation and Signal Selection	57
2.2	Generation of Measurements	
2.3	Time Management 2.3.1 Free-Running Clock 2.3.2 Clock Steering	59
2.4	Computation of Position, Velocity, and Time (PVT Solution)	62

2



		2.4.3	RTK Positioning	63
			2.4.3.2 Floating Ambiguities (RTK-float)	
		2.4.4	Precise Point Positioning	
			2.4.4.1 PPP Seeding	
			2.4.4.2 PPP Datum Offset	
			2.4.4.3 Tide Corrections	
		2.4.5	Transition between PVT Modes	
		2.4.6	Datum Transformation	
			2.4.6.1 Transformation to Regional Datum	
			2.4.6.2 Transformation to Local Datum	65
	2.5	Anten	ına Effects	66
		2.5.1	Antenna Effects in Rover Mode	66
		2.5.2	Antenna Effects in Base Mode	
	2.6		o OSNMA	
		2.6.1	Use of OSNMA in Simulated Scenarios	68
	2.7	Receiv	ver Autonomous Integrity Monitoring (RAIM)	69
		2.7.1	Integrity Algorithm	
		2.7.2	Internal and External Reliability Levels	71
_	C		lina Defevence	72
3	Com	mand i	Line Reference	73
	3.1		nand Line Interface Outline	
		3.1.1	Command Types	74
		3.1.2	Command Line Syntax	
		3.1.3	Command Replies	
		3.1.4	Command Syntax Tables	76
	3.2	Comm	nand Definitions	79
		3.2.1	Receiver Administration	79
		3.2.2	Standby and Sleep Configuration	97
		3.2.3	User Management	
		3.2.4	Tracking and Measurement Generation	
		3.2.5	Frontend and Interference Mitigation	119
		3.2.6	Navigation Filter	
		3.2.7	Authentication	
		3.2.8	Datum Definition	155
		3.2.9	Timing and Time Management	160
		3.2.10	Time Transfer Configuration	
			Station Settings	
			General Input/Output	
		3.2.13	NTRIP Settings	196
		3.2.14	WiFi Settings	203
			NMEA Configuration	
			SBF Configuration	
			BINEX Configuration	
			RTCM v2.x Settings	
		3.2.19	RTCM v3.x Settings	234
		3.2.20	RTCM v3.x Settings	243
		3.2.20 3.2.21	RTCM v3.x Settings	243 248



		3.2.23 Cloudlt Configuration	
		3.2.24 MSS/L-Band Configuration	286
		3.2.25 Cosmos Configuration	293
		G	
4		eference	294
	4.1	SBF Outline	
		4.1.1 SBF Block Header Format	
		4.1.2 SBF Block Names and Numbers	295
		4.1.3 SBF Block Time Stamp (TOW and WNc)	296
		4.1.4 Sub-blocks	
		4.1.5 Padding Bytes	
		4.1.6 SBF Revision Number	
		4.1.7 Do-Not-Use Value	
		4.1.8 Output Rate	
		4.1.9 Satellite ID and GLONASS Frequency Number	
		4.1.10 Signal Type	
		4.1.11 Channel Numbering	
		4.1.12 Decoding of SBF Blocks	300
	4.2	SBF Block Definitions	301
	4.2	4.2.1 Measurement Blocks	
		4.2.2 Navigation Page Blocks	
		4.2.3 GPS Decoded Message Blocks	
		4.2.4 GLONASS Decoded Message Blocks	
		4.2.5 Galileo Decoded Message Blocks	
		4.2.6 BeiDou Decoded Message Blocks	
		4.2.7 QZSS Decoded Message Blocks	
		4.2.8 NavIC/IRNSS Decoded Message Blocks	365
		4.2.9 SBAS L1 Decoded Message Blocks	367
		4.2.10 GNSS Position, Velocity and Time Blocks	381
		4.2.11 Receiver Time Blocks	423
		4.2.12 External Event Blocks	
		4.2.13 Differential Correction Blocks	
		4.2.14 L-Band Demodulator Blocks	
		4.2.15 Status Blocks	
		4.2.16 Miscellaneous Blocks	
		4.2.17 Advanced Blocks	
	4.2		
	4.3	SBF Change Log	403
Α	List	f SBF Blocks	485
В	List	f BINEX Records	488
C	List	f NMEA Sentences	489
	C.1	Proprietary NMEA Sentences	490
		C.1.1 RBD : Rover-Base Direction	
		C.1.2 RBP : Rover-Base Position	
		C.1.3 RBV : Rover-Base Position	
		C.1.4 SDI : Disk Status	
		C.1.4 SDI: DISK Status	
		C.1.6 SPW: Power Status	493 493
		I I / NDX 'DACAMAR STATUS	VO.5



		C.1.8 TFM: Used RTCM Coordinate Transformation Messages	494
D	List	of CMR and RTCM Messages	495
	D.1	CMR Messages	495
	D.2	RTCM v2.x Messages	495
	D.3	RTCM v3.x Messages	495
	Inde	x of Commands	498
	Inde	x of SBF Blocks	510



Scope

This document contains reference information about the receiver firmware.

Chapter 1 provides a set of step-by-step "how-to's" to help you find your way around the receiver's commands and logs.

Chapter 2 provides some background on the main algorithms running in the receiver and on the way to configure them.


Chapter 3 contains the complete description of the user command interface.

Chapter 4 contains the complete description of the SBF format.

Typographical Conventions

- **abc** User command name. Clicking a command name redirects to the full command description.
- abc Command argument name.
- abc Command replies.
 - SBF block name or SBF field name. Clicking an SBF block name redirects to the full SBF block description.





List of Acronyms

Abbreviation Description

AGC Automatic Gain Control

API Application Program Interface

ARP Antenna Reference Point

ASCII American Standard Code for Information Interchange

ASN.1 Abstract Syntax Notation One
BeiDou BeiDou Navigation System
BGD Broadcast Group Delay

CA Coarse Acquisition

CGGTTS Common GPS GLONASS Time Transfer Standard

CMR Compact Measurement Record

COG Course Over Ground
CPU Central Processing Unit
CRC Cyclic Redundancy Check

DGPS Differential GPS

DHCP Dynamic Host Configuration Protocol

DLL Dynamically Linked Library

DNS Domain Name Server
DOP Dilution Of Precision
DVS Data Validity Status

ECEF Earth-Centered Earth-Fixed

EGNOS European Geostationary Navigation Overlay System

ENU East-North-Up

FTP File Transfer Protocol





GEO Geostationary Earth Orbiter

GLONASS Global Orbiting Navigation Satellite System

GNSS Global Navigation Satellite System

GPS Global Positioning System

GST Galileo System Time

GUI Graphical User Interface

HDOP Horizontal DOP

HERL Horizontal External Reliability Level
HMI Hazardously Misleading Information
HPCA HMI Probability Computation Algorithm

HPL Horizontal Protection Level

HS Health Status

ICD Interface Control Document

IEEE Institute of Electrical and Electronics Engineers

IERS International Earth Rotation Service

IF Intermediate Frequency
 IGP Ionospheric Grid Point
 IGS International GPS Service
 IMU Inertial Measurement Unit
 INS Inertial Navigation System

IODC Issue of Data - Clock

IODE Issue Of Data Ephemeris

IP Internet Protocol

IRNSS Indian Regional Navigational Satellite System
ITRF International Terrestrial Reference Frame
ITRS International Terrestrial Reference System

LBand L-Band Receiver

L1 L1 carrier
L2 L2 carrier
L2C L2C code

LED Light Emitting Diode LSB Least Significant Bit

MDB Minimum Detectable Bias



MIB Management Information Base

MSB Most Significant Bits

MT Message Type

NATO North Atlantic Treaty Organisation

NAV Navigation

NavIC Navigation with Indian Constellation

NAVSTAR Navigation Satellite Timing And Ranging

NMEA National Marine Electronics Association

OSNMA Open Service Navigation Message Authentication

P P(Y) code P1 P1 code P2 P2 code

PC Phase Center
PDOP Position DOP

PLL Phase Locked Loop

PPP Precise Point Positioning

PPS Pulse Per Second

PRC Pseudorange Correction
PRN Pseudo Random Noise
PVT Position, Velocity and Time
QZSS Quasi-Zenith Satellite System

RAIM Receiver Autonomous Integrity Monitoring
RINEX Receiver Independent Exchange Format

RTCA Radio Technical Commission for Aeronautics

RTCM Radio Technical Commission for Maritime Services

RTK Real-Time Kinematic

SBAS Space-Based Augmentation System

SBF Septentrio Binary Format

SIS Signal In Space

SISA Signal in Space Accuracy

SNMP Simple Network Management Protocol

SV Space Vehicle
SVID Space Vehicle ID





TDOP Time DOP

TOW Time Of Week

UDRE User Differential Range Error
UERE User Equivalent Range Error

UHF Ultra High Frequency
URA User Range Accuracy
USB Universal Serial Bus

UTC Coordinated Universal Time

VDOP Vertical DOP

VERL Vertical External Reliability Level

VPL Vertical Protection Level
VRS Virtual Reference Station

WAAS Wide Area Augmentation System WGS84 World Geodetic System 1984

WN Week Number
WNc Week number

XERL External Reliability Levels

XOR Exclusive OR

XPL Horizontal or Vertical Protection Level



Chapter 1

How To...

This chapter contains step-by-step instructions to help you with typical tasks. It will help you to familiarize yourself with the receiver commands without going into too much detail.

For a comprehensive description of the command set, refer to chapter 3. You can also click on any command or SBF block name in this manual to be redirected to the full description of that command or SBF block.

You can enter user commands in many different ways:

- Commands can be accessed graphically through menus in RxControl and in the web interface (see section 1.1.4).
- Using the Data Link program provided in the RxTools suite (or any suitable terminal emulation program), you can enter commands manually through one of the receiver input ports (see section 1.1). In this chapter, user commands are referred to by their full name for readability. When typing the command, you can always use the short mnemonic equivalent to save typing effort. For instance, instead of typing setCOMSettings, you can type scs.
- You can type commands or mnemonics in the console window of RxControl (menu Tools > Expert Console) or of the web interface (menu Admin > Expert Console).



Depending on the capabilities of your particular receiver (see section 1.33), some of the user commands, SBF blocks or communication interfaces described in this document may not be supported.



1.1 Connect to the Receiver

1.1.1 Via COM Ports

A simple way to communicate with the receiver is to connect one of its COM-ports to a COM-port of your host computer. You can use the provided COM cable for this purpose. The default COM-port settings are:

Parameter	Value		
baud rate	115200		
data bits	8		
parity	no		
stop bits	1		
flow control	none		

The baud rate can be modified at any time by using the **setCOMSettings** command.

RxControl and Data Link can communicate with the receiver over a COM-port connection: select *Serial Connection* option when opening the connection to the receiver.

1.1.2 Via USB

The Windows USB driver provided with your receiver emulates two virtual serial ports, which can be used as standard COM ports to access the receiver. The Windows USB diver can be installed through the RxTools software suite. On Linux, the standard Linux CDC-ACM driver is suitable. Most terminal emulation programs will make no distinction between virtual and native COM ports. Note that the port settings (baud rate, etc) for virtual serial ports are not relevant, and can be left in their default configuration in the terminal emulation program.

When connecting the USB cable to a Windows PC, a new drive appears in the file manager. This drive contains an installer for the USB driver. Running this installer is not needed if you have already installed the RxTools suite. A second drive is created when the receiver is configured as a USB mass-storage device, as explained in section 1.23.

1.1.3 Via a TCP/IP Port

TCP/IP connections allow remote control of the receiver and are potentially much faster than serial connections. Up to eight independent TCP/IP connections can be opened in parallel through port 28784 (the port number can be changed with the command **setIPPortSettings**).

RxControl and Data Link can communicate with remote receivers over a TCP/IP connection: select *TCP/IP Connection* option when opening the connection to the receiver.

TCP/IP connections can be made over the following interfaces.



1.1.3.1 Ethernet

Over the Ethernet interface, the receiver can be configured for dynamic or fixed IP address allocation. The default is dynamic address allocation, using the DHCP protocol. The hostname is polarx5tr-xxxxxxx, where xxxxxxx consists of the last seven digits of the serial number of the receiver.

Dynamic IP address allocation requires the availability of a DHCP server in your local network. In the absence of a DHCP server, or when a fixed IP address is desirable, it is possible to disable the DHCP client and use a fixed address. This is done using the **setIPSettings** command.

1.1.3.2 WiFi

1.1.3.2.1 Receiver as WiFi Access Point

By default, the receiver is configured in WiFi access point mode, with the SSID set to "PolaRx5TR-xxxxxxx" where xxxxxxx is the serial number. Encryption is disabled by default.

When you are connected to the receiver WiFi access point, the receiver can be reached at the fixed IP address 192.168.20.1, or with the hostname polarx5tr (depending on your network configuration, you may need to use polarx5tr.local instead).

WiFi can be turned on and off with the **setWiFiMode** command, and the access point parameters (SSID, encryption, channel number, ...) can be adjusted with the **setWiFiAccessPoint** command.

1.1.3.2.2 Receiver as WiFi Client

It is possible to configure the receiver in WiFi client mode with the **setWiFiMode** command. In client mode, the receiver will attempt to connect to a reachable access point. The access point password must be entered with the command **exeAddWiFiAccessPoint** (this must be done only once). The list of access points can be obtained with the **lstWiFiAccessPoints**, **all** command.

In client mode, the receiver gets its IP address dynamically, and its hostname is polarx5tr-xxxxxxx.

1.1.3.3 Ethernet-over-USB

When an USB cable is connected, the receiver supports Ethernet-over-USB. The IP address allocated to the Ethernet-over-USB interface is 192.168.3.1. That address cannot be changed, so that this feature is only to be used when a single receiver is connected to your computer.

By default, the receiver is not allowed to access the Internet over USB. This can be changed with the **setUSBInternetAccess** command. Note that this requires allowing Internet sharing on your computer. The procedure to do so depends on your operating system. For



example, on Windows, it involves enabling "Allow other network users to connect through this computer's Internet connection." in the properties of the adapter providing Internet access. When Internet sharing is enabled, the receiver gets its IP address from a DHCP server on your computer. Depending on your computer's routing table, it may be that it is not reachable anymore at 192.168.3.1.

1.1.3.4 Point-to-Point Link

The receiver incorporates a point-to-point protocol server, by which it can accept TCP/IP connections over a serial link.

Configuring the point-to-point server is done with the **setPointToPoint** command. For example, to set up a point-to-point communication over COM1, with the server (i.e. the receiver) having address 192.168.60.1 and the client having address 192.168.60.2, and using CHAP authentication with password "mypwd", use this command:

```
setPointToPoint, P2PP1, Server, COM1, 192.168.60.2, 192.168.60.1,
CHAP, mypwd <CR>
```

If the client is a Linux computer, make sure the password is set in the /etc/ppp/chap-secrets file. For example, the contents of that file could be as follows:

```
# Secrets for authentication using CHAP
# client server secret IP addresses
* mypwd 192.168.60.1
```

Assuming that the serial cable is connected to the first serial port of your PC, and that the receiver's COM1 port is left in its default configuration (115200 baud and no hardware flow control), the client PPP daemon can be started with the following Linux command:

```
pppd /dev/ttyS0 115200 nocrtscts local
```

After a few seconds, the PPP link is established and it is possible to access the receiver at IP address 192.168.60.1.

1.1.4 Via a Web Browser

The receiver can be controlled and configured using a web browser. The hostname or fixed IP address is defined as explained in section 1.1.3.

For example, if your receiver's hostname is polarx5tr-1234567, simply use the following URL in your preferred web browser:

http://polarx5tr-1234567

or, for a secure connection:

https://polarx5tr-1234567

The https certificate (.pem file) can be uploaded through the *Communication > Web Server/TLS* menu of the web interface.



Most user commands described in section 3.2 can be accessed graphically from the web interface. You can also go to *Admin > Expert Control > Expert Console* to manually type ASCII commands and view replies.

By default, the web interface provides unrestricted read and write access to the receiver. This can be changed, as further explained in section 1.31 of this document.

Note that a lightweight (text only) version of the web interface is available by appending **/lite** to the URL, for example:

http://polarx5tr-1234567/lite

1.1.5 Connection Descriptors

Receiver connections are identified by their connection descriptor (CD). The different connection descriptors are shown in the table below. The three rightmost columns indicate the direction (input or output or both), and whether the connection can accept user command input.

CD	Description	In	Out	Cmd
COMx	one of the serial ports	•	•	•
USBx	one of the USB-device serial ports	•	•	•
LOGx	one of the log sessions. See section 1.15		•	
IP1x	one of the TCP/IP connections	•	•	•
NTRx	one of the NTRIP connections. Input in NTRIP client mode (section 1.10), output in NTRIP server mode (section 1.9)	•	•	
IPSx	one of the IP server connections. See section 1.12	•	•	•
IPRx	one of the IP receive connections. See section 1.13	•	•	•





1.2 Understand the Output of the Receiver

The receiver outputs proprietary and standardized messages. Each proprietary message begins with a two-character identifier, which identifies the message type.

Proprietary messages	First two characters
ASCII command replies and command error notification	\$R
ASCII transmissions (e.g. periodic output of the status screen), terminated by a prompt. Two sub-types are defined: • \$TD: ASCII display generated by the receiver; • \$TE: event notification (e.g. receiver is shutting down).	\$T
Formatted information blocks (e.g. formal command description)	\$-
SNMP' binary command replies (Septentrio proprietary)	\$&
Proprietary binary data (SBF)	\$@

1.2.1 Proprietary Binary Output (SBF)

The binary messages conform to the SBF definition. The data are arranged in SBF blocks identified by block IDs. All the blocks begin with the SBF identifier \$@. Please refer to section 4 for a description of the SBF format.

The benefit of SBF is completeness. This format should be your first choice if you wish to receive detailed information from the receiver.

The list of supported SBF messages can be found in appendix A

SBF Converter, provided in the RxTools package is an intuitive GUI which allows SBF conversion into e.g. RINEX, KML, GPX or ASCII.

1.2.2 **BINEX**

The list of supported BINEX messages can be found in appendix B

Section 1.4 explains how to stream BINEX records, and section 1.19 explains how to log BINEX files on the internal disk.

1.2.3 **NMEA**

The receiver can generate a set of approved NMEA sentences, which conform to the NMEA Standard (version 3.01⁽¹⁾ and version 4.10⁽²⁾ are supported). The benefit of the NMEA format

NMEA 0183, Standard for Interfacing Marine Electronic Devices, Version 3.01, National Marine Electronics Association, 2002

⁽²⁾ NMEA 0183, Standard for Interfacing Marine Electronic Devices, Version 4.10, National Marine Electronics Association, 2012



is that it is standardized. Many electronic devices and software packages support NMEA. The drawback of NMEA is a relatively low level of detail.

NMEA output is configured with the **setNMEAOutput** command, and the NMEA version (3.01 or 4.10) is selected with the **setNMEAVersion** command.

The list of supported NMEA sentences can be found in appendix C.

1.2.4 RTCM and CMR

The receiver can operate as DGPS and/or RTK base station and output the corresponding RTCM or CMR messages. The instructions to set the receiver in base station mode can be found in section 1.6.

The list of supported RTCM and CMR messages can be found in appendix D.



1.3 Define an SBF Output Stream

As an example, this section explains how to use the command line interface to configure the receiver to output the MeasEpoch SBF block at 10 Hz, the PVTCartesian SBF block at 1 Hz, and the GPSNav block at its On-Change rate (see section 4.1.8 for more details on the SBF output rate). In this example, we will assume that these blocks must be output through the USB2 connection.

- First make sure that the USB2 connection is configured for SBF output (this is the default). In case this is not so, you should invoke: setDataInOut, USB2, , +SBF <CR>
- 2. Scheduling SBF blocks for output is done by defining so-called "SBF streams". At least 10 SBF streams can be defined by the user. A stream consists of a set of SBF blocks that need to be output at a given rate through a given connection. By default, all streams are empty, and no SBF blocks are output. For our example, we will need to use two streams. Defining these SBF streams involves the setSBFOutput command: setSBFOutput, Stream1, USB2, MeasEpoch+GPSNav, msec100 <CR> setSBFOutput, Stream2, USB2, PVTCartesian, sec1 <CR> Note that the rate specified with the setSBFOutput command (msec100 or sec1 above) only applies to the blocks that support a flexible output rate (see appendix A). The GPSNav block does not support flexible rate: it is always output at its "On-Change" rate regardless of the stream rate. For this reason, in the above example, we could equally have enabled GPSNav in Stream2.
- 3. To stop outputting SBF on a given connection, you can either redefine or empty the corresponding streams:

```
setSBFOutput, Stream1, USB2, none <CR>
setSBFOutput, Stream2, USB2, none <CR>
A second possibility is to disable all SBF messages on that connection:
setDataInOut, USB2, , -SBF <CR>
```

Note that the **exeSBFOnce** command can be used to output a set of blocks once, instead of at regular interval. This is typically used to output all currently available satellite ephemerides at once. For example, the following command instructs the receiver to output all known GPS, GLONASS, Galileo and BeiDou ephemerides over USB2:

```
exeSBFOnce, USB2, GPS+GLO+GAL+BDS <CR>
```

This is a one-time action: the requested blocks are inserted in the stream, and then the normal flow of blocks as defined with **setSBFOutput** resumes. When logging the SBF stream for post-processing, it is a good practice to request all satellite ephemerides with the **exeSBFOnce** command when starting a new log file. Make sure however not to request measurement or PVT blocks with **exeSBFOnce** when these blocks are also enabled with **setSBFOutput** as it could cause the same epoch to be duplicated in the log file. Some post-processing tools may not work properly when the same epoch is repeated twice.



1.4 Define a BINEX Output Stream

As an example, this section explains how to use the command line interface to configure the receiver to output BINEX observation records (record 0x7F-05) at a 1-second interval through the USB2 connection, together with the decoded navigation records at their "On-Change" rate.

1. First make sure that BINEX output is enabled through the USB2 connection. BINEX is enabled by default through all connections, but in case the receiver is not in its default configuration, you should invoke:

setDataInOut,USB2, ,+BINEX <CR>

2. Scheduling BINEX records for output is done by defining so-called "BINEX streams". Up to 16 BINEX streams can be defined by the user. A stream consists of a set of BINEX records that need to be output at a given rate through a given connection. By default, all streams are empty, and no BINEX records are output. For our example, we can use a single stream, defined as follows:

setBINEXOutput, Stream1, USB2, Rec7F05+Rec01Nav, sec1 <CR>
The above command defines a record interval of 1 second. Note that this interval is only applied to the observation record. Navigation records are always output at their OnChange interval. See also appendix B.

3. To stop outputting BINEX through a given connection, you can either redefine or empty the corresponding stream:

setBINEXOutput, Stream1, USB2, none <CR>



1.5 Save the Configuration in Non-Volatile Memory

The receiver configuration includes all the user-selectable parameters, such as the elevation mask, the PVT mode, the COM port settings,...

By default, the receiver starts up in its factory default configuration. The factory defaults for each of the receiver parameters are underlined for each argument of each command in section 3.2

The current receiver configuration can be checked with the **lstConfigFile** command: **lstConfigFile**, **Current <CR>**

At any time, it is possible to save the current configuration into non-volatile memory, in order to force the receiver to always start up in that configuration. To do so, the following command should be entered:

exeCopyConfigFile,Current,Boot <CR>

To revert to the default setting where the receiver starts in the default configuration, you should use:

exeCopyConfigFile,RxDefault,Boot <CR>



1.6 Configure the Receiver in DGPS/RTK-Base Mode

The receiver can generate and output DGPS and/or RTK corrections in the RTCM and CMR formats. The list of supported RTCM and CMR messages can be found in appendix D.

1.6.1 Static Base Station Mode

To configure the receiver in static base station mode, the following has to be done:

1. For accurate and repetitive absolute positioning, you must provide the accurate coordinates of the antenna reference point (ARP). The ARP usually corresponds to the center of the bottom of the antenna (see also section 2.5). For example, assuming the WGS84 position of the ARP is 50.5°N, 4°E and its altitude above the WGS84 ellipsoid is 100m, use:

```
setStaticPosGeodetic, Geodetic1, 50.5, 4, 100 <CR>
setPVTMode, Static, , Geodetic1 <CR>
```

If you are only interested in accurate determination of the base-rover baseline, with the absolute position of the rover being of lesser importance, accurate positioning of the base station is not required, and you may simply let the receiver determine its fixed position autonomously ("auto-base" mode), by typing:

```
setPVTMode, Static, , auto <CR>
```

2. For RTCM 3.x, the antenna information in message types 1007, 1008 and 1033 can be specified using the **setAntennaOffset** command, with the serial number as sixth argument, and the antenna type (called "antenna descriptor" in RTCM) as fifth argument (see also section 2.5). For instance:

```
setAntennaOffset, Main, , , , "AT2775-54SW", "5684" <CR>
```

3. Use the commands setRTCMv2Interval, setRTCMv2IntervalObs, setRTCM-v3Interval or setCMRv2Interval to specify the message interval (default is one second for most messages). For instance, to change the interval at which RTCM 3.x message type 1033 is generated to 10 seconds, type:

```
setRTCMv3Interval,RTCM1033,10 <CR>
```

- 4. Use the commands **setRTCMv2Formatting**, **setRTCMv3Formatting** or **set-CMRv2Formatting** to specify the base station ID. If you are setting up multiple base stations, make sure to select a unique ID for each of them. For instance: **setRTCMv3Formatting**, **496 <CR>**
- 5. By default, the receiver is configured to output all RTCM and CMR messages necessary for DGPS and RTK operation. If necessary, the set of output messages can be specified with the commands **setRTCMv2Output**, **setRTCMv3Output** or **setCMRv2Output**. For instance, to output RTCM3.x messages 1006, 1033 and 1074 on COM2, use: **setRTCMv3Output**, **COM2**, **RTCM1006+RTCM1033+RTCM1074 <CR>**

If you are using the RTCM3.x MSM messages (see appendix D), you can use the **setRTCMv3Formatting** command to configure the signal types that need to be



encoded in MSM.

- 6. The RTCM stream can be output through any output connection listed in section 1.1.5. For instance, to enable RTCM 3.x output through COM2, use: setDataInOut, COM2, , RTCMv3 <CR>
- 7. When sending differential corrections over a serial port, do not forget to specify the baud rate. For instance if the differential correction stream needs to be output on COM2 at 9600 baud, use:

setCOMSettings,COM2,baud9600 <CR>

To stop transmitting RTCM messages, enter the following command: setDataInOut, COM2, , none <CR>

Note that, even in static mode, the receiver computes a PVT solution to estimate the clock bias.



1.7 Configure the Receiver in DGPS/RTK-Royer Mode

The receiver computes a DGPS and/or an RTK solution when it receives the relevant differential correction messages on one of its connections. The list of supported differential correction messages can be found in appendix D.

To configure the receiver in DGPS/RTK-rover mode, the following has to be done:

- 1. Make sure that at least one of the receiver connections is receiving differential corrections. Any input connection listed in section 1.1.5 is suitable. When using a serial connection, make sure to configure the baud rate to match the baud rate of the incoming RTCM stream. For instance if the incoming RTCM stream is received through COM2 at a baud rate of 9600 baud, use:
 - setCOMSettings, COM2, baud9600 <CR>
- 2. The receiver automatically detects the format of the differential corrections (RTCM or CMR) and switches between standalone, DGPS or RTK modes according to the type of corrections it receives, provided these modes are enabled with the **setPVTMode** command (all modes are enabled by default).

Refer to sections 2.4.2 and 2.4.3 for further details on the DGPS and RTK positioning mode.



1.8 Use the SECORX Services

Your receiver is fully compatible with the SECORX services (see http://www.septentrio.com/products/correction-services/secorx) offering high-accuracy positioning without the need for a local base station.

In this section, we address the case where the primary positioning mode is RTK, and where the receiver uses the SECORX-D precise point positioning (PPP) service to continue outputting high-accuracy positions during RTK outages.

Configuring your receiver for RTK/SECORX-D positioning involves the following steps:

1. Make sure that both RTK and PPP positioning modes are enabled in your receiver. This is the default, but in case the receiver is not in its default configuration, you can enable RTK and PPP by issuing the following command:

setPVTMode,Rover,+RTK+PPP <CR>

2. RTK positions are typically expressed in a regional datum which depends on your local RTK provider. Instead, SECORX-D PPP positions relate to a recent version of the global ITRF reference frame. To avoid coordinate jumps each time the PVT engine switches between RTK and PPP modes, the regional datum used by your RTK provider must be provided to the receiver. For example, in Europe, the RTK datum will often be ETRS89, and you would need to enter the following command:

setGeodeticDatum, ETRS89 <CR>

3. Enable the automatic seeding of the PPP engine with RTK positions: setPPPAutoSeed, RTKFixed <CR>





1.9 Configure the Receiver in NTRIP Server Mode

In the example below, we show how to configure the receiver to send RTCM 3.x corrections to an NTRIP caster using the following parameters:

- NTRIP caster hostname: ntrip.example.com
- NTRIP caster port: 2101
- User name/password for basic authentication: USER / PASSWD
- Mount Point: LEUV1
- TLS: enabled and the caster is trusted by a public certification authority
- 1. Configure one of the NTRIP connections (see section 1.1.5) in server mode for sending data to the NTRIP caster. Here, we assume that the first NTRIP connection (NTR1) is free and can be used for that purpose:
 - setNTRIPSettings,NTR1,Server,ntrip.example.com,2101,USER,PASSWD,LEUV1
 <CR>
- 2. To enable TLS for NTR1, use:
 setNtripTlsSettings, NTR1, on, "" <CR>
- 3. By default, for RTCM 3.x, the receiver is configured to send message types 1004, 1006, 1012 ans 1033 at an interval of one second. This can be changed by using the **setRTCMv3Output** and **setRTCMv3Interval** commands. For instance, to change the interval of RTCM1033 to 10 seconds, use: **setRTCMv3Interval**, RTCM1033, 10 <CR>
- 4. Enable the output of RTCM 3.x corrections on the NTR1 connection: setDataInOut, NTR1, , RTCMv3 <CR>
- 5. Closing the NTRIP connection is done with the following command: setNTRIPSettings, NTR1, off <CR>

See also section 1.6 for more information on configuring the receiver as a base station.

The NTRIP server can also send data to the built-in caster, by specifying "localhost" as host-name. Refer to section 1.11 for details.



1.10 Configure the Receiver in NTRIP Client Mode

In this section, we show how to configure the receiver to receive and use RTK corrections from an NTRIP caster. In the example below, the NTRIP caster and Mount Point details are as follows:

- NTRIP caster hostname: ntrip.example.com
- NTRIP caster port: 2101
- User name/password for basic authentication: USER / PASSWD
- Mount Point: LEUV1
- TLS: enabled and the caster is trusted by a public certification authority
- 1. Configure one of the NTRIP connections (see section 1.1.5) for communication with the NTRIP caster in client mode. Here, we assume that the first NTRIP connection (NTR1) is free and can be used for that purpose:

setNTRIPSettings,NTR1,Client,ntrip.example.com,2101,USER,PASSWD,LEUV1
<CR>

2. To enable TLS for NTR1, use:
 setNtripTlsSettings, NTR1, on, "" <CR>

- 3. The receiver will automatically receive and decode the RTK corrections from the NTRIP caster and switch to RTK positioning mode, unless RTK is disabled with the **setPVTMode** command.
- 4. Closing the NTRIP connection is done with the following command: setNTRIPSettings, NTR1, off <CR>

The status of the NTRIP client connection is reported in the NTRIP client Status SBF block.



1.11 Use the Built-In NTRIP Caster

The receiver contains an NTRIP caster, which is able to broadcast local data streams originating from the receiver itself, or streams from any remote NTRIP server. The hostname or IP address of the built-in caster is as defined in section 1.1.3.

1.11.1 Broadcasting Local Streams

This section explains how to use the built-in NTRIP caster to broadcast a local stream generated by the receiver's own NTRIP server.

- 1. Define the mount point you want to use for streaming the data. For example, the following command enables the first mount point, gives it the name "MyMP", and specify that this mount point only accepts local streams:
 - setNtripCasterMountPoints, MP1, on, MyMP, No <CR>
- 2. Define the data format. For example, if the mount point defined above is meant to stream RTCM v3.x corrections, use the following command:
 - setNtripCasterMPFormat, MP1, RTCMv3 <CR>
- 3. Define the NTRIP client accounts. For example, the command below enables an NTRIP client connecting as user "u1" and with password "p1" to receive data from the first mount point:
 - setNtripCasterUsers, User1, u1, p1, MP1 <CR>
- 4. Configure the local NTRIP server to send data to the mount point, as explained in section 1.9. To have the local NTRIP server send data to the built-in caster, the hostname has to be set to "localhost". For example, to send data to the mount point "MyMP" of the caster, use:
 - setNTRIPSettings,NTR1,Server,localhost,,,,MyMP <CR>
- 5. Enable the built-in NTRIP caster: setNtripCasterSettings, on <CR>

1.11.2 Broadcasting Remote Streams

To configure the caster to broadcast a stream originating from a remote NTRIP server, follow the following steps.

- 1. Define the mount point. For example, the following command enables the first mount point, gives it the name "MyMP", and specifies the credentials that the remote NTRIP server will need to use in order to feed data to this mount point ("FeedUser" and "FeedPwd"):
 - setNtripCasterMountPoints, MP1, on, MyMP, Yes, FeedUser,
 FeedPwd <CR>
- 2. Define the stream data format. For example, if the mount point defined above is meant to stream RTCM v3.x corrections, use the following command:



setNtripCasterMPFormat, MP1, RTCMv3 <CR>

- 3. Define the NTRIP client accounts. Up to five client accounts can be configured. For example, the command below enables an NTRIP client connecting as user "u1" and with password "p1" to receive data from the first mount point:
 - setNtripCasterUsers, User1, u1, p1, MP1 <CR>
- 4. Enable the built-in NTRIP caster:
 setNtripCasterSettings, on <CR>

From now on, the NTRIP caster is ready to receive a data stream from a remote NTRIP server and to distribute it to NTRIP clients.



1.12 Configure an IP Server Port

In this example, we show how to configure the receiver such that any client connecting to TCP/IP port 28785 will receive the NMEA GGA message at a 1-second interval.

- Configure one of the IP server connections (see section 1.1.5) to listen to port 28785.
 Here, we assume that the first IP server connection (IPS1) is free:
 setIPServerSettings, IPS1, 28785, TCP <CR>
- Output the GGA NMEA message to the IPS1 connection, at a 1-Hz rate: setNMEAOutput, Stream1, IPS1, GGA, sec1 <CR>
- 3. Make sure that NMEA output is enabled on the IPS1 connection. It is enabled by default, but in case your receiver is not in its default configuration, you should invoke: setDataInOut, IPS1, ,+NMEA <CR>

A way to check the IP server functionality is to enter the URL http://polarx5tr-xxxxxxx:28785 in your preferred web browser (replace polarx5tr-xxxxxxx by the hostname of your particular receiver). You should see the NMEA GGA message coming every second.

Note that up to eight clients can concurrently connect to the same IP server port.

The example above showed how to set up a TCP server. It is also possible to configure the receiver in UDP server mode. For example, to broadcast the GGA message to any UDP client listening to its port 28785, the command in step 1. above must be replaced by: setIPServerSettings, IPS1, 28785, UDP, 255.255.255.255 <CR>

Conversely, the receiver can be configured to automatically receive data from an IP server. This is explained in section 1.13.



1.13 Configure an IP Receive Port

The receiver can be configured to automatically receive data (typically differential corrections) from an IP server. In this example, we show how to connect to an IP server having the hostname MyServer and using port 28786.

- Configure one of the IP receive connections (see section 1.1.5) to listen to port 28786 of MyServer. Here, we assume that the first IP receive connection (IPR1) is free: setIPReceiveSettings, IPR1, 28786, TCP2Way, MyServer <CR>
- 2. If the data stream from the IP server contains differential corrections in CMR or RTCM format, the receiver will automatically decode them and use them in the PVT processing.
- 3. To close the connection, enter the following command: setIPReceiveSettings, IPR1, 0 <CR>

The TCP connection initiated by the receiver is bidirectional. Once the connection is established, the receiver accepts input data from the server (as shown above), but it can also send data to the server, or process user commands from the server.

The example showed how to set up a TCP connection with the server. The receiver can also listen to incoming UDP messages. In that case, the connection is unidirectional and the server address or hostname must not be specified. For example, to listen to UDP messages on port 28786, use the command:

setIPReceiveSettings, IPR1, 28786, UDP <CR>



1.14 Manage Power Saving Mode

The receiver can put itself in low-power mode when its supply voltage drops below a user-configurable level. This can for example be used to prevent battery over-discharge when the receiver is powered from an external battery.

Power saving is configured with the **setPowerThresholds** and **setStandbyMonitoring** commands. When the supply voltage at the PWR connector drops below the threshold set with the **setPowerThresholds** command, the receiver enters low-power sleep mode for a duration given by **setStandbyMonitoring**. At the end of this period, the receiver wakes up and either resumes operation normally if the supply voltage is sufficient, or otherwise returns into sleep mode after about 30 seconds for a new period of time.

For example, to configure the receiver to sleep for one hour when the external supply voltage drops below 11.6V, use the following commands:

setStandbyMonitoring, 3600 <CR>

setPowerThresholds, 11.6 <CR>

exeCopyConfigFile, Current, Boot <CR>

The last command makes sure to save the configuration in non-volatile memory (see section 1.5), so that power monitoring remains active when the receiver wakes up.

During the sleep period, power-cycling the receiver will make it alive for at least 30 seconds before it goes back into sleep if the supply voltage is too low. This should give enough time to change the settings, or disable power saving if necessary.

Note that it is also possible to have the receiver sleep and wake up following a user-defined pattern, independently of the supply voltage. See the ScheduledSleep mode in the exePowerMode command.



1.15 Manage Log Sessions

Logging is done in multiple logging sessions referred to as LOGx (see also section 1.1.5). Each log session corresponds to a given directory on the disk (internal or USB drive).

For each session, the user can specify where to log (DSK1: internal disk, or DSK2: USB drive), the session name, how long to keep the log files, and the session priority.

Log sessions are configured with the **setLogSession** command. By default, logging is continuous, but it is also possible to configure a logging schedule, for example to log for one hour every day. See the **setLogSessionSchedule** command for details.

To prevent the disk from becoming full, log files are automatically deleted after the interval specified with the **setLogSession** command. Should the disk become full anyway, the receiver will either stop logging or attempt to remove old files according to the settings of the **setDiskFullAction** command. When attempting to remove old files, the receiver will first consider the log sessions with low priority. Refer to the description of the **setDiskFullAction** command for details.

It is possible to prevent auto-deletion of important files covering an event of interest (e.g. an Earthquake). The event of interest must be signaled to the receiver through one of its Event inputs (see section 1.28). Refer to the **setPreserveOnEvent** command for details.

Each session can log SBF files (see section 1.16), BINEX files (see 1.19), NMEA files (see 1.20), RTCM files (see 1.18), CGGTTS files (see 1.22) and RINEX files (see 1.17).

The log files can be automatically FTP-pushed to a remote server. A different FTP server can be configured for each log session, and different files types logged in the same session can be sent to different servers. Refer to section 1.25 to learn how to configure FTP push.





1.16 Log SBF Files

Enabling SBF logging on one of the log sessions involves the following steps:

1. Define the SBF naming convention and file duration in the log session of interest. By default, the receiver logs SBF blocks into a file named "log.sbf". You can specify any other file name, or you can select the IGS/RINEX naming convention, where the file name automatically changes every fifteen minutes, hour, six hours or day. File naming conventions can be selected independently for each log session. For instance, to let the receiver create daily files in the second log session (LOG2), use:

```
setFileNaming,LOG1,IGS24H <CR>
```

If the file name you selected already exists, the receiver will append new data at the end of the existing file.

- 2. Use the command **setSBFOutput** to define which SBF blocks need to be logged and at which interval (see also section 1.3). For instance, to log all SBF blocks necessary to build RINEX files in the LOG2 session, with a data interval of 10 seconds, use: **setSBFOutput**, **Stream1**, **LOG1**, **rinex**, **sec10 <CR>**
- 3. Make sure that the log session is defined and enabled: setLogSession, LOG1, enabled <CR>
- 4. To stop SBF logging, disable the SBF stream as follows: setSBFOutput, Stream1, none <CR> or temporarily disable the log session: setLogSession, LOG1, disabled <CR>

Note that the maximum file size supported by the receiver is 4GBytes.

Section 1.15 explains how to set up log sessions, section 1.25 shows how to automatically FTP push SBF files to a remote server and section 1.23 shows how to download log files.



1.17 Log RINEX Files

The receiver can log RINEX observation, navigation and meteo files on its internal disk. RINEX v2.11, 3.04, 3.05 and 4.00 are supported.

RINEX logging is configured independently for each log session.

Internal RINEX logging is typically configured as follows:

- The information needed to generate the RINEX file names is taken from the setMarkerParameters command. For example, to set the station name designator (the first four characters of the RINEX file names) to "LEUV", use: setMarkerParameters, , , , LEUV <CR>
- 2. The fields in the RINEX observation header are specified with the **setMarkerParameters**, **setObserverParameters** and **setAntennaOffset** commands. For example, if the observer's name is "MyName" and its agency is "MyAgency", use the command:

setObserverParameters, MyName, MyAgency <CR>

3. For static installations, the reference marker position to put in the "APPROX POSITION XYZ" header line can be defined with the *RefPos* argument of **setPVTMode**, with the marker-to-ARP offset being defined with **setAntennaOffset**. For example, assuming the WGS84 position of the ARP is 50.5°N, 4°E and its altitude above the WGS84 ellipsoid is 100m, and the ARP is 1.5 meters above the marker, use:

```
setStaticPosGeodetic,Geodetic1,50.5,4,100 <CR>
setPVTMode,,,Geodetic1 <CR>
setAntennaOffset,Main,0,0,1.5 <CR>
```

4. Use the **setRINEXLogging** command to configure the RINEX options: the file duration, the observation interval, etc. This is done independently for each log session. For example, to log daily RINEX files with the observation file containing only GPS L1CA data at a 30-s interval in the LOG1 log session, use:

```
setRINEXLogging, LOG1, Hour24, sec30, GPSL1CA <CR>
```

Note that the maximum file size supported by the receiver is 4GBytes.

Section 1.15 explains how to set up log sessions, section 1.25 shows how to automatically FTP push RINEX files to a remote server and section 1.23 shows how to download the RINEX files.

Instead of logging RINEX files inside the receiver, you can also convert an SBF file to RINEX using the sbf2rin program or the SBFConverter graphical tool.



1.18 Log RTCM-MSM Files

The receiver can log RTCM-MSM messages (a subset of the RTCM v3 messages) on its internal disk.

Internal RTCM-MSM logging is typically configured as follows:

1. The information needed to generate the RTCM-MSM file names is taken from the **setMarkerParameters** command. For example, to set the station name designator (the first four characters of the file names) to "LEUV", use:

```
setMarkerParameters, , , , LEUV <CR>
```

2. The antenna information in message types 1008 or 1033 can be specified using the **setAntennaOffset** command, with the serial number as sixth argument, and the antenna type (called "antenna descriptor" in RTCM) as fifth argument (see also section 2.5). For instance:

```
setAntennaOffset, Main, , , , "AT2775-54SW", "5684" <CR>
```

3. The reference position in message type 1006 is defined with the *RefPos* argument of **setPVTMode**. For example, assuming the WGS84 position of the ARP is 50.5°N, 4°E and its altitude above the WGS84 ellipsoid is 100m, use:

```
setStaticPosGeodetic, Geodetic1, 50.5, 4, 100 <CR>
setPVTMode, , , Geodetic1 <CR>
```

4. Use the **setRTCMMSMLogging** command to configure the RTCM-MSM logging options: the file duration, the observation interval, etc. This is done independently for each log session. For example, to log daily RTCM-MSM files in the first log session, with the files containing observations at a 30-s interval in MSM5 format, together with station- and ephemerides-related messages, use:

```
setRTCMMSMLogging, LOG1, Hour24, off, MSM5+Nav+Station, sec30
<CR>
```

Note that the maximum file size supported by the receiver is 4GBytes.

Section 1.15 explains how to set up log sessions, section 1.25 shows how to automatically FTP push RTCM files to a remote server and section 1.23 shows how to download the RTCM-MSM files.



1.19 Log BINEX Files

The receiver can log BINEX files on its internal disk. BINEX logging is configured independently for each log session.

Internal BINEX logging is typically configured as follows:

1. The BINEX file naming convention is inspired from the RINEX 2.11 file naming convention. The difference with RINEX is that the file type character is omitted and that the .bnx suffix is added. See the description of the setBINEXLoggingParameters command for details. The four-character station code must be specified with the setMarkerParameters command. For example, to set the station code to "LEUV", use:

```
setMarkerParameters, , , , LEUV <CR>
```

- 2. Use the setBINEXLoggingParameters command to specify the BINEX file duration (fifteen minutes, one hour, six hours or one day). This is done independently for each log session. For example, to log daily BINEX files in the LOG1 log session, use: setBINEXLoggingParameters, LOG1, Hour24 <CR>
- 3. Use the **setBINEXOutput** command to define which BINEX records need to be logged and at which interval (see also section 1.4). For instance, to log observation records (0x7F-05) at 10-second interval together with all decoded navigation records and metadata (0x00) at the beginning of the file, use: **setBINEXOutput**, **Stream1**, **Rec7F05+Rec01Nav+Rec00**, **sec10 <CR>**
- 4. Make sure that the log session is defined and enabled:

```
setLogSession,LOG1,enabled <CR>
```

5. To stop BINEX logging, disable the BINEX stream as follows:

```
setBINEXOutput, Stream1, none <CR>
or temporarily disable the log session:
setLogSession, LOG1, disabled <CR>
```

Note that the maximum file size supported by the receiver is 4GBytes.

Section 1.15 explains how to set up log sessions, section 1.25 shows how to automatically FTP push BINEX files to a remote server and section 1.23 shows how to download the BINEX files.



1.20 Log NMEA Files

Enabling NMEA logging on one of the log sessions involves the following steps:

1. Define the NMEA naming convention and file duration in the log session of interest. By default, the receiver logs NMEA into a file named "log.nma". You can specify any other file name, or you can select the IGS/RINEX naming convention, where the file name automatically changes every fifteen minutes, hour, six hours or day. File naming conventions can be selected independently for each log session. For instance, to let the receiver create daily files in the second log session (LOG2), use:

```
setNMEALogging,LOG1,IGS24H <CR>
```

If the file name you selected already exists, the receiver will append new data at the end of the existing file.

2. Use the command **setNMEAOutput** to define which NMEA sentences need to be logged and at which interval. For instance, to log the GGA sentences at an interval of 10 seconds in the LOG2 session, use:

```
setNMEAOutput, Stream1, LOG1, GGA, sec10 <CR>
```

- 3. Make sure that the log session is defined and enabled: setLogSession, LOG1, enabled <CR>
- 4. To stop NMEA logging, disable the NMEA stream as follows: setNMEAOutput, Stream1, none <CR> or temporarily disable the log session: setLogSession, LOG1, disabled <CR>

Note that the maximum file size supported by the receiver is 4GBytes.

Section 1.15 explains how to set up log sessions, section 1.25 shows how to automatically FTP push NMEA files to a remote server and section 1.23 shows how to download log files.



1.21 Estimate the Size of the Log Files

The table below compares the file size for different logging formats, with and without compression. It shows the disk space required to log all code and carrier phase measurements from all GNSS signals over one day at a 1-Hz rate.

The values have been measured in October 2020 in Belgium. They will change depending on the location and will also increase as more satellites are launched, but the table gives a good idea of the relative size between the different logging options.

Data format	File Size	File Size
	(uncompressed)	(gzip-compressed)
SBF (Rinex group)	261 MB	186 MB
SBF (RinexMeas3 group)	70 MB	64 MB
RINEX (v3)	638 MB	64 MB (Hatanaka+gzip)
BINEX (7F-05)	143 MB	118 MB
RTCM-MSM (MSM4)	132 MB	96 MB

As can be seen, the smallest files are obtained when logging the RinexMeas3 SBF group (see the **setSBFOutput** command in section 1.16), or with the compressed Hatanaka format.



1.22 Log CGGTTS Files

The receiver can generate and log CGGTTS-v2E files for the GPS, GLONASS, Galileo and Bei-Dou constellations.

Internal CGGTTS logging is typically configured as follows:

1. Specify the antenna phase center position (not the ARP!) to be used for the CGGTTS file generation. This is done with the **setCGGTTSPosition** command. The specified position only affects the CGGTTS processing and has otherwise no effect on the receiver operation. For example, use:

```
setCGGTTSPosition, all, manual, 4021429.16, 332877.37,
4923031.62 <CR>
```

- Configure all CGGTTS parameters and relevant electrical delays with the setTimeLabParameters, setCGGTTSTrackParameters, setINTDLY, setCABDLY and setREFDLY commands. For example, if the antenna+receiver electrical delay (INTDLY) at the GPSL1 frequency has been calibrated to be 30.2ns, use: setINTDLY, GPSL1, 30.2 <CR>
- 3. Enable CGGTTS logging. For example, to enable CGGTTS logging for the GPS and Galileo constellations in the ${\tt LOG1}$ log session, use:

setCGGTTSLogging, LOG1, GPS+GALILEO <CR>

Section 1.15 explains how to set up log sessions, section 1.25 shows how to automatically FTP push CGGTTS files to a remote server and section 1.23 shows how to download the CGGTTS files.

Instead of logging CGGTTS files inside the receiver, you can also convert an SBF file to CGGTTS using the sbf2cggtts program or the SBFConverter graphical tool.



1.23 Download Log Files from the Receiver

There are different ways to download or delete files from the internal disk:

1. Using RxControl. Select *Logging > Download Internal Files* to download files to your computer, and *Logging > Remove Internal File* to remove a file from the internal disk.




Figure 1-2: Download Internal Files from RxControl.

2. Using FTP or SFTP. The hostname or fixed IP address is defined as explained in section 1.1.3. For example, if your receiver's hostname is polarx5tr-1234567, you can type the following URL in your preferred web browser to open a session as anonymous user:

ftp://polarx5tr-1234567

User authentication for SFTP access can be done by entering a password or using an ssh public key, as defined with the **setUserAccessLevel** command.

By default, anonymous users can download and delete files. This can be changed as explained in section 1.31.

3. Using rsync. If an rsync client is available on your computer, you can use rsync to download files or directories from the receiver. The hostname or IP address is the same as for (S)FTP, see above.

For example, to download the contents of the $LOG1_TST/16134$ folder of the internal disk (DSK1) to the current folder on your local computer, you could invoke rsync as follows:

rsync -r anonymous@polarx5tr-1234567:DSK1/SSN/LOG1_TST/16134 . when prompted for a password, just press the enter key as no password is required for



anonymous accesses.

If the same command is issued again at a later stage, rsync will only transfer the deltas with respect to the files already present on the local machine, significantly reducing the number of bytes sent compared to retransmitting the entire files.

User authentication can be done by entering a password, or using an ssh public key, as defined with the **setUserAccessLevel** command.

By default, rsync is enabled for anonymous users. This can be changed with the **setDefaultAccessLevel** command.

- 4. Using the web interface (select the *Logging* tab).
- 5. Using a standard file browser and accessing the receiver as a removable drive (USB mass-storage device). This requires the USB cable to be connected to your computer, and the internal disk to be unmounted by the receiver so that it can be accessed by your computer's operating system. This is done using the **exeManageDisk** command. For example, to see the internal disk (DSK1) as a removable drive in your file browser, enter the command:

exeManageDisk, DSK1, Unmount <CR>

Internal logging is disabled on a disk that is unmounted. To resume logging by the receiver, the internal disk must be mounted again using the command:

exeManageDisk, DSK1, Mount <CR>

On Linux, it is needed to first eject the removable drive before entering this command.



1.24 Cloudlt Workflow (beta)



Cloudit is a beta feature. The instructions in this "How to" section are subject to changes.

1.24.1 Introduction

CloudIt offers an alternative to FTP log file submission from the PolaRx5TR receivers. CloudIt supports OAuth2 for authentication. The implementation is compliant with the specification of "The OAuth 2.0 Authorization Framework".

Note that CloudIt only supports the "Authorization Code" grant to comply with the security requirements and the authorization process for third party applications.

1.24.2 Server Setup

Cloudit expects the user to set up two servers, an authentication server and a resource server. The authentication server is used to verify if the receiver running CloudIt can access the resource server. The resource server stores the data files from the receiver.

In this section, the difference between the authentication and resource servers is used towards the network administrator. However inside the receiver configuration, this difference is invisible to the end user, as both the authentication and resource servers are, on the receiver, one Cloudit Server, such as in the **setCloudItConfig** command.

Authentication Server Setup 1.24.2.1

Keycloack is recommended as an Identity and Access Management platform for the authentication server, as CloudIt has been tested and validated using this tool (Keycloack.4.5.0). Other Access Management platforms were not tested but can offer similar possibilities. However, since most other tools offer more specific and/or proprietary implementations of the OAuth2 protocol, CloudIt might not (yet) be compatible with these.

Inside the authentication server it is required to create an application. At this level it should be possible to get a ClientID and a ClientSecret and to define the Scope. The Scope should, as an example, include the permission to write on your resource server.

The Access Management platform also provides the Authentication URL (identified in the receiver as AuthURL) and Token URL (identified in the receiver as TokenURL). The exact procedure on how to get this information depends on the Access Management platform setup.

These arguments will be used to configure CloudIt using **setCloudItConfig**.

Currently, Cloudit only supports the stateless access/refresh token authorization process. If the authorization server does not respond with both the access and refresh tokens, the authorization will fail.

The authorization server should be configured to accept authorization requests without a redirect_uri. However, the server will need to redirect all successful authorization requests



to a web page that displays the authorization code, referenced in this document as *Authcode*. The user will use this code later in step 3 of the Receiver configuration of Cloudlt.

1.24.2.2 Resource Server Setup

The resource server stores the data files from the receiver. This server should be configured to accept HTTP PUT requests only from authorized receivers. When authorized, the receiver will send HTTP PUT requests to the server to perform a multipart upload. The sent request is the following:

```
curl -H "Authorization: Bearer 654sdf542sdfkjsdf5484fgh74" \
    -F "path=/my/remote/directory" \
    -F "file=@/localpath/myfile.sbf;type=application/octet-stream" \
    "https://myresourceserver.com/api/upload/?uploadType=multipart")
```

Please note that the remote directory (where the file will be stored in the server) is sent via the *Path* argument. It is the responsibility of the server to interpret it and to manage, if needed, the creation of the folder. The remote directory, defined by the *Path*, can be set with the **setSBFCloudIt**, **setRINEXCloudIt**, **setBINEXCloudIt** or **setRTCMMSMCloudIt** commands depending on the type of files to upload. The *UploadURL* parameter defines the upload endpoint accepting the uploaded files. This parameter is required to configure the CloudIt server using the **setCloudItConfig** command.

1.24.3 Receiver Configuration of CloudIt

When the CloudIt authentication and resource servers are up and running, the PolaRx5TR can be configured following the steps below:

- 1. Set the CloudIt server parameters using **setCloudItConfig** command.
- 2. Use the **lstAuthorizationLinkCloudIt** command to get an authorization link. This link needs to be visited through a web browser where the user needs to login and authorize the receiver. When authorized, the user will be redirected to a web page displaying the authorization code on the page or in the URL.
- 3. Use **exeAuthorizeCloudIt** to authorize the receiver using the code given in step 2.

1.24.4 File Upload

When a log session is enabled, it is possible to upload the internally-logged files to a remote CloudIt server with the **setSBFCloudIt**, **setBINEXCloudIt**, **setNMEACloudIt**, **setNMEACloudIt**, **setRTCMMSMCloudIt** and **setRINEXCloudIt** commands depending on the file type. It is possible to upload each file type to a different server. The user can configure up to 8 servers.

For example, to configure the LOG2 log session to automatically upload RINEX files to the directory mydata/rin/ on the remote server Cloud1, the following command needs to be



entered:

setRINEXCloudIt, LOG2, Cloud1, mydata/rin/ <CR>

Note that the folder structure on the remote server will be similar to the folder structure on the receiver. For example, if you have a file in the receiver under LOG2/19141, the actual *Path* sent to the server in the HTTP upload request is: mydata/rin/LOG2/19141.

If the file transfer fails, the receiver will retry at a user-defined interval. See the description of the setSBFCloudIt, setBINEXCloudIt, setNMEACloudIt, setRTCMMSMCloudIt and setRINEXCloudIt commands for details.

Note: Within one log session and file type, it is possible to configure CloudIt and FTPPush (section 1.25) at the same time. However, if the user enables both features for the same log session and file type, only FTPPush will be processed.



1.25 FTP Push Log files

It is possible to configure the receiver to automatically send internally-logged files to a remote FTP server (FTP Push). This is done with the **setSBFFTP**, **setBINEXFTP**, **setNMEAFTP**, **setRTCMMSMFTP**, **setCGGTTSFTP** and **setRINEXFTP** commands depending on the file type. It is possible to configure the FTP server independently for each log session.

For example, to configure the LOG2 log session to automatically FTP RINEX files to the directory mydata/rin/YYDDD (with YY and DDD the year and day-of-year) on the remote server myftp.com, with username myname and password mypwd, you would enter the following command:

setRINEXFTP, LOG2, myftp.com, mydata/rin/%y%j, myname, mypwd <CR>

FTP push will create the folder on the remote server if it does not exist yet.

If the file transfer fails, the receiver will retry at a user-defined interval. See the description of the **setSBFFTP**, **setBINEXFTP**, **setNMEAFTP**, **setRTCMMSMFTP** and **setRINEXFTP** commands for details.

Note: Within one log session and file type, it is possible to configure Cloudlt (section 1.24) and FTPPush at the same time. However, if the user enables both features for the same log session and file type, only FTPPush will be processed.

For example, if the user issues the following commands: setSBFCloudIt, LOG1, Cloud1, mydata/rin/ <CR>
setSBFFTP, LOG1, myftp.com, mydata/rin/, myname, mypwd <CR>

the SBF files created in session LOG1 will only be pushed to the FTP server. If the user wants to upload the same files with CloudIt another log session with the same configuration needs to be configured.



1.26 Communicate with External Equipment

The receiver can send periodical queries to external equipment (such as a meteo sensor) connected to one of its serial ports, and log the replies from that sensor. In the following example, we show how to retrieve meteo data every 10 seconds from a meteo sensor connected to the receiver's COM2 port.

1. Tell the receiver which command to use to query the external sensor, and the interval at which this command must be sent to the sensor. For instance, for a MET3/MET4-compatible sensor, the command *0100P9<CR><LF> queries the meteo data. Assuming you want to get meteo data at a 10-second interval, enter the following command:

setPeriodicEcho, com2, A: *0100P9%%CR%%LF, sec10 <CR>

2. Enable unformatted ASCII input on COM2 (to receive the replies from the meteo sensor):

setDataInOut,COM2,ASCIIIn <CR>

The replies from the meteo sensor (containing the temperature, pressure and humidity) are available in the ASCIIIn SBF block and in BINEX record 0x7E-01.

You can convert an SBF file containing ASCIIIn SBF blocks to RINEX using the sbf2rin program or the SBFConverter graphical tool. Alternatively, you can log the RINEX meteo file directly on the receiver (see section 1.17). To be able to generate a RINEX file, the output of the meteo sensor must be formatted according to the NMEA XDR sentence.



1.27 Generate a "Pulse Per Second" Signal

The receiver is able to generate an x-pulse-per-second (xPPS) signal aligned with a selected GNSS system time, with UTC or with the internal receiver time.

The **setPPSParameters** command is used to set the xPPS parameters (rate, polarity, time system, ...). For instance, to synchronize the xPPS pulses with UTC and have one pulse every ten seconds, use:

setPPSParameters, sec10, , , UTC <CR>




Figure 1-3: xPPS output granularity.

Although the position of the PPS pulse is computed accurately by the receiver, the actual pulse is generated at the nearest "tick" of the internal receiver digital clock, as illustrated in the figure above. This leaves an offset (noted "D" in the figure) between the true xPPS pulse and the one actually generated by the receiver. This offset can reach a few nanoseconds. It is available in real-time in the xPPSOffset SBF block.

To be able to align its xPPS output with the GNSS system time, the receiver needs a fresh estimate of the GNSS time from its PVT solution. If the last PVT solution is older than a prescribed timeout (set by the **setPPSParameters** command), no PPS pulse is generated. In addition, to align its PPS with UTC, the receiver needs to have received the UTC offset parameters from the satellite navigation messages. If these parameters are not available and the user has requested to align the xPPS with UTC, no xPPS pulse is generated.



1.28 Time Tag External Events

The receiver can time-tag electrical level transitions on its EventX inputs with an accuracy of 20ns.

By default, the receiver reacts on low-to-high transitions. You can use the setEventParameters command to react on falling edges instead: setEventParameters, EventA, High2Low <CR>

Upon detection of a transition, the receiver can output the time and/or the position at the instant of the event (see for example the ExtEvent SBF block).

The following constraints must be observed to ensure proper event detection:

- There must be no more than 20 events in any interval of 100 milliseconds, all event pins considered.
- The minimum time between two events on the same Event *X* input must be at least 5ms.

Missed events are flagged by the MISSEDEVENT bit in the ReceiverStatus SBF block.

The external event inputs can also be used to flag log files as "to be preserved". If this is enabled, files logged during the occurrence of an external event are preserved from auto-deletion. Refer to the **setPreserveOnEvent** command for details.



1.29 Monitor the RF Spectrum

You can monitor the RF spectrum using the spectral analyzer in RxControl (go to the *View > Spectral View* menu) or in the web interface (go to the *GNSS > Spectrum* menu). This allows to detect the presence of interferences in the GNSS bands.

In the example shown below, a narrowband interference at 1180 MHz is clearly visible.




Figure 1-4: Spectral Analyser functionality of RxControl.

The spectrum is computed from baseband samples taken at the output of the receiver's analog to digital converters. These samples are available to the users in the BBSamples SBF block.



1.30 Use Galileo OSNMA

With the Open Service Navigation Message Authentication (OSNMA) feature, Galileo satellites allow to verify the authenticity of navigation messages received from GNSS satellites, offering a powerful means to detect and counter spoofing attacks.

In Septentrio receivers, OSNMA is used to discard untrusted satellites from the PVT computation. Three operating modes are supported: *off* where OSNMA authentication is disabled, *loose* where satellites are included in the PVT if they are successfully authenticated or if their authentication status is unknown, and *strict* where only successfully-authenticated satellites are included in the PVT.

In *strict* mode, the number of satellites available to the PVT may be limited as OSNMA does not authenticate all visible satellites (e.g. only Galileo and GPS satellites depending on the OSNMA service status).

After enabling OSNMA (in *loose* or *strict* mode), it typically takes a few tens of seconds to a few minutes to authenticate messages. In *strict* mode, no PVT is computed during that time.

OSNMA is configured as follows:

- 1. Use the **setGalOSNMAUsage** command to enable OSNMA authentication. For example, to enable OSNMA in *loose* mode, use:
 - setGalOSNMAUsage, loose <CR>
- 2. In strict mode, OSNMA authentication requires the availability of external time information. In loose mode, this is optional but recommended for enhanced security. The receiver can connect to an NTP time server for this purpose, as configured with the setNTPClient command. For example, to enable time retrieval from the default NTP server, use:

setNTPClient, on, default

The receiver has been optimized for use with live Galileo signals. Necessary keys are embedded into the software. For example the Galileo Merkle Tree root key, needed to enable over-the-air reception of public keys, is known by the receiver, obviating the need for the user to provide it.

Refer to section 2.6 for further details.



1.31 Manage Users

When connecting to the receiver, users can remain "anonymous", or can log in using the <code>login</code> command. What anonymous users can do depends on the connection type. By default, anonymous users have full control of the receiver. This default configuration can be changed with the <code>setDefaultAccessLevel</code> command. For example, to prevent anonymous access to the web interface and to the FTP server, you would use: <code>setDefaultAccessLevel</code>, <code>none</code>, <code>none</code> <code><CR></code>

To perform actions not allowed to anonymous users, you first need to authenticate your-self by entering a user name and a password through the <code>login</code> command. The list of user names and passwords and their respective access level is managed with the <code>setUserAccessLevel</code> command. Login fails if the provided user name or password is not in that list.

Logged-in users are granted one of the following access levels: "User" or "Viewer". The "User" level allows full control of the receiver, while the "Viewer" level only allows to view the configuration.

The following explains how to add or delete a user.

1. Check the current user list by entering the following command:

```
getUserAccessLevel <CR>
```

The reply to this command looks like:

```
UserAccessLevel, User1, "admin", "R46NCG", User UserAccessLevel, User2, "", "", Viewer UserAccessLevel, User3, "", "", Viewer
```

2. In the example shown above, only one user is defined: User1 with user name admin. For security reasons, the password shown here (R46NCG) is random and does not correspond to the actual password. It can be seen that the level of access of the admin user is "User": that particular user has full control of the receiver.

To add a new user "john" with password "abc123" and to give full access to that user, select a free user index, e.g. User2 in the above example, and type:

```
setUserAccessLevel, User2, john, abc123, User <CR>
```

3. You can add up to eight users in this way. Deleting a user involves entering an empty string ("") as user name and password. For example, to delete the "admin" user from the above list, use:

```
setUserAccessLevel,User1,"","" <CR>
```

The user list also applies to FTP, SFTP and rsync accesses. Users having the "User" access right are allowed to delete files from the internal disk via FTP, SFTP or rsync, while "Viewer" users can only download files.



Upgrade the Receiver

Upgrading the receiver is the process of installing a new GNSS firmware, a new permission file (see section 1.34) or a new antenna calibration file (see section 2.5).



In some cases, upgrading the GNSS firmware can clear the receiver configuration stored in non-volatile memory (see section 1.5). It is therefore advised to recheck the configuration after the upgrade.



Do not switch power off during the upgrade procedure.



Upgrading the receiver over a serial port can be very slow and it is recommended to upgrade. using a faster connection whenever possible (USB, WiFi or Ethernet).

Septentrio upgrade files have the extension ".suf". There are several ways to upgrade the receiver:

- 1. By double clicking the ".suf" file. This should launch the RxUpgrade program.
- 2. By using the RxControl graphical interface (go to the File menu).
- 3. From the web interface (go to Admin > Upgrade). This requires to log in as a user with the "User" access level (see section 1.31).
- 4. By commanding the receiver to upgrade itself by fetching the upgrade file from a remote FTP server. This is done with the command **exeFTPUpgrade**.
- 5. By manually downloading upgrade files to the receiver. This upgrade procedure is explained below.

To manually upgrade the receiver, follow this procedure:

- 1. Reset the receiver into upgrade mode by entering the following command: exeResetReceiver, Upgrade, none <CR>
- 2. Wait till the receiver outputs the string: "Ready for SUF download ...". From that moment on, the receiver is waiting for an upgrade file to be downloaded. The file download must start within 200 seconds, otherwise the receiver will restart in normal mode.
- 3. Download the upgrade file to the receiver. Any of the receiver connections can be used. Make sure to send the file in binary mode, i.e. without changing its contents. During the download, the receiver outputs a progress indicator at regular interval.
- 4. At the end of the download, the receiver automatically executes the upgrade instructions and restarts with the new firmware version. You can check the firmware version by entering the following command:

lif, Identification <CR>

Before executing the upgrade instructions, the receiver checks the integrity of the downloaded file. If the file is corrupted, or is not a valid upgrade file, the receiver discards it and restarts in normal mode.

If the download is interrupted for any reason, the receiver will restart in normal mode after a timeout period of 200 seconds.





1.33 Check the Capabilities of your Receiver

The capabilities of your receiver are defined by the set of enabled features. The capabilities depend on the hardware, the current firmware version and the current set of permissions. Permissions are further explained in section 1.34.

The command **getReceiverCapabilities** lists the capabilities. You can also check them using the web interface (go to *Admin >About >Permitted Capabilities*) or RxControl (go to *Help >Receiver Interface* and select the *Permitted Capabilites* tab):




Figure 1-5: Example of receiver capabilities.



1.34 Check or Change the Permission File

The permission file lists which optional features (such as GLONASS, Galileo, RTK, ...) are permitted on your receiver, for how long they are permitted and in which region they are permitted.

The permission file is stored in the receiver's non-volatile memory, and can be checked with the command **lstInternalFile**, **Permissions**, or with RxControl by clicking *Help >Receiver Permissions*.

Note that, for a given feature to be enabled in the receiver, it must be permitted and the hardware and firmware version must support it. See also section 1.33.

Each receiver is delivered with a permission file applicable to that receiver only. To enable new options, the user can order a new permission file to Septentrio, and install it on his/her receiver using the standard upgrade procedure (see section 1.32).





Chapter 2

Operation Details

This chapter describes the key processes implemented in the receiver and explains how they can be configured.

2.1 Channel Allocation and Signal Selection

The receiver automatically allocates satellites to tracking channels up to the limit of the number of channels. It is possible to override this automatic channel allocation by forcing a satellite to a given channel with the **setChannelAllocation** command. Also, a subset of satellites or a whole constellation can be disabled with the **setSatelliteTracking** command.

For each satellite, the receiver tries to track all signal types enabled with the **setSignalTracking** command. For example, if that command enables the GPSL1CA, GPSL2PY and GLOL1CA signals, GPS satellites will be tracked in dual-frequency mode (GPSL1CA and GPSL2PY) and GLONASS satellites will be tracked in single-frequency mode (GLOL1CA only). It is a good practice to only enable those signal types that are needed for your application to avoid wasting tracking channels.

2.2 Generation of Measurements

For each tracked GNSS signal, the receiver generates a "measurement set", mainly consisting of the following observables:

- a pseudorange in meters;
- a carrier phase in cycles;
- a Doppler in Hertz;
- · a carrier-to-noise ratio in dB-Hz.

All data in a measurement set, and all measurement sets are taken at the same time, which is referred to as the "measurement epoch". All the measurement sets taken at a given measurement epoch are output in a MeasEpoch SBF block.

Several commands affect the way the receiver produces and outputs measurements:



- The **setHealthMask** command can be used to filter out measurements from unhealthy satellites: these measurements will not be used by the PVT algorithm, nor will they be included in the MeasEpoch SBF block.
- To further reduce the code measurement noise, the receiver can be ordered to smooth the pseudorange by the carrier phase. This technique, sometimes referred to as a "Hatch filtering", allows to reduce the pseudorange noise and multipath. It is controlled by the **setSmoothingInterval** command and is disabled by default.
- The **setMultipathMitigation** command can be used to enable or disable the mitigation of multipath errors on the pseudorange and carrier phase measurements. It is enabled by default.

For advanced applications or in-depth signal analysis, the MeasExtra SBF block contains various additional data complementing the MeasEpoch SBF block. Among other things, this block reports the multipath correction applied to the pseudorange (allowing one to recompute the original pseudorange), and the observable variances.

2.2.1 Pilot vs. Data Component


Most modern GNSS signals consist of two components: a so-called pilot component and a data component. For such signals, the measurements are based on the pilot component for optimal performance. In particular, the reported C/N_o value is that of the pilot component only.

For all signals having a pilot and a data component, the table below indicates which component is tracked by Septentrio receivers. Note that your particular receiver model may not support all of these signals.

Signal	Signal component being used for measurement generation
GPS/QZSS L1C	L1C-P
GPS/QZSS L2C	L2C-L
GPS/QZSS L5	L5-Q
GLONASS L3	L3-Q
Galileo E1	E1-C
Galileo E6	E6-C or E6-B if E6-C is encrypted
Galileo E5a	E5a-Q
Galileo E5b	E5b-Q
Galileo E5AltBOC	E5AltBOC-Q
BeiDou B1C	B1C_pilot
BeiDou B2a	B2a_pilot
BeiDou B2b	B2b_I

See also the corresponding RINEX observation code in section 4.1.10.





2.3 Time Management

The receiver time is kept in two counters: the time-of-week counter in integer milliseconds (TOW) and the week number counter (WNc). TOW and WNc follow the GPS convention, i.e. WNc counts the number of complete weeks elapsed since January 6, 1980, and there are no leap seconds. The TOW and WNc counters are reported in all SBF blocks.

The synchronization of TOW and WNc involves the following steps:

- Upon powering up the receiver, TOW and WNc are assumed unknown, and set to a "Do-Not-Use value" in the SBF blocks.
- The transmission time-of-week and week number are decoded from the GNSS satellites (all constellations considered, not only GPS):
 - As soon as the first time-of-week is decoded, the TOW counter is initialized to within 20 ms of GPS time and starts counting. This is also the time when the receiver starts generating GNSS measurements (pseudoranges and carrier phases).
 - As soon as the week number is decoded (which can be either simultaneously with the time-of-week, or several seconds later), the WNc counter is set and starts counting.
- After the first position and time fix has been computed (for which measurements from at least 4 satellites are required), TOW is set to within X milliseconds of GPS time. This is done by introducing a jump of an integer number of milliseconds in the TOW counter. X is the maximal allowed offset between the receiver time and GPS time, and is set by the setClockSyncThreshold command (by default, X=0.5ms). This initial clock synchronization leads to a simultaneous jump in all the pseudorange and carrier phase measurements.

Note that in cases when the satellite visibility is obstructed, the receiver can also set its time from NMEA GPRMC or GPZDG sentences received on one of its serial ports. The time in the NMEA sentences must refer to the GPS time scale (and not to UTC), and the serial port receiving the NMEA sentences must be configured in ASCIIIn input mode with the **setDataInOut** command. This feature is only enabled when an external frequency and time pulse is provided on the REF IN and PPS IN connectors.

The synchronization level is given by three status bits (TOWSET, WNSET and FINETIME) available both in the ReceiverTime SBF block and the ReceiverStatus SBF block. Once the FINETIME bit is set, it remains set until the next reset of the receiver.

The receiver clock can be configured in free-running mode, or in steered mode using the command **setClockSyncThreshold**.

2.3.1 Free-Running Clock

In free-running mode, the receiver time slowly drifts with respect to GNSS time. The receiver continuously monitors this time offset: this is the clock bias term computed in the PVT solution, as provided in the RxClkBias field of the PVTCartesian and PVTGeodetic SBF blocks. A clock jump of an integer number of milliseconds is imposed on the receiver clock each time the clock bias exceeds X milliseconds by an absolute value (X is set by **setClockSyncThreshold**). This typically results in a saw-tooth profile similar to that shown in Figure 2-1. In this example, X=0.5ms and each time the clock bias becomes greater than 0.5ms, a jump of 1ms is applied.






Figure 2-1: Example of the evolution of the receiver time offset with respect to the GNSS time in free-running mode.

Note that the clock bias is computed with respect to a particular GNSS time system (GPS, Galileo, BeiDou, ...) as set with the **setTimingSystem** command. The time offset between those systems is at the level of a few tens of nanoseconds only, and is ignored when applying the X-millisecond threshold.

When a receiver clock jump occurs, all measurements jump simultaneously. For example, a clock jump of 1ms will cause all the pseudoranges to jump by 0.001s * velocity_of_light = 299792.458m. The jump is applied on both the pseudoranges and the carrier phase measurements, and hence will not be seen on a code-minus-phase plot.

The cumulated clock jumps since the last reset of the receiver is reported in the CumClkJumps field of the MeasEpoch SBF block.

As can be seen in Figure 2-1, the initial clock bias is not necessarily zero, but it can take any value within -0.5ms and +0.5ms. This is the default configuration. You can use the second argument of the **setClockSyncThreshold** command to force the clock bias to be close to zero (typically <100ns) at startup. When this feature is enabled, a jump of a non-integer number of milliseconds is applied right after the first position fix, followed by a short loss of signal tracking.

2.3.2 Clock Steering

In steered mode, the receiver time is continuously steered to a GNSS time. The particular time realization (GPS, Galileo, BeiDou, ...) is generally irrelevant as the difference is very small. It can be selected with the **setTimingSystem** command if needed.

In the example of Figure 2-1, if the user would have enabled clock steering one hour after start up of the receiver, the clock bias would have been like in Figure 2-2 below.






Figure 2-2: Effect of clock steering on the clock bias (clock steering enabled at an up time of 1 hour).

Clock steering accuracy is dependent on the satellite visibility, and it is recommended to only enable it under open-sky conditions.

Bit 3 of the CommonFlags field of the MeasEpoch SBF block indicates whether clock steering is active or not.



Note for the users of a GNSS constellation simulator:

When using a constellation simulator, and if the only simulated signals are the legacy L1 and L2 GPS and GLONASS signals, make sure to set the simulation time after December 31, 2019. The receiver time will be incorrect before that date.

For correct time determination, it is mandatory to reset the receiver before every (re)start of the simulation.

2.4 Computation of Position, Velocity, and Time (PVT Solution)

The receiver computes the position, velocity and time (PVT) based on the pseudoranges, the Doppler measurements and, if applicable, the differential corrections.

The availability of the PVT depends on:

- the number of available pseudoranges and Doppler measurements, equal to the number of tracked satellites, or a subset of them as specified by the setSatelliteUsage command;
- the number of valid sets of broadcast ephemerides, which are needed to compute the position, velocity, and clock bias for each tracked satellite;
- the number of valid sets of fast and long-term SBAS corrections and their age in the case of SBAS-aided positioning;
- the number of valid differential corrections and their age in the case of DGPS/RTK positioning.

A position fix requires a minimum of 4 tracked satellites with associated ephemerides. When a PVT solution is not available, PVT-related SBF blocks are still output with all the numeric fields set to Do-Not-Use values, and with the Error field set to indicate the source of the problem.



The accuracy of the PVT depends on:

- · The signal level.
- The geometry of the satellite constellation expressed in the DOP values: these values indicate the ratio of positional errors to range errors and are computed on the basis of the error propagation theory. When the DOP is high, the accuracy of positioning will be low.
- The number of available satellites: the more satellites are available, the lower the DOP. Measurement redundancy also enables better outlier detection.
- Multipath errors on the pseudorange measurements: multipath errors can be largely attenuated by enabling the APME multipath mitigation method (see setMultipathMitigation) and/or using code smoothing (see setSmoothingInterval).
- The PVT mode as set by the **setPVTMode** command.
- The data available to compute ionospheric delays (see setIonosphereModel).
- The choice of the dynamics model: if the dynamics parameter set by the **setReceiverDynamics** command does not correspond to the actual dynamics of the receiver platform, the position estimation will be sub-optimal.

The a-posteriori accuracy estimate of the computed position is reported in the variance-covariance matrix, which comes in the PosCovCartesian and PosCovGeodetic SBF blocks. This accuracy estimate is based on the assumed measurement noise model and may differ from actual errors due to many external factors, most of all multipath.

2.4.1 SBAS Positioning

SBAS, which stands for 'Space Based Augmentation System', enables differential operation over a large area with associated integrity information. System errors are computed from a dataset recorded over a continental area and disseminated via a geostationary satellite. The operation of SBAS is documented in the RTCA DO 229 standard. SBAS improves over DGPS corrections, in that it provides system corrections (ionosphere corrections and ephemeris long-term corrections) next to range corrections (the "fast corrections" in the DO 229 terminology).

The receiver provides an SBAS-aided position when it has sufficient satellites with at least fast and long-term corrections. The corrections are used as long as their applicability has not timed out. During the time-out interval the receiver applies correction degradation using the information received in message type (MT) 07 and 10.

By default, the receiver selects the SBAS satellite with the most SBAS corrections available. With the **setSBASCorrections** command, it is possible to force the receiver to use a particular SBAS satellite or a particular SBAS provider.

2.4.2 DGPS Positioning

DGPS (Differential GPS) is a pseudorange-based positioning technique where GNSS system errors are reduced by the use of range corrections. To work in DGPS rover mode, the receiver needs to receive differential corrections in the RTCM or CMR format.



Note on the RTCM v2.x corrections: the receiver takes the τ_{gd} parameter transmitted by the GPS satellites into account during the computation of the pseudorange corrections, as prescribed in v2.2 and v2.3 of the RTCM standard. The RTCM standard version 2.1 is ambiguous in this respect: it does neither prescribe nor discourage the use of τ_{gd} . The receiver can be configured in both modes using the command **setRTCMv2Compatibility**.

2.4.3 RTK Positioning

Real-Time Kinematic (RTK) is a carrier phase positioning method where the carrier phase ambiguities are estimated in a kinematic mode.

To work in RTK mode, the receiver requires the reception of RTK messages. Both the RTCM and the CMR message formats are supported. Multiple-base RTK is not supported: by default, the receiver selects the nearest base station if more than one base station is available.

In RTK mode, the absolute position is reported in the PVTCartesian or PVTGeodetic SBF blocks, and the baseline vector is reported in the BaseVectorCart and BaseVectorGeod SBF blocks.

2.4.3.1 Integer Ambiguities (RTK-fixed)

The key to high-accuracy carrier phase positioning is the fixing of the carrier phase integer ambiguities. Under normal circumstances the receiver will compute the integer ambiguities within several seconds and yield an RTK-fixed solution with centimeter-level accuracy. The less accurate pseudorange measurements will not be used. As long as no cycle slips or loss-of-lock events occurs, the carrier phase position is readily available.

RTK with fixed ambiguities is also commonly referred to as phase positioning using 'On-The-Fly' (OTF) ambiguity fixing. The RTK positioning engine of the receiver uses the LAMBDA method⁽¹⁾ developed at Delft University, department of Geodesy.

2.4.3.2 Floating Ambiguities (RTK-float)

When data availability is low (e.g. low number of satellites) or when the data are not of sufficient quality (high multipath), the receiver will not fix the carrier phase ambiguities to their integer value, but will keep them floating. At the start of the RTK-float convergence process, the position accuracy is equal to that of code-based DGPS. Over the course of several minutes the positional accuracy will converge from several decimeters to several centimeters as the floating ambiguities become more accurate.

2.4.4 Precise Point Positioning

Precise Point Positioning (PPP) provides high accuracy positioning without the need for a local base station. PPP uses precise satellite orbit and clock corrections computed by a global

⁽¹⁾ Teunissen, P.J.G., and C.C.J.M. Tiberius (1994) Integer least-squares estimation of the GPS phase ambiguities. Proceedings of International Symposium on Kinematic Systems in Geodesy, Geomatics and Navigation KIS'94, Banff, Canada, August 30-September 2, pp. 221-231.



network of reference stations and broadcast in real time by geostationary satellites in the L band.

2.4.4.1 PPP Seeding

PPP provides centimeter-level position accuracy, but suffers from a relatively long convergence time that can reach 15 to 20 minutes depending on the local multipath environment. The convergence time can be dramatically reduced by feeding the known position into the PPP engine. This process is referred to as PPP seeding, and the position fed into the PPP engine is called the PPP seed. The receiver supports two seeding modes:

Manual Seeding: in manual seeding, the user provides the accurate marker position (see section 2.5 for a definition of the marker position) to the PPP engine by using the **exePPPSetSeedGeod** command.

Automatic Seeding: the receiver can be configured to automatically seed the PPP engine from its current DPGS or RTK position. Automatic seeding is configured with the **setPPPAutoSeed** command.

2.4.4.2 PPP Datum Offset

By default, PPP positions are expressed in ITRS (which ITRF realization of ITRS depends on the PPP service provider), while RTK positions refer to the regional datum used by your RTK provider. To avoid coordinate jumps each time the PVT engine switches between RTK and PPP, and to ensure accurate seeding of the PPP engine from RTK, the regional datum must be provided with the **setGeodeticDatum** command.

Note that local RTK positions obtained after applying the datum transformation parameters transmitted in RTCM v3.x MT1021-1023 are never used for PPP seeding. In other words, the position reported in the PosLocal SBF block is not suitable for PPP seeding. See also section 2.4.6.

2.4.4.3 Tide Corrections

Since PPP is based on global satellite corrections, the PPP position would be sensitive to earth tide variations if no correction were applied. The receiver applies a tide correction based on the Sinko Earth tide model⁽²⁾. All positions reported in the PVTCartesian, PVTGeodetic and PosCart SBF blocks are always tide-corrected.

2.4.5 Transition between PVT Modes

Whenever possible, the transitions from a more accurate PVT mode to a less accurate PVT mode are smooth. For example, when switching from RTK to DGPS mode, the position does not exhibit a sudden jump, but slowly degrades from RTK to DGPS accuracy.

Sinko, J., A Compact Earth Tides Algorithm for WADGPS. Proceedings of ION GPS-95, Palm Springs, California, September 12-15, 1995, pp. 35-44.





2.4.6 Datum Transformation

By default the datum to which the coordinates refer depends on the positioning mode. For standalone, PPP and SBAS positioning for example, the coordinates refer to a global datum: WGS84 or ITRS. When using DGPS or RTK corrections from a DGPS/RTK provider, the coordinates usually refer to a regional datum (e.g. ETRS89 in Europe).

Recent realisations of WGS84 and ITRS are closely aligned and the difference can be neglected in most cases. The receiver considers them equivalent. However, regional datums may significantly differ from WGS84/ITRS, which may lead to coordinate jumps when switching between different positioning modes.

2.4.6.1 Transformation to Regional Datum

It is possible to avoid this datum shift by configuring the receiver to transform all coordinates to the regional datum used by the RTK base stations. This is done with the **setGeodeticDatum** command. The receiver knows the transformation parameters applicable to the most common datums (e.g. ETRS89 or NAD83), but user datums can also be defined with the **setUserDatum** command.

Coordinates in the PVTCartesian and PVTGeodetic SBF blocks refer to the datum selected in **setGeodeticDatum**. The datum can be checked by decoding the Datum field of these blocks.

2.4.6.2 Transformation to Local Datum

Sometimes it is needed to relate the coordinates to a local datum. Some RTK networks provide the necessary transformation and projection parameters as part of their RTCM stream, in message types 1021 to 1027.

The local geodetic coordinates (latitude, longitude and height) are reported in the PosLocal SBF block, and the plane grid coordinates (easting, northing, height) are reported in the PosProjected SBF block.

The following conditions must be met for the receiver to provide local coordinates from the information sent by the RTK network:

- the usage of RTCM v3.x MT1021-1027 must be enabled by the command **setRTCMv3Usage** (these messages are enabled by default).
- the complete set of datum transformation messages must have been received from the network. Plane grid coordinates are only available if the network supports one of the messages in the 1025-1027 range. Otherwise, only the local latitude, longitude and height are available.
- the position must be in the area of validity of the transformation parameters.
- to continue to get unbiased local coordinates when the positioning mode is not DGPS or RTK, the network regional datum must be set with the **setGeodeticDatum** command. See section 2.4.6.1.





2.5 Antenna Effects

To achieve the highest positioning precision, it is essential to take antenna effects into account.




Figure 2-3: Antenna mount.

The GNSS measurements (pseudoranges and carrier phases observables) refer to a theoretical point in space called the phase center (noted PC in Figure 2-3). The position of this point is dependent on the elevation of the satellite and on the frequency band. It varies with time and it is different for the different GNSS frequency bands. The phase center variation can reach a few centimeters.

If no correction is applied, the computed position refers to an average phase center with no easy link with the antenna physical element. This average phase center fluctuates with time and cannot be used for accurate millimeter-level positioning.

For high-precision positioning, the GNSS measurements need to be corrected in such a way that they all refer to a common and stable point in space. That point is referred to as the antenna reference point (ARP). For convenience, it is usually selected at the center of the bottom surface of the antenna. PC to ARP calibration tables are available on Internet for a large number of geodetic-grade antennas. For example, the National Geodetic Survey (NGS) publishes calibration tables that can be downloaded from the following URL:

https://www.ngs.noaa.gov/ANTCAL/.

The antenna naming convention in such table is the one adopted by the IGS Central Bureau.

The receiver has a similar table in its non-volatile memory. This table can be upgraded following the standard upgrade procedure as described in section 1.32 (the upgrade file is named ant_info.suf).

2.5.1 Antenna Effects in Rover Mode

If the user specifies the type of his/her antenna using the **setAntennaOffset** command, the receiver compensates for the phase center variation in all rover positioning modes. If the antenna is not specified, or the antenna type is not present in the built-in antenna calibration



file, the receiver cannot make the distinction between phase center and ARP, and the position accuracy is slightly degraded, especially in the height component.

The point to be positioned is the "marker" (see Figure 2-3). The offset between the ARP and the marker is a function of the antenna monumentation. It must be measured by the user and specified with the **setAntennaOffset** command.

The absolute position reported in the PVTCartesian and PVTGeodetic SBF blocks is always the marker position.

In DGPS or RTK modes, the receiver needs to know the type of antenna used at the base station in order to properly compensate for the phase center variation at the base. This information is typically included in the correction stream received from the base station.

The base-to-rover baseline coordinates in the <code>BaseVectorCart</code> and <code>BaseVectorGeod</code> SBF blocks is from ARP to ARP unless the receiver is not able to properly compensate for the phase center variation at base or rover. Refer to the description of the <code>BaseVectorCart</code> SBF blocks for details.

2.5.2 Antenna Effects in Base Mode

Phase center compensation always happens at the rover side. The base station sends uncompensated measurements in its differential correction messages, together with its ARP position and antenna type. The antenna type information allows the rover to apply the appropriate phase center compensation to the base measurements.

When setting up a base station, it is therefore important that the coordinates entered with the **setStaticPosGeodetic** or the **setStaticPosCartesian** commands refer to the ARP. The coordinates are encoded without change in the relevant differential correction messages. The antenna type must be provided with the **setAntennaOffset** command.

2.6 Galileo OSNMA

The receiver supports Galileo Open-Service Navigation Message Authentication (OSNMA), when enabled with the **setGalOSNMAUsage** command.

The authentication status is reported in the GALAuthStatus SBF block. The main steps involved in OSNMA authentication are summarized below.

- 1. The receiver may still need to gather initial information (e.g. public keys) from the Galileo satellites before being able to launch its authentication function. The initialization progress is reported in % in the OSNMAStatus field of GALAuthStatus. Once 100% is reached, all necessary information is available. The process of information gathering can take up to a few minutes, but is typically only needed once as the receiver stores the data in its non-volatile memory.
- 2. After initialization, the authentication process starts, indicated by the OSNMAStatus field of GALAuthStatus changing to *authenticating*. Roughly a minute after this transition, satellite authentication results are expected to become available. The ActiveMask and AuthenticMask fields indicate for which satellites authentication



is available and successful.

3. The authentication status gets reflected in the satellite status window of RxControl, as shown below.




Figure 2-4: Example OSNMA satellite status. The satellites marked with a green square are successfully authenticated.

2.6.1 Use of OSNMA in Simulated Scenarios

By default, OSNMA authentication is configured to work with live Galileo signals. In case the receiver is used in a simulated environment where the OSNMA public keys and Merkle Tree root key do not correspond with the live OSNMA keys, the following steps are needed to configure the OSNMA engine correctly:

- Determine whether an NTP server (linked to the simulator) is available. If there is one, make the receiver aware of it using the setNTPClient command. If not, disable the NTP server connection using setNTPClient, off.
- 2. When Public Key Renewal (PKR) is not available, or to speed-up the authentication process, a user can manually introduce public keys using the **setGalOSNMAPublicKeys** command.
- 3. In case the PKR feature is needed, the appropriate Merkle Tree root key needs to be introduced using the second argument of the **setGalOSNMAUsage** command. Make



sure to enable the OSNMA operation at the same time (using either the *loose* or *strict* argument).

2.7 Receiver Autonomous Integrity Monitoring (RAIM)

The receiver features RAIM to ensure the integrity of the computed position solution, provided that sufficient satellites are available. The RAIM algorithm consists of three steps: detection, identification and adaptation, or shortly "D-I-A"⁽³⁾:

- Detection: an overall model statistical test is performed to assess whether an integrity problem has occurred;
- Identification : statistical w-tests are performed on each individual measurement to assess whether it should be marked as an outlier;
- Adaptation: measurements marked as an outlier are removed from the position computation to restore the integrity of the position solution. This step is only applied if outliers have been detected in the detection step.

If the overall model statistical test fails, the RAIM module attempts to recover from the integrity failure by removing the responsible measurement(s) identified in the second step. As a consequence, the RAIM module will generally increase the continuity of integrity. The IntegrityFlag field of the RAIMStatistics SBF block reports an integrity failure if insufficient measurements remain after outlier removal (after several D-I-A steps), or if the overall model statistical test fails while no outliers can be identified. In the latter case the "sum of squared residuals too large" error is reported in the Error field of the PVT related SBF blocks.

The statistical tests assume an a-priori model of the measurement error probability distribution. As such, these tests can have the four classical outcomes in hypothesis testing, as shown in the table below (the letters A, B, C and D refer to the samples in Figure 2-5):

	no outlier	outlier present
outlier detected	False Alarm	Correct
	(type l error)	
	Α	D
	Correct	Missed Detection
no outlier detected		(type ll error)
	В	С

The RAIM module makes a correct decision in two cases: an outlier present in the data is indeed detected, and no outlier is detected when none is present. However, when no outlier is present and the RAIM module declares an outlier is present, a false alarm is triggered. When an outlier remains undetected, a missed detection occurs.



⁽³⁾ Baarda, W., A Testing Procedure For Use in Geodetic Networks, Netherlands Geodetic Commission, Publ. On Geodesy, Vol.2, no. 5, 1968



The probability computations are based on the assumption that the residuals are distributed as a Normal distribution (central if there is no outlier, and non-central if there is one), as illustrated in Figure 2-5.




Figure 2-5: Statistical test outcomes.

Samples corresponding to the four test outcomes are represented in Figure 2-5: samples A and B are from the unbiased measurement distribution, while samples C and D are from a biased measurement distribution corresponding to an outlier. Since sample A is larger than the test threshold, it will be incorrectly flagged as an outlier (false alarm). Sample C is not detected as an outlier although it is part of the biased distribution (missed detection). The acceptable probability of false alarm and the probability of missed detection for the application must be determined and provided to the receiver. This is the purpose of the **setRAIMLevels** command.

2.7.1 Integrity Algorithm

Two kinds of statistical tests are performed: the detection step uses an *overall model* test to evaluate the integrity of the position solution as a whole, and the identification step uses the *w*-test (also known as "datasnooping") to evaluate the integrity of individual measurements. Depending on the positioning mode, the overall model test is computed for range, range-rate and/or phase measurements simultaneously, while the *w*-test is computed for each range, range rate and/or phase measurement individually. Both the overall model and the *w*-tests are of the *Generalized Likelihood Ratio Test* type.

The overall model test uses the weighted sum of the squared residuals as test statistic. This test statistic is distributed as a χ^2 distribution with r degrees of freedom, where r is the redundancy number equal to the number of satellites used in the position computation minus 4. The test reads:

$$\sigma^2 = \overline{e}^T Q_y^{-1} \overline{e} > \chi_\alpha^2(r,0)$$

where:

- σ^2 is the overall model test statistic;
- \overline{e} is the vector of residuals;
- + $Q_{\underline{y}}$ is the variance-covariance matrix of the measurements;
- $\chi^2_{\alpha}(r,0)$ is the test threshold yielding a probability α of false alarm.



The probability of false alarm of the overall model test is selectable by the user with the *ModelReliability* argument of the **setRAIMLevels** command.

If the overall model test statistic is lower than the test threshold, the test is passed and the integrity is guarantueed under the statistical assumptions specified by the **setRAIMLevels** command.

If the overall model test statistic is higher than the threshold, the test is rejected. In this case, the identification step will attempt to identify the measurement responsible for the rejection using the *w*-test discussed below. After removal of the responsible outlier(s), the overall model test statistic is recomputed to verify the integrity of the solution without the outlier present. This iterative process continues until either the overall model test along with the associated *w*-tests are accepted, or until the *w*-tests for each individual measurement are accepted with a rejected overall model test. In the latter case an integrity loss is declared; in the former case integrity is available. Note that under extreme circumstances the interactive D-l-A process can also halt due to insufficient available measurements for testing, after removal of outliers. In this case the "too many outliers" error is reported in the PVT related SBF blocks.

For the evaluation of the w-test statistic, the following inequality is verified:

$$-k_{\alpha}^{1/2} < w_i = \frac{e_i}{\sigma_{e_i}} < +k_{\alpha}^{1/2}$$

where:

- *w_i* is the *w*-test statistic for the *i*th satellite;
- *e_i* is the residual for the *i*th satellite;
- σ_{e_i} is the standard deviation of the residual for the *i*th satellite;
- $k_{\alpha}^{1/2}$ is the test threshold yielding a probability α of false alarm.

The probability of false alarm of the *w*-test is selectable by the user with the *Pfa* argument of the **setRAIMLevels** command.

The test threshold is computed by the receiver with the assumption that the w-test statistic is distributed as a Normal distribution. For instance, if Pfa is set to 10%, residuals larger than 1.64 sigma are flagged as outliers. If Pfa is 0.01% the threshold will be 3.89.

2.7.2 Internal and External Reliability Levels

To assess the impact of undetected measurement errors on the computed position, the minimal detectable bias (MDB) in the range domain is computed and propagated to the position domain.

The MDB describes the internal reliability of the corresponding *w*-test. It is a measure of the range error that can be detected with a given probability of missed detection. It is computed as follows for each satellite (neglecting the probability that the biased measurement falls on the left-hand side of the non-biased distribution shown in Figure 2-5):



$$MDB_{i} = \sigma_{y_{i}} \left(\frac{\lambda_{0}}{(1 - \frac{\sigma_{\hat{y}_{i}}^{2}}{\sigma_{y_{i}}^{2}})} \right)^{1/2}$$

where:

- σ_{y_i} is the standard deviation of the range measurement of the *i*th satellite;
- $\sigma_{\hat{y}_i}$ is the standard deviation of the estimator for the (measured) range of the *i*th satellite:
- λ_0 is the non-centrality parameter, which depends upon the probability of false alarm of the *w*-test and the probability of missed detection.

The user can select the probability of missed detection acceptable for his/her application with the *Pmd* argument of the **setRAIMLevels** command.


The external reliability is defined as the influence of a model error of size MDB on the user position. It is computed by propagating the MDB for each satellite to the position domain, taking the satellite geometry into account. The receiver computes a distinct external reliability level (XERL) for the horizontal and the vertical components (referred to as HERL and VERL respectively). These values should be compared to the alarm threshold of your specific application in order to verify if the position solution is adequate for that application.

Detailed results of the RAIM algorithm are available in the RAIMStatistics and the PVTResiduals SBF blocks and in the GBS NMEA message.



Chapter 3

Command Line Reference



3.1 Command Line Interface Outline

The receiver outputs a prompt when it is ready to accept a user command. The prompt is of the form:

CD>

where CD is the connection descriptor of the current connection, e.g. COM1 (see section1.1.5).

The prompt indicates the termination of the processing of a given command. When sending multiple commands to the receiver, it is necessary to wait for the prompt between each command.

Sometimes a connection is not configured to accept user commands, for example because it is put into differential correction input mode. A way to force a connection to accept commands is to send a succession of ten "S" characters to that connection and then to press the enter key (SSSSSSSSSCR>). See also the description of the **setDataInOut** command.

3.1.1 Command Types

Most commands fall into one of the following categories:

set-commands to change one or more configuration parameters;

get-commands to get the current value of one or more configuration parameters;

exe-commands to initiate some action;

1st-commands to retrieve the contents of internal files or list the commands.

Each **set**-command has its **get**-counterpart, but the opposite is not true. For instance, the **setNMEAOutput** command has a corresponding **getNMEAOutput**, but **getReceiverCapabilities** has no **set**-counterpart. Each **exe**-command also has its **get**-counterpart which can be used to retrieve the parameters of the last invocation of the command.

3.1.2 Command Line Syntax

Each ASCII command line consists of a command name optionally followed by a list of arguments and terminated by <CR>, <LF> or <CR><LF> character(s) usually corresponding to pressing the "Enter" key on the keyboard.

To minimize typing effort when sending commands by hand, the command name can be replaced by its 3-5 character mnemonic. For instance, grc can be used instead of getReceiverCapabilities.

The receiver is case insensitive when interpreting a command line.



The maximum length of any ASCII command line is 2000 characters.

For commands requiring arguments, the comma "," must be used to separate the arguments from each other and from the command's name. Any number of spaces can be inserted before and after the comma.

Each argument of a **set**-command corresponds to a single configuration parameter in the receiver. Usually, each of these configuration parameters can be set independently of the others, so most of the **set**-command's arguments are optional. Optional arguments can be omitted but if omitted arguments are followed by non-omitted ones, a corresponding number of commas must be entered. Omitted arguments always keep their current value.

3.1.3 Command Replies

The reply to ASCII commands always starts with "\$R" and ends with <CR><LF> followed by the prompt corresponding to the connection descriptor you are connected to.

The following types of replies are defined for ASCII commands:

• For comment lines (user input beginning with "#") or empty commands (just pressing "Enter"), the receiver replies with the prompt.

```
COM1> # This is a comment! <CR>
COM1>
```

- For invalid commands, the reply is an error message, always beginning with the keyword "\$R?" followed by an error message.
- For all valid **set**-, **get** and **exe**-commands, the first line of the reply is an exact copy of the command as entered by the user, preceded with "\$R:". One or more additional lines are printed depending on the command. These lines report the configuration of the receiver after execution of the command.

```
COM1>setNMEAOutput, stream1, com1, GGA, sec1 <CR>
$R: setNMEAOutput, stream1, com1, GGA, sec1
   NMEAOutput, stream1, com1, GGA, sec1
COM1>
```

For commands which reset or halt the receiver (e.g. **exeResetReceiver**), the reply is terminated by "STOP>" instead of the standard prompt, to indicate that no further command can be entered.

• For all valid **1st**-commands, the first line of the reply is an exact copy of the command as entered by the user, preceded with "\$R;". The second line is a pseudo-prompt "--->" and the remaining of the reply is a succession of formatted blocks, each of them starting with "\$-- BLOCK".



ASCII replies to **set-**, **get-** and **exe-**commands, including the terminating prompt, are atomic: they cannot be broken by other messages from the receivers. For the **1st-**commands, the replies may consist of several atomic formatted blocks which can be interleaved with other output data. If more than one formatted block is output for a lst-command, each of the intermediate blocks is terminated with a pseudo-prompt "———>". The normal prompt will only be used to terminate the last formatted block of the reply so that one single prompt is always associated with one command.

3.1.4 Command Syntax Tables

All ASCII commands are listed in section 3.2. Each command is introduced by a compact formal description of it called a "syntax table". Syntax tables contain a complete list of arguments with their possible values and default settings when applicable.

The conventions used in syntax tables are explained below by taking a fictitious **setCommandName** command as example. The syntax table for that command is:

scn	setCommandName	Cd	Distance	Time	Message (120)	Password (40)	Mode	PRN
gcn	getCommandName	Cd						
		+ Com1	-20.00 <u>0.00</u> 20.00	<u>1</u> 50 sec	<u>Unknown</u>		<u>on</u>	none
		+ Com2	m				off	+ G01 G32
		all						+ S120 S138
								+ SBAS
								+ GPS
								all

GUI: Navigation > Receiver Operation > Example

The associated **set**- and **get**-commands are always described in pairs, and the same holds for the associated **exe**- and **get**-commands. The command name and its equivalent 3-5 character mnemonic are printed in the first two columns. The list of arguments for the set- and get-commands is listed in the first and second row respectively. In our example, **setCommandName** can accept up to 6 arguments and **getCommandName** only accepts one argument. Mandatory arguments are printed in bold face. Besides the mandatory arguments, at least one of the optional arguments must be provided in the command line.

The list of possible values for each argument is printed under each of them. Default values for optional arguments are underlined.

The link printed in blue under the syntax table shows under which GUI menu the command can be found.

The fictitious command above contains all the possible argument types:

• *Cd* serves as an index for all following arguments. This can be noticed by the possibility to use this argument in the **get**-command. This argument is mandatory in the **set**-command. The accepted values are COM1, COM2 and all, corresponding to the first or second serial ports, or to both of them respectively. The "+" sign before the first two values indicates that they can be combined to address both serial ports in the same command.



Examples: COM1, COM1+COM2, all (which is actually an alias for COM1+COM2).

• *Distance* is a number between -20 and 20 with a default value of 0, and up to 2 decimal digits. An error is returned if more digits are provided. The "m" indicates that the value is expressed in meters. Note that this "m" should not be typed when entering the command.

```
Examples: 20, 10.3, -2.34
```

• *Time* is a number between 1 and 50, with no decimal digit (i.e. this is an integer value). This value is expressed in seconds.

```
Examples: 1, 10
```

• *Message* is a string with a maximum length of 120 characters. The default value of that argument is "Unknown". When spaces must to be used, the string has to be put between quotes and these enclosing quotes are not considered part of the string. The list of allowed characters in strings is:

```
ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789 !#%@()*+-./:;<=>?[\]^_`{|}~
```

```
Example: "Hello World!"
```

- Password is a password argument with a maximum length of 20 characters (40/2). Password arguments are always named Password or Key. Only half of the total password length is available to the user, the other half being reserved by the system. Passwords are obfuscated by the receiver so that they cannot be read back in command replies. In addition to the characters above (see the Message argument), special characters are allowed in passwords using the corresponding escape sequence:
 - Type %%DQ to obtain "
 - Type %%SQ to obtain '
 - Type %%DL to obtain \$
 - Type %%AM to obtain &
 - Type %%CM to obtain,

Example: "ab%%AM123"

• *Mode* is a range of individual values that cannot be combined (they are not preceded by a "+" sign). Either off or on can be selected for that argument and the default value is on.

Example: on



• *PRN* is a range of values that can be combined together with the "+" sign. The default value GPS is an alias for G01+G02+ . . . +G32, SBAS is an alias for S120+ . . . +S138 and all an alias for GPS+SBAS. A "+" sign can be set before the argument to indicate to add the specified value(s) to the current list. If the value "none" is supported (which is the case in this example), a "-" sign can be set before the argument to remove the specified value(s) from the current list. It is possible to add or remove multiple values at once by "adding" or "subtracting" them with the "+" or "-" operator. However, "+" and "-" can never be combined in a single argument.

Examples: G01+G02, +G03, GPS+S120, +G04+G05, -S122-S123, -GPS



3.2 Command Definitions

3.2.1 Receiver Administration

lai	IstAntennalnfo	Antenna				
		Overview				
		Main				
		[antenna name]				

Use this command with the argument *Antenna* set to Overview to get a list of all antenna names for which the receiver knows the phase center variation parameters (see section 2.5).

Use this command with the argument *Antenna* set to one of the antenna names returned by **lstAntennaInfo**, **Overview** to retrieve the complete phase center variation parameters for that particular antenna. Do not forget to enclose the name between double quotes if it contains whitespaces.

Using the values Main will return the phase center variation parameters corresponding to the main antenna type as specified in the command **setAntennaOffset**.

```
COM1> lai, Overview <CR>
$R; lai, Overview
<?xml version="1.0" encoding="ISO-8859-1" ?>
<AntennaInfo version="0.1">
  <Antenna ID="AERAT1675 29</pre>
                              NONE"/>
 <Antenna ID="AERAT2775_150 NONE"/>
 <Antenna ID="AERAT2775_159</pre>
                                    "/>
  <Antenna ID="AERAT2775_159</pre>
                                SPKE"/>
  <Antenna ID="AERAT2775_160</pre>
                                    "/>
                                    "/>
  <Antenna ID="TRM_R8_GNSS</pre>
</AntennaInfo>
COM1>
COM1> lai, "AERAT2775_159 SPKE"<CR>
$R; lai, "AERAT2775_159 SPKE"
<?xml version="1.0" encoding="ISO-8859-1" ?>
<AntennaInfo version="0.1">
  <Antenna ID="AERAT2775_159 SPKE"/>
    <L1>
      <offset north="0.4" east="0.1" up="77.2"/>
      <phase elevation="90" value="0.0"/>
      <phase elevation="85" value="-0.2"/>
      <phase elevation=" 5" value="0.0"/>
      <phase elevation=" 0" value="0.0"/>
    </L2>
</AntennaInfo>
COM1>
```



hel	IstCommandHelp	Action (255)				
		Overview				

Use this command to retrieve a short description of the ASCII command-line interface.

When invoking this command with the Overview argument, the receiver returns the list of all supported **set**-, **get**- and **exe**-commands. The **lstCommandHelp** command can also be called with any supported **set**-, **get**- or **exe**-command (the full name or the mnemonic) as argument.

The reply to this command is free-formatted and subject to change in future versions of the receiver's software. This command is designed to be used by human users. When building software applications, it is recommended to use the formal **lstMIBDescription**.

```
COM1> help, Overview <CR>
$R; help, Overview
$-- BLOCK 1 / 0
MENU: communication
  GROUP: ioSelection
    sdio, setDataInOut
   gdio, getDataInOut
COM1>
COM1> help, getReceiverCapabilities <CR>
$R; help, getReceiverCapabilities
... Here comes a description of getReceiverCapabilities ...
COM1>
COM1> help, grc <CR>
$R; help, grc
... Here comes a description of getReceiverCapabilities ...
COM1>
```





lcf	IstConfigFile	File				
		Current				
		Boot				
		RxDefault				
		User1				
		User2				

Use this command to list the contents of a configuration file. A configuration file contains the list of user commands needed to bring the receiver from factory default to a certain non-default configuration.

The following configuration files are available:

File	Description
Current	The current configuration.
Boot	The configuration that is loaded at boot time, after a power cycle or after a hard reset (see also the exeResetReceiver command).
RxDefault	The default configuration.
User1	A user-defined configuration.
User2	A user-defined configuration.

See also the related **exeCopyConfigFile** command to learn how to manage configuration files.

```
COM1> smp, TestMarker <CR>
$R: smp, TestMarker
  MarkerParameters, "TestMarker"

COM1> lcf, Current <CR>
$R; lcf, Current
$-- BLOCK 1 / 1
  setMarkerParameters, "TestMarker"

COM1>
```





eccf	exeCopyConfigFile	Source	Target				
gccf	getCopyConfigFile						
		Current	Current				
		Boot	Boot				
		User1	User1				
		User2	User2				
		RxDefault					

RxControl: File > Copy Configuration

Use this command to manage the configuration files. See the **lstConfigFile** command for a description of the different configuration files.

With this command, the user can copy configurations files into other configuration files. For instance, copying the Current file into the Boot file makes that the receiver will always boot in the current configuration.

Examples

To save the current configuration in the Boot file, use:

```
COM1> eccf, Current, Boot <CR>
$R: eccf, Current, Boot
   CopyConfigFile, Current, Boot
COM1>
```

To load the configuration stored in User1, use:

```
COM1> eccf, User1, Current <CR>
$R: eccf, User1, Current
   CopyConfigFile, User1, Current
COM1>
```





setEthernetMode getEthernetMode	Enable				
	off on				
	<u> </u>				

RxControl: Communication > Network Settings > General

Use this command to turn the Ethernet interface on or off.



Before turning Ethernet off, make sure that the receiver will still be accessible through another interface (serial, USB,...). This is especially important for remote receivers. It will not be possible to access the receiver over Ethernet after invoking the **setEthernetMode**, **off** command.

```
COM1> seth, on<CR>
$R: seth, on
  EthernetMode, on
COM1>
```





efup	exeFTPUpgrade	Server (32)	Path (64)	Login (12)	Password (24)			
gfup	getFTPUpgrade							
				anonymous				

RxControl: File > Upgrade Receiver using FTP

Use this command to upgrade the receiver by fetching the upgrade file from an FTP server. The arguments specify the FTP server, the path to the upgrade file (.SUF format), and the login and password to use.

This procedure always resets the receiver, even if the upgrade file does not exist.

Before resetting, the receiver broadcasts a "\$TE ResetReceiver" message to all active communication ports, to inform all users of the imminent reset.

After a reset, the user may have to adapt the communication settings of his/her terminal program as they may be reset to their default values.





sgpf	setGPIOFunctionality	GPPin	Mode	Input	Output			
ggpf	getGPIOFunctionality	GPPin						
		+ GP1	Output	<u>none</u>	<u>LevelLow</u>			
		+ GP2			LevelHigh			
		all						

RxControl: Navigation > Receiver Operation > GPIO

Use these commands to define/inquire the functionality assigned to every GPIO pin.

Currently, only the output pins (GPx) can be controlled by this command, and the *Mode* and *Input* arguments can only take the values Output and none respectively. The argument *Output* sets the electrical level to be applied to the pin specified in *GPPin*.

In housed products, the number of GPIO pins configurable by this command is larger than the number of GPIO pins available to the user. The extra pins are used for internal purposes, and their settings should not be modified. Please refer to the Hardware Manual or the User Manual of your product to check which GPIO pins are available.

Example

To set the signal on GP2 to a logical 1, use:

```
COM1> sgpf, GP2, Output, , LevelHigh <CR>
$R: sgpf, GP2, Output, , LevelHigh
   GPIOFunctionality, GP2, Output, none, LevelHigh
COM1>
```





lif	IstInternalFile	File				
		Permissions				
		Identification				
		Debug				
		Error				
		SisError				
		DiffCorrError				
		SetupError				
		LBAS1Access				
		LBAS1Subscr				
		IPParameters				
		RxMessages				

Use this command to retrieve the contents of one of the receiver internal files:

File	Description
Permissions	List of permitted options in your receiver.
Identification	Information about the different components being part of the receiver (e.g. serial number, firmware version, etc.).
Debug	Program flow information that can help support engineers to debug certain issues.
Error	Last internal error reports.
SisError	Last detected signal-in-space anomalies.
DiffCorrError	Last detected anomalies in the incoming differential correction streams.
SetupError	Last detected anomalies in the receiver setup.
LBAS1Access	LBAS1 (L-Band Augmentation Service 1) Access information.
LBAS1Subscr	LBAS1 (L-Band Augmentation Service 1) Subscription status.
IPParameters	Hostname, MAC and IP addresses, DNS addresses, netmask and gateway.
RxMessages	Event log from the receiver. This is the list of the recent event log messages. These messages are also available in the RxMessage SBF block.

```
COM1> lif, Permissions <CR>
$R; lif, Permissions
---->
$-- BLOCK 1 / 1
... here follows the permission file ...
COM1>
```





slm		GPLED				
glm	getLEDMode					
		DIFFCORLED				
		LOGLED				

RxControl: Navigation > Receiver Operation > GPIO

Use this command to define/inquire the blinking mode of the General Purpose LED(s).

The different LED blinking modes are described in the Hardware Manual or in the User Manual of your receiver.

Example

COM1> slm, DIFFCORLED <CR>
\$R: slm, DIFFCORLED
 LEDMode, DIFFCORLED
COM1>





lmd	IstMIBDescription	File (255)				
		Overview SBFTable				

Use this command to retrieve the ASN.1-compliant syntax of the user command interface. The name of the command refers to the MIB (Management Information Base), which holds the whole receiver configuration. There is a one-to-one relationship between the formal MIB description and the ASCII command-line interface for all exe-, get- and set-commands.

When the value Overview is used, the general syntax of the interface is returned. With the value SBFTable, the receiver will output the list of supported SBF blocks and whether they can be output at a user-selectable rate or not. The **lstMIBDescription** command can also be called with every supported **set**-, **get**- or **exe**-command (the full name or the mnemonic) as argument.

No formal description of the lst-commands can be retrieved with lstMIBDescription.

```
COM1> lmd, Overview <CR>
$R; lmd, Overview
... Here comes the generic command syntax ...
COM1>

COM1> lmd, grc <CR>
$R; lmd, grc
... Here comes the description of getReceiverCapabilities ...
COM1>
```





grc	getReceiverCapabilities					

RxControl: Help > Receiver Interface > Permitted Capabilities

Use this command to retrieve the so-called "capabilities" of your receiver. The first returned value is the list of supported antenna(s), followed by the list of supported signals, the list of available communication ports and the list of enabled features.

The three values at the end of the reply line correspond to the default measurement interval, the default PVT interval and the default integrated INS/GNSS interval respectively. This is the interval at which the corresponding SBF blocks are output when the OnChange rate is selected with the **setSBFOutput** command. These values are expressed in milliseconds.

Each of the above-mentioned lists contain one or more of the elements in the tables below.

Antennas	Description
Main	The receiver's main antenna.

Signals	Description
GPSL1CA	GPS L1 C/A signal.
GPSL1PY	GPS L1 P(Y) signal.
GPSL2PY	GPS L2 P(Y) signal.
GPSL2C	GPS L2 C signal.
GPSL5	GPS L5 signal.
GPSL1C	GPS L1C signal.
GLOL1CA	GLONASS L1 C/A signal.
GLOL1P	GLONASS L1 P signal.
GLOL2P	GLONASS L2 P signal.
GLOL2CA	GLONASS L2 C/A signal.
GLOL3	GLONASS L3 signal.
GALL1BC	Galileo L1 BC signal.
GALE6BC	Galileo E6 BC signal.
GALE5a	Galileo E5a signal.
GALE5b	Galileo E5b signal.
GALE5	Galileo E5 AltBOC signal.
GEOL1	SBAS L1 C/A signal.
GEOL5	SBAS L5 signal.
BDSB1I	BeiDou B1I signal.
BDSB2I	BeiDou B2I signal.
BDSB3I	BeiDou B3I signal.
BDSB1C	BeiDou B1C signal.
BDSB2a	BeiDou B2a signal.



Signals (Continued)	Description
BDSB2b	BeiDou B2b signal.
QZSL1CA	QZSS L1 C/A signal.
QZSL2C	QZSS L2 C signal.
QZSL5	QZSS L5 signal.
QZSL6	QZSS L6 signal.
QZSL1C	QZSS L1C signal.
QZSL1S	QZSS L1S signal.
QZSL5S	QZSS L5S signal.
QZSL1CB	QZSS L1 C/B signal.
LBAND	MSS L-Band signal.
NAVICL5	NavIC/IRNSS L5 signal.

ComPorts	Description
COM1	Serial port 1.
COM2	Serial port 2.
COM3	Serial port 3.
COM4	Serial port 4.
USB1	USB-device virtual serial port 1.
USB2	USB-device virtual serial port 2.
IP10	TCP/IP port 1.
IP11	TCP/IP port 2.
IP12	TCP/IP port 3.
IP13	TCP/IP port 4.
IP14	TCP/IP port 5.
IP15	TCP/IP port 6.
IP16	TCP/IP port 7.
IP17	TCP/IP port 8.
NTR1	NTRIP port 1.
NTR2	NTRIP port 2.
NTR3	NTRIP port 3.
IPS1	IP Server port 1.
IPS2	IP Server port 2.
IPS3	IP Server port 3.
IPS4	IP Server port 4.
IPS5	IP Server port 5.
IPR1	IP Receive port 1.
IPR2	IP Receive port 2.
IPR3	IP Receive port 3.



Capabilities	Description
SBAS	Positioning with SBAS corrections.
DGPSRover	Positioning with DGPS corrections.
DGPSBase	Generation of DGPS corrections.
RTKRover	Positioning with RTK corrections.
RTKBase	Generation of RTK corrections.
RTCMv23	Generation/decoding of RTCM v2.3 corrections.
RTCMv3x	Generation/decoding of RTCM v3.x corrections.
CMRv20	Generation/decoding of CMR v2.0 corrections.
TimeSync	Internal clock synchronisation to external PPS signal.
xPPSOutput	Generation of xPPS output signal.
TimedEvent	Accurate time mark of event signals.
InternalLogging	Internal logging.
APME	A-Posteriori Multipath Estimator.
RAIM	Receiver Autonomous Integrity Monitoring.
PPPLand	PPP through Wide Area Augmentation Service for land based use.
LBAS1L	L Band Augmentation data Service 1 Land only.
MeasAv	Measurement availability.
IM	Interference mitigation.
WiFi	WiFi.
Bat	Battery.



gri	getReceiverInterface	Item				
		+ RxName				
		+ SNMPLanguage + SNMPVersion				
		all				

RxControl: Help > Receiver Interface > Interface Version

Use this command to retrieve the version of the receiver command-line interface. The reply to this command is a subset of the reply returned by the **lstInternalFile**, **Identification** command.

```
COM1> gri <CR>
$R: gri
  ReceiverInterface, RxName, AsteRx1
  ReceiverInterface, SNMPLanguage, English
  ReceiverInterface, SNMPVersion, 20060308
COM1>
```





era	exeRegisteredApplications	Cd	Application (12)				
gra	getRegisteredApplications	Cd					
		+COM1	<u>Unknown</u>				
		+COM2					
		+COM3					
		+COM4					
		+USB1					
		+USB2					
		+ IP10 IP17					
		all					

RxControl: Communication > Registration

Use these commands to define/inquire the name of the application that is currently using a given connection descriptor (Cd - see 1.1.5).

Registering an application name for a connection does not affect the receiver operation, and is done on a voluntary basis. Application registration can be useful to developers of external applications when more than one application is to communicate with the receiver concurrently. Whether or not this command is used, and the way it is used is up to the developers of external applications.

```
COM1> era, com1, MyApp <CR>
$R: era, com1, MyApp

RegisteredApplications, COM1, "MyApp"

RegisteredApplications, COM2, "Unknown"

RegisteredApplications, COM3, "Unknown"

RegisteredApplications, USB1, "Unknown"

RegisteredApplications, USB2, "Unknown"

COM1>
```





erst	exeResetReceiver	Level	EraseMemory				
grst	getResetReceiver						
		Soft	none				
		<u>Hard</u>	+ Config				
		Upgrade	+ PVTData				
			+ SatData				
			+ BaseStations				
			+ WiFiAccessPoints				
			+ HTTPSCertificate				
			+ SISAuthData				
			all				

RxControl: File > Reset Receiver

Use this command to reset the receiver and to erase some previously stored data. The first argument specifies which level of reset you want to execute:

Level	Description
Soft	This is a reset of the receiver's firmware. After a few seconds, the receiver will restart operating in the same configuration as before the command was issued, unless the "Config" value is specified in the second argument.
Hard	This is similar to a power off/on sequence. After hardware reset, the receiver will use the configuration saved in the boot configuration file.
Upgrade	Set the receiver into upgrade mode. After a few seconds, the receiver is ready to accept an upgrade file (SUF format) from any of its connections.

The second argument specifies which part of the non-volatile memory should be erased during the reset. The following table contains the possible values for the *EraseMemory* argument:

EraseMemory	Description					
Config	The receiver's configuration is reset to the factory default, with the following exceptions.					
	The IP settings set by the setIPSettings and setIPPortSettings commands keep their value.					
	The UHF table set by the setUHFChannelTable command is maintained.					
	After reset, the Current and Boot configuration files are erased (see the exeCopyConfigFile command), but the User1 and User2 configuration files are kept unchanged.					
PVTData	The latest computed PVT data stored in non-volatile memory is erased.					
SatData	All satellite navigation data (ephemeris, almanac, ionosphere parameters, UTC,) stored in non-volatile memory is erased.					
BaseStations	All base stations stored in non-volatile memory are erased.					



EraseMemory (Continued)	Description
WiFiAccessPoints	The list of known WiFi access points is erased (see the exeAddWiFiAccessPoint command).
	Remove current HTTPS certificate. It will be replaced by a self-signed certificate at boot.
SISAuthData	Remove stored OSNMA data (PKR - Public Keys, floating KROOT)

Before resetting, the receiver broadcasts a "\$TE ResetReceiver" message to all active communication ports, to inform all users of the imminent reset.

After a reset, the user may have to adapt the communication settings of his/her terminal program as they may be reset to their default values.

Example

COM1> erst, soft, none <CR>
\$R: erst, soft, none
 ResetReceiver, Soft, none
STOP>
\$TE ResetReceiver Soft
STOP>



suia guia	setUSBInternetAccess getUSBInternetAccess	Enable				
		off on				

RxControl: Communication > Network Settings > General

Use this command to enable or disable outgoing network access over USB.

If enabled, the receiver will attempt to obtain an IP address via DHCP over the USB connection. It will then be able to access the Internet through that connection, allowing, for example, to communicate with a NTRIP server. Note that this requires that Internet sharing is enabled on the computer attached to the receiver.

The IP address assigned to the receiver can be retrieved from the lstInternalFile, IPParameters command.

See also section 1.1.3.3.

```
COM1> suia, on<CR>
$R: suia, on
   USBInternetAccess, on
COM1>
```



3.2.2 Standby and Sleep Configuration

epwm	exePowerMode	Mode				
gpwm	getPowerMode					
		ScheduledSleep				
		StandBy				
		-				

RxControl: File > Power Mode > Shut Down

Use this command to set the receiver in sleep or standby mode, in which it consumes only a fraction of its normal operational power.

When in standby mode, the receiver can be awoken by sending the appropriate signal to one of its input pins (see the receiver Hardware Manual or User Manual for details).

With the ScheduledSleep option, the receiver automatically sleeps and wakes up at regular intervals. This functionality is controlled by the **setWakeUpInterval** command.

Upon waking up, the receiver applies the configuration that is stored in the boot configuration file (see the **lstConfigFile** command).

Before entering standby mode, the receiver broadcasts a "\$TE PowerMode" message to all active communication ports, to inform all users of the imminent halt.

```
COM1> epwm, Standby <CR>
$R: epwm, Standby
   PowerMode, StandBy
STOP>
$TE PowerMode Standby
STOP>
```





spth	setPowerThresholds	ExtPowerSupply				
gpth	getPowerThresholds					
		<u>0.0</u> 30.0 V				

RxControl: File > Power Mode > Monitoring

This command sets the supply voltage level at which the receiver enters power-saving mode. It is to be used in conjunction with the **setStandbyMonitoring** command.

When the supply voltage (e.g. from an external battery) drops below the threshold set with the <code>ExtPowerSupply</code> argument, the receiver enters low-power sleep mode for a duration given by the <code>setStandbyMonitoring</code> command. At the end of this duration, the receiver wakes up and either resumes operation normally if the supply voltage is sufficient, or otherwise returns into sleep mode.

Each time the receiver wakes up, it applies the boot configuration. For the receiver to wake up in the current configuration, it has to be saved in the boot configuration with the **exeCopyConfigFile** command. When the condition to go to sleep is met at the time the **setPowerThresholds** command is entered, the user has 30 seconds to save the configuration before the receiver goes to sleep.

When the *ExtPowerSupply* argument of this command is zero, or when the *StandbyPeriod* argument of **setStandbyMonitoring** is zero, the voltage threshold is not monitored.

Note that only the voltage of the main PWR connector is monitored. If the receiver is powered over Ethernet (PoE), the voltage monitoring is not applicable.

Example

If you want the receiver to go to sleep for an hour each time the external power supply drops below 11.4V, use:

```
COM1> ssm, 3600 <CR>
$R: ssm, 3600
StandbyMonitoring, 3600

COM1> spth, 11.4 <CR>
$R: spth, 11.4
PowerThresholds, 11.4

COM1> eccf, Current, Boot <CR>
$R: eccf, Current, Boot
CopyConfigFile, Current, Boot
COM1>
```





ssm	setStandbyMonitoring	StandbyPeriod				
gsm	getStandbyMonitoring					
		<u>0</u> 15724800 s				

RxControl: File > Power Mode > Monitoring

This command is to be used in conjunction with the **setPowerThresholds** command. It specifies the sleep duration when the supply voltage drops below the level set with **setPowerThresholds**.

When the supply voltage (e.g. from an external battery) drops below the threshold set with **setPowerThresholds**, the receiver enters low-power sleep mode for a duration given by the *StandbyPeriod* argument. At the end of this duration, the receiver wakes up and either resumes operation normally if the supply voltage is sufficient, or otherwise returns into sleep after about 30 seconds for a new *StandbyPeriod* duration.

This power-monitoring and -saving feature is enabled if both the *StandbyPeriod* argument of this command and the *ExtPowerSupply* argument of the **setPowerThresholds** command are different from zero.

Note that power monitoring can be enabled together with the scheduled sleep feature (see the **exePowerMode** command). In that case, the scheduled-sleep pattern will be interrupted for at least *StandbyPeriod* when the supply voltage drops under the threshold.

Example

If you want the receiver to go to sleep for an hour each time the external power supply drops below 11.4V, use:

```
COM1> ssm, 3600 <CR>
$R: ssm, 3600
   StandbyMonitoring, 3600

COM1> spth, 11.4 <CR>
$R: spth, 11.4
   PowerThresholds, 11.4

COM1> eccf, Current, Boot <CR>
$R: eccf, Current, Boot
   CopyConfigFile, Current, Boot
COM1>
```





swui	setWakeUpInterval	WakeUpTime (30)	AwakeDuration	RepetitionPeriod			
gwui	getWakeUpInterval						
	2	2000-01-01 00:00:00	<u>0</u> 604800 s	<u>0</u> 604800 s			

RxControl: File > Power Mode > Scheduling

This command can be used to set up an automatic receiver awake/sleep pattern. It is possible to order the receiver to wake up at a given time, for a certain period, and/or at regular intervals. A possible application is keeping fast time-to-first-fix even after days in sleep mode. This can be done by waking up the receiver every few hours for a few minutes, such that it can regularly refresh its ephemerides.

The *WakeUpTime* argument defines the epoch when the receiver should automatically wake up the first time. It also serves as reference epoch for the *RepetitionPeriod* argument. It refers to the GPS time scale. The format of the *WakeUpTime* argument is "YYYY-MM-DD hh:mm:ss".

The AwakeDuration argument defines the period for which the receiver should stay awake. If this argument is set to 0 (the default value), the receiver will remain awake indefinitely.

The *RepetitionPeriod* can be used to repeat the awake/sleep pattern at regular interval. *RepetitionPeriod* should be at least 5 seconds longer than *AwakeDuration* to allow a minimum sleep time of 5 seconds between awake periods. If *RepetitionPeriod* is set to a value smaller than *AwakeDuration*, the repetition functionality is disabled.

Be aware that the receiver must know the time to automatically go into sleep mode: if no antenna is connected to the receiver or if not enough satellites could be tracked after boot, the receiver will continue operating beyond its prescribed awake duration, and only possibly enter sleep mode at the next scheduled "go-to-sleep" epoch, if any.

To force the receiver to go into sleep mode immediately, use the command **exePowerMode**, **ScheduledSleep** instead.

If interaction with the receiver is needed during the sleep period, the user can always force the receiver to wake up by hardware means. See the receiver Hardware Manual or User Manual for details. When maintenance is done, the user should put the receiver back in sleep mode by typing <code>exePowerMode</code>, <code>ScheduledSleep</code>. This does not perturb the awake/sleep pattern: the receiver will continue to automatically wake up at the next wake-up epoch.

Each time the receiver wakes up, it applies the boot configuration. For the receiver to wake up in the current configuration, it has to be saved in the boot configuration with the <code>exeCopyConfigFile</code> command. In particular, when using the repetitive awake/sleep pattern, the command <code>exeCopyConfigFile</code>, <code>current</code>, <code>boot</code> must be entered before the first time that the receiver enters sleep mode. This is to make sure that the awake/sleep pattern configuration is not lost during the sleep periods.

Examples

If you want the receiver waking up on December 31, 2012 at 23h00 for 2 hours, use:

```
COM1> swui, "2012-12-31 23:0:0", 7200 <CR>
$R: swui, "2012-12-31 23:0:0", 7200
    WakeUpInterval, "2012-12-31 23:00:00", 7200, 0
COM1>
```



If you want to set up an automatic wake up every day at midnight for 1 hour, use:

COM1> swui, , 3600, 86400 <CR>
\$R: swui, , 3600, 86400
 WakeUpInterval, "2000-01-01 00:00:00", 3600, 86400
COM1> eccf, Current, Boot <CR>
\$R: eccf, Current, Boot
 CopyConfigFile, Current, Boot
COM1>



3.2.3 User Management

lcu	IstCurrentUser					

Use this command to check which user is currently logged in on this port, if any. See also the **login** command.

```
COM1> lcu <CR>
$R! lstCurrentUser
  Not logged in.
COM1> login, admin, admin <CR>
$R! LogIn
  User admin logged in.
COM1> lcu <CR>
$R! lstCurrentUser
  Logged in as admin.
COM1>
```



sdal	setDefaultAccessLevel	Web	FileTransfer	lp	Com	Usb		
gdal	getDefaultAccessLevel							
		none	none	none	none	none		
		Viewer	<u>Viewer</u>	Viewer	Viewer	Viewer		
		User	User	<u>User</u>	User	<u>User</u>		

RxControl: File > User Management

This command defines what an anonymous user is authorized to do when connected to the receiver. An anonymous user is one who has not logged in with the **login** command.

The anonymous authorization level can be set independently for the different interfaces.

For all arguments except *FileTransfer*, setting the authorization level to User grants full control of the receiver to the anonymous user connected through the corresponding connection. The Viewer level allows the anonymous user to view the receiver configuration without changing it (i.e. to only issue **get**-commands). none prevents anonymous users from viewing or changing the configuration.

For the *FileTransfer* argument, <code>Viewer</code> means that the anonymous user is allowed to download log files from the receiver using FTP, SFTP or <code>rsync</code>, but not to delete them. <code>User</code> means that the anonymous user can both download and delete files, and <code>none</code> disables anonymous accesses.

To perform actions not allowed to anonymous users, you first need to authenticate yourself by entering a *UserName* and *Password* through the **login** command.

See also the commands **setUserAccessLevel** to learn how to define user accounts.

This command does not change the status of existing connections. For example, for *Com* or *Usb* connections, it will only take effect after a reset.

```
COM1> sdal, none, Viewer, Viewer, Viewer, Viewer<CR>
$R: sdal, none, Viewer, Viewer, Viewer, Viewer
   DefaultAccessLevel, none, Viewer, Viewer, Viewer, Viewer
COM1>
```





login	LogIn	UserName (16)	Password (32)				

Use this command to authenticate yourself. When initially connecting to the receiver, a user is considered "anonymous". The level of control granted to anonymous users is defined by the command **setDefaultAccessLevel**.

To perform actions not allowed to anonymous users, you need to authenticate yourself by entering a *UserName* and *Password* through the **login** command.

The list of user names and passwords and their respective access level can be managed with the **setUserAccessLevel** command. Login fails if the provided *UserName* or *Password* is not in that list.

The **logout** command returns to unauthenticated (anonymous) access. The **lstCurrentUser** command can be invoked to find out which user is logged in on the current port.

It is not necessary to log out before logging in as a different user.

Examples

To log in as user "admin" with password "admin", use

```
COM1> login, admin, admin <CR>
$R! LogIn
  User admin logged in.
COM1>
```

Logging in with a wrong username or password gives an error:

```
COM1> login, foo, foo <CR>
$R? LogIn: Wrong username or password!
COM1>
```

If the user does not have sufficient access right, some commands may give an error:

```
COM1> sso, Stream1, COM1, MeasEpoch, sec1 <CR>
$R? SBFOutput: Not authorized!
COM1>
```





logout	LogOut					

Use this command to return to anonymous access. It is the reverse of login.

Example

The following sequence of commands logs in as user "admin" with password "admin", reconfigures SBF output, and logs out again:

```
COM1> login, admin, admin <CR>
$R! LogIn
   User admin logged in.

COM1> sso, Stream1, COM1, PVTCartesian, sec1 <CR>
$R: sso, Stream1, COM1, PVTCartesian, sec1
   SBFOutput, Stream1, COM1, PVTCartesian, sec1
COM1> logout <CR>
$R! LogOut
   User admin logged out.
COM1>
```



sual	setUserAccessLevel	UserID	UserName (16)	Password (32)	UserLevel	SSHKey (232)		
gual	getUserAccessLevel	UserID						
		+ User1 User8			Viewer			
		all			User			

RxControl: File > User Management

Use these commands to manage the user accounts and their access rights on the receiver. Up to eight user accounts can be defined (User1 to User8).

Each user is identified with a *UserName* and *Password*, and has a certain level of acces (*UserLevel*). If *UserLevel* is <code>User</code>, the user has full control of the receiver. If it is <code>Viewer</code>, the user can only issue <code>qet-commands</code>.

The *SSHKey* argument can be used to associate an SSH public key to a user. ECDSA, Ed25519 and RSA PEM-encoded (base64) public keys conforming to RFC 4716 are supported. The number of bits in the key must be such that the corresponding base64 public key does not exceed 232 characters. RSA keys need to be at least 1024 bits long. Whenever possible, ECDSA or Ed25519 keys are recommended for enhanced security.

When an SSH key is defined with the *SSHKey* argument, a user can download log files using SFTP or rsync without the need for entering a password, provided the matching private key is known by the key agent running on his machine.

To delete an user account, use the empty string "" as *UserName* and *Password*.

Note that the receiver encrypts the password so that it cannot be read back with the command **getUserAccessLevel**.

```
COM1> sual, User3, Mildred, mypwd, Viewer, AAAAE2VjZH ...
   a9YSdPMw==<CR>
$R: sual, User3, Mildred, mypwd, Viewer, AAAAE2VjZH ... a9YSdPMw==
   UserAccessLevel, User3, Mildred, mypwd, Viewer, AAAAE2VjZH ...
   a9YSdPMw==
COM1>
```





3.2.4 Tracking and Measurement Generation

sca	setChannelAllocation	Channel	Satellite	Search	Doppler	Window		
gca	getChannelAllocation	Channel						
		+ Ch01 Ch80	<u>auto</u>	<u>auto</u>	-50000 <u>0</u>			
		all	G01 G32	manual	50000 Hz	100000 Hz		
			F01 F14					
			E01 E36					
			S120 S158					
			C01 C63					
			J01 J07					
			101 114					

RxControl: Navigation > Advanced User Settings > Channel Allocation

Use these commands to define/inquire the satellite-to-channel allocation of the receiver.

The action of the **setChannelAllocation** command is to force the allocation of a particular satellite on the set of channels identified with the *Channel* argument, thereby overruling the automatic channel allocation performed by the receiver. It is possible to allocate the same satellite to more than one channel. If you assign a satellite to a given channel, any other channel that was automatically allocated to the same satellite will be stopped and will be reallocated.

The values Gxx, Exx, Fxx, Cxx, Ixx, Jxx and Sxxx for the *Satellite* argument represent GPS, Galileo, GLONASS, BeiDou, NavIC/IRNSS, QZSS and SBAS satellites respectively. For GLONASS, the frequency number (with an offset of 8) should be provided, and not the slot number (hence the "F"). Setting the *Satellite* argument to auto brings the channel back in auto-allocation mode.

The user can specify the Doppler window in which the receiver has to search for the satellite. This is done by setting the *Search* argument to manual. In that case, the *Doppler* and *Window* arguments can be provided: the receiver will search for the signal within an interval of *Window* Hz centred on *Doppler* Hz. The value to be provided in the *Doppler* argument is the expected Doppler at the GPS L1 carrier frequency (1575.42MHz). This value includes the geometric Doppler and the receiver and satellite frequency biases. Specifying a Doppler window can speed up the search process in some circumstances. A satellite already in tracking that falls outside of the prescribed window will remain in tracking.

If Search is set to auto, the receiver applies its usual search procedure, as it would do for auto-allocated satellites, and the Doppler and Window arguments are ignored.

Be aware that this command may disturb the normal operation of the receiver and is intended only for expert-level users.

Note that, when manually allocating a large number of channels to a single constellation, it is possible that some channels are left idle if the receiver does not have enough tracking hardware of the type required for the selected constellation.

```
COM1> sca, Ch05, G01 <CR>
$R: sca, Ch05, G01
   ChannelAllocation, Ch05, G01, auto, 0, 16000
COM1>
```



COM1> gca, Ch05 <CR>
\$R: gca, Ch05
 ChannelAllocation, Ch05, G01, auto, 0, 16000



scm	setCN0Mask	Signal	Mask				
gcm	getCN0Mask	Signal					
		+ GPSL1CA	0 <u>10</u> 60 dB-				
		+ Reserved1	Hz				
		+ Reserved2					
		+ GPSL2C					
		+ GPSL5					
		+ GPSL1C					
		+ GLOL1CA					
		+GLOL1P					
		+ GLOL2P					
		+ GLOL2CA					
		+ GLOL3					
		+ GALL1BC					
		+ GALE6BC					
		+ GALE5a					
		+ GALE5b					
		+ GALE5					
		+ GEOL1					
		+ GEOL5					
		+BDSB1I					
		+BDSB2I					
		+ BDSB3I					
		+BDSB1C					
		+BDSB2a					
		+BDSB2b					
		+ QZSL1CA					
		+ QZSL2C					
		+ QZSL5					
		+ QZSL6					
		+ QZSL1C					
		+QZSL1S					
		+ QZSL5S					
		+ QZSL1CB					
		+ NAVICL5					
		all					

RxControl: Navigation > Receiver Operation > Masks

Use these commands to define/inquire the carrier-to-noise ratio mask for the generation of measurements. The receiver does not generate measurements for those signals of which the C/N_0 is under the specified mask, and does not include these signals in the PVT computation. However, it continues to track these signals and to decode and use the navigation data as long as possible, regardless of the C/N_0 mask.

The mask can be set independently for each of the signal types supported by the receiver, except for the GPS P-code, of which the mask is fixed at 1 dB-Hz (this is because of the codeless tracking scheme needed for GPS P-code).

```
COM1> scm, GEOL1, 30 <CR>
$R: scm, GEOL1, 30
    CN0Mask, GEOL1, 30

COM1>

COM1> gcm, GEOL1 <CR>
$R: gcm, GEOL1
    CN0Mask, GEOL1, 30

COM1>
```



setMultipathMitigation getMultipathMitigation	Code	Carrier				
	off	off				
	<u>on</u>	<u>on</u>				

RxControl: Navigation > Receiver Operation > Tracking and Measurements > Multipath

Use these commands to define/inquire whether multipath mitigation is enabled or not.

The arguments *Code* and *Carrier* enable or disable the A-Posteriori Multipath Estimator (APME) for the code and carrier phase measurements respectively. APME is a technique by which the receiver continuously estimates the multipath error and corrects the measurements accordingly.

This multipath estimation process slightly increases the thermal noise on the pseudoranges. However, this increase is more than compensated by the dramatic decrease of the multipath noise.

```
COM1> smm, on, off <CR>
$R: smm, on, off
   MultipathMitigation, on, off
COM1>

COM1> gmm <CR>
$R: gmm
   MultipathMitigation, on, off
COM1>
```





sst	setSatelliteTracking	Satellite				
gst	getSatelliteTracking					
		none				
		+ <u>G01</u> <u>G32</u>				
		+ <u>R01</u> <u>R30</u>				
		+ <u>E01</u> <u>E36</u>				
		+ <u>S120</u> <u>S158</u>				
		+ <u>C01</u> <u>C63</u>				
		+ <u>J01</u> <u>J07</u>				
		+ <u>101</u> <u>114</u>				
		+ GPS				
		+ GLONASS				
		+ GALILEO				
		+ SBAS				
		+ BEIDOU				
		+ QZSS				
		+ NAVIC				
		all				

RxControl: Navigation > Advanced User Settings > Tracking > Satellite Tracking

Use these commands to define/inquire which satellites are allowed to be tracked by the receiver. It is possible to enable or disable a single satellite (e.g. G01 for GPS PRN1), or a whole constellation. Gxx, Exx, Rxx, Cxx, Ixx, Jxx and Sxxx refer to a GPS, Galileo, GLONASS, BeiDou, NavIC/IRNSS, QZSS or SBAS satellite respectively. GLONASS satellites must be referenced by their slot number in this command.

For a satellite to be effectively tracked by the receiver, make sure that at least one of its signals is enabled in the **setSignalTracking** command.

A satellite which is disabled by this command is not considered anymore in the automatic channel allocation mechanism, but it can still be forced to a given channel, and tracked, using the **setChannelAllocation** command.

Tracking a satellite does not automatically mean that the satellite will be included in the PVT computation. The inclusion of a satellite in the PVT computation is controlled by the **setSatelliteUsage** command.

Examples

To only enable the tracking of GPS satellites, use:

```
COM1> sst, GPS <CR>
$R: sst, GPS
    SatelliteTracking, G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11
    +G12+G13+G14+G15+G16+G17+G18+G19+G20+G21+G22+G23+G24+G25+G26+G27
    +G28+G29+G30+G31+G32
COM1>
```

To add all SBAS satellites in the list of satellites to be tracked, use:

```
COM1> sst, +SBAS <CR>
$R: sst, +SBAS
    SatelliteTracking, G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11
    +G12+G13+G14+G15+G16+G17+G18+G19+G20+G21+G22+G23+G24+G25+G26+G27
    ...
COM1>
```



To remove SBAS PRN120 from the list of allowed satellites, use:

```
COM1> sst, -S120 <CR>
$R: sst, -S120
    SatelliteTracking, G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11
    +G12+G13+G14+G15+G16+G17+G18+G19+G20+G21+G22+G23+G24+G25+G26+G27
    ...
COM1>
```



snt	setSignalTracking	Signal				
gnt	getSignalTracking	Signar				
5	ggg	+ GPSL1CA				
		+ GPSL1PY				
		+ GPSL2PY				
		+ GPSL2C				
		+ GPSL5				
		+ GPSL1C				
		+ GLOL1CA				
		+ GLOL1P				
		+ GLOL2P				
		+ GLOL2CA				
		+ GLOL3				
		+ GALL1BC				
		+ GALE6BC				
		+ GALE5a				
		+ GALE5b				
		+ GALE5				
		+ GEOL1				
		+ GEOL5				
		+BDSB1I				
		+ <u>BDSB2I</u>				
		+ BDSB3I				
		+ BDSB1C				
		+ BDSB2a				
		+ BDSB2b				
		+ QZSL1CA				
		+ QZSL2C				
		+ <u>QZSL5</u>				
		+ QZSL6				
		+ QZSL1C				
		+ QZSL1S + QZSL5S				
		+ QZSL3S + QZSL1CB				
		+ NAVICL5				
		+ GPS				
		+ GLONASS				
		+ GLONASS + GALILEO				
		+ SBAS				
		+ BEIDOU				
		+ QZSS				
		+ NAVIC				
		all				

RxControl: Navigation > Advanced User Settings > Tracking > Signal Tracking

Use these commands to define/inquire which signals are allowed to be tracked by the receiver. The signals can be addressed individually, or all signals from a constellation can be addressed at once. For example, GALILEO is an alias for all Galileo signals.

Note that some signals can only be enabled together with other signals:

- enabling GPSL1PY has no effect unless GPSL1CA and GPSL2PY are enabled as well;
- enabling GPSL2PY has no effect unless GPSL1CA is enabled as well;
- enabling GLOL1P has no effect unless GLOL1CA is enabled as well;
- enabling GLOL2P has no effect unless GLOL2CA is enabled as well;
- enabling GLOL3 has no effect unless GLOL1CA is enabled as well;
- enabling QZSL6 has no effect unless QZSL1CA or QZSL1CB is enabled as well.

Invoking this command causes all tracking loops to stop and restart.



COM1>

To configure the receiver in a single-frequency L1 GPS+SBAS mode, use:

COM1> snt, GPSL1CA+GEOL1 <CR>
\$R: snt, GPSL1CA+GEOL1
 SignalTracking, GPSL1CA+GEOL1
COM1>

COM1> gnt <CR>
\$R: gnt
 SignalTracking, GPSL1CA+GEOL1

114



ssi	setSmoothingInterval	Signal	Interval	Alignment			
gsi	getSmoothingInterval	Signal					
		+ GPSL1CA	<u>0</u> 1000 s	<u>0</u> 1000 s			
		+ GPSL2PY					
		+ GPSL2C					
		+ GPSL5					
		+ GPSL1C					
		+ GLOL1CA					
		+GLOL1P					
		+ GLOL2P					
		+ GLOL2CA					
		+ GLOL3					
		+ GALL1BC					
		+ GALE6BC					
		+ GALE5a					
		+ GALE5b					
		+ GALE5					
		+ GEOL1					
		+ GEOL5					
		+ BDSB1I					
		+ BDSB2I					
		+ BDSB3I					
		+BDSB1C					
		+ BDSB2a					
		+ BDSB2b					
		+ QZSL1CA					
		+ QZSL2C					
		+ QZSL5					
		+ QZSL6					
		+ QZSL1C					
		+ QZSL1S					
		+ QZSL5S					
		+ QZSL1CB					
		+ NAVICL5					
		all					

RxControl: Navigation > Receiver Operation > Tracking and Measurements > Smoothing

Use these commands to define/inquire the code measurement smoothing interval.

The *Interval* argument defines the length of the smoothing filter that is used to smooth the code measurements by the carrier phase measurements. It is possible to define a different interval for each signal type. If *Interval* is set to 0, the code measurements are not smoothed. The smoothing interval can vary from 1 to 1000 seconds.

To prevent transient effect from perturbing the smoothing filter, smoothing is disabled during the first ten seconds of tracking, i.e. when the lock time is lower than 10s. Likewise, the smoothing effectively starts with a delay of 10 seconds after entering the **setSmoothingInterval** command.

Code smoothing allows reducing the pseudoranges noise and multipath. It has no influence on the carrier phase and Doppler measurements. The smoothing filter has an incremental effect; the noise of the filtered pseudoranges will decrease over time and reach its minimum after *Interval* seconds. For some applications, it may be necessary to wait until this transient effect is over before including the measurement in the PVT computation. This is the purpose of the *Alignment* argument. If *Alignment* is not set to 0, measurements taken during the first *Alignment*+10 seconds of tracking will be discarded. The effective amount of *Alignment* is never larger than *Interval*, even if the user sets it to a larger value.



COM1> ssi, GPSL1CA, 300 <CR>

\$R: ssi, GPSL1CA, 300

SmoothingInterval, GPSL1CA, 300, 0

COM1>

COM1> gsi, GPSL1CA <CR>

\$R: gsi, GPSL1CA

SmoothingInterval, GPSL1CA, 300, 0

COM1>



stlp	setTrackingLoopParameters	Signal	DLLBandwidth	PLLBandwidth	MaxTpDLL	MaxTpPLL	Adaptive		
gtlp	getTrackingLoopParameters	Signal							
		+ GPSL1CA	0.01 0.25	1 <u>15</u> 100	1 <u>100</u> 500	1 <u>10</u> 200	off		
		+ Reserved1	5.00 Hz	Hz —	ms	ms	<u>on</u>		
		+ Reserved2							
		+ GPSL2C							
		+ GPSL5							
		+ GPSL1C							
		+ GLOL1CA							
		+GLOL1P							
		+ GLOL2P							
		+ GLOL2CA							
		+ GLOL3							
		+ GALL1BC							
		+ GALE6BC							
		+ GALE5a							
		+ GALE5b							
		+ GALE5							
		+ GEOL1							
		+ GEOL5							
		+ BDSB1I							
		+ BDSB2I							
		+ BDSB3I							
		+BDSB1C							
		+ BDSB2a							
		+ BDSB2b							
		+ QZSL1CA							
		+ QZSL2C							
		+ QZSL5							
		+ Reserved3 + QZSL1C							
		l							
		+ QZSL1S + QZSL5S							
		l							
		+ QZSL1CB + NAVICL5							
		all							
		all							
		l .	l					L	

RxControl: Navigation > Advanced User Settings > Tracking > Tracking Loop Parameters

Use these commands to define/inquire the tracking loop parameters for each individual signal type.

The *DLLBandwidth* and *PLLBandwidth* arguments define the single-sided DLL and PLL noise bandwidth, in Hz.

The *MaxTpDLL* argument defines the maximum DLL pre-detection time, in millisecond. The actual pre-detection time applied by the receiver (*TpDLL*) depends on the presence of a pilot component. For signals having a pilot component (e.g. GPS L2C), *TpDLL* = *MaxTpDLL*. For signals without pilot component (e.g. GPS L1CA), *TpDLL* is the largest divider of the symbol duration smaller than or equal to *MaxTpDLL*.

The *MaxTpPLL* argument defines the maximal PLL pre-detection time, in millisecond. The actual pre-detection time in the receiver (*TpPLL*) is computed in the same way as indicated for the *MaxTpDLL* argument.

Setting the *Adaptive* argument to on allows the receiver to dynamically change the loop parameters in order to optimize performance in specific conditions.

After entering this command, all active tracking loops stop and restart with the new settings.

This command should only be used by expert users who understand the consequences of modifying the default values. In some circumstances, changing the tracking parameters may



result in the impossibility for the receiver to track a specific signal, or may significantly increase the processor load. It is recommended that the product of *TpPLL* (in milliseconds) and *PLLBandwidth* (in Hz) be kept between 100 and 200.

Note that decreasing the pre-detection times increases the load on the processor.

```
COM1> stlp, GPSL1CA, 0.20, 12, , , off <CR>
$R: stlp, GPSL1CA, 0.20, 12, , , off
   TrackingLoopParameters, GPSL1CA, 0.20, 12, 100, 10, off
COM1>
```



3.2.5 Frontend and Interference Mitigation

sam	setAGCMode	Band	Mode	Gain			
gam	getAGCMode	Band					
		+ L1	<u>auto</u>	0 <u>35</u> 70 dB			
		+ L2L5	frozen				
		+ E6	manual				
		all					

RxControl: Navigation > Advanced User Settings > Frontend and Interference Mitigation > Frontend Settings

Use these commands to define/inquire the operation mode of the Automatic Gain Control (AGC) in the receiver frontend. The AGC is responsible for amplifying the input RF signal to an appropriate level.

By default (*Mode* is set to auto), the AGC automatically adjusts its gain in function of the input signal power. In frozen mode, the AGC gain is kept constant at its current value (after a ten-second stabilisation period) and does not follow any subsequent variation of the input signal power. In manual mode, the user can set the gain to a fixed value specified by the *Gain* argument. The *Gain* argument is ignored in auto and frozen modes.

The first argument (*Band*) specifies for which frequency band the settings apply.

```
COM1> sam, all, frozen <CR>
$R: sam, all, frozen
  AGCMode, L1, frozen, 30
COM1>
```



setBBSamplingMode getBBSamplingMode	Mode				
	BeforeIM AfterIM				

RxControl: Navigation > Advanced User Settings > Frontend and Interference Mitigation > Frontend Settings

Use this command to configure the baseband samples (ADC samples) logged in the ${\tt BBSamples}$ SBF block.

The following sampling modes are defined:

Mode	Description
BeforeIM	The samples in the BBSamples SBF block are taken before interference mitigation (see the setNotchFiltering command). All frequency bands are sampled in turn.
AfterIM	The samples in the BBSamples SBF block are taken after interference mitigation (see the setNotchFiltering command). All frequency bands are sampled in turn.

Example

COM1> sbbs, BeforeIM <CR>
\$R: sbbs, BeforeIM
 BBSamplingMode, BeforeIM
COM1>





snf	setNotchFiltering	Notch	Mode	CenterFreq	Bandwidth			
gnf	getNotchFiltering	Notch						
		+ Notch1	<u>auto</u>	1100.000	<u>30</u> 1600 kHz			
		+ Notch2		2550.000 MHz				
		+ Notch3	manual	IVII IZ				
		all						

RxControl: Navigation > Advanced User Settings > Frontend and Interference Mitigation > Frontend Settings

Use these commands to set the position of the notch filter(s) in the receiver's frontend. Notch filters are used to cancel narrowband interferences.

The *Mode* argument is used to enable or disable the notch filter specified in the first argument. When set to auto, the receiver performs automatic detection of the region of the spectrum affected by interference if any. In manual mode, the user forces a certain region of the spectrum to be blanked by the notch filter. That region must be specified by the arguments *CenterFreq* and *Bandwidth*. *Bandwidth* is the double-sided bandwidth centered at *CenterFreq*. Specifying a region outside of a GNSS band has no effect.

In some cases, changing the operating mode of the notch filters (i.e. modifying the *Mode* argument) can cause the tracking loops to reset.

```
COM1> snf, Notch1, manual, 1227.0, 30<CR>
$R: snf, Notch1, manual, 1227.0, 30
  NotchFiltering, Notch1, manual, 1227.000, 30
COM1>
```





swbi	setWBIMitigation	Mode				
gwbi	getWBIMitigation					
		<u>off</u>				
		on				

RxControl: Navigation > Advanced User Settings > Frontend and Interference Mitigation > Frontend Settings

Use this command to enable or disable the mitigation of wideband interferences, including swept-frequency or pulsed interferences. When enabled (argument *Mode* set to on), the interference mitigation is done automatically and can be monitored with the RFStatus SBF block.

Invoking this command causes all tracking loops to stop and restart.

Example

COM1> swbi, on<CR>
\$R: swbi, on
 WBIMitigation, on
COM1>



3.2.6 Navigation Filter

sao	setAntennaOffset	Antenna	DeltaE	DeltaN	DeltaU	Туре (20)	SerialNr (20)	SetupID	
gao	getAntennaOffset	Antenna							
		+ Main all	-1000.0000 <u>0.0000</u> 1000.0000 m	-1000.0000 <u>0.0000</u> 1000.0000 m	-1000.0000 <u>0.0000</u> 1000.0000 m	<u>Unknown</u>	<u>Unknown</u>	<u>0</u> 255	

RxControl: Navigation > Receiver Setup > Antennas

Use these commands to define/inquire the parameters that are associated with the antenna connected to your receiver.

The arguments *DeltaE*, *DeltaN* and *DeltaU* are the offsets of the antenna reference point (ARP, see section 2.5) with respect to the marker, in the East, North and Up (ENU) directions respectively, expressed in meters. All absolute positions reported by the receiver are marker positions, obtained by subtracting this offset from the ARP. The purpose is to take into account the fact that the antenna may not be located directly on the surveying point of interest.

Use the argument *Type* to specify the type of your antenna. For best positional accuracy, it is recommended to select a type from the list returned by the command <code>lstAntennaInfo</code>, <code>Overview</code>. This is the list of antennas for which the receiver can compensate for phase center variation (see section 2.5). If *Type* does not match any entry in the list returned by <code>lstAntennaInfo</code>, <code>Overview</code>, the receiver will assume that the phase center variation is zero at all elevations and frequency bands, and the position will not be as accurate. If the antenna name contains whitespaces, it has to be enclosed between double quotes. For proper name matching, it is important to keep the exact same number of whitespaces and the same case as the name returned by <code>lstAntennaInfo</code>, <code>Overview</code>.

The argument *SerialNr* is the serial number of your particular antenna. It may contain letters as well as digits (do not forget to enclose the string between double quotes if it contains whitespaces).

The argument *SetupID* is the antenna setup ID as defined in the RTCM standard. It is a parameter for use by the service provider to indicate the particular reference station-antenna combination. The number should be increased whenever a change occurs at the station that affects the antenna phase center variations. Setting *SetupID* to zero means that the values of a standard model type calibration should be used. The value entered for this argument is used to set the setup ID field in the message type 23 of RTCM2.3, and in message types 1007, 1008 and 1033 of RTCM3. It has otherwise no effect on the receiver operation.

```
COM1> sao, Main, 0.1, 0.0, 1.3, "AERAT2775_159 SPKE", 5684, 0<CR>
$R: sao, Main, 0.1, 0.0, 1.3, "AERAT2775_159 SPKE", 5684, 0
AntennaOffset, Main, 0.1000, 0.0000, 1.3000, "AERAT2775_159
SPKE", 5684, 0
COM1>
```





sdca	setDiffCorrMaxAge	DGPSCorr	RTKCorr	PPPCorr	Iono			
gdca	getDiffCorrMaxAge							
		0.0 <u>400.0</u> 3600.0 s		0.0 <u>360.0</u> 3600.0 s	0.0 <u>600.0</u> 3600.0 s			

RxControl: Navigation > Positioning Mode > PPP and Differential Corrections

Use these commands to define/inquire the maximum age acceptable for a given differential correction type. A correction is applied only if its age (aka latency) is under the timeout specified with this command and if it is also under the timeout specified with the <code>MaxAge</code> argument of the <code>setDiffCorrUsage</code> command. In other words, the command <code>setDiffCorrUsage</code> sets a global maximum timeout value, while the command <code>setDiffCorrMaxAge</code> can force shorter timeout values for certain correction types.

The argument *DGPSCorr* defines the timeout of the range corrections when the PVT is computed in DGPS mode.

The argument *RTKCorr* defines the timeout of the base station code and carrier phase measurements when the PVT is computed in RTK mode.

The argument *PPPCorr* defines the timeout of the wide-area satellite clock and orbit corrections used in PPP mode (only applicable if your receiver supports PPP positioning mode).

The argument *lono* defines the timeout of the ionospheric corrections (such as transmitted in RTCM2.x MT15) used in DGPS PVT mode.

If the timeout is set to 0, the receiver will never apply the corresponding correction.

Note that this command does not apply to the corrections transmitted by SBAS satellites. For these corrections, the receiver always applies the timeout values prescribed in the DO229 standard.

```
COM1> sdca, 10 <CR>
$R: sdca, 10
   DiffCorrMaxAge, 10.0, 20.0, 300.0, 300.0
COM1>
```





sdcu	setDiffCorrUsage	Mode	MaxAge	BaseSelection	BaseID			
gdcu	getDiffCorrUsage							
		LowLatency	0.1 <u>3600.0</u> s	<u>auto</u>	<u>0</u> 4095			
				manual				

RxControl: Navigation > Positioning Mode > PPP and Differential Corrections

Use these commands to define/inquire the usage of incoming differential corrections in DGPS or RTK rover mode.

The *Mode* argument defines the type of differential solution that will be computed by the receiver. If LowLatency is selected, the PVT is computed at the moment local measurements of the receiver are available and the most recently received differential corrections are extrapolated to the current time.

The MaxAge argument defines the maximum age of the differential corrections to be considered valid. MaxAge applies to all types of corrections (DGPS, RTK, satellite orbit, etc), except for those received from a SBAS satellite. See also the command **setDiffCorrMaxAge** to set different maximum ages for different correction types.

The *BaseSelection* argument defines how the receiver should select the base station(s) to be used. If auto is selected and the receiver is in DGPS-rover mode, it will use all available base stations. If auto is selected and the receiver is in RTK-rover mode, it will automatically select the nearest base station. If manual is selected, the receiver will only use the corrections from the base station defined by the *BaseID* argument (in both DGPS and RTK modes).

```
COM1> sdcu, LowLatency, 5.0, manual, 1011<CR>
$R: sdcu, LowLatency, 5.0, manual, 1011
   DiffCorrUsage, LowLatency, 5.0, manual, 1011
COM1>
```





sem	setElevationMask	Engine	Mask				
gem	getElevationMask	Engine					
		+ Tracking	-90 <u>0</u> 90 deg				
		+ PVT					
		all					

RxControl: Navigation > Receiver Operation > Masks

Use these commands to set or get the elevation mask in degrees. There are two masks defined: a tracking mask and a PVT mask.

Satellites under the tracking elevation mask are not tracked, and therefore there is no measurement, nor navigation data available from them. The tracking elevation mask does not apply to SBAS satellites: SBAS satellites are generally used to supply corrections and it is undesirable to make the availability of SBAS corrections dependent on the satellite elevation. The tracking elevation mask does not apply to satellites that are manually assigned with the **setChannelAllocation** command.

Satellite under the PVT mask are not included in the PVT solution, though they still provide measurements and their navigation data is still decoded and used. The PVT elevation mask do apply to the SBAS satellites: the ranges to SBAS satellites under the elevation mask are not used in the PVT, but the SBAS corrections are still decoded and potentially used in the PVT.

Although possible, it does not make sense to select a higher elevation mask for the tracking than for the PVT, as, obviously, a satellite which is not tracked cannot be included in the PVT.

The mask can be negative to allow the receiver to track satellites below the horizon. This can happen in case the receiver is located at high altitudes or if the signal is refracted through the atmosphere.

```
COM1> sem, PVT, 15<CR>
$R: sem, PVT, 15
ElevationMask, PVT, 15
COM1>
```





sgu ggu	setGeoidUndulation getGeoidUndulation	Mode	Undulation				
		auto manual	-250.000 <u>0.000</u> 250.000 m				

RxControl: Navigation > Receiver Operation > Position > Earth Models

Use these commands to define/inquire the geoid undulation at the receiver position. The geoid undulation specifies the local difference between the geoid and the WGS84 ellipsoid.

If *Mode* is set to auto, the receiver computes the geoid undulation with respect to the WGS84 ellipsoid using the model defined in Technical Characteristics of the NAVSTAR GPS, NATO, June 1991', regardless of the datum specified with the **setGeodeticDatum** command. In auto mode, the *Undulation* argument is ignored.

The geoid undulation is included in the PVTCartesian and the PVTGeodetic SBF blocks and in the NMEA position messages.

```
COM1> sgu, manual, 25.3 <CR>
$R: sgu, manual, 25.3
  GeoidUndulation, manual, 25.3
COM1>

COM1> ggu <CR>
$R: ggu
  GeoidUndulation, manual, 25.3
COM1>
```





shm	setHealthMask	Engine	Mask				
ghm	getHealthMask	Engine					
		+ Tracking	off				
		+ PVT	<u>on</u>				
		all					

RxControl: Navigation > Receiver Operation > Masks

Use these commands to define/inquire whether measurements (pseudoranges, carrier phases...) should be produced for unhealthy satellite signals (i.e. signals for which the unhealthy flag is set in the satellite navigation message), and whether these measurements should be included in the PVT solution.

If *Mask* is on for the Tracking engine, GNSS measurements are only generated for healthy signals or when the health is unknown. Signals flagged unhealthy remain internally tracked and their navigation data is still decoded and processed, but the corresponding measurements are discarded.

If *Mask* is on for the PVT engine, measurements from unhealthy signals or from signals of which the health is unknown are not included in the PVT. Setting this mask to off must be done with caution: including a non-healthy signal in the PVT computation may lead to unpredictable behaviour of the receiver.

Examples

To track unhealthy satellites/signals, use:

```
COM1> shm, Tracking, off <CR>
$R: shm, Tracking, off
  HealthMask, Tracking, off
COM1>

COM1> ghm <CR>
$R: ghm
  HealthMask, Tracking, off
  HealthMask, PVT, on
COM1>
```





sim	setlonosphereModel	Model				
gim	getlonosphereModel					
		<u>auto</u>				
		off				
		Klobuchar				
		SBAS				
		MultiFreq				
		KlobucharBeiDou				

RxControl: Navigation > Receiver Operation > Position > Atmosphere

Use these commands to define/inquire the type of model used to correct ionospheric errors in the PVT computation. The following models are available:

Model	Description
auto	With this selection, the receiver will, based on the available information, automatically select the best model on a satellite to satellite basis.
off	The receiver will not correct measurements for the ionospheric delay. This may be desirable if the receiver is connected to a GNSS signal simulator.
Klobuchar	This model uses the parameters as transmitted by the GPS satellites to compute the ionospheric delays.
SBAS	This model complies with the DO229 standard: it uses the near real-time ionospheric delays transmitted by the SBAS satellites in MT18 and MT26. If no such message has been received, the Klobuchar model is selected automatically.
MultiFreq	This model uses a combination of measurements on different carriers to accurately estimate ionospheric delays. It requires the availability of at least dual-frequency measurements.
KlobucharBeiDou	This model uses the parameters as transmitted by the BeiDou satellites to compute the ionospheric delays.

Unless the model is set to \mathtt{auto} , the receiver uses the same model for all satellites, e.g. if the $\mathtt{Klobuchar}$ model is requested, the Klobuchar parameters transmitted by GPS satellites are used for all tracked satellites, regardless of their constellation.

If not enough data is available to apply the prescribed model to a given satellite (for instance if only single-frequency measurements are available and the model is set to MultiFreq), the satellite in question will be discarded from the PVT. Under most circumstances, it is recommended to leave the model to auto.

Examples

To disable the compensation for ionospheric delays, use:

COM1> sim, off <CR>
\$R: sim, off
 IonosphereModel, off
COM1>



COM1> gim <CR>
\$R: gim
 IonosphereModel, off
COM1>



scls	setL6CLASSource	Satellite	Message				
gcls	getL6CLASSource						
		<u>auto</u>	L6D				
		none	L6E				
		J01 J07					

RxControl: Navigation > Positioning Mode > QZSS CLAS Configuration

This command sets the QZSS satellite from which the L6 signal will be tracked and CLAS corrections will be decoded. If the *Satellite* argument is set to auto, the receiver automatically selects the optimal QZSS satellite.

QZSS satellites transmit two message streams on the L6 carrier (L6D and L6E). The second argument selects the message stream that the receiver needs to decode.

```
COM1> scls, J03, L6D<CR>
$R: scls, J03, L6D
  L6CLASSource, J03, L6D
COM1>
```



smv gmv	setMagneticVariance getMagneticVariance	Mode	Variation				
		auto manual	-180.0 <u>0.0</u> 180.0 deg				

RxControl: Navigation > Receiver Operation > Position > Earth Models

Use these commands to define the magnetic variation (a.k.a. magnetic declination) at the current position. The magnetic variation specifies the local offset of the direction to the magnetic north with respect to the geographic north. The variation is positive when the magnetic north is east of the geographic north.

By default (the argument *Mode* is set to auto), the receiver automatically computes the variation according to the 12th generation of the International Geomagnetic Reference Field (IGRF) model, using the IGRF2015 coefficients corrected for the secular variation.

Note that the magnetic variation is used solely in the generation of NMEA messages.

```
COM1> smv, manual, 1.1 <CR>
$R: smv, manual, 1.1
  MagneticVariance, manual, 1.1
COM1>

COM1> gmv <CR>
$R: gmv
  MagneticVariance, manual, 1.1
COM1>
```





snrc gnrc	setNetworkRTKConfig getNetworkRTKConfig	NetworkType				
		<u>auto</u> VRS				

RxControl: Navigation > Positioning Mode > PPP and Differential Corrections

Use these commands to define/inquire the type of the RTK network providing the differential corrections.

In most cases, it is recommended to leave the Type argument to auto to let the receiver autodetect the network type. For some types of VRS networks (especially for those having long baselines between the base stations), optimal performance is obtained by forcing the type to VRS.

Example

COM1> snrc, VRS <CR>
\$R: snrc, VRS
 NetworkRTKConfig, VRS
COM1>





spas	setPPPAutoSeed	Mode				
gpas	getPPPAutoSeed					
		<u>none</u>				
		+DGPS				
		+ RTKFixed				
		all				

RxControl: Navigation > Positioning Mode > PPP and Differential Corrections

Use this command to specify which position mode is allowed to be used as a seed for the PPP engine.

If both RTKFixed and DGPS modes are enabled, the receiver gives priority to RTKFixed seeding over DGPS seeding.

In any case, a manual seed entered with the command **exePPPSetSeedGeod** overrules any automatic seeding.

Before enabling seeding from DGNSS or RTK, make sure that the DGNSS/RTK datum is specified with the **setGeodeticDatum** command.

Example

COM1> spas, RTKFixed <CR>
\$R: spas, RTKFixed
 PPPAutoSeed, RTKFixed
COM1>





epss	exePPPSetSeedGeod	Latitude	Longitude	Altitude	Datum			
gpss	getPPPSetSeedGeod							
		-90.000000000			WGS84			
		90 00000000	<u>0.000000000</u>	<u>0.0000</u> 30000.0000 m	ETRS89			
			deg		NAD83			
					NAD83_PA			
					NAD83_MA			
					GDA94			
					GDA2020			
					User1			
					User2			
					Other			

RxControl: Navigation > Receiver Initialization > PPP Set Seed

Use this command to seed the PPP engine with the specified position. The geodetic coordinates in the *Latitude*, *Longitude* and *Altitude* arguments are that of the marker, and not of the ARP. The argument *Longitude* is positive to the east of Greenwich.

The datum to which the coordinates refer must be specified with the *Datum* argument:

Datum	Description
WGS84	WGS84 or ITRFxx (the receiver does not make a distinction between them)
ETRS89	European ETRS89 (ETRF2000 realization)
NAD83	NAD83(2011), North American Datum (2011)
NAD83_PA	NAD83(PA11), North American Datum, Pacific plate (2011)
NAD83_MA	NAD83(MA11), North American Datum, Marianas plate (2011)
GDA94	GDA94(2010), Geocentric Datum of Australia (2010)
GDA2020	GDA2020, Geocentric Datum of Australia 2020
User1	First user-defined datum. The corresponding transformation parameters must be specified by the setUserDatum and setUserDatumVel commands, while the corresponding ellipsoid must be defined by the setUserEllipsoid command.
User2	Second user-defined datum
Other	Datum not in the list or unknown

The receiver applies the necessary transformations to ITRF (the datum used by the PPP engine) automatically. If the *Datum* argument is set to Other, no datum transformation is applied.

It is the user's responsibility to ensure that the specified marker position is centimeter-accurate and that the datum is properly specified. Inaccurate seeding will result in a long convergence time, and/or in an incorrect estimate of the variance/covariance matrix of the PPP solution.

At the moment when the command is entered, the receiver must be static. To prevent gross errors, the command is ignored when the seed significantly differs from the current position computed by the receiver, or when the current velocity is not zero.



In the event that the command is issued when the receiver is already in PPP mode, the PPP filter is reset and re-seeded.

```
COM1> epss, 4.5, 3.568, 0.1, WGS84<CR>
$R: epss, 4.5, 3.568, 0.1, WGS84
    PPPSetSeedGeod, 4.500000000, 3.568000000, 0.1000, WGS84
COM1>
```



spm	setPVTMode	Mode	RoverMode	RefPos			
gpm	getPVTMode						
		Static	+ StandAlone	<u>auto</u>			
		Rover	+ SBAS	Geodetic1			
			+ DGPS	Cartesian1			
			+ RTKFloat				
			+ RTKFixed				
			+ <u>PPP</u>				
			+RTK				
			all				

RxControl: Navigation > Positioning Mode > PVT Mode

Use these commands to define/inquire the main PVT mode of the receiver. The argument *Mode* specifies the general positioning mode. If Rover is selected, the receiver assumes that it is moving and it computes the best PVT allowed by the *RoverMode* argument. If Static is selected, the receiver assumes that it is static and it reports a constant position. The static position can be specified by the user or computed by the receiver, according to the settings of the *RefPos* argument.

The argument *RoverMode* specifies the allowed PVT modes when the receiver is operating in Rover mode. Different modes can combined with the "+" operator. Refer to section 2.4 for a description of the PVT modes. The value RTK is an alias for RTKFloat+RTKFixed. When more than one mode is enabled in *RoverMode*, the receiver automatically selects the mode that provides the most accurate solution with the available data.

The *RefPos* argument defines the reference position of the antenna ARP. This is the position that is encoded in the RINEX header (after application of the marker-ARP offset specified with the **setAntennaOffset** command) and in the relevant RTCM and CMR differential correction messages.

If *RefPos* is set to Geodetic*i* or Cartesian*i*, the fixed ARP coordinates must be provided by the user with the **setStaticPosCartesian** or the **setStaticPosGeodetic** commands.

If *RefPos* is set to auto, the reference ARP position is computed by the receiver. In rover mode, the reference position is not fixed. This is the setting that must be used on moving platforms.

Examples

```
COM1> spm, Rover, StandAlone+RTK <CR>
$R: spm, Rover, StandAlone+RTK
   PVTMode, Rover, StandAlone+RTK, auto
COM1>
```

To set up a fixed base station at a known location, use the following:

```
COM1> sspg, Geodetic1, 50.5209, 4.4245, 113.3 <CR>
$R: sspg, Geodetic1, 50.5209, 4.4245, 113.3
   StaticPosGeodetic, Geodetic1, 50.52090000, 4.42450000, 113.3000
COM1> spm, Static, , Geodetic1 <CR>
$R: spm, Static, , Geodetic1
   PVTMode, Static, StandAlone+RTK, Geodetic1
COM1>
```



srl	setRAIMLevels	Mode	Pfa	Pmd	Reliability			
grl	getRAIMLevels							
		off	-12 <u>-4</u> 1	-12 <u>-4</u> 1	-12 <u>-3</u> 1			
		<u>on</u>						

RxControl: Navigation > Receiver Operation > Position > Integrity

Use these commands to define/inquire the parameters of the Receiver Autonomous Integrity Monitoring (RAIM) algorithm in rover PVT mode.

The *Mode* argument acts as an on/off switch: it determines whether RAIM is active or not.

The *Pfa* argument sets the probability of false alarm of the w-test used in the "identification" step of the RAIM algorithm. Increasing this parameter increases the integrity but may reduce the availability of the positional solution.

The *Pmd* argument sets the probability of missed detection, which the receiver uses to compute the Minimal Detectable Bias and hence the XERL values.

The *Reliability* argument sets the probability of false alarm of the Overall Model test used in the "detection" step of the RAIM algorithm.

The value to be provided in the *Pfa*, *Pmd* and *Reliability* arguments are the base-10 logarithms of the desired probabilities. For instance, if you want a probability of false alarm of 1e-6, you have to set the *Pfa* argument to -6.

Note that this command has no effect when the receiver is configured in static PVT mode with the **setPVTMode**, **Static** command. In static PVT mode, the RAIM algorithm uses fixed parameters that cannot be changed by the user.

Examples

To configure the receiver outlier detection with a probability of 1e-4 (0.01%) that a false alarm will be raised (type I error), a probability of 1e-4 (0.01%) that an outlier will be missed (type II error) and an Overall Model probability of false alarm of 1e-6 (0.0001%), use:

```
COM1> srl, on, -4, -4, -6 <CR>
$R: srl, on, -4, -4, -6

RAIMLevels, on, -4, -4, -6

COM1>
```

To disable the outlier detection, use:

```
COM1> srl, off <CR>
$R: srl, off
   RAIMLevels, off, -4, -4, -6
COM1>
```



srd	setReceiverDynamics	Level	Motion				
grd	getReceiverDynamics						
		Max	Static				
		High	Quasistatic				
		<u>Moderate</u>	Pedestrian				
		Low	<u>Automotive</u>				
			EarthquakeMon				
			Unlimited				

RxControl: Navigation > Receiver Operation > Position > Motion

Use these commands to set the type of dynamics the GNSS antenna is subjected to.

The *Level* argument sets the balance between noise and dynamics in the GNSS measurements and the PVT solution. If rapid displacements (such as those caused by shocks, drops, and oscillations) need to be detected, the *Level* argument can be set to High. In that case, high-frequency motion becomes visible at the expense of an increase in the noise. Conversely, if noise reduction is important, the *Level* argument can be set to Low. It is generally recommended to keep the default value (Moderate), where the receiver will sense the dynamics and adapt itself accordingly. The Max level is a special setting, for which the navigation filter is disabled and the receiver computes epoch-by-epoch independent PVT solutions. Note that the Max level can lead to a longer latency of the PVT output.

The *Motion* argument defines the general characteristics of the receiver motion, such as the expected speed, rotation, and vibration level. This can help the receiver to optimize certain parameters for your application.

For example, when selecting the Pedestrian motion, signal reacquisition will be faster after a long outage, as the position is known not to have changed much.

Motion	Description
Static	Fixed base and reference stations.
Quasistatic	Low speed, limited area motion typical of surveying applications.
Pedestrian	Low speed (<7m/s) motion. E.g. pedestrians, low-speed land vehicles,
Automotive	Medium speed (<50m/s) motion. E.g. passenger cars, rail vehicles. This setting is generally adequate for most applications.
EarthquakeMon	Specific setting for earthquake monitoring, where the position is mostly static, but can suddenly change during an earthquake.
Unlimited	Unconstrained motion.

Example

COM1> srd, High, Automotive<CR>
\$R: srd, High, Automotive
 ReceiverDynamics, High, Automotive
COM1>





ernf	exeResetNavFilter	Level				
grnf	getResetNavFilter					
		+ <u>PVT</u>				
		+ AmbRTK				
		all				

RxControl: Navigation > Receiver Initialization > Reset Navigation Filter

Use this command to reset the different navigation filters in the receiver. The user can reset each navigation filter independently or together with the value all.

The following values for *Level* are defined:

Level	Description
PVT	Reset the whole PVT filter such that all previous positioning information is discarded, including the RTK ambiguities and the INS/GNSS integration filter when applicable.
AmbRTK	Only reset the ambiguities used in RTK positioning to float status.

Example

COM1> ernf, PVT <CR>
\$R: ernf, PVT
 ResetNavFilter, PVT
COM1>



ssu	setSatelliteUsage	Satellite				
gsu	getSatelliteUsage					
		none				
		+ <u>G01</u> <u>G32</u>				
		+ <u>R01</u> <u>R24</u>				
		+ R25				
		+ R26				
		+ R27				
		+ R28				
		+ R29				
		+ R30				
		+ <u>E01</u> <u>E36</u>				
		+ S120 S158				
		+ <u>C01</u> <u>C63</u>				
		+ <u>J01</u> <u>J07</u>				
		+ GPS				
		+ GLONASS				
		+ GALILEO				
		+ SBAS				
		+ BEIDOU				
		+ QZSS				
		all				

RxControl: Navigation > Advanced User Settings > PVT > Satellite Usage

Use these commands to define/inquire which satellites are allowed to be included in the PVT computation. It is possible to enable or disable a single satellite (e.g. G01 for GPS PRN1), or a whole constellation. Gxx, Exx, Rxx, Cxx and Sxxx refer to a GPS, Galileo, GLONASS, BeiDou and SBAS satellite respectively. GLONASS satellites must be referenced by their slot number in this command.

Examples

To only use GPS measurements in the PVT computation, use:

```
COM1> ssu, GPS <CR>
$R: ssu, GPS
    SatelliteUsage, G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11
    +G12+G13+G14+G15+G16+G17+G18+G19+G20+G21+G22+G23+G24+G25+G26
    +G27+G28+G29+G30+G31+G32
COM1>
```

To add the usage of SBAS measurements in the PVT, use:

```
COM1> ssu, +SBAS <CR>
$R: ssu, +SBAS
    SatelliteUsage, G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11
    +G12+G13+G14+G15+G16+G17+G18+G19+G20+G21+G22+G23+G24+G25+G26
    ...
COM1>
```

To remove the measurement of one satellite from the PVT, use:

```
COM1> ssu, -S120 <CR>
$R: ssu, -S120
    SatelliteUsage, G01+G02+G03+G04+G05+G06+G07+G08+G09+G10+G11
    +G12+G13+G14+G15+G16+G17+G18+G19+G20+G21+G22+G23+G24+G25+G26
    ...
CM1>
```



ssbc	setSBASCorrections	Satellite	SISMode	NavMode	DO229Version			
gsbc	getSBASCorrections							
		<u>auto</u>	Test	EnRoute	<u>auto</u>			
		EGNOS	Operational	PrecApp	DO229C			
		WAAS		MixedSystems				
		MSAS						
		GAGAN						
		SDCM						
		S120 S158						

RxControl: Navigation > Positioning Mode > SBAS Corrections

Use these commands to define/inquire the details on the usage of SBAS data in the PVT computation. This command does not define whether SBAS corrections are to be used or not in the PVT (this is done by the **setPVTMode** command), but it specifies how these corrections should be used.

The Satellite argument defines the provider of SBAS corrections, being either an individual satellite or a satellite system. If EGNOS, WAAS, MSAS, GAGAN or SDCM is selected, the receiver restricts the automatic selection of a satellite to those that are part of the EGNOS, WAAS, MSAS, GAGAN or SDCM system. When auto is selected for the Satellite argument, the receiver will automatically select a satellite on the basis of the location of the receiver and on the availability of SBAS corrections.

The *SISMode* argument defines the interpretation of a "Do Not Use for Safety Applications" message. It depends on the SBAS service selection with the **setSBASService** command.

For the DO229 service: When set to <code>Operational</code>, the receiver will discard all SBAS corrections received from a satellite upon reception of a MT00 from that satellite. Note that MT02 content encoded in a MT00 message will be interpreted by the receiver as a MT02 message: only MT00 with all '0' symbols will be interpreted as a true "Do Not Use for Safety Applications". When the argument <code>SISMode</code> is set to <code>Test</code>, the receiver will ignore the reception of a "Do Not Use for Safety Applications" message. This provides the possibility to use a signal from a SBAS system in test mode.

For the DFMC service: When set to <code>Operational</code>, the receiver will discard all SBAS corrections received from a satellite upon reception of a MT00 from that satellite. When the argument <code>SISMode</code> is set to <code>Test</code>, the receiver will ignore the reception of a "Do Not Use for Safety Applications" message. This provides the possibility to use a signal from a SBAS system in test mode. In this case the MT00 message content will be interpreted by the receiver as integrity data (MT34, MT35 or MT36).

The SBAS standards, which have their origin in aviation, make a distinction between two positioning applications: en-route and precision approach. The choice between both applications influences the length of the interval during which the SBAS corrections are valid. During a precision approach the validity of the data is much shorter. The receiver can operate in both modes, which is controlled by the *NavMode* argument.

In EnRoute or in PrecApp mode, the receiver only uses the satellite systems for which SBAS corrections are available. For best positioning accuracy, it is typically preferable to include all satellites in the position computation, even if they are not corrected by SBAS. This is achieved by the MixedSystems mode.

The *DO229Version* argument can be used to specify which version of the DO 229 standard to conform to.



Example

To force the receiver to use corrections from PRN 122 and ignore message MT00:

COM1> ssbc, S122, Test <CR>
\$R: ssbc, S122, Test
 SBASCorrections, S122, Test, MixedSystems, auto
COM1>



setSBASService getSBASService	Service				
	DO229 DFMC				

RxControl: Navigation > Positioning Mode > SBAS Corrections

Use this command to define/inquire the SBAS service to be used in the PVT computation.

If DO229 is selected, the SBAS corrections provided on the L1 signal are used (only for GPS satellites). If DFMC is selected, the Dual-Frequency Multi-Constellation (DFMC) corrections provided on L5 are used.

Example

COM1> sssc, DO229<CR>
\$R: sssc, DO229
 SBASService, DO229
COM1>





snu	setSignalUsage	PVT	NavData				
gnu	getSignalUsage						
		+ GPSL1CA	+ GPSL1CA				
		+ GPSL1PY	+ GPSL1PY				
		+ GPSL2PY	+ GPSL2PY				
		+ GPSL2C	+ GPSL2C				
		+ GPSL5	+ GPSL5				
		+ GPSL1C	+ GPSL1C				
		+ GLOL1CA	+GLOL1CA				
		+ GLOL1P	+GLOL1P				
		+ GLOL2P	+GLOL2P				
		+ GLOL2CA	+ GLOL2CA				
		+ GLOL3	+ GLOL3				
		+ GALL1BC	+ GALL1BC				
		+ GALE6BC	+ GALE6BC				
		+ GALE5a	+ GALE5a				
		+ GALE5b	+ GALE5b				
		+ GALE5	+ GALE5				
		+ GEOL1	+GEOL1				
		+ GEOL5	+ GEOL5				
		+BDSB1I	+BDSB1I				
		+ <u>BDSB2I</u>	+BDSB2I				
		+ BDSB3I	+ BDSB3I				
		+BDSB1C	+BDSB1C				
		+ BDSB2a	+ <u>BDSB2a</u>				
		+ BDSB2b	+ BDSB2b				
		+QZSL1CA	+ QZSL1CA				
		+ QZSL2C	+ QZSL2C				
		+ QZSL5	+ QZSL5				
		+ QZSL6	+ QZSL6				
		+QZSL1C	+ QZSL1C				
		+QZSL1S	+QZSL1S				
		+ QZSL5S	+ QZSL5S				
		+QZSL1CB	+QZSL1CB				
		+ NAVICL5	+ NAVICL5				
		all	all				

RxControl: Navigation > Advanced User Settings > PVT > Signal Usage

Use these commands to define/inquire which signal types are used by the receiver.

The *PVT* argument lists the signals that can be used by the PVT. Removing a signal from the list will disable the usage of the corresponding range, phase & Doppler measurements in the PVT computation.

The NavData argument lists the signals for which the receiver is allowed to decode the navigation message. Removing a signal from the list will disable further decoding of the corresponding navigation data (ephemeris, ionosphere parameters ...). Beware that data decoded in the past will still be used. Past data can be erased with the **exeResetReceiver**, **hard**, **SatData+PVTData** command.

Example

To force the receiver to only use the L1 GPS C/A measurements and navigation information in the PVT solution, use:

```
COM1> snu, GPSL1CA, GPSL1CA <CR>
$R: snu, GPSL1CA, GPSL1CA
   SignalUsage, GPSL1CA, GPSL1CA
COM1>
```



sspc	setStaticPosCartesian	Position	X	Υ	Z	Datum		
gspc	getStaticPosCartesian	Position						
		+ Cartesian1	-8000000.0000	-8000000.0000	-8000000.0000	WGS84		
		all	<u>0.0000</u> 800000.0000	<u>0.0000</u> 800000.0000	<u>0.0000</u> 800000.0000	ETRS89		
						NAD83		
						NAD83_PA		
						NAD83_MA		
						GDA94		
						GDA2020		
						User1		
						User2		
						Other		

RxControl: Navigation > Positioning Mode > PVT Mode

Use these commands to define/inquire a set of Cartesian coordinates. This command should be used in conjunction with the **setPVTMode** command to specify a reference position. The Cartesian coordinates in the *X*, *Y* and *Z* arguments must refer to the antenna reference point (ARP), and not to the marker.

The argument *Datum* specifies the datum to which the coordinates refer. When the PVT engine is in static mode (**setPVTMode**, **Static** command), the specified datum is reflected in the <code>Datum</code> field of the position-related SBF blocks (e.g. <code>PVTCartesian</code>). Note that the receiver does not apply any datum transformation to the *X*, *Y* and *Z* coordinates. In particular, the coordinates are encoded without change into the relevant differential correction messages.

Datum	Description
WGS84	WGS84 or ITRFxx (the receiver does not make a distinction between them)
ETRS89	European ETRS89 (ETRF2000 realization)
NAD83	NAD83(2011), North American Datum (2011)
NAD83_PA	NAD83(PA11), North American Datum, Pacific plate (2011)
NAD83_MA	NAD83(MA11), North American Datum, Marianas plate (2011)
GDA94	GDA94(2010), Geocentric Datum of Australia (2010)
GDA2020	GDA2020, Geocentric Datum of Australia 2020
User1	First user-defined datum. The corresponding ellipsoid must be defined with the setUserEllipsoid command.
User2	Second user-defined datum
Other	Datum not in the list or unknown

Example

To set up a static base station in Cartesian coordinates:

yr. spm, static, , cartesian





sspg	setStaticPosGeodetic	Position	Latitude	Longitude	Altitude	Datum		
gspg	getStaticPosGeodetic	Position						
		+ Geodetic1	-90.000000000 0.000000000	-180.000000000 0.0000000000	0.0000	WGS84		
		all	90.00000000			ETRS89		
			deg	deg		NAD83		
						NAD83_PA		
						NAD83_MA		
						GDA94		
						GDA2020		
						User1		
						User2		
						Other		

RxControl: Navigation > Positioning Mode > PVT Mode

Use these commands to define/inquire a set of geodetic coordinates. This command should be used in conjunction with the **setPVTMode** command to specify a reference position. The geodetic coordinates in the *Latitude*, *Longitude* and *Altitude* arguments must refer to the antenna reference point (ARP), and not to the marker.

The argument *Datum* specifies the datum to which the coordinates refer. See the **setStaticPosCartesian** command for a short description of the supported datums.

Example

To set up a static base station in geodetic coordinates:

```
COM1> sspg, Geodetic1, 50.86696443, 4.71347657, 114.880 <CR>
$R: sspg, Geodetic1, 50.86696443, 4.71347657, 114.880
    StaticPosGeodetic, Geodetic1, 50.86696443, 4.71347657, 114.8800,
        WGS84

COM1> spm, Static, , Geodetic1 <CR>
$R: spm, Static, , Geodetic1
    PVTMode, Static, StandAlone+SBAS+DGPS+RTKFloat+RTKFixed,
        Geodetic1
COM1>
```





stm	setTroposphereModel	ZenithModel	MappingModel				
gtm	getTroposphereModel						
		off	Niell				
		Saastamoinen	MOPS				
		MOPS					

RxControl: Navigation > Receiver Operation > Position > Atmosphere

Use these commands to define/inquire the type of model used to correct tropospheric errors in the PVT computation.

The ZenithModel parameter indicates which model the receiver uses to compute the dry and wet delays for radio signals at 90 degree elevation. The modelled zenith tropospheric delay depends on assumptions for the local air total pressure, the water vapour pressure and the mean temperature. The following zenith models are defined:

ZenithModel	Description
off	The measurements will not be corrected for the troposphere de- lay. This may be desirable if the receiver is connected to a GNSS signal simulator.
Saastamoinen	Saastamoinen, J. (1973). "Contributions to the theory of atmospheric refraction". In three parts. Bulletin Geodesique, No 105, pp. 279-298; No 106, pp. 383-397; No. 107, pp. 13-34.
MOPS	Minimum Operational Performance Standards for Global Positioning/Wide Area Augmentation System Airborne Equipment RTCA/DO-229C, November 28, 2001.

The Saastamoinen model uses user-provided values of air temperature, total air pressure referenced to the Mean Sea Level and relative humidity (see **setTroposphereParameters** command) and estimates actual values adjusted to the receiver height.

The MOPS model neglects the user-provided values and instead assumes a seasonal model for all the climatic parameters. Local tropospheric conditions are estimated based on the coordinates and time of the year.

The use of the Saastamoinen model can be recommended if external information on temperature, pressure, humidity is available. Otherwise it is advisable to rely on climate models.

The zenith delay is mapped to the current elevation for each satellite using the requested *MappingModel*. The following mapping models are defined:

MappingModel	Description
	Niell, A.E. (1996). Global Mapping Functions for the atmosphere delay at radio wavelengths, Journal of Geophysical Research, Vol. 101, No. B2, pp. 3227-3246.
	Minimum Operational Performance Standards for Global Positioning/Wide Area Augmentation System Airborne Equipment RTCA/DO-229C, November 28, 2001.







COM1>

COM1> stm, MOPS, MOPS <CR>
\$R: stm, MOPS, MOPS
 TroposhereModel, MOPS, MOPS
COM1>

COM1> gtm <CR>
\$R: gtm
TroposhereModel, MOPS, MOPS



stp	setTroposphereParameters	Temperature	Pressure	Humidity			
gtp	getTroposphereParameters						
			800.00 <u>1013.25</u> 1500.00 hPa	0 <u>50</u> 100 %			

RxControl: Navigation > Receiver Operation > Position > Atmosphere

Use these commands to define/inquire the climate parameters to be used when the zenith troposphere is estimated using the Saastamoinen model (see the **setTroposphereModel** command).

The troposphere model assumes the climate parameters to be valid for a receiver located at the Mean Sea Level (MSL). If you want to use your receiver with a weather station, you have to convert the measured *Temperature*, *Pressure* and *Humidity* to MSL.

```
COM1> stp, 25, 1013, 60<CR>
$R: stp, 25, 1013, 60
  TroposphereParameters, 25.0, 1013.00, 60
COM1>
```





3.2.7 Authentication

lopk	IstGalOSNMAPublicKeys					

Use this command to retrieve the list of applicable OSNMA public keys.

The list contains user-defined public keys, as introduced with **setGalOSNMAPublicKeys** command, possibly updated with new keys provided through the Galileo OSNMA protocol (over the air).

This command is very similar to the command **getGalOSNMAPublicKeys**, the only difference being that the latter only reports the list of user-defined public keys.

```
COM1> lstGalOSNMAPublicKeys <CR>
$R; lstGalOSNMAPublicKeys
---->
$-- BLOCK 1 / 1
   GalOSNMAPublicKeys, Key0, ""
   GalOSNMAPublicKeys, Key1, "MFkwEwYHKoZIzj0CAQYIKoZIzj0DAQcDQgAE+
        Q2wvmvfdQg1sQF6OmCEy8skCSiu79vBnRrKmaPpCJnaMOOvm26Us6ELhebL+
        q75MAyWAXJjlyRZZwp68gSAHw=="
...
COM1>
```



sopk	setGalOSNMAPublicKeys	ID	Key (233)				
gopk	getGalOSNMAPublicKeys	ID					
		+ Key0 Key15					
		all					

RxControl: Navigation > Advanced User Settings > Galileo OSNMA > Public Keys

Public keys for live OSNMA operation are hardcoded in the receiver, as they are not expected to change frequently. In order to have the OSNMA function operate with live signals, the user is not required to input any keys.

However, in simulated environments, different keys may be needed and they can be provided with this command. OSNMA defines 16 different keys which can be provided individually with the *ID* and *Key* arguments.

The format of the Key argument is equivalent to PEM (Private Mail Enhanced), a Base64 encoded certificate, but without the "—BEGIN—" header and "—END—" footer.



If the keys provided with this command do not correspond to the Galileo keys, the receiver will not be able to authenticate live Galileo messages. Make sure to delete all user-selected keys (e.g. with the setGalOSNMAPublicKeys, all, "" command) when leaving the simulated environment.

Example

COM1> sopk, Key2, ME4wEAYHKoZIzj0CAQYFK4EEACEDOgAEnAtF3t3kbYx6tH80MEIuis+ HtLdGNGU8Cj8kUesPfc/OEbNRcbedY5iQHsc+t5bEN0GV6gkLIp0= <CR>

\$R: sopk, Key2,

ME4wEAYHKoZIzj0CAQYFK4EEACEDOgAEnAtF3t3kbYx6tH80MEIuis+ HtLdGNGU8Cj8kUesPfc/OEbNRcbedY5iQHsc+t5bEN0GV6gkLIp0= GalOSNMAPublicKeys, Key2,

"ME4wEAYHKoZIzj0CAQYFK4EEACEDOqAEnAtF3t3kbYx6tH80MEIuis+ HtLdGNGU8Cj8kUesPfc/OEbNRcbedY5iQHsc+t5bEN0GV6qkLIp0=" COM1>





sou	setGalOSNMAUsage	Mode	MTRoot (65)				
gou	getGalOSNMAUsage						
		<u>off</u>					
		loose					
		strict					

RxControl: Navigation > Advanced User Settings > Galileo OSNMA > Settings

Use this command to configure the OSNMA processing of the receiver.

By default, the *Mode* argument is set to off and the authentication function is switched off. No OSNMA authentication checking is being performed and no authentication results presented.

In loose mode, authentication results are reported in the GALAuthStatus SBF block and used for those satellites supported by OSNMA. In case authentication fails for a particular satellite, it is excluded from the PVT. In all other cases (authentication successful or unknown), it is used in the PVT.

In strict mode, only proven authentic satellites are included in the PVT. Satellites for which authentication is not available (e.g. BeiDou satellites) or which have not been verified yet are excluded. The reported PVT solution is solely based on authenticated satellites.

Another difference between loose and strict modes is the usage of an NTP time server. In loose mode, NTP access is optional. In strict mode, it is mandatory. See also the **setNTPClient** command.

The *MTRoot* argument allows users to specify the root of the Merkle Tree used to validate new public keys. The format is an hexademical string representing the bits of the key. This is only needed in simulated environments. When using the receiver for live OSNMA operation, no Merkle Root key should be specified (the argument should be left blank).



3.2.8 Datum Definition

sgd	setGeodeticDatum	TargetDatum				
ggd	getGeodeticDatum					
		WGS84				
		ETRS89				
		NAD83				
		NAD83_PA				
		NAD83_MA				
		GDA94				
		GDA2020				
		<u>Default</u>				
		User1				
		User2				

RxControl: Navigation > Receiver Operation > Position > Datum

Use this command to define the datum to which you want the coordinates to refer.

TargetDatum	Description
WGS84	Equivalent to Default
ETRS89	European ETRS89 (ETRF2000 realization)
NAD83	NAD83(2011), North American Datum (2011)
NAD83_PA	NAD83(PA11), North American Datum, Pacific plate (2011)
NAD83_MA	NAD83(MA11), North American Datum, Marianas plate (2011)
GDA94	GDA94(2010), Geocentric Datum of Australia (2010)
GDA2020	GDA2020, Geocentric Datum of Australia 2020
Default	Default datum, which depends on the positioning mode as explained below.
User1	First user-defined datum. The corresponding transformation parameters must be specified by the setUserDatum and setUserDatumVel commands, while the corresponding ellipsoid must be defined by the setUserEllipsoid command.
User2	Second user-defined datum

By default (argument *TargetDatum* set to <code>Default</code>), the datum depends on the positioning mode. For standalone and SBAS positioning, the coordinates refer to a global datum: WGS84 or ITRF (recent realisations of WGS84 and ITRF are closely aligned and the receiver considers them equivalent). When using PPP corrections, the coordinates refer to ITRF. When using DGNSS or RTK corrections from a regional DGNSS/RTK provider, the coordinates usually refer to a regional datum (e.g. ETRS89 in Europe or NAD83 in North America).

With this command, the user can select the datum the coordinates should refer to. In case you are using corrections from a regional DGNSS/RTK provider, the datum to be specified here must be the datum used by your correction provider.

When a non-default datum is selected, the receiver transforms the coordinates obtained in standalone, SBAS and PPP modes to the specified datum. Positions obtained using local or regional DGNSS/RTK corrections are not transformed, as it is assumed that the selected datum is the one used by the DGNSS/RTK provider.



In the current firmware version, the $\tt WGS84$ value for the $\it TargetDatum$ argument has no effect, but it is kept for backwards compatibility reasons. Setting $\it TargetDatum$ to $\tt WGS84$ is equivalent to setting it to $\tt Default$.

Example

COM1> sgd, ETRS89 <CR>
\$R: sgd, ETRS89
 GeodeticDatum, ETRS89
COM1>



sud	setUserDatum	Datum	Tx	Ту	Tz	Rx	Ry	Rz	D	
gud	getUserDatum	Datum								
		+ User1 + User2 all	-2000000.00 <u>0.00</u> 2000000.00 mm	<u>0.00</u> 2000000.00	-2000000.00 <u>0.00</u> 2000000.00 mm	-100.0000 <u>0.0000</u> 100.0000 mas	-100.0000 0.0000 100.0000 mas	-100.0000 <u>0.0000</u> 100.0000 mas	-100.00000 <u>0.00000</u> 100.00000 ppb	

RxControl: Navigation > Receiver Operation > Position > Datum

Use these commands to define datum transformation parameters from the global WGS84/ITRF datum to the user datum identified by the first argument.

The receiver applies the linearized form of the Helmert similarity transformation. The coordinates in WGS84/ITRF are transformed to the user datum using the following formula:

$$\begin{pmatrix} X \\ Y \\ Z \end{pmatrix}_{User} = \begin{pmatrix} T_x \\ T_y \\ T_z \end{pmatrix} + \begin{pmatrix} D+1 & -R_z & R_y \\ R_z & D+1 & -R_x \\ -R_y & R_x & D+1 \end{pmatrix} \cdot \begin{pmatrix} X \\ Y \\ Z \end{pmatrix}_{WGS84/ITRF}$$

where T_x , T_y and T_z are the three translation components, R_x , R_y and R_z are the rotation angles and D is the scale factor. Note that the rotation angles are expressed in radians in the above formula, but they must be provided in milliarcsecond (1 mas = $2\pi/360/3600000$ radians) in the arguments of the command. The sign convention corresponds to that of the IERS Conventions (2010), Technical Note No. 36.

The time derivative of the transformation parameters can be specified with the command **setUserDatumVel**.

For the receiver to apply the transformation parameters, the corresponding user datum must be selected in the **setGeodeticDatum** command.



sudv	setUserDatumVel	Datum	TxVel	TyVel	TzVel	RxVel	RyVel	RzVel	DVel	RefYear
gudv	getUserDatumVel	Datum								
		+ User2	2000.00 mm/yr	-2000.00 <u>0.00</u> 20000.00 mm/yr	2000.00 mm/yr	<u>0.0000</u> 10.0000	-10.0000 <u>0.0000</u> 10.0000	<u>0.0000</u> 10.0000	-1.00000 <u>0.00000</u> 1.00000 ppb/yr	1900.00 <u>2000.00</u> 2100.00 yr
		all				mas/yr	mas/yr	mas/yr		

RxControl: Navigation > Receiver Operation > Position > Datum

Use these commands to define the time derivative of the seven datum transformation parameters defined with the **setUserDatum** command.

For instance, *TxVel* is the yearly change of the X-translation component. At the epoch specified with *RefYear* (in decimal years), the X-translation component is *Tx* as defined in **setUserDatum**. One year later, the X-translation component is *Tx+TxVel*, etc.

Refer to the **setUserDatum** command for a description of the datum transformation formula implemented in the receiver.



sue	setUserEllipsoid	Datum	Α	Invf			
gue	getUserEllipsoid	Datum					
		+ User1 + User2 all	6300000.000 6378137.000 6400000.000 m	290.000000000 298.257223563 305.0000000000			

RxControl: Navigation > Receiver Operation > Position > Datum

Use these commands to define the ellipsoid associated with the User1 or User2 datum. a is the reference ellispoid semi-major axis and Invf is the inverse of the flattening. See also the setGeodeticDatum and the setUserDatum commands.

```
COM1> sue, User1, 6378388, 297 <CR>
$R: sue, User1, 6378388, 297
  UserEllipsoid, User1, 6378388.000, 297.000000000
COM1>
```



3.2.9 Timing and Time Management

scst	setClockSyncThreshold	Threshold	StartupSync				
gcst	getClockSyncThreshold						
		ClockSteering	<u>off</u>				
		<u>usec500</u>	on				
		msec1					
		msec2					
		msec3					
		msec4					
		msec5					

RxControl: Navigation > Receiver Operation > Timing

Use these commands to define/inquire the maximum allowed offset between the receiver internal clock and the system time defined by the **setTimingSystem** command.

If the argument <code>ClockSteering</code> is selected, the receiver internal clock is continuously steered to the system time to within a couple of nanoseconds. Clock steering accuracy is dependent on the satellite visibility, and it is recommended to only enable it under open-sky conditions.

If any other argument is selected, the internal clock is left free running. Synchronization with the system time is done through regular millisecond clock jumps. More specifically, when the receiver detects that the time offset is larger than *Threshold*, it initiates a clock jump of an integer number of milliseconds to re-synchronise its internal clock with the system time. These clock jumps have no influence on the generation of the xPPS pulses: the xPPS pulses are always maintained within a few nanoseconds from the requested time, regardless of the value of the *Threshold* argument.

The *StartupSync* argument can be used to force the receiver to start with a small clock bias value (less than 100ns). This setting will only have effect at the next reset or reboot of the receiver. So, when enabling startup synchronization (*StartupSync* set to on), do not forget to save the configuration in the boot configuration file with the **exeCopyConfigFile** command

This argument has no effect when clock steering is enabled or when a PPS IN signal is available.

Refer to section 2.3 for a more detailed description of the time keeping in your receiver.

```
COM1> scst, msec1, on<CR>
$R: scst, msec1, on
  ClockSyncThreshold, msec1, on
COM1>
```



sep	setEventParameters	Event	Polarity	Delay			
gep	getEventParameters	Event					
		+ EventA + EventB all	HighzLow	-500.000000 <u>0.000000</u> 500.000000 ms			

Use these commands to define/inquire the polarity of the electrical transition on which the receiver will react on its Event input(s). The polarity of each event pin can be set individually or simultaneously by using the value all for the *Event* argument.

The command also allows defining a time delay for each event. This can be handy when the electrical transition at the event pin is not synchronous with the actual event that needs to be timed. For example, if the electrical transition occurs 100 milliseconds prior to the actual event of interest, the *Delay* argument must be set to 100. *Delay* is positive when the event of interest occurs after the electrical transition, and negative otherwise.

The event time (corrected by the specified delay) is available in the ExtEvent SBF block. The position at that time is available in the ExtEventPVTCartesian and ExtEventPVTGeodetic SBF blocks. Beware that, when using large *Delay* values in high-dynamics conditions, the position accuracy may degrade.

```
COM1> sep, EventA, High2Low, 10
$R: sep, EventA, High2Low, 10
   EventParameters, EventA, High2Low, 10.000000
COM1>
```





snc gnc	setNtpClient getNtpClient	Mode	Server (40)				
		on off	default				

Use this command to configure the retrieval of the time from an external NTP time server. Getting the time from an external source can help the receiver to perform some sanity checks on the signal received from the GNSS satellites. It is fully optional, except in case of strict OSNMA operation (see the **setGalOSNMAUsage** command).

If *Mode* is on, the receiver will attempt to get the current time from the NTP server specified with the *Server* argument.

The *Server* argument accepts a host name or a raw IP address. If set to "default", a server is automatically selected by the receiver.

Accessing the NTP server requires the receiver to have access to the Internet. If the receiver is not connected to a network, the access fails with no error message.

```
COM1> snc, on, pool.ntp.org<CR>
$R: snc, on, pool.ntp.org
  NtpClient, on, pool.ntp.org
COM1>
```



sntp gntp	setNTPServer getNTPServer	Enable				
		<u>off</u>				
		on				

Use this command to enable or disable the built-in NTP (Network Time Protocol) server.

When enabled, the NTP server accepts UDP timestamp requests on port number 123.

```
COM1> sntp, on<CR>
$R: sntp, on
   NTPServer, on
COM1>
```



spps	setPPSParameters	Interval	Polarity	Delay	TimeScale	MaxSyncAge	PulseWidth		
gpps	getPPSParameters								
		off	Low2High	-1000000.00	<u>GPS</u>	0 <u>60</u> 3600 s			
		msec10	High2Low	<u>0.00</u> 1000000.00 ns	Galileo		1000.000 ms		
		msec20			BeiDou				
		msec50			GLONASS				
		msec100			UTC				
		msec200			RxClock				
		msec250							
		msec500							
		sec1							
		sec2							
		sec4							
		sec5							
		sec10							
		sec30							
		sec60							

Use these commands to define/inquire the parameters of the x-pulse-per-second (xPPS) output. Refer to section 1.27 for additional information on the xPPS functionality.

The *Interval* argument specifies the time interval between the pulses. A special value "off" is defined to disable the xPPS signal.

The *Polarity* argument defines the polarity of the xPPS signal.

The *Delay* argument can be used to compensate for the overall signal delays in the system (including antenna, antenna cable and xPPS cable). Setting *Delay* to a higher value causes the xPPS pulse to be generated earlier. For example, if the antenna cable is replaced by a longer one, the overall signal delay could be increased by, say, 20 ns. If *Delay* is left unchanged, the xPPS pulse will come 20 ns too late. To re-synchronize the xPPS pulse, *Delay* has to be increased by 20 ns.

The xPPS pulses are aligned with the time system set with the *TimeScale* argument. RxClock corresponds to the receiver time scale. When setting *TimeScale* to RxClock, the xPPS pulses are synchronous with the internal measurement epochs.

The xPPS timing information is derived primarily from the satellites of the system selected with the *TimeScale* argument. If there is no satellite from that system available, the receiver will use information from other constellations to maintain the continuity of the pulses. If all satellite signals are blocked, the xPPS pulses will continue to be generated for a duration set with the *MaxSyncAge* argument. If *MaxSyncAge* is set to 0, or if *TimeScale* is set to RxClock, this timeout is disabled.

The *PulseWidth* argument sets the duration of the PPS pulse. The maximum duration of the pulse equals the PPS interval minus 100 microseconds, even if the requested *PulseWidth* is longer than that.

```
COM1> spps, sec1, Low2High, 23.40, GPS, 60, 0.1<CR>
$R: spps, sec1, Low2High, 23.40, GPS, 60, 0.1
PPSParameters, sec1, Low2High, 23.40, GPS, 60, 0.100
COM1>
```





setREFOUTMode getREFOUTMode	Enable	Disciplined	FreqOffset			
	-	off on	-1.000 <u>0.000</u> 1.000 ppm			

RxControl: Navigation > Advanced User Settings > Receiver Clock

Use this command to configure the 10-MHz REF OUT frequency reference output of the receiver.

The *Enable* argument enables or disables the frequency reference output at the REF OUT connector.

The *Disciplined* argument enables or disables the disciplining of the frequency reference to GNSS time. When enabled, the frequency reference at the REF OUT connector is locked to GNSS time scale. This locking process can take a few minutes. When lock is achieved, the REFOUT_LOCKED bit is set in the RxState field of the ReceiverStatus SBF block.

Instead of locking the frequency to the GNSS time scale, a small offset can be forced with the *FreqOffset* argument. In that case, the REFOUT_LOCKED bit is never set.

Note that the *Disciplined* and the *FreqOffset* arguments have no effect when the receiver is fed with an external frequency reference through the REF IN connector.

```
COM1> srom, on, off, 0.0<CR>
$R: srom, on, off, 0.0

REFOUTMode, on, off, 0.000

COM1>
```



		System				
gts	getTimingSystem					
		Galileo				
		GPS				
		BeiDou				
		<u>auto</u>				

Use these commands to define/inquire the reference time system for the computation of the receiver clock bias.

As part of the PVT computation, the receiver determines the offset between its own time (receiver time) and the time of the GNSS system specified with the System argument. This offset is reported in the RxClkBias field of the PVTCartesian and PVTGeodetic SBF blocks.



! Note that at least one satellite of the selected system must be visible and tracked by the receiver. Otherwise no PVT will be computed.

When the System argument is set to auto, the receiver automatically selects the GNSS system according to the availability of satellites. This is the recommended setting.

Example

COM1> sts, GPS<CR> \$R: sts, GPS TimingSystem, GPS





3.2.10 Time Transfer Configuration

scdy	setCABDLY	CABDLY				
gcdy	getCABDLY					
		-1000.000 <u>0.000</u> 1000.000 ns				

RxControl: Logging > Internal CGGTTS Logging > CGGTTS Parameters

This command sets the electrical delay in the cable from the antenna to the receiver. This delay is commonly referred to as $X_{\rm C}$ in the time-transfer literature.

The delay provided by this command is only used for the CGGTTS processing, and does not otherwise affect the receiver operation.

Example

COM1> scdy, 36.411<CR>
\$R: scdy, 36.411
 CABDLY, 36.411
COM1>



scpo	setCGGTTSPosition	SatSystem	Mode	X	Υ	Z		
gcpo	getCGGTTSPosition	SatSystem						
		+ GPS	<u>manual</u>	-8000000.0000	-8000000.0000	-8000000.0000		
		+ GLONASS		<u>0.0000</u> 8000000.0000	0.0000	800000.0000		
		+ GALILEO		m	m	m		
		+ BEIDOU						
		all						

Use this command to specify the antenna coordinates applicable to the CGGTTS processing. Contrary to other commands dealing with the antenna position, the (X, Y, Z) coordinates refer to the mean antenna phase center and not to the ARP. If needed, if is possible to enter different coordinates for the different GNSS systems.

The specified coordinates are copied to the CGGTTS file header and are used in the computation of the various fields of the CGGTTS file. They otherwise do not affect the receiver operation.

```
COM1> scpo, all, manual, 4021429.16, 332877.37, 4923031.62<CR>
$R: scpo, all, manual, 4021429.16, 332877.37, 4923031.62
CGGTTSPosition, all, manual, 4021429.1600, 332877.3700,
4923031.6200
COM1>
```





•	setCGGTTSTrackParameters getCGGTTSTrackParameters	ElMask	TrackSchedule				
		-90 <u>10</u> 90 deg	BIPM Contiguous				

This command configures some parameters of the CGGTTS computation.

The *ElMask* argument specifies the elevation mask to be used when computing the CGGTTS data. This mask is only used in the context of CGGTTS. The global receiver elevation mask is set with the **setElevationMask** command.

The scheduling of the 13-minute CGGTTS tracks is defined with the *TrackSchedule* argument. By default, the conventional BIPM scheduling is applied (13-minute tracks starting at predefined epochs with 3-minute idle intervals between tracks). In Contiguous mode, the CGGTTS parameters are computed every 13 minutes without idle interval, starting directly when CGGTTS logging is enabled. This non-standard mode provides a faster update rate of the time-transfer parameters.

```
COM1> scgt, 15, BIPM<CR>
$R: scgt, 15, BIPM
    CGGTTSTrackParameters, 15, BIPM
COM1>
```



sidy	setINTDLY	Frequency	INTDLY				
gidy	getINTDLY	Frequency					
		+ GPSL1	-1000.000				
		+ GPSL2	<u>0.000</u> 1000.000 ns				
		+ GLOL1	1000.000				
		+ GLOL2					
		+ GALE1					
		+ GALE5a					
		+BDSB1I					
		+ BDSB2I					
		all					

This command sets the electrical delays (INTDLY) applicable to the receiver and antenna. INTDLY is the sum of the delay in the antenna and in the receiver, commonly referred to as $X_{\rm S}$ and $X_{\rm R}$ in the literature. These delays are frequency dependent and are typically determined through a calibration campaign.

The delays provided by this command are only used for the CGGTTS processing, and do not otherwise affect the receiver operation.

```
COM1> sidy, BDSB1I, 3.65<CR>
$R: sidy, BDSB1I, 3.65
  INTDLY, BDSB1I, 3.650
COM1>
```



spim gpim	setPPSINMonitor getPPSINMonitor	Mode				
		off on				

By default, the receiver uses the PPS IN signal only at startup for initial synchronization. During operation, PPS IN is ignored and the receiver time is kept in sync by counting the cycles of the 10-MHz REF IN reference. It is assumed that the phase of PPS IN remains constant with respect to the 10-MHz reference, or in other words, that there are exactly 10 millions of cycles of the 10-MHz reference between each PPS IN pulse.

In some cases, this assumption is not valid, for example when the PPS IN phase can jump independently of the 10 MHz reference. When enabling PPS IN monitoring with the **setPPSINMonitor** command, the receiver continuously monitors the phase of the PPS IN signal. In case of jump, the receiver resets and resynchronizes to the new PPS IN phase. This ensures that the receiver time is always aligned with PPS IN. The jump detection threshold is set to about one nanosecond.

Example

COM1> spim, on<CR>
\$R: spim, on
 PPSINMonitor, on
COM1>





setPPSINParameters getPPSINParameters	XOCompensation				
	<u>off</u>				
	auto				

Use this command to enable or disable automatic compensation of the delay between the PPS IN pulse at the PPS IN connector and the receiver internal time reference. This delay is commonly referred to as $X_{\rm O}$ in the literature.

When delay compensation is enabled (the *XOCompensation* argument is set to \mathtt{auto}), X_O can be considered zero in all time transfer applications.

When delay compensation is disabled, $X_{\rm O}$ is not zero and must be measured by external means.

Refer to the User Manual for more details on the usage of the PPS IN input signal.

```
COM1> spin, off<CR>
$R: spin, off
   PPSINParameters, off
COM1>
```



srdy	setREFDLY	REFDLY				
grdy	getREFDLY					
		-1000.000 <u>0.000</u> 1000.000 ns				

This command sets the electrical delay between the laboratory clock and the receiver internal time reference. This delay is commonly referred to as $X_P + X_O$ in the literature. If the PPS IN internal delay compensation is enabled with the **setPPSINParameters** command, this is the delay in the cable from the clock to the PPS IN connector of the receiver (X_P).

See also the User Manual for a description of the various delays relevant to time transfer.

The delay provided by this command is only used for the CGGTTS processing, and does not otherwise affect the receiver operation.

Example

COM1> srdy, 23.4<CR>
\$R: srdy, 23.4
 REFDLY, 23.400
COM1>



stmp	setTimeLabParameters	LabName (40)	LabID (2)	RxID (2)	CalID (30)	CalRevDate (30)	TimeRef (30)	Comment (80)	
gtmp	getTimeLabParameters								

Use this command to specify the value of various fields of the CGGTTS file header and file name.

LabName is the name of the time laboratory, corresponding to the "LAB" field of the CGGTTS header.

LabID is the 2-character code assigned to the laboratory, used in the CGGTTS file name.

RxID is the 2-character receiver identification, used in the CGGTTS file name.


CalID is the calibration ID, corresponding to the "CAL_ID" field of the CGGTTS header.

CalRevDate is the revision date of the CGGTTS header data, corresponding to the "REV DATE" field of the CGGTTS header.

TimeRef is the identifier of the time reference, corresponding to the "REF" field of the CGGTTS header.

Comment is any comment, which will be added to the "COMMENTS" field of the CGGTTS header.

```
COM1> stmp, MyLab, L1, R1, MyCal, 2017-12-31, UTC(MyLab), This is
   a comment < CR>
$R: stmp, MyLab, L1, R1, MyCal, 2017-12-31, UTC(MyLab), This is a
   comment
   TimeLabParameters, MyLab, L1, R1, MyCal, 2017-12-31, UTC(MyLab),
        This is a comment
COM1>
```



3.2.11 Station Settings

smp	setMarkerParameters	MarkerName (60)	MarkerNumber (2	MarkerType (20)	StationCode (10)	Monumentldx	ReceiverIdx	CountryCode (3)	
gmp	getMarkerParameters								
		<u>SEPT</u>	<u>Unknown</u>	Unknown		<u>0</u> 9	<u>0</u> 9		

RxControl: Navigation > Receiver Setup > Station Settings

Use these commands to define/inquire the marker and station parameters.

The set of allowed characters for the *MarkerName* argument and for the *StationCode* argument is limited to:

```
_0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz
```

The *StationCode* argument is the site code associated to the station (typically four characters). *Monumentldx* can be used to identify the monument when there are multiple monuments at the same station. *Receiverldx* can be used to identify the receiver when there are multiple receivers at the same monument. A three-letter ISO country code can be specified with the *CountryCode* argument.

If internal logging is enabled in one of the IGS file naming modes, the file name depends on the settings of the **setMarkerParameters** command. Refer to the description of the logging commands (**setFileNaming**, **setBINEXLoggingParameters**, **setNMEALogging**, **setRTCMMSMLogging**, **setRINEXLogging**) for details.

The parameters set by this command are copied into the ReceiverSetup SBF block, which defines the file name and the header contents when converting SBF files into RINEX with the sbf2rin program.

```
COM1> smp, Test, 356, GEODETIC, TST1, 0, 0, BEL<CR>
$R: smp, Test, 356, GEODETIC, TST1, 0, 0, BEL
   MarkerParameters, Test, 356, GEODETIC, TST1, 0, 0, BEL
COM1>
```





soc	setObserverComment	Comment (120)				
goc	getObserverComment					
		<u>Unknown</u>				

RxControl: Navigation > Receiver Setup > Station Settings

Use these commands to define/inquire the content of the ${\tt Comment}$ SBF block.

```
COM1> soc, "Data taken with choke ring antenna" <CR>
$R: soc, "Data taken with choke ring antenna"
   ObserverComment, "Data taken with choke ring antenna"
COM1>

COM1> goc <CR>
$R: goc
   ObserverComment, "Data taken with choke ring antenna"
COM1>
```



sop	setObserverParameters	Observer (20)	Agency (40)				
gop	getObserverParameters						
		<u>Unknown</u>	<u>Unknown</u>				


RxControl: Navigation > Receiver Setup > Station Settings

Use these commands to define/inquire the observer name or ID, and his/her agency. These parameters are copied in the ReceiverSetup SBF block and in the header of RINEX observation files.

The length of the arguments complies with the RINEX format definition.

```
COM1> sop, TestObserver, TestAgency <CR>
$R: sop, TestObserver, TestAgency
  ObserverParameters, "TestObserver", "TestAgency"
COM1>

COM1> gop <CR>
$R: gop
  ObserverParameters, "TestObserver", "TestAgency"
COM1>
```



3.2.12 General Input/Output

scs	setCOMSettings	Cd	Rate	DataBits	Parity	StopBits	FlowControl		
gcs	getCOMSettings	Cd							
		+COM1	baud1200	bits8	<u>No</u>	bit1	<u>none</u>		
		+ COM2	baud2400				RTS CTS		
		+ COM3	baud4800						
		+ COM4	baud9600						
		all	baud19200						
			baud38400						
			baud57600						
			baud115200						
			baud230400						

RxControl: Communication > COM Port Settings

Use these commands to define/inquire the communication settings of the receiver's COM ports. By default, all COM ports are set to a baud rate of 115200 baud, using 8 data-bits, no parity, 1 stop-bit and no flow control.

Depending on your receiver hardware, it may be that not all COM ports support flow control. Please refer to the receiver Hardware Manual or User Manual to check which COM ports are equipped with the RTS/CTS lines.

When modifying the settings of the current connection, make sure to also modify the settings of your terminal emulation program accordingly.

Example

COM1> scs, COM1, baud19200, bits8, No, bit1, RTS|CTS<CR> \$R: scs, COM1, baud19200, bits8, No, bit1, RTS|CTS COMSettings, COM1, baud19200, bits8, No, bit1, RTS|CTS COM1>



scda gcda	setCrossDomainWebAccess getCrossDomainWebAccess	Mode				
		off on				

RxControl: Communication > Network Settings > General

This command enables or disables true open access across domain boundaries according to the CORS specification (Cross-Origin Resource Sharing).

Setting the *Mode* argument to on enables the cross-domain access to the receiver web server, and as such it allows external client applications (e.g. your own web application) to access receiver data via HTTP requests. Please contact Septentrio support for additional information on the receiver's JavaScript libraries.

Example

COM1> scda, on <CR>
\$R: scda, on
 CrossDomainWebAccess, on
COM1>



sdcm	setDaisyChainMode	DC	Mode				
gdcm	getDaisyChainMode	DC					
		+DC1	<u>Raw</u>				
		+ DC2	ASCII				
		all					

RxControl: Communication > Input/Output Selection

Use this command to define how data is transferred in a daisy chain configured with the **setDataInOut** command.

By default (Mode is Raw), incoming bytes are transferred in small chunks from the input to the output connector.

In some cases, it is preferred to transmit complete ASCII strings at once. This can be done by configuring the daisy chain in ASCII mode. A string is considered complete when a carriage-return and/or a line-feed character is received.

Example

COM1> sdcm, DC1, ASCII<CR>
\$R: sdcm, DC1, ASCII
 DaisyChainMode, DC1, ASCII
COM1>



sdio	setDataInOut	Cd	Input	Output	Show			
gdio	getDataInOut	Cd		,				
		+ COM1	none	none	(off)			
		+ COM2	CMD		(on)			
		+ COM3	RTCMv2	+ RTCMv3	(waiting)			
		+ COM4	RTCMv3	+ CMRv2				
		+ USB1	CMRv2	+ <u>SBF</u>				
		+ USB2	DC1	+ NMEA				
		+ IP10 IP17	DC2	+ ASCIIDisplay				
		+NTR1	RTCMV	+DC1				
		+ NTR2	ASCIIIN	+DC2				
		+ NTR3	<u>auto</u>	+ BINEX				
		+ IPS1		+ LBandBeam1				
		+ IPS2		+ LBandBeam2				
		+ IPS3						
		+ IPS4						
		+ IPS5						
		+ IPR1						
		+ IPR2						
		+ IPR3						
		+LOG1 LOG8						
		all						

RxControl: Communication > Input/Output Selection

Use these commands to define/inquire the type of data that the receiver should accept/send on a given connection descriptor (*Cd* - see 1.1.5).

The *Input* argument is used to tell the receiver how to interpret incoming bytes on the connection *Cd*. If a connection is to be used for receiving user commands or differential corrections in RTCM or CMR format, it is recommended to leave it in the default <code>auto</code> input mode. In this mode, the receiver automatically detects the input format.

It is also possible to set the input format explicitly. CMD means that the connection is to be used for user command input exclusively. RTCMv2, RTCMv3 and CMRv2 can be used to manually select the differential correction format, overriding the auto detection. RTCMV is the LBAS1-proprietary differential correction stream decoded from L-Band. ASCIIIN is used for connections receiving free-formatted ASCII messages, e.g. from an external meteo sensor.

In auto mode, the receiver automatically detects the CMD, RTCMv2, RTCMv3, RTCMV, or CMRv2 formats. The other input formats must be specified explicitly.

A connection that is not configured in CMD mode or auto mode will be blocked for user commands. There are two ways to re-enable the command input on a blocked connection. The first way is to reconfigure the connection by entering the command <code>setDataInOut</code> from another connection. The second way is to send the "escape sequence" consisting of a succession of ten "S" characters to the blocked connection within a time interval shorter than 5 seconds.

A connection that is configured in auto mode will initially accept user commands and differential corrections. However, as soon as differential corrections have been detected, the connection is blocked for user commands until the escape sequence is received.

The *Output* argument is used to select the types of data allowed as output. The receiver supports outputting different data types on the same connection. The <code>ASCIIDisplay</code> is a textual report of the tracking and PVT status at a fixed rate of 1Hz. It can be used to get a quick overview of the receiver operation. The <code>LBandBeami</code> option is to output the stream of bytes decoded from an L-Band beam (not available for some proprietary streams).



When opening an IPxx connection, the *Input* and *Output* modes are always reset to their default value.

DC1 and DC2 represent two internal pipes that can be used to create a daisy-chain. Set the *Input* argument to DCi to connect the input of pipe i to the specified connection. Set the *Output* argument to DCi to connect the output of pipe i to the specified connection. The daisy-chain can operate in binary or ASCII mode, as configured with the **setDaisyChainMode** command.

After the *Cd*, *Input* and *Output* arguments, an extra read-only *Show* argument will be returned in the command reply. This last argument can take the value on, off or waiting, depending on whether the connection descriptor is open, close, or waiting for a connection.

The *Input* argument is ignored for output-only connections, and the *Output* argument is ignored for input-only connections. See section 1.1.5 for details.

Note that not all input connections can accept user commands, check section 1.1.5 for details.

Examples

```
COM1> sdio, COM1, CMD <CR>
$R: sdio, COM1, CMD
  DataInOut, COM1, CMD, SBF, (on)
COM1>
```

On receivers that have three COM ports, to set up a two-way daisy-chain between COM2 and COM3, i.e. to have all incoming bytes from COM2 redirected to COM3 and all incoming bytes from COM3 redirected to COM2, enter the following commands from a connection different than COM2 and COM3:

```
COM1> sdio, COM2, DC1, DC2 <CR>
$R: sdio, COM2, DC1, DC2
   DataInOut, COM2, DC1, DC2, (on)
COM1> sdio, COM3, DC2, DC1 <CR>
$R: sdio, COM3, DC2, DC1
   DataInOut, COM3, DC2, DC1, (on)
COM1>
```



sdds	setDynamicDNS	Provider	UserName (40)	Password (40)	Hostname (40)	Bind		
gdds	getDynamicDNS							
		<u>off</u>				<u>auto</u>		
		dyndns.org				Ethernet		
		no-ip.com				WiFi		

RxControl: Communication > Network Settings > DynDNS

This command configures the built-in dynamic DNS client (DynDNS or DDNS).

Before using DynDNS, you will need to create an account and define a hostname for your receiver at one of the supported DynDNS providers. The list of supported providers is shown below.

Provider	Description
off	DynDNS disabled
dyndns.org	dyndns.org
no-ip.com	no-ip.com

The *Provider* argument specifies your DynDNS provider, the *UserName* and *Password* arguments specify the account credentials at this provider, and the *Hostname* is the full hostname associated to your receiver. Setting the *Provider* to off disabled the DynDNS functionality.

On receivers with multiple active network interfaces, the receiver registers the public IP address of the interface with the highest priority (Ethernet first, then WiFi), unless a specific interface is forced with the *Bind* argument.

The receiver checks every 2 minutes if the public IP address has changed, and updates the DynDNS server if needed. In addition a forced DynDNS server update is performed every 30 days. This is done to prevent the expiration of a DynDNS entry.

The DynDNS settings configured by this command are applied immediately and are kept upon a power cycle and even after a reset to factory default (see command exeResetReceiver).

Note that this command is not shown in the output of the **lstConfigFile** command.

Example

COM1> sdds, dyndns.org, Bart, MyPwd, rx1.dyndns-free.com, auto<CR>
\$R: sdds, dyndns.org, Bart, MyPwd, rx1.dyndns-free.com, auto
 DynamicDNS, dyndns.org, Bart, MyPwd, rx1.dyndns-free.com, auto
COM1>





eecm	exeEchoMessage	Cd	Message (242)	EndOfLine			
gecm	getEchoMessage						
		COM1	A:Unknown	none			
		COM2		+CR			
		СОМЗ		+LF			
		COM4		all			
		USB1					
		USB2					
		IP10 IP17					
		IPS1					
		IPS2					
		IPS3					
		IPS4					
		IPS5					
		IPR1					
		IPR2					
		IPR3					
		DC1					
		DC2					

RxControl: Communication > Output Settings > Echo Message

Use this command to send a message to one of the connections of the receiver.

The *Message* argument defines the message that should be sent on the Cd port. If the given message starts with "A:", the remainder of the message is considered an ASCII string that will be forwarded without changes to the requested connection. If the given message starts with "H:", the remainder of the message is considered a hexadecimal representation of a succession of bytes to be sent to the requested connection. In this case, the string should be a succession of 2-character hexadecimal values separated by a single whitespace.

Make sure to enclose the string between double quotes if it contains whitespaces. The maximum length of the *Message* argument (including the A: or H: prefix) is 242 characters.

The *EndOfLine* argument defines which end-of-line character should be sent after the message. That argument is ignored when the *Message* argument starts with \mathbb{H} :.

To send a message at a regular interval instead of once, use the command **setPeriodicEcho**.

When the *Cd* argument is DC1 or DC2, the message is injected into one of the internal daisy-chain pipes. See the **setDataInOut** command for details.

Examples

COM1>

To send the string "Hello world!" to COM2, use:

```
COM1> eecm, COM2, "A:Hello world!", none <CR>
$R: eecm, COM2, "A:Hello world!", none
    EchoMessage, COM2, "A:Hello world!", none
COM1>
```

To send the same string, the following command can also be used:



shs	setHttpsSettings	Protocol				
ghs	getHttpsSettings					
		+ HTTP				
		+ HTTPS				
		all				

RxControl: Communication > Network Settings > Security

This command can be used to enable or disable HTTP and/or HTTPS access to the receiver. By default, both HTTP and HTTPS are enabled.

Secure HTTP access requires the user to provide a certificate to the receiver. This is done by navigating to the "Communication > Web Server/TLS" page of the web interface, and uploading a .pem file containing the certificate. By default, if no user-provided certificate is available, the receiver will use a self-signed certificate instead. The user-provided certificate can be erased with exeResetReceiver, hard, HTTPSCertificate command, reverting to the self-signed certificate.

Note that the HTTPS certificate is also applicable to the built-in NTRIP caster in TLS mode. See also the **setNtripCasterSettings** command.

Example

COM1> shs, HTTP<CR>
\$R: shs, HTTP
 HttpsSettings, HTTP
COM1>



sipf gipf	setIPFiltering getIPFiltering	Mode	AddrList (200)				
		<u>off</u>					
		on					

RxControl: Communication > Network Settings > Security

Use this command to configure the IP filtering functionality. When IP filtering is enabled, only the specified IP addresses are allowed to connect to the receiver.

By default, IP filtering is off (the *Mode* argument is off) and the receiver accepts connections from any IP address.

When enabling IP filtering (*Mode* set to on), the *AddrList* argument must contain a whitespace-separated list of IP addresses (IPv4) allowed to connect to the receiver. Only IP addresses are allowed here, not hostnames. To enable a whole range of IP addresses, a netmask can also be specified using the so-called "slash notation", where the IP address is followed by a forward slash (/) and the subnet mask number from 0 to 32.

After entering the command, existing IP connections are kept active, but any new connection from a non-allowed IP address will be rejected.

Note that IP filtering is not applicable to the WiFi interface when the receiver is configured in access point mode.

```
COM1> sipf, on, 192.168.0.7 192.168.2.0/24<CR>
$R: sipf, on, 192.168.0.7 192.168.2.0/24

IPFiltering, on, 192.168.0.7 192.168.2.0/24

COM1>
```



sipk	setIPKeepAlive	Enable	IdleTime	Interval	MaxCount			
gipk	getIPKeepAlive							
		<u>off</u>	<u>15</u> 18000 s	<u>1</u> 3600 s	1 <u>15</u> 3600			
		on						

Use these commands to configure the TCP/IP KeepAlive mechanism.

When enabled, the receiver sends periodic KeepAlive messages over idle IP and IPS connections to solicit a response from the other end. The *IdleTime* argument sets the idle time after which the first KeepAlive is sent. If the connection stays idle (no response received), other KeepAlive messages are sent every *Interval* until *MaxCount* KeepAlives have been sent, after which the connection is closed.

KeepAlive messages are only sent when the connection is idle and no data is being transfered.



Keep in mind that when the *Interval* is set to a low number on a high latency connection, this might cause unnecessary traffic on the connection as well as premature disconnection.

```
COM1> sipk, on, 20, 20, 20<CR>
$R: sipk, on, 20, 20, 20
 IPKeepAlive, on, 20, 20, 20
COM1>
```



sipp	setIPPortSettings	Command	FTPControl				
gipp	getIPPortSettings						
		1 <u>28784</u> 65535	1 <u>21</u> 65535				

Use these commands to define/inquire the port numbers where the receiver listens for incoming TCP/IP connections.

The *Command* argument defines the port where the receiver listens for user commands.

The FTPControl argument defines the FTP control port number.

The IP port numbers configured by this command keep their value upon a power cycle and even after a reset to factory default (see command exeResetReceiver).

Note that this command is not shown in the output of the lstConfigFile command.



! When selecting a port number, make sure to avoid conflicts with other services (for example select a different port than in the setIPServerSettings and the setIPReceiveSettings commands).

```
COM1> sipp, 12345, 21<CR>
$R: sipp, 12345, 21
 IPPortSettings, 12345, 21
COM1>
```





sirs	setIPReceiveSettings	Cd	Port	Mode	TCPAddress (40)			
girs	getIPReceiveSettings	Cd						
		+IPR1	<u>0</u> 65535	TCP2Way	0.0.0.0			
		+ IPR2		UDP				
		+ IPR3						
		all						

This command configures the "IP receive" ports (IPR).

When Mode is set to TCP2Way, the receiver connects to the specified port of a server of which the IP address or hostname is provided in the TCPAddress argument. It then receives all data sent by this server on that port. The TCP2Way connection is bidirectional, and it is possible to send data to the server or to process commands from the server.

When Mode is set to UDP, the receiver listens for incoming UDP messages on its port identified by the *Port* argument. In UDP mode, the *TCPAddress* argument is ignored. Note that, contrary to the TCP connection, the UDP connection is unidirectional.

If *Port* is set to 0, the corresponding IPR connection is disabled.

This command is the counterpart of the **setIPServerSettings** command. setIPServerSettings configures the sender side of the communication, while **setIPReceiveSettings** configures the receiver side.



When selecting a port number, make sure to avoid conflicts with other services (for example) select a different port than in the **setIPPortSettings** command).

```
sirs, IPR1, 28785, TCP2Way, 192.168.10.5<CR>
$R: sirs, IPR1, 28785, TCP2Way, 192.168.10.5
 IPReceiveSettings, IPR1, 28785, TCP2Way, 192.168.10.5
COM1>
```





siss	setIPServerSettings	Cd	Port	Mode	UDPAddress (200)			
giss	getIPServerSettings	Cd						
		+ IPS1	<u>0</u> 65535	TCP	255.255.255.255			
		+ IPS2		UDP				
		+ IPS3		TCP2Way				
		+ IPS4						
		+ IPS5						
		all						

By default (Mode set to TCP), this command defines the TCP/IP port where the receiver's IP Servers (IPS) listen for incoming TCP/IP connections. When a client connects to an IPS port, all output data specified for that port are streamed to the client.

In TCP mode, the IPS port is unidirectional: it only sends data and incoming bytes are discarded. The TCP2Way mode is the same as the TCP mode, except that the receiver will also process input data (such as user commands or differential corrections). An IPS port configured in TCP2Way mode can only accept a single client at a time.

When Mode is set to UDP and UDPAddress is set to 255.255.255.255, the IPS works in UDP broadcast mode. In that mode, the IPS data stream is delivered to any host on the local network listening to the IP port specified by the *Port* argument.

When *Mode* is set to UDP and *UDPAddress* contains a whitespace-separated list of IP addresses or hostnames, the IPS data stream is only delivered to the specified hosts. Remember to enclose the *UDPAddress* argument between double quotes when it contains whitespaces.

Use the **setDataInOut** command and the various output setting commands (e.g. setNMEAOutput) to define the data stream to be output by the IPS connections. Note that the UDP implementation is meant to be used with small data volumes and low update rates. It is the user's responsibility to only enable short messages at low rate when using UDP, in order to prevent throughput degradation of the network.

It is possible to configure some IPS connections in UDP mode, and others in TCP mode. The UPDAddress argument is ignored in TCP mode.



When selecting a port number, make sure to avoid conflicts with other services (for example) select a different port than in the **setIPPortSettings** command).

All IPS connections must use different ports. Set the Port argument to 0 to disable an IPS connection.

```
COM1> siss, IPS1, 28785, UDP, 255.255.255.255<CR>
$R: siss, IPS1, 28785, UDP, 255.255.255.255
 IPServerSettings, IPS1, 28785, UDP, 255.255.255.255
```





sips	setIPSettings	Mode	IP (16)	Netmask (16)	Gateway (16)	Domain (63)	DNS1 (16)	DNS2 (16)	MTU	
gips	getIPSettings									
		DHCP	0.0.0.0	<u>255.255.255.0</u>	0.0.0.0		0.0.0.0	0.0.0.0	<u>0</u> 1500	
		Static								I
										ļ

Use these commands to define the IP (Internet Protocol) settings of the receiver's Ethernet port. By default, the receiver is configured to use DHCP.

In Static mode, the receiver will not attempt to request an address via DHCP. It will use the specified IP address, netmask, gateway, domain name and DNS. *DNS1* is the primary DNS, and *DNS2* is the backup DNS. The arguments *IP*, *Netmask*, *Gateway*, *Domain*, *DNS1*, and *DNS2* are ignored in DHCP mode.

In Static mode, the value of *MTU* is used as the MTU of the Ethernet port. When *MTU* is set to 0, the receiver will use the default MTU. In DHCP mode, setting *MTU* to 0 will result in using the MTU supplied by the DHCP server. When set to any other value, *MTU* will override the DHCP Server once the link is established.

The IP settings configured by this command keep their value upon a power cycle and even after a reset to factory default (see command exeResetReceiver).

Note that this command is not shown in the output of the lstConfigFile command.

The command **getIPSettings** cannot be used to get the current IP address assigned to the receiver by the DHCP server. The current IP address can be retrieved from the command **lstInternalFile**, **IPParameters**, or from the IPStatus SBF block.

```
COM1> sips, Static, 192.168.1.123, 255.255.252.0, 192.168.1.255,
   mydomain.local, 192.168.100.3, 192.168.100.4, 1500
$R: sips, Static, 192.168.1.123, 255.255.252.0, 192.168.1.255,
   mydomain.local, 192.168.100.3, 192.168.100.4, 1500
IPSettings, Static, 192.168.1.123, 255.255.252.0, 192.168.1.255,
   mydomain.local, 192.168.100.3, 192.168.100.4, 1500
COM1>
```





spe	setPeriodicEcho	Cd	Message (201)	Interval			
gpe	getPeriodicEcho	Cd					
		+ COM1	A:Unknown	<u>off</u>			
		+ COM2		once			
		+ COM3		msec100			
		+ COM4		msec200			
		all		msec500			
				sec1			
				sec2			
				sec5			
				sec10			
				sec15			
				sec30			
				sec60			
				min2			
				min5			
				min10			
				min15			
				min30			
				min60			

RxControl: Communication > Output Settings > Periodic Echo message

Use this command to periodically send a message to one of the connections of the receiver.

The Message argument defines the message that should be sent on the Cd port. If the given message starts with "A:", the remainder of the message is considered an ASCII string that will be forwarded to the requested connection. All occurrences of the %%CR character sequence are replaced by a single carriage return character (ASCII code 13d) and all occurrences of the %%LF character sequence are replaced by a single line feed character (ASCII code 10d). If the Message argument starts with "H:", the remainder of the message is considered a hexadecimal representation of a succession of bytes to be sent to the requested connection. In this case, the string should be a succession of 2-character hexadecimal values separated by a single whitespace.

Make sure to enclose the string between double quotes if it contains whitespaces. The maximum length of the *Message* argument (including the A: or H: prefix) is 201 characters.

The Interval argument defines the interval at which the message should be sent.

To send a message only once, set *Interval* to once. The only difference with the command **exeEchoMessage** is that **exeEchoMessage** cannot be stored in the boot configuration file, while **setPeriodicEcho** can. This can be used to output a message once at each reset or reboot. The third example below shows how to do this.

Examples

To send the string "Hello!<CR><LF>" to COM2 every minute, use:

```
COM1> spe, COM2, "A:Hello!%%CR%%LF", sec60 <CR>
$R: spe, COM2, "A:Hello!%%CR%%LF", sec60
   PeriodicEcho, COM2, "A:Hello!%%CR%%LF", sec60
COM1>
```

The same can be achieved with the following command:

```
COM1> spe, COM2, "H:48 65 6C 6C 6F 21 0D 0A", sec60 <CR> $R: spe, COM2, "H:48 65 6C 6C 6F 21 0D 0A", sec60
```



PeriodicEcho, COM2, "H:48 65 6C 6C 6F 21 0D 0A", sec60 COM1>

To let the receiver output the string "Hello!<CR><LF>" to COM2 at each reset, use the following command sequence:

COM1> spe, COM2, "A:Hello!%%CR%%LF", once <CR>
\$R: spe, COM2, "A:Hello!%%CR%%LF", once
PeriodicEcho, COM2, "A:Hello!%%CR%%LF", once
COM1> eccf, Current, Boot <CR>
\$R: eccf, Current, Boot
CopyConfigFile, Current, Boot



sp2p	setPointToPoint	SessionID	Mode	Cd	ClientIP (20)	ServerIP (20)	Auth	Password (40)	ConnectTimeout	ActivityTimeout
gp2p	getPointToPoint	SessionID								
		+ <u>P2PP1</u>	Off	COM1	192.168.50.2	<u>192.168.50.1</u>	<u>None</u>		<u>60</u> 300 s	10 <u>600</u>
		all	Server	COM2			PAP			32000 s
				СОМЗ			CHAP			
				COM4						

RxControl: Communication > Network Settings > P2P Protocol

The receiver features a Point-to-Point Protocol (P2PP) server, which emulates an IP link over a serial port. To avoid confusion with Precise Point Positioning, this feature is referred to as P2PP in Septentrio receivers. This command configures the P2PP server.

In the current version, the receiver implements a single P2PP server, and the first argument (ServerID) can only take the value P2PP1.

The *Mode* argument enables the P2PP server (it is disabled by default).

Cd sets the COM port to be used for the point-to-point communication. The baud rate and hardware flow control must be configured with the **setCOMSettings** command.

ClientIP sets the IP address that will be given to the client (i.e. your local computer) when a connection is established.

ServerIP sets the IP address that will be given to the server (i.e. the receiver) when a connection is established.

Auth determines whether the client needs to authenticate itself when establishing the connection. PAP will use Password Authentication Protocol and CHAP will use Challenge Handshake Authentication Protocol. When authentication is enabled, the *Password* argument sets the password that will need to be supplied.

ConnectTimeout sets the maximum time, in seconds, that a connection attempt may consume before being refused.

ActivityTimeout sets the maximum time, in seconds, that a connection may be idle (no data transfer) before it is disconnected.

When a timeout occurs, the receiver will shut down the P2PP server and restart it. When a server is enabled, and the configuration is correct, the receiver will start the P2PP server within a maximum of 30 seconds.

```
COM1> sp2p, P2PP1, Off, COM1, 255.255.255.255, 255.255.255.255,
    CHAP, P@ssw0rd1, 60, 600<CR>
$R: sp2p, P2PP1, Off, COM1, 255.255.255.255, 255.255.255.255, CHAP,
    P@ssw0rd1, 60, 600
PointToPoint, P2PP1, Off, COM1, 255.255.255.255, 255.255.255.255,
    CHAP, P@ssw0rd1, 60, 600
COM1>
```





spfw	setPortFirewall	Interface	OpenPorts	PortList (100)			
gpfw	getPortFirewall	Interface					
		+ Ethernet	none				
		+ WiFi	<u>default</u>				
		all	all				
			PortList				

RxControl: Communication > Network Settings > Security

Use this command to configure the receiver firewall, i.e. to specify the list of IP ports which are open to receive data.

The list of open ports can be specified independently for all network interfaces. The default (*OpenPorts* is set to default) depends on the interface, as follows:

Interface	Description
Ethernet	By default, all ports open.
	By default, all ports open. Note that the WiFi settings only applies when the receiver is configured as WiFi client (see 1.1.3.2.2). The WiFi firewall is disabled when the receiver is the access point.

It is possible to close all ports (*OpenPorts* is none), to open all ports (*OpenPorts* is all), or to manually specify a list of ports to open (*OpenPorts* is PortList). In the latter case, the list of port numbers needs to be specified in the *PortList* argument. The different port numbers must be separated by whitespaces. The *PortList* argument is ignored if *OpenPorts* is not set to PortList.

```
COM1> spfw, Ethernet, PortList, "21 80 28784"<CR>
$R: spfw, Ethernet, PortList, "21 80 28784"
   PortFirewall, Ethernet, PortList, "21 80 28784"
COM1>
```





3.2.13 NTRIP Settings

snmp	setNtripCasterMountPoints	MountPointID	Enable	MPName (32)	ExtServer	UserName (20)	Password (40)	ClientAuth	
gnmp	getNtripCasterMountPoints	MountPointID							
		+ MP1	<u>off</u>		<u>No</u>			none	
		+ MP2	on		Yes			<u>basic</u>	
		+ MP3							
		all							

RxControl: Communication > NTRIP Settings > NTRIP Caster settings

This command defines the general characteristics of the mount points available on the built-in NTRIP caster. The caster supports up to three mount points.

The *Enable* argument disables or disables a mount point. The *MPName* argument is the mount point name, as it will appear in the stream record of the caster source table. Make sure to give each enabled mount point a different name.

The *ExtServer* argument defines if the mount point is allowed to receive a stream from a remote NTRIP server (argument set to Yes), or if only local streams are allowed, i.e. streams originating from the receiver's own NTRIP server. The *UserName* and *Password* arguments are the credentials needed for the remote server to feed data. These arguments are ignored if *ExtServer* is set to No.

The *ClientAuth* argument defines the mount point client access protection. If set to none, all clients will be able to connect without providing credentials.

Note that the caster is reset each time a setting is changed with this command.

```
COM1> snmp, MP1, on, MyMP, Yes, MyUser, MyPwd, basic<CR>
$R: snmp, MP1, on, MyMP, Yes, MyUser, MyPwd, basic
   NtripCasterMountPoints, MP1, on, MyMP, Yes, MyUser, MyPwd, basic
COM1>
```





smpf	setNtripCasterMPFormat	MountPointID	Format	ManualFt (30)	FtDetails (100)			
gmpf	getNtripCasterMPFormat	MountPointID						
		+ MP1	RTCMv2					
		+ MP2	RTCMv3					
		+ MP3	CMR					
		all	NMEA					
			BINEX					
			RAW					
			manual					

RxControl: Communication > NTRIP Settings > NTRIP Caster settings

Use this command to define the format of the streams available on the caster mount points.

The Format argument defines the stream format, as will be reported in the <format> field of the sourcetable STR records. It is possible to select one of the predefined formats, or to enter a user-defined format. The latter is done by setting the Format argument to manual and by providing the format string with the ManualFt argument. The ManualFt argument is ignored when Format is not set to manual.

The FtDetails argument sets the contents of the <format-details> field of the sourcetable STR records.

When you need a comma in the ManualFt or FtDetails argument, use the "%%CM" escape sequence. Do not forget to enclose the string between double quotes if it contains whitespaces.

Note that the caster is reset each time a stream format is changed with this command.



When feeding a stream to the caster, make sure that the format of the stream corresponds to the settings in this command.

```
COM1> smpf, MP1, manual, RAW%%CMNMEA, "SBF (1s)%%CM NMEA (5s)"<CR>
$R: smpf, MP1, manual, RAW%%CMNMEA, "SBF (1s)%%CM NMEA (5s)"
 NtripCasterMPFormat, MP1, manual, RAW%%CMNMEA, "SBF (1s)%%CM NMEA
      (5s)"
COM1>
```





sncs gncs	setNtripCasterSettings getNtripCasterSettings	Mode	Port	Identifier (100)	TlsPort			
		off on	0 <u>2101</u> 65535	default	0 <u>2102</u> 65535			

RxControl: Communication > NTRIP Settings > NTRIP Caster settings

Use this command to enable and configure the built-in NTRIP caster.

Note that, if *Port* and *TlsPort* are equal, TLS is disabled.

The *Identifier* argument is a free text that can be used to describe the caster. If *Identifier* is set to the string "default", it is replaced by the receiver name and serial number. This text will appear in the "Identifier" field of the caster record in the NTRIP source table.

```
COM1> sncs, on, 2101, default, 2102<CR>
$R: sncs, on, 2101, default, 2102
  NtripCasterSettings, on, 2101, default, 2102
COM1>
```





sncu	setNtripCasterUsers	UserID	UserName (20)	Password (40)	MountPoints	MaxClients		
gncu	getNtripCasterUsers	UserID						
		+ User1			none	1 <u>10</u>		
		+ User2			+ MP1			
		+ User3			+ MP2			
		+ User4			+ MP3			
		+ User5			all			
		all						

RxControl: Communication > NTRIP Settings > NTRIP Caster settings

This command defines the user accounts (user name and password) that clients can use to connect to the built-in NTRIP caster. The password must contain at least one character (empty passwords are not supported). Up to five user accounts can be defined.

The *MounPoints* argument defines the list of mount points allowed for a given user account.

The caster can accept up to 10 concurrent client connections in total. The *MaxClients* argument can be used to limit the number of clients that are allowed to concurrently connect using a particular account.

To delete a user account, enter this command with an empty *UserName* argument.

Note that the caster is reset each time a user account is added, deleted or modified with this command.

```
COM1> sncu, User1, MyUser, MyPwd, all, 1<CR>
$R: sncu, User1, MyUser, MyPwd, all, 1
   NtripCasterUsers, User1, MyUser, MyPwd, all, 1
COM1>
```



snts	setNtripSettings	Cd	Mode	Caster (40)	Port	UserName (20)	Password (40)	MountPoint (32)	Version	SendGGA
gnts	getNtripSettings	Cd								
		+NTR1	<u>off</u>		0 <u>2101</u>				v1	<u>auto</u>
		+ NTR2	Server		65535				<u>v2</u>	off
		+NTR3	Client							sec1
		all								sec5
										sec10
										sec60

RxControl: Communication > NTRIP Settings > NTRIP Server/Client settings

Use this command to specify the parameters of the NTRIP connection referenced by the *Cd* argument.

The *Mode* argument specifies the type of NTRIP connection. In Server mode, the receiver is sending data to an NTRIP caster. In Client mode, the receiver gets data from the NTRIP caster. Set *Mode* to off to disable the connection.

Caster is the hostname or IP address of the NTRIP caster to connect to. To send data to the built-in NTRIP caster, use "localhost" for the Caster argument. Port, UserName, Password and MountPoint are the IP port number, the user name, the password and the mount point to be used when connecting to the NTRIP caster. The default NTRIP port number is 2101. Note that the receiver encrypts the password so that it cannot be read back with the command getNtripSettings.

The Version argument specifies which version of the NTRIP protocol to use (v1 or v2).

The SendGGA argument specifies whether or not to send NMEA GGA messages to the NTRIP caster, and at which rate. In auto mode (the default), the receiver automatically sends GGA messages if requested by the caster. This argument is ignored in NTRIP server mode.

```
COM1> snts, NTR1, Client, ntrip.com, 2101, USER, PWD, MP1, v2,
   auto<CR>
$R: snts, NTR1, Client, ntrip.com, 2101, USER, PWD, MP1, v2, auto
   NtripSettings, NTR1, Client, ntrip.com, 2101, USER, PWD, MP1, v2,
   auto
COM1>
```





Inst	IstNTRIPSourceTable	Caster (40)	Port				
			0 <u>2101</u> 65535				

Use this command to retrieve the source table from the specified NTRIP caster.

Caster is the hostname or IP address of the NTRIP caster to connect to, and *Port* is the IP port number. The default NTRIP port number is 2101.

```
COM1> Inst, ntripcaster <CR>
$R; lnst, ntripcaster
---->
$-- BLOCK 1 / 0 C
HTTP/1.1 200 OK
Ntrip-Version: Ntrip/2.0
Ntrip-Flags: st_filter, st_auth, st_match, st_strict
Server: NTRIP Caster/2.0.15
...
$-- BLOCK 1 / 0 C
ENDSOURCETABLE
COM1>
```



sntt	setNtripTlsSettings	Cd	Enable	Fingerprint (96)			
gntt	getNtripTlsSettings	Cd					
		+NTR1	<u>off</u>				
		+ NTR2	on				
		+NTR3					
		all					

RxControl: Communication > NTRIP Settings > NTRIP Server/Client settings

Use this command to enable or disable TLS on the NTRIP connection referenced by the *Cd* argument.

If the caster's certificate is known by a publicly-trusted certification authority (CA), the receiver will authenticate it by following the usual CA chain of trust, starting from root certificates present on the receiver. In that case, the *Fingerprint* argument should be left empty. If the NTRIP caster uses a self-signed certificate or a certificate only known by a private CA, its SHA-256 fingerprint must be provided. The self-signed certificate of the built-in caster (localhost) is present in the trust-zone of the receiver, and so the *Fingerprint* argument can be left empty for NTRIP client or server connections to localhost.

The examples below show different formats for the *Fingerprint* argument.

Examples

```
COM1> sntt, NTR1, on, ""<CR>
$R: sntt, NTR1, on, ""
  NtripTlsSettings, NTR1, on, ""
COM1>
```

Lower and upper case characters are allowed:

```
COM1> sntt, NTR1, on, Aa:Bb:56:78:90:12: ... 78:90:12:34 <CR>
$R: sntt, NTR1, on, Aa:Bb:56:78:90:12: ... 78:90:12:34
  NtripTlsSettings, NTR1, on, "AA:BB:56:78:90:12: ... 78:90:12:34"
COM1>
```


When using whitespaces as delimiter, do not forget to enclose the fingerprint in double quotes:

```
COM1> sntt, NTR1, on, "Aa Bb 56 78 90 12 ... 78 90 12 34" <CR> $R: sntt, NTR1, on, "Aa Bb 56 78 90 12 ... 78 90 12 34" NtripTlsSettings, NTR1, on, "AA:BB:56:78:90:12: ... 78:90:12:34" COM1>
```

It is also allowed to leave out the delimiters in the fingerprint:

```
COM1> sntt, NTR1, on, AaBb56789012 ... 78901234 <CR>
$R: sntt, NTR1, on, AaBb56789012 ... 78901234
  NtripTlsSettings, NTR1, on, "AA:BB:56:78:90:12: ... 78:90:12:34"
COM1>
```





3.2.14 WiFi Settings

eawa	exeAddWiFiAccessPoint	SSID (32)	Key (40)				
gawa	getAddWiFiAccessPoint						

RxControl: Communication > WiFi Settings > Client Add Network

Use this command to add a WiFi access point to the list of known access points, or to modify the password of a known access point. The *SSID* argument is the identifier of the access point and the *Key* argument is the password needed to connect to the access point.

This command must be entered for all access points that the receiver is to connect to. For open access points that do not require a key, set *Key* to "".

When the receiver is configured in WiFi client mode with the **setWiFiMode** command, it will check if a known access point is reachable and automatically connect to it.

By default, if multiple WiFi access points are reachable, the last one that was added with the **exeAddWiFiAccessPoint** command has the priority. Use the **exeManageWiFiAccessPoint** to overrule this and manually define the preferred access point.

The command permanently adds the WiFi access point to the list of known networks. The list is persistent across power cycles. The **exeManageWiFiAccessPoint** command can be used to remove an access point from the list (i.e. to forget an access point), and the **exeResetReceiver**, **hard**, **WiFiAccessPoints** command can be used to erase the complete list.

Use the command **lstWiFiAccessPoints** to get a list of the known and/or reachable WiFi access points.

```
COM1> eawa, MyWiFi, 12345678<CR>
$R: eawa, MyWiFi, 12345678
  AddWiFiAccessPoint, MyWiFi, "7VBC0NULTV6I"
COM1>
```





exeManageWiFiAccessPoint getManageWiFiAccessPoint	SSID (32)	Action				
		Promote Remove				

RxControl: Communication > WiFi Settings > Client Manage Network

Use this command to remove a WiFi access point from the list of known access points, or to promote it as preferred access point.

If the *Action* argument is Promote, the access point identified by the *SSID* argument is given the highest priority in case multiple known access points are reachable.

If the *Action* argument is Remove, the access point identified by the *SSID* argument is removed from the list of known access points. This will prevent the receiver from connecting to this access point until it is re-enabled with the **exeAddWiFiAccessPoint** command.

Example

COM1> emwa, MyWiFi, Promote<CR>
\$R: emwa, MyWiFi, Promote
 ManageWiFiAccessPoint, MyWiFi, Promote
COM1>





swfa	setWiFiAccessPoint	SSID (32)	EncryptionType	Key (40)	Channel	SSIDActual (32)		
gwfa	getWiFiAccessPoint							
		<u>default</u>	<u>none</u>	password	1 <u>6</u> 11	model-sn		
			WPA2					

RxControl: Communication > WiFi Settings > Access Point

Use this command to configure the WiFi access point.

The SSID is the name of your receiver in the WiFi network. By default, the SSID is the receiver model name followed by its serial number. Use the *SSID* argument to assign your receiver a different WiFi access point name. Using the reserved keyword "default" reverts to the default SSID.

By default, WiFi encryption is turned off. The encryption type and password can be specified with the second and third arguments.

The *Channel* argument sets the WiFi frequency channel to be used. It is not necessary to change this value unless you notice interference problems with another nearby WiFi device.

The last argument (*SSIDActual*) is read-only. It shows the actual SSID. It is a copy of the *SSID* argument except when the *SSID* argument is set to "default".



lwa	IstWiFiAccessPoints	Туре				
		+ Known				
		+ Reachable				
		all				

Use this command to list the known and/or the reachable WiFi access points.

The following information is provided for each access points (AP): the SSID, the signal level in dBm (only if AP is in reach), the security type, the current status (Connected, Known or Unknown), and, for known APs, the access point priority (P1 for highest priority). A "known" AP is an AP that has been defined with the **exeAddWiFiAccessPoint** command.

The *Type* argument defines the contents of the list:

Туре	Description
Known	List of known access points.
Reachable	List of the access points that are currently in reach of the receiver.

```
COM1> lwa, all <CR>
$R; lwa, all
---->
$-- BLOCK 1 / 0 C
"TestAP", -62, Unsecured, Unknown, None
"MyAP", -75, Unsecured, Connected, P2
"guest", -78, WPA, Unknown, None
COM1>
```



swfm gwfm	setWiFiMode getWiFiMode	Enable	Mode				
		off on	AccessPoint Client				

RxControl: Communication > WiFi Settings > General

Use this command to turn WiFi on and off, and to specify in which WiFi mode the receiver should operate (client or access point).

```
COM1> swfm, off<CR>
$R: swfm, off
  WiFiMode, off, AccessPoint
COM1>
```



3.2.15 NMEA Configuration

	exeNMEAOnce	Cd	Messages				
gnoc	getNMEAOnce						
		COM1	+ ALM				
		COM2	+ DTM				
		СОМЗ	+ GBS				
			+ GGA				
			+ GLL				
		USB2	+ GNS				
			+ GRS				
			+ GSA				
			+GST				
			+ GSV				
		IPS1	+ HDT				
		IPS2	+RMC				
		IPS3	+ ROT				
		IPS4	+ VTG				
		IPS5	+ ZDA				
		IPR1	+LLQ				
		IPR2	+ RBP				
		IPR3	+ RBV				
		LOG1 LOG8	+ RBD				
			+ AVR				
			+ GGK				
			+ GFA				
			+ GGQ				
			+ LLK				
			+ GMP				
			+ TFM				
			+ SNC				
			+ SRX				
			+ SDI				
			+SPW				

RxControl: Communication > Output Settings > NMEA Output Once

Use this command to output a set of NMEA messages on a given connection. This command differs from the related **setNMEAOutput** command in that it instructs the receiver to output the specified messages only once, instead of at regular intervals.

The *Cd* argument defines the connection descriptor (see 1.1.5) on which the message(s) should be output and the *Messages* argument defines the list of messages that should be output. Refer to appendix C for a short description of the NMEA sentences.

Please make sure that the connection specified by *Cd* is configured to allow NMEA output (this is the default for all connections). See the **setDataInOut** command.

Example

To output the receiver position on COM1, use:

COM1> enoc, COM1, GGA <CR>
\$R: enoc, COM1, GGA
 NMEAOnce, COM1, GGA
COM1>





sno	setNMEAOutput	Stream	Cd	Messages	Interval			
gno	getNMEAOutput	Stream						
			. <u>none</u>	none	<u>off</u>			
		Stream10	COM1	+ ALM	OnChange			
		all	COM2	+ DTM	msec10			
			COM3	+GBS	msec20			
			COM4	+GGA	msec40			
			USB1	+GLL	msec50			
			USB2	+GNS	msec100			
			IP10 IP17	+GRS	msec200			
			NTR1	+GSA	msec500			
				+GST	sec1			
			NTR3	+GSV	sec2			
				+ HDT	sec5			
			IPS2	+RMC	sec10			
			IPS3	+ROT	sec15			
				+VTG	sec30			
			IPS5	+ZDA	sec60			
				+LLQ	min2			
			IPR2	+RBP	min5			
				+RBV	min10			
			LOG1 LOG8	+RBD	min15			
				+ PUMRD	min30			
				+ AVR	min60			
				+GGK				
				+ GFA				
				+GGQ				
				+LLK				
				+GMP				
				+TXTbase				
				+TFM				
				+SNC				
				+SRX				
				+SDI				
				+ SPW				
<u></u>						i		

RxControl: Communication > Output Settings > NMEA Output > NMEA Output Intervals

Use this command to output a set of NMEA messages on a given connection at a regular interval. The *Cd* argument defines the connection descriptor (see 1.1.5) on which the message(s) should be output and the *Messages* argument defines the list of messages that should be output. Refer to appendix C for a short description of the NMEA sentences.

This command is the counterpart of the **setSBFOutput** command for NMEA sentences. Please refer to the description of that command for a description of the arguments.

Examples

To output GGA at 1Hz and RMC at 10Hz on COM1, use:

```
COM1> sno, Stream1, COM1, GGA, sec1 <CR>
$R: sno, Stream1, COM1, GGA, sec1
  NMEAOutput, Stream1, COM1, GGA, sec1
COM1> sno, Stream2, COM1, RMC, msec100 <CR>
$R: sno, Stream2, COM1, RMC, msec100
  NMEAOutput, Stream2, COM1, RMC, msec100
COM1>
```

To get the list of NMEA messages currently output, use:

```
COM1> gno <CR>
$R: gno
```



```
NMEAOutput, Stream1, COM1, GGA, sec1
NMEAOutput, Stream2, COM1, RMC, msec100
NMEAOutput, Stream3, none, none, off
NMEAOutput, Stream4, none, none, off
NMEAOutput, Stream5, none, none, off
NMEAOutput, Stream6, none, none, off
NMEAOutput, Stream7, none, none, off
NMEAOutput, Stream8, none, none, off
NMEAOutput, Stream9, none, none, off
NMEAOutput, Stream9, none, none, off
NMEAOutput, Stream10, none, none, off
COM1>
```



snp	setNMEAPrecision	NrExtraDigits	Compatibility	LocalDatum	MinStdDev			
gnp	getNMEAPrecision							
				off only	0.000 <u>0.001</u> 1.000 m			

RxControl: Communication > Output Settings > NMEA Output > Customize

Use these commands to define/inquire the number of extra digits in the latitude, longitude and altitude reported in NMEA sentences and to tune certain sentences to be compatible with third-party applications that are not fully compliant with the NMEA 0183 standard.

When *NrExtraDigits* is 0, the latitude and longitude are reported in degrees with 5 decimal digit, and altitude is reported in meters with 2 decimal digit. These default numbers of digits lead to a centimeter-level resolution of the position. To represent RTK positions with their full precision (millimeter-level), it is recommended to set *NrExtraDigits* to 2.

Note that increasing the number of digits (setting *NrExtraDigits* to a non-zero value) may cause the NMEA standard to be broken, as the total number of characters in a sentence may end up exceeding the prescribed limit of 82.

When setting the argument *Compatibility* to <code>Mode1</code>, the GPS Quality Indicator in GGA sentences is set to the value "2: Differential GPS" for all non-standalone positioning modes, the Mode Indicator in GNS sentences is set to "D: Differential" for all non-standalone positioning modes, and the Course Over Ground in the VTG sentences is not a null field for stationary receivers.

When setting the argument Compatibility to Mode2, the Course Over Ground in the VTG sentences is not a null field for stationary receivers.

The LocalDatum argument specifies whether transformation parameters sent out by the RTK service provider should be applied or not in NMEA sentences GGA and GNS. If LocalDatum is off, the transformation parameters are not applied, and the coordinates in GGA and GNS correspond to the coordinates in the PVTGeodetic SBF block. If LocalDatum is only and the relevant transformation parameters have been received, the coordinates are transformed to the local datum and correspond to the Poslocal SBF block. If the transformation parameters are not available, the coordinates are untransformed (in particular, the datum setting of the setGeodeticDatum command has no effect). The TFM proprietary NMEA sentence can be used to determine which transformation has been applied.

The *MinStdDev* argument defines the minimum standard deviation values that can be encoded in the GST sentence. If an actual standard deviation is below the value provided in *MinStdDev*, the value in *MinStdDev* is encoded instead.

```
COM1> snp, 2, Mode2, off, 0.05<CR>
$R: snp, 2, Mode2, off, 0.05
   NMEAPrecision, 2, Mode2, off, 0.050
COM1>
```





snti	setNMEATalkerID	TalkerID				
gnti	getNMEATalkerID					
		auto				
		<u>GP</u>				
		GN				

RxControl: Communication > Output Settings > NMEA Output > Customize

Use these commands to define/inquire the "Device Talker" for NMEA sentences. The device talker allows users to identify the type of equipment from which the NMEA sentence was issued.

When the *TalkerID* argument is set to auto, the talker will depend on the type of solution that is output. For a GNSS solution, "GN" is used if satellites from multiple constellations are used, "GP" for a GPS only solution, "GA" for a Galileo only solution, and "BD" for a BeiDou only solution.

Note that the command is ignored for the NMEA sentences where it would conflict with the standard. For example, the GSV sentence reporting the GPS visibility will always have its device talker set to "GP" regardless of the **setnmeatalkerID** command.

Example

COM1> snti, GP <CR>
\$R: snti, GP
 NMEATalkerID, GP
COM1>



snv gnv	setNMEAVersion getNMEAVersion	Version				
		<u>v3x</u> v4x				

RxControl: Communication > Output Settings > NMEA Output > Customize

Use this command to set the NMEA version the receiver should comply with.

If v3x is selected, the NMEA sentences are formatted according to the 3.01 version of the standard. If v4x is selected, system ID, signal ID and navigational status fields are added in some sentences according to version 4.11 of the NMEA standard.

Example

COM1> snv, v4x<CR>
\$R: snv, v4x
 NMEAVersion, v4x
COM1>



3.2.16 SBF Configuration

smrf	setMeas3MaxRefInterval	MaxIntrvl				
gmrf	getMeas3MaxRefInterval					
		OnlyRef				
		msec500				
		sec1				
		sec5				
		sec10				
		sec30				
		sec60				

RxControl: Communication > Output Settings > SBF Output > Customize

Use this command to define at which interval to encode reference epochs (i.e. full measurements) into the Meas 3Ranges SBF block. Refer to the description of the Meas 3Ranges block for a definition of the reference epochs.

When generating the Meas 3Ranges SBF block, the receiver automatically selects an optimal interval between reference epochs. This command allows the user to define the maximum interval allowed for his application. Setting the *MaxIntrvl* argument to OnlyRef forces the receiver to only encode reference epochs in Meas 3Ranges. This will allow to decode all epochs independently of any previous epoch, at the expense of a larger average SBF block size.

```
COM1> smrf, OnlyRef<CR>
$R: smrf, OnlyRef
   Meas3MaxRefInterval, OnlyRef
COM1>
```





ssgp	setSBFGroups	Group	Messages				
gsgp	getSBFGroups	Group					
		+ Group1	none				
		+ Group2	[SBF List]				
		+ Group3	+ Measurements				
		+ Group4	+ Meas3				
		all	+ RawNavBits				
			+ GPS				
			+ GLO				
			+ GAL				
			+ GEO				
			+ BDS				
			+ QZS				
			+ NavIC				
			+ PVTCart				
			+ PVTGeod				
			+ PVTExtra				
			+ Time				
			+ Events				
			+ DiffCorr				
			+ Status				
			+ LBand				
			+ Advanced				
			+ PostProcess				
			+ Rinex				
			+ RinexMeas3				
			+ Support				

RxControl: Communication > Output Settings > SBF Groups

Use these commands to define/inquire user-defined groups of SBF blocks that can be re-used in the **exeSBFOnce** and the **setSBFOutput** commands. The purpose of defining groups is to ease the typing effort when the same set of SBF blocks are to be addressed regularly.

The list of supported SBF blocks [SBF List] can be found in appendix A.

A number of predefined groups of SBF blocks are available (such as Measurements). See the command **setSBFOutput** for a description of these predefined groups.

Example

To output the messages MeasEpoch, PVTCartesian and DOP as one group on COM1 at a rate of 1Hz, you could use the following sequence of commands:

```
COM1> ssgp, Group1, MeasEpoch+PVTCartesian+DOP <CR>
$R: ssgp, Group1, MeasEpoch+PVTCartesian+DOP
   SBFGroups, Group1, MeasEpoch+PVTCartesian+DOP

COM1> sso, Stream1, COM1, Group1, sec1 <CR>
$R: sso, Stream1, COM1, Group1, sec1
   SBFOutput, Stream1, COM1, Group1, sec1
COM1>
```





esoc	exeSBFOnce	Cd	Messages				
gsoc	getSBFOnce						
		COM1	[SBF List]				
		COM2	+ Measurements				
		СОМЗ	+ Meas3				
		COM4	+ GPS				
		USB1	+ GLO				
		USB2	+ GAL				
		IP10 IP17	+ GEO				
		NTR1	+ BDS				
		NTR2	+ QZS				
		NTR3	+ NavIC				
		IPS1	+ PVTCart				
		IPS2	+ PVTGeod				
		IPS3	+ PVTExtra				
		IPS4	+ Time				
		IPS5	+ Status				
		IPR1	+ LBand				
		IPR2	+ UserGroups				
		IPR3	+ Advanced				
		LOG1 LOG8	+ PostProcess				
			+ Rinex				
			+ RinexMeas3				
			+ Support				

RxControl: Communication > Output Settings > SBF Output Once

Use this command to output a set of SBF blocks on a given connection. This command differs from the related **setSBFOutput** command in that it instructs the receiver to output the specified SBF blocks only once, instead of at regular intervals.

The *Cd* argument defines the connection descriptor (see 1.1.5) on which the message(s) should be output and the *Messages* argument defines the list of messages that should be output. The list of SBF blocks [SBF List] supported by the **exeSBFOnce** command can be found in appendix A.

Make sure that the connection specified by *Cd* is configured to allow SBF output (this is the default for all connections). See also the **setDataInOut** command.

Predefined groups of SBF blocks (such as Measurements) can be addressed in the *Messages* argument. These groups are defined in the table below.

When using this command to output a block that is also scheduled with the **setSBFOutput** command, the block will be sent twice. Note that this can cause duplicate measurement or PVT epochs in the SBF stream.

Messages	Description
Measurements	+MeasEpoch +MeasExtra +EndOfMeas
Meas3	+Meas3Ranges +Meas3CN0HiRes +Meas3Doppler +Meas3PP +Meas3MP
GPS	+GPSNav +GPSCNav +GPSAlm +GPSIon +GPSUtc
GLO	+GLONav +GLOAlm +GLOTime
GAL	+GALNav +GALAlm +GALIon +GALUtc +GALGstGps
GEO	+GEONav +GEOAlm
BDS	+BDSAlm +BDSNav +BDSCNav2 +BDSlon +BDSUtc



Messages (Continued)	Description
QZS	+QZSNav +QZSAlm
NavIC	+NavICLNav
PVTCart	+PVTCartesian +PosCovCartesian +VelCovCartesian +BaseVectorCart
PVTGeod	+PVTGeodetic +PosCovGeodetic +VelCovGeodetic +BaseVector- Geod +PosLocal
PVTExtra	+DOP +PVTSatCartesian +PVTResiduals +RAIMStatistics +GEO- Corrections +PVTSupport +PVTSupportA +EndOfPVT
Time	+ReceiverTime
Status	+SatVisibility +ChannelStatus +ReceiverStatus +InputLink +OutputLink +IPStatus +NTRIPClientStatus +NTRIPServerStatus +WiFiAPStatus +WiFiClientStatus +CosmosStatus +PowerStatus +QualityInd +DiskStatus +LogStatus +RFStatus +DynDNSStatus +P2PPStatus
LBand	+LBandTrackerStatus +LBAS1DecoderStatus +LBAS1Messages +LBandBeams
UserGroups	+Group1 +Group2 +Group3 +Group4
Advanced	+SystemInfo
PostProcess	+MeasEpoch +MeasExtra +GPSNav +GPSIon +GPSUtc +GLONav +GLOTime +GALNav +GALIon +GALUtc +GALGstGps +GEONav +BDSNav +BDSIon +BDSUtc +QZSNav +ReceiverSetup +Com- mands
Rinex	+MeasEpoch +GPSNav +GPSCNav +GPSIon +GPSUtc +GLONav +GALNav +GALUtc +GALGstGps +GEONav +BDSNav +BDSCNav2 +QZSNav +NavICLNav +PVTGeodetic +ReceiverSetup +Com- ment
RinexMeas3	+Meas3Ranges +GPSNav +GPSCNav +GPSIon +GPSUtc +GLONav +GALNav +GALUtc +GALGstGps +GEONav +BDSNav +BDSCNav2 +QZSNav +NavICLNav +ReceiverSetup +Comment
Support	+MeasEpoch +MeasExtra +EndOfMeas +GPSNav +GPSAlm +GPSIon +GPSUtc +GLONav +GLOAlm +GLOTime +GALNav +GALAlm +GALIon +GALUtc +GALGstGps +GEONav +GEOAlm +BDSAlm +BDSNav +BDSIon +BDSUtc +QZSNav +PVTGeodetic +PosCovGeodetic +BaseVectorGeod +DOP +PVTSupport +PVTSupportA +EndOfPVT +ChannelStatus +ReceiverStatus +Input-Link +OutputLink +ReceiverSetup +RxComponents +Commands +RxMessage +LBandTrackerStatus +LBAS1DecoderStatus +IPStatus +NTRIPClientStatus +NTRIPServerStatus +WiFiAPStatus +WiFiClientStatus +CosmosStatus +PowerStatus +QualityInd +LBandBeams +DiskStatus +LogStatus +RFStatus +DynDNSStatus +P2PPStatus +SystemInfo

Example

To output the next MeasEpoch block, use:



COM1> esoc, COM1, MeasEpoch <CR>
\$R: esoc, COM1, MeasEpoch
 SBFOnce, COM1, MeasEpoch
COM1>



SSO	setSBFOutput	Stream	Cd	Messages	Interval			
gso	getSBFOutput	Stream						
		+ Stream1 Stream16	none COM1	none [SBF List]	off OnChange			
		+ Res1	COM2	+ Measurements	msec10			
		+ Res2	СОМЗ	+ Meas3	msec20			
		+ Res3	COM4	+ RawNavBits	msec40			
		+ Res4	USB1	+ GPS	msec50			
		all	USB2	+ GLO	msec100			
			IP10 IP17	+ GAL	msec200			
			NTR1	+ GEO	msec500			
			NTR2	+BDS	sec1			
			NTR3	+ QZS	sec2			
			IPS1	+ NavIC	sec5			
			IPS2	+ PVTCart	sec10			
			IPS3	+ PVTGeod	sec15			
			IPS4	+ PVTExtra	sec30			
			IPS5	+ Time	sec60			
			IPR1	+ Event	min2			
			IPR2	+ DiffCorr	min5			
			IPR3		min10			
			LOG1 LOG8		min15			
					min30			
				+ Advanced	min60			
				+ PostProcess				
				+ Rinex				
				+ RinexMeas3				
				+ Support				

RxControl: Communication > Output Settings > SBF Output > SBF Output

Use this command to output a set of SBF blocks on a given connection at a regular interval.

A *Stream* is defined as a list of messages that should be output with the same interval on one connection descriptor (*Cd* - see 1.1.5). In other words, one *Stream* is associated with one *Cd* and one *Interval*, and contains a list of SBF blocks defined by the *Messages* argument.

The list of supported SBF blocks [SBF List] can be found in appendix A.

Predefined groups of SBF blocks (such as Measurements) can be addressed in the *Messages* argument. These groups are defined in the table below.

Messages	Description
Measurements	+MeasEpoch +MeasExtra +EndOfMeas
Meas3	+Meas3Ranges +Meas3CN0HiRes +Meas3Doppler +Meas3PP +Meas3MP
RawNavBits	+GPSRawCA +GPSRawL2C +GPSRawL5 +GPSRawL1C +GLO-RawCA +GALRawFNAV +GALRawINAV +GALRawCNAV +GEO-RawL1 +GEORawL5 +BDSRaw +BDSRawB1C +BDSRawB2a +BD-SRawB2b +NAVICRaw +QZSRawL1CA +QZSRawL2C +QZSRawL5 +QZSRawL6 +QZSRawL1C +QZSRawL1S +QZSRawL5S
GPS	+GPSNav +GPSCNav +GPSAlm +GPSIon +GPSUtc
GLO	+GLONav +GLOAlm +GLOTime
GAL	+GALNav +GALAlm +GALIon +GALUtc +GALGstGps +GALSAR-RLM



Messages (Continued)	Description
GEO	+GEOMT00 +GEOPRNMask +GEOFastCorr +GEOIntegrity +GE-OFastCorrDegr +GEONav +GEODegrFactors +GEONetworkTime +GEOAlm +GEOIGPMask +GEOLongTermCorr +GEOIonoDelay +GEOServiceLevel +GEOClockEphCovMatrix
BDS	+BDSAlm +BDSNav +BDSCNav2 +BDSIon +BDSUtc
QZS	+QZSNav +QZSAlm
NavIC	+NavICLNav
PVTCart	+PVTCartesian +PosCovCartesian +VelCovCartesian +BaseVectorCart
PVTGeod	+PVTGeodetic +PosCovGeodetic +VelCovGeodetic +BaseVector- Geod +PosLocal
PVTExtra	+DOP +PVTSatCartesian +PVTResiduals +RAIMStatistics +GEO- Corrections +PVTSupport +PVTSupportA +EndOfPVT
Time	+ReceiverTime +xPPSOffset
Event	+ExtEvent +ExtEventPVTCartesian +ExtEventPVTGeodetic +ExtEventBaseVectGeod
DiffCorr	+DiffCorrln +BaseStation +RTCMDatum
Status	+SatVisibility +ChannelStatus +ReceiverStatus +InputLink +Out- putLink +IPStatus +NTRIPClientStatus +NTRIPServerStatus +WiFiAPStatus +WiFiClientStatus +CosmosStatus +PowerStatus +QualityInd +DiskStatus +LogStatus +RFStatus +DynDNSStatus +P2PPStatus +GALAuthStatus
LBand	+LBandTrackerStatus +LBAS1DecoderStatus +LBAS1Messages +LBandBeams
UserGroups	+Group1 +Group2 +Group3 +Group4
Advanced	+SystemInfo
PostProcess	+MeasEpoch +MeasExtra +GEORawL1 +GPSNav +GPSlon +GP- SUtc +GLONav +GLOTime +GALNav +GALIon +GALUtc +GALGst- Gps +GEONav +BDSNav +BDSlon +BDSUtc +QZSNav +DiffCorrIn +ReceiverSetup +Commands +ExtEvent
Rinex	+MeasEpoch +GPSNav +GPSCNav +GPSIon +GPSUtc +GLONav +GALNav +GALUtc +GALGstGps +GEONav +BDSNav +BDSCNav2 +QZSNav +NavICLNav +PVTGeodetic +ReceiverSetup +Com- ment
RinexMeas3	+Meas3Ranges +GPSCNav +GPSNav +GPSIon +GPSUtc +GLONav +GALNav +GALUtc +GALGstGps +GEONav +BDSNav +BDSCNav2 +QZSNav +NavICLNav +ReceiverSetup +Comment



Messages (Continued)	Description
Support	+MeasEpoch +MeasExtra +EndOfMeas +GPSRawCA +GP-
	SRawL2C +GPSRawL5 +GPSRawL1C +GLORawCA +GALRawFNAV
	+GALRawINAV +GALRawCNAV +GEORawL1 +GEORawL5 +BD-
	SRaw +BDSRawB1C +BDSRawB2a +BDSRawB2b +NAVICRaw
	+QZSRawL1CA +QZSRawL2C +QZSRawL5 +QZSRawL6 +QZS-
	RawL1C +QZSRawL1S +QZSRawL5S +GPSNav +GPSAlm +GPSIon
	+GPSUtc +GLONav +GLOAlm +GLOTime +GALNav +GALAlm
	+GALIon +GALUtc +GALGstGps +GALAuthStatus +GEONav
	+GEOAlm +BDSAlm +BDSNav +BDSlon +BDSUtc +QZSNav
	+QZSAlm +PVTGeodetic +PosCovGeodetic +BaseVectorGeod
	+DOP +PVTSupport +PVTSupportA +EndOfPVT +ExtEvent +Dif-
	fCorrIn +BaseStation +ChannelStatus +ReceiverStatus +Input-
	Link +OutputLink +ReceiverSetup +RxComponents +Commands
	+RxMessage +LBandTrackerStatus +LBAS1DecoderStatus +IP-
	Status +NTRIPClientStatus +NTRIPServerStatus +WiFiAPStatus
	+WiFiClientStatus +CosmosStatus +PowerStatus +QualityInd
	+LBandBeams +DiskStatus +LogStatus +RFStatus +DynDNSSta-
	tus +P2PPStatus +SystemInfo

The *Interval* argument defines the rate at which the SBF blocks specified in the *Messages* argument are output. If set to off, the SBF blocks are disabled. If set to OnChange, the SBF blocks are output at their natural renewal rate (see section 4.1.8). If a specific interval is specified (e.g. sec1 corresponds to an interval of 1 second), the SBF blocks are decimated from their renewal rate to the specified interval. Some blocks can only be output at their renewal rate (e.g. the GPSNav block). For these blocks, the receiver ignores the value of the *Interval* argument and always assumes OnChange. The list of those blocks can be found in appendix A (see the "Flex Rate" column).

Please make sure that the connection specified by *Cd* is configured to allow SBF output (this is the default for all connections). See the **setDataInOut** command.

Res1 to Res4 are reserved values of *Stream*. These streams are not saved in the configuration files and, as a consequence, they will always be reset at boot time. For most users, it is not recommended to use these streams.

Example

To output the MeasEpoch block at 10Hz and the PVTGeodetic block at 1Hz on COM1, use the following sequence:

```
COM1> sso, Stream1, COM1, MeasEpoch, msec100 <CR>
$R: sso, Stream1, COM1, MeasEpoch, msec100
   SBFOutput, Stream1, COM1, MeasEpoch, msec100
COM1> sso, Stream2, COM1, PVTGeodetic, sec1 <CR>
$R: sso, Stream2, COM1, PVTGeodetic, sec1
   SBFOutput, Stream2, COM1, PVTGeodetic, sec1
COM1>
```



3.2.17 BINEX Configuration

sbfm	setBINEXFormatting	ObsSignals	ExtraObsTypes				
gbfm	getBINEXFormatting	Ü	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
		+ GPSL1CA	none				
		+ GPSL1PY	+ Doppler				
		+ GPSL2PY					
		+ GPSL2C					
		+ GPSL5					
		+ GPSL1C					
		+ GLOL1CA					
		+GLOL1P					
		+ GLOL2P					
		+ GLOL2CA					
		+ GLOL3					
		+ GALL1BC					
		+ GALE6BC					
		+ GALE5a					
		+ GALE5b					
		+ GALE5					
		+ GEOL1					
		+ GEOL5					
		+ BDSB1I					
		+ BDSB2I					
		+ BDSB3I					
		+ BDSB1C					
		+ BDSB2a					
		+ BDSB2b					
		+ QZSL1CA					
		+ QZSL2C					
		+ QZSL5					
		+ QZSL1C					
		+QZSL1S					
		+ QZSL5S					
		+ NAVICL5					
		+ GPS					
		+ GLONASS					
		+ GALILEO					
		+ SBAS					
		+ BEIDOU					
		+ QZSS					
		+ NAVIC					
		all					
	L						

RxControl: Communication > Output Settings > BINEX Output > Record Options

Use these commands to configure the contents of the observation records.

The *ObsSignals* argument specifies the signal types to be encoded in BINEX 0x7f-05 records. GPS, GLONASS, etc. are aliases to enable/disable all signals from a constellation at once.

For an observable to be actually encoded in BINEX, the corresponding signal type must be enabled with this command and the signal must be enabled for tracking (see the **setSignalTracking** command). By default, BINEX 0x7f records contain observables for all tracked signals.

The *ExtraObsTypes* argument is used to include or exclude Doppler observables in record 0x7f-05.

Note that this command is not connection-specific. For example, it is not possible to send observation records without Doppler through COM1, and at the same time to send observation records with Doppler through COM2.



Example

COM1> sbfm, GPSL1CA+GPSL2PY, Doppler<CR>
\$R: sbfm, GPSL1CA+GPSL2PY, Doppler
 BINEXFormatting, GPSL1CA+GPSL2PY, Doppler
COM1>



ebio	exeBINEXOnce	Cd	Messages				
gbio	getBINEXOnce						
		COM1	+ Rec00				
		COM2	+ Rec0101				
		СОМЗ	+ Rec0102				
		COM4	+ Rec0103				
		USB1	+ Rec0105				
		USB2	+ Rec0106				
		IP10 IP17	+ Rec0107				
		NTR1	+ Rec0114				
		NTR2	+ Rec05Geod				
		NTR3	+ Rec7D00				
		IPS1	+ Rec7F05				
		IPS2	+ Rec01Nav				
		IPS3					
		IPS4					
		IPS5					
		IPR1					
		IPR2					
		IPR3					
		LOG1 LOG8					

RxControl: Communication > Output Settings > BINEX Output Once

Use this command to output a set of BINEX records on a given connection. This command differs from the related **setBINEXOutput** command in that it instructs the receiver to output the specified BINEX records only once, instead of at regular intervals.

The *Cd* argument defines the connection descriptor (see 1.1.5) on which the records should be output and the *Messages* argument defines the list of records that should be output.

Refer to appendix B for a short description of the available BINEX records. Rec01Nav is an alias for the set of all decoded ephemeris records.

Make sure that the connection specified by *Cd* is configured to allow BINEX output (this is the default for all connections). See also the **setDataInOut** command.

Example

To output all the current decoded navigation records once, use:

```
COM1> ebio, COM1, Rec01Nav <CR>
$R: ebio, COM1, Rec01Nav
   BINEXOnce, COM1, Rec0101+Rec0102+Rec0103+Rec0114+Rec0105+Rec0106
COM1>
```





sbo	setBINEXOutput	Stream	Cd	Messages	Interval			
gbo	getBINEXOutput	Stream						
		+ Stream1 Stream16 all	NONE	Rec0147 + Rec05Geod + Rec7D00 + Rec7E01	off OnChange msec100 msec200 msec500 sec1 sec2 sec5 sec10 sec15 sec30 sec60 min2 min5 min10 min15 min30 min60			

RxControl: Communication > Output Settings > BINEX Output > BINEX Output Intervals

Use this command to output a set of BINEX records on a given connection at a regular interval.

A *Stream* is defined as a list of records that should be output with the same interval on one connection descriptor (*Cd* - see 1.1.5). In other words, one *Stream* is associated with one *Cd* and one *Interval*, and contains a list of BINEX records defined by the *Messages* argument.

Refer to appendix B for a short description of the available BINEX records. Rec01Nav is an alias for "Rec0101+Rec0102+Rec0103+Rec0114+Rec0105+Rec0106+Rec0107", and Rec01Raw is an alias for "Rec0141+Rec0142+...+Rec0147".

The *Interval* argument defines the rate at which the BINEX records specified in the *Messages* argument are output. If set to off, the BINEX records are disabled. If set to OnChange, the BINEX records are output at their OnChange rate defined in appendix B. If another interval is specified (e.g. sec1 corresponding to an interval of 1 second), the BINEX records are decimated from their OnChange rate to the specified interval. Many records can only be output at their OnChange rate. For these records, the receiver ignores the value of the *Interval* argument and always assumes OnChange. See the "Flex Rate" column in appendix B to know if a record can be output at a flexible rate.

Please make sure that the connection specified by *Cd* is configured to allow BINEX output (this is the default for all connections). See the **setDataInOut** command.

Example

To output all the decoded ephemeris records at their OnChange rate together with the GNSS observables at 1 Hz on COM1, use the following command:

```
COM1> sbo, Stream1, COM1, Rec01Nav + Rec7F05, sec1 <CR>
$R: sbo, Stream1, COM1, Rec01Nav + Rec7F05, sec1
BINEXOutput, Stream1, COM1, Rec0101+Rec0102+Rec0103+Rec0114+
Rec0105+Rec0106+Rec7F05, sec1
COM1>
```





3.2.18 RTCM v2.x Settings

sr2c	setRTCMv2Compatibility	PRCType	GLOToD	RTKVersion			
gr2c	getRTCMv2Compatibility						
		<u>Standard</u>	<u>Tk</u>	v2.1			
		GroupDelay	ТЬ	v2.2orLater			

RxControl: Communication > Input Settings > Differential Corrections > RTCMv2

Use these commands to define/inquire the compatibility of the RTCM 2.x input correction stream. This command applies to rover receivers only and should be used in case the available base station correction stream is not fully compatible with the latest version of the RTCM 2.x standard.

The *PRCType* argument is used to handle a difference in the interpretation of DGPS corrections between the version 2.0 of the RTCM standard and later versions. If the base station is sending RTCM Message Type 1 based on version 2.0, the value <code>GroupDelay</code> must be selected to have a correct usage of incoming corrections.

The *GLOToD* argument specifies how to interpret the time-of-day field in the differential GLONASS correction message (MT31). Select ${\tt Tb}$ to be compatible with RTCM version up to 2.2, and select ${\tt Tk}$ to be compatible with RTCM 2.3 and later.

The *RTKVersion* argument specifies if the base station encodes RTK correction messages (MT18 to MT21) according to version 2.1 of the RTCM standard, or according to version 2.2 or above.

Example

To make to rover receiver compatible with a base station sending RTCM 2.2 corrections, use:

```
COM1> sr2c, , Tb <CR>
$R: sr2c, , Tb
   RTCMv2Compatibility, Standard, Tb, v2.2orLater
COM1>
```



sr2h	setRTCMv2EphemerisHoldoff	TimeGPS	TimeGLO				
gr2h	getRTCMv2EphemerisHoldoff						
		<u>0</u> 300 s	<u>0</u> 300 s				

This command specifies the delay in applying new navigation data sets when generating DGPS correction messages such as MT1.

The delay can be set independently for GPS and GLONASS satellites with the *TimeGPS* and *TimeGLO* arguments.

Upon reception of a new navigation data set from GPS(GLONASS) satellites (IOD change), the DGPS corrections continue to refer to the previous data set for *TimeGPS*(*TimeGLO*) seconds.

```
COM1> sr2h, 60, 60<CR>
$R: sr2h, 60, 60
   RTCMv2EphemerisHoldoff, 60, 60
COM1>
```





sr2f gr2f	setRTCMv2Formatting getRTCMv2Formatting	ReferenceID	GLOToD			
		<u>0</u> 1023	Tk Tb			

Use these commands to define/inquire the reference station ID assigned to the receiver when operating in base station mode. The reference station ID is transmitted in the first word of each outgoing RTCM v2.x message.

The argument *GLOToD* specifies how to encode the time-of-day field in the differential GLONASS correction message (MT31). Select ${\tt Tb}$ to be compatible with RTCM version up to 2.2, and select ${\tt Tk}$ to be compatible with RTCM 2.3 and later.

```
COM1> sr2f, 345 <CR>
$R: sr2f, 345
  RTCMv2Formatting, 345, Tk
COM1>

COM1> gr2f <CR>
$R: gr2f
  RTCMv2Formatting, 345, Tk
COM1>
```



sr2i	setRTCMv2Interval	Message	ZCount				
gr2i	getRTCMv2Interval	Message					
		+ RTCM1	1 <u>2</u> 1000				
		+ RTCM3					
		+ RTCM9					
		+RTCM16					
		+ RTCM17					
		+ RTCM22					
		+ RTCM23 24					
		+ RTCM31					
		+ RTCM32					
		all					

Use these commands to define/inquire at which interval the RTCM v2.x messages specified in the *Message* argument should be generated. The related **setRTCMv2IntervalObs** command must be used to specify the interval of some RTK-related messages such as messages 18 and 19.

The interval for every message is given in the *ZCount* argument, in units of 0.6 seconds. For example, to generate a message every 6 seconds, *ZCount* should be set to 10.

For the ephemerides message (RTCM17), the ephemerides are sent out one satellite at a time, at a rate specified by this command. For instance, if *ZCount* is set to 1 and there are 12 ephemerides to send out, it takes 0.6*12=7.2 seconds to send the whole ephemerides set.

The intervals specified with this command are not connection-specific: all the connections which output a given RTCM v2.x message will output it with the same interval.

Note that this command only defines the interval of RTCM messages. To make the receiver actually output these messages, use the **setRTCMv2Output** and **setDataInOut** commands.

Refer to appendix D for an overview of the supported RTCM v2.x messages.

```
COM1> sr2i, RTCM22, 15 <CR>
$R: sr2i, RTCM22, 15
RTCMv2Interval, RTCM22, 15
COM1>

COM1> gr2i <CR>
$R: gr2i
RTCMv2Interval, RTCM1, 2
RTCMv2Interval, RTCM3, 2
RTCMv2Interval, RTCM3, 2
RTCMv2Interval, RTCM16, 2
RTCMv2Interval, RTCM22, 15
RTCMv2Interval, RTCM22, 15
RTCMv2Interval, RTCM23|24, 2
COM1>
```





sr2b	setRTCMv2IntervalObs	Message	Interval				
gr2b	getRTCMv2IntervalObs	Message					
		+ RTCM18 19	<u>1</u> 600 s				
		+ RTCM20 21					
		all					

Use these commands to define/inquire at which interval the RTCM v2.x messages specified in the *Message* argument should be generated. The related **setRTCMv2Interval** command must be used to specify the interval of other supported RCTCM v2.x messages.

The intervals specified with this command are not connection-specific: all the connections which output a given RTCM v2.x message will output it with the same interval.

Note that this command only defines the interval of RTCM messages. To make the receiver actually output these messages, use the **setRTCMv2Output** and **setDataInOut** commands.

```
COM1> sr2b, RTCM20|21, 2 <CR>
$R: sr2b, RTCM20|21, 2
  RTCMv2IntervalObs, RTCM20|21, 2
COM1>

COM1> gr2b <CR>
$R: gr2b
  RTCMv2IntervalObs, RTCM18|19, 1
  RTCMv2IntervalObs, RTCM20|21, 2
COM1>
```





sr2m	setRTCMv2Message16	Message (90)				
gr2m	getRTCMv2Message16					
		<u>Unknown</u>				

Use these commands to define/inquire the string that will be transmitted in the RTCM v2.x message 16. The argument *Message* can contain up to 90 characters.

Note that this command only defines the content of message 16. To make the receiver actually output this message, use the **setRTCMv2Output** and **setDataInOut** commands.

Example

To send the string "Hello" in message 16 over COM2 at the default interval, use the following sequence:

```
COM1> sr2m, Hello <CR>
$R: sr2m, Hello
  RTCMv2Message16, "Hello"

COM1> sr2o, COM2, RTCM16 <CR>
$R: sr2o, COM2, RTCM16
  RTCMv2Output, COM2, RTCM16

COM1> sdio, COM2, RTCMv2 <CR>
$R: sdio, COM2, RTCMv2
  DataInOut, COM2, auto, RTCMv2
COM1>
```





sr2o	setRTCMv2Output	Cd	Messages				
gr2o	getRTCMv2Output	Cd					
		+ COM1	none				
		+ COM2	+RTCM1				
		+ COM3	+ RTCM3				
		+ COM4	+ RTCM9				
		+ USB1	+RTCM16				
		+ USB2	+ RTCM18 19				
		+ IP10 IP17	+ RTCM20 21				
		+NTR1	+ RTCM22				
		+NTR2	+ RTCM23 24				
		+NTR3	+ RTCM31				
		+ IPS1	+RTCM32				
		+ IPS2	+RTCM17				
		+ IPS3	+ DGPS				
		+ IPS4	+RTK				
		+ IPS5	all				
		+ IPR1					
		+ IPR2					
		+ IPR3					
		all					

Use these commands to define/inquire which RTCM v2.x messages are enabled for output on a given connection descriptor (*Cd* - see 1.1.5). The *Messages* argument specifies the RTCM message types to be enabled. Some pairs of messages are always enabled together, such as messages 18 and 19. DGPS is an alias for "RTCM1+RTCM3+RTCM31" and RTK is an alias for "RTCM3+RTCM18|19+RTCM22+RTCM31".

Refer to appendix D for an overview of the supported RTCM v2.x messages.

Please make sure that the connection specified by *Cd* is configured to allow RTCMv2 output, which can be done with the **setDataInOut** command. The interval at which each message is output is to be specified with the **setRTCMv2Interval** or the **setRTCMv2IntervalObs** command.

Example

To enable RTCM v2.x messages 3, 18, 19 and 22 on COM2, use the following sequence:

```
COM1> sr2o, COM2, RTCM3+RTCM18|19+RTCM22 <CR>
$R: sr2o, COM2, RTCM3+RTCM18|19+RTCM22
  RTCMv2Output, COM2, RTCM3+RTCM18|19+RTCM22
COM1> sdio, COM2, , RTCMv2 <CR>
$R: sdio, COM2, , RTCMv2
  DataInOut, COM2, auto, RTCMv2
COM1>
```





sr2u	setRTCMv2Usage	MsgUsage				
gr2u	getRTCMv2Usage					
		none				
		+ RTCM1				
		+ RTCM3				
		+ RTCM9				
		+RTCM15				
		+ RTCM18 19				
		+ RTCM20 21				
		+ RTCM22				
		+ RTCM23 24				
		+ RTCM31				
		+ RTCM32				
		+ RTCM34				
		+ RTCM17				
		+ RTCM59				
		all				

Use this command to restrict the list of incoming RTCM v2.x messages that the receiver is allowed to use in its differential PVT computation.

A short description of the supported RTCM v2.x messages can be found in appendix D.

Example

To only accept RTCM1 and RTCM3 corrections from the base station 1011, use the following sequence:

```
COM1> sr2u, RTCM1+RTCM3 <CR>
$R: sr2u, RTCM1+RTCM3
   RTCMv2Usage, RTCM1+RTCM3
COM1> sdcu, , , manual, 1011 <CR>
$R: sdcu, , , manual, 1011
   DiffCorrUsage, LowLatency, 3600.0, manual, 1011 ...
COM1>
```



3.2.19 RTCM v3.x Settings

setRTCMv3CRSTransfo getRTCMv3CRSTransfo	Mode	TargetName (32)				
	auto manual					

RxControl: Communication > Input Settings > Differential Corrections > RTCMv3

Use this command to specify how to apply the coordinate reference system (CRS) transformation parameters contained in RTCM v3.x message types 1021 to 1023.

In auto mode (the default), the receiver decodes and applies the coordinate transformation parameters from message types 1021-1023. If your RTK provider sends transformation parameters for more than one target CRS, the receiver selects the first transformation parameters it receives.

In manual mode, you can force the receiver to only apply the transformation to the target CRS specified with the second argument. The *TargetName* argument must exactly match the name used by the RTK provider. The available target datum names can be found in the RTCMDatum SBF block.

Example

To force using the target CRS identified as "4258" by the RTK network, use:

```
COM1> sr3t, manual, "4258"<CR>
$R: sr3t, manual, "4258"
  RTCMv3CRSTransfo, manual, "4258"
COM1>
```



sr3d	setRTCMv3Delay	Delay				
gr3d	getRTCMv3Delay					
		<u>0.0</u> 600.0 s				

Use this command to instruct the receiver to generate and output RTCM v3.x messages with a certain delay.

It is possible to impose a global delay to all RTCM v3.x messages by setting the *Delay* to a nonzero value. This can be used in situations where multiple base stations must be configured to transmit their corrections in a time-multiplexed way. For example, base station A would compute and transmit its corrections at every 10-second epoch (in the GPS time scale), and base station B would compute and transmit its corrections 5 seconds after the 10-second epochs. In that case, receiver B would be configured with the *Delay* argument set to 5.

See also the **setRTCMv3Interval** command to configure the message interval.

Example

To generate the RTCM1001 message with an interval of 10 seconds and a time shift of 2 seconds, use:

```
COM1> sr3i, RTCM1001|2, 10 <CR>
$R: sr3i, RTCM1001|2, 10
   RTCMv3Interval, RTCM1001|2, 10
COM1> sr3d, 2 <CR>
$R: sr3d, 2
   RTCMv3Delay, 2
COM1>
```





sr3f	setRTCMv3Formatting	ReferenceID	MSMSignals	GLOL2	RxType (32)			
gr3f	getRTCMv3Formatting							
		<u>0</u> 4095			<u>default</u>			
			+ GPSL1PY	L2P				
			+ GPSL2PY					
			+ GPSL2C					
			+ GPSL5					
			+ GPSL1C					
			+ GLOL1CA					
			+GLOL1P					
			+ GLOL2P					
			+ GLOL2CA					
			+ GLOL3					
			+ GALL1BC					
			+ GALE6BC					
			+ GALE5a					
			+ GALE5b					
			+ GALE5					
			+ GEOL1					
			+ GEOL5					
			+ BDSB1I					
			+ BDSB2I					
			+ BDSB3I					
			+ BDSB1C + BDSB2a					
			+ BDSB2a + BDSB2b					
			+ QZSL1CA					
			+ QZSLTCA + QZSL2C					
			+ QZSL2C + QZSL5					
			+ QZSL3 + QZSL1C					
			+ QZSLTC + NAVICL5					
			all					
			all					

Use these commands to configure the RTCM v3.x message contents when operating in base station mode.

The *ReferenceID* argument specifies the reference station ID transmitted in the header of each outgoing RTCM v3.x message.

The MSMSignals argument specifies the signal types to be encoded in MSM messages. For an observable to be actually encoded in MSM, the corresponding signal type must be enabled with this command, the signal must be enabled for tracking (see the **setSignalTracking** command), and a suitable MSM message must be enabled with the **setRTCMv3Output** command.

The *GLOL2* argument applies to message types 1011 and 1012 (GLONASS L1 and L2 observables). It specifies which of the L2P or the L2CA observables must be encoded in RTCM1011 and RTCM1012.

The *RxType* argument can be used to change the receiver type that is transmitted in message 1033, i.e. to change the way the receiver identifies itself to the RTCM network. Setting *RxType* to "default" reverts to the default receiver type.

Example

COM1> **sr3f**, **345 <CR>**

\$R: sr3f, 345

RTCMv3Formatting, 345, GPSL1CA+GPSL2PY+GLOL1CA+GLOL2CA+GALL1BC+GALE5a+BDSB1I+BDSB2I+QZSL1CA+QZSL2C, L2CA, default



COM1>



sr3i	setRTCMv3Interval	Message	Interval				
gr3i	getRTCMv3Interval	Message					
		+RTCM1001 2	0.1 <u>1.0</u>				
		+ RTCM1003 4	600.0 s				
		+ RTCM1005 6					
		+ RTCM1007 8					
		+ RTCM1009 10					
		+RTCM1011 12					
		+ RTCM1013					
		+ RTCM1019					
		+ RTCM1020					
		+ RTCM1029					
		+ RTCM1033					
		+ RTCM1041					
		+ RTCM1042					
		+ RTCM1044					
		+ RTCM1045					
		+ RTCM1046					
		+ RTCM1230					
		+ MSM1 MSM7					
		all					

Use these commands to define/inquire at which interval RTCM v3.x messages should be generated.

The intervals specified with this command are not connection-specific: all the connections which output a given RTCM v3.x message will output it with the same interval.

Using \mathtt{MSMi} for the *Message* argument sets the interval of all Multiple Signal Messages of type \mathtt{i} . Refer to appendix D for an overview of the supported RTCM v3.x messages.

For the ephemerides messages (e.g. RTCM1019), the ephemerides are sent out one satellite at a time, at a rate specified by this command. For instance, if *Interval* is set to 1 and there are 12 GPS ephemerides to send out, it takes 12 seconds to send the whole GPS ephemerides set.

By default, RTCM v3.x messages are generated at integer multiples of the specified interval in the GPS time scale. The command **setRTCMv3Delay** can be used to introduce a time offset.

Note that this command only defines the interval of RTCM messages. To make the receiver actually output these messages, use the **setRTCMv3Output** and **setDataInOut** commands.

```
COM1> sr3i, RTCM1001|2, 2 <CR>
$R: sr3i, RTCM1001|2, 2
   RTCMv3Interval, RTCM1001|2, 2
COM1>
```





sr3m	setRTCMv3Message1029	Message (120)				
gr3m	getRTCMv3Message1029					
		<u>Unknown</u>				

Use these commands to define/inquire the string that will be transmitted in the RTCM v3.x message 1029. The argument *Message* can contain up to 120 characters.

Note that this command only defines the content of message 1029. To make the receiver actually output this message, use the **setRTCMv3Output** and **setDataInOut** commands.

Example

To send the string "Hello" in message 1029 over COM2 at the default interval, use the following sequence:

```
COM1> sr3m, Hello <CR>
$R: sr3m, Hello
RTCMv3Message1029, "Hello"

COM1> sr3o, COM2, RTCM1029 <CR>
$R: sr3o, COM2, RTCM1029
RTCMv3Output, COM2, RTCM1029

COM1> sdio, COM2, RTCMv3 <CR>
$R: sdio, COM2, RTCMv3
DataInOut, COM2, auto, RTCMv3

COM1>
```



sr3o	setRTCMv3Output	Cd	Messages				
gr3o	getRTCMv3Output	Cd					
		+ COM1	none				
		+ COM2	+ RTCM1001				
		+ COM3	+ RTCM1002				
			+ RTCM1003				
		+ COM4					
		+ USB1	+ RTCM1004				
		+ USB2	+ RTCM1005				
		+ IP10 IP17	+ RTCM1006				
		+NTR1	+ RTCM1007				
		+ NTR2	+ RTCM1008				
		+ NTR3	+ RTCM1009				
		+ IPS1	+ RTCM1010				
		+ IPS2	+ RTCM1011				
		+ IPS3	+ RTCM1012				
		+ IPS4	+ RTCM1013				
		+ IPS5	+ RTCM1019				
		+ IPR1	+ RTCM1020				
		+ IPR2	+ RTCM1029				
		+ IPR3	+ RTCM1033				
		all	+ RTCM1041				
		all	+ RTCM1042				
			+ RTCM1044				
			+ RTCM1045				
			+ RTCM1046				
			DECLARATA				
			+ RTCM1071 RTCM1077				
			+ RTCM1081 RTCM1087				
			+ RTCM1091				
			RTCM1097 + RTCM1101				
			RTCM1107				
			+ RTCM1111 RTCM1117				
			+ RTCM1121 RTCM1127				
			+ RTCM1131 RTCM1137				
			+ RTCM1230				
1		1	+ MSM1 + MSM2				
1		1					
			+ MSM3				
			+ MSM4				
			+ MSM5				
1		1	+ MSM6				
1		1	+ MSM7				
1			all				
	1						

Use these commands to define/inquire which RTCM v3.x messages are enabled for output on a given connection descriptor (Cd - see 1.1.5). The *Messages* argument specifies the RTCM message types to be enabled.

A short description of the supported RTCM v3.x message types can be found in appendix D. MSMi enables the Multiple Signal Message - Type i from all constellations. Make sure to disable the legacy observation messages (MT1001-1004 and MT1009-1012) when enabling MSM messages as it is not advised to mix them.

Please make sure that the connection specified by *Cd* is configured to allow RTCMv3 output, which can be done with the **setDataInOut** command. The interval at which each message is output is to be specified with the **setRTCMv3Interval** command.



To enable RTCM v3.x messages 1001, 1002, 1005 and 1006 on COM2, use the following sequence:

COM1> sr3o, COM2, RTCM1001+RTCM1002+RTCM1005+RTCM1006 <CR>
\$R: sr3o, COM2, RTCM1001+RTCM1002+RTCM1005+RTCM1006
 RTCMv3Output, COM2, RTCM1001+RTCM1002+RTCM1005+RTCM1006
COM1> sdio, COM2, , RTCMv3 <CR>
\$R: sdio, COM2, , RTCMv3
 DataInOut, COM2, auto, RTCMv3
COM1>



sr3u	setRTCMv3Usage	MsgUsage				
gr3u	getRTCMv3Usage	Wisgosuge				
grou	gentromvoosage	none				
		+ RTCM1001				
		RTCM1013				
		+ RTCM1015				
		+ RTCM1016				
		+ RTCM1017				
		+ RTCM1019				
		RTCM1027				
		+ RTCM1029				
		+ RTCM1033				
		+ RTCM1037				
		+ RTCM1038				
		+ RTCM1039				
		+ RTCM1041				
		+ RTCM1042 + RTCM1044				
		+ RTCM1045 + RTCM1046				
		DECLARATA				
		+ RTCM1071 RTCM1077				
		+ <u>RTCM1081</u> RTCM1087				
		+ RTCM1091				
		RTCM1097				
		+ <u>RTCM1111</u> <u>RTCM1117</u>				
		+ <u>RTCM1121</u> <u>RTCM1127</u>				
		+ RTCM1230				
		+ MSM1				
		+ MSM2				
		+ MSM3				
		+ MSM4				
		+ MSM5				
		+ MSM6				
		+ MSM7				
		all				


Use this command to restrict the list of incoming RTCM v3.x messages that the receiver is allowed to use in its differential PVT computation.

A short description of the supported RTCM v3.x messages can be found in appendix D. MSMi is an alias to enable the Multiple Signal Message - Type i from all constellations at once.

Example

To only accept RTCM1001 and RTCM1002 corrections from the base station 1011, use the following sequence:

```
COM1> sr3u, RTCM1001+RTCM1002 <CR>
$R: sr3u, RTCM1001+RTCM1002
  RTCMv3Usage, RTCM1001+RTCM1002
COM1> sdcu, , , manual, 1011 <CR>
$R: sdcu, , , manual, 1011
  DiffCorrUsage, LowLatency, 3600.0, manual, 1011 ...
COM1>
```



3.2.20 CMR v2.0 Settings

sc2f	setCMRv2Formatting	ReferenceID				
gc2f	getCMRv2Formatting					
		<u>0</u> 31				

RxControl: Communication > Output Settings > Differential Corrections > CMRv2

Use these commands to define/inquire the reference station ID assigned to the receiver when operating in base station mode. The reference station ID is transmitted in the header of each outgoing CMR v2.0 message.

```
COM1> sc2f, 12 <CR>
$R: sc2f, 12
   CMRv2Formatting, 12
COM1>

COM1> gc2f <CR>
$R: gc2f
   CMRv2Formatting, 12
COM1>
```



sc2i	setCMRv2Interval	Message	Interval				
gc2i	getCMRv2Interval	Message					
		+CMR0	0.1 <u>1.0</u>				
		+ CMR1	600.0 s				
		+CMR2					
		+CMR3					
		all					

Use these commands to define/inquire at which interval CMR v2.0 messages should be generated.

The intervals specified with this command are not connection-specific: all the connections which output a given CMR v2.0 message will output it with the same interval.

Note that this command only defines the interval of CMR messages. To make the receiver actually output these messages, use the **setCMRv2Output** and **setDataInOut** commands.

Refer to appendix D for an overview of the supported CMR v2.0 messages.

```
COM1> sc2i, CMR0, 2 <CR>
$R: sc2i, CMR0, 2
   CMRv2Interval, CMR0, 2
COM1>

COM1> gc2i <CR>
$R: gc2i CMRv2Interval, CMR0, 2
   CMRv2Interval, CMR1, 1 CMRv2Interval, CMR2, 1
COM1>
```



sc2m	setCMRv2Message2	ShortID (8)	LongID (50)	COGO (16)			
gc2m	getCMRv2Message2						
		<u>Unknown</u>	<u>Unknown</u>	<u>Unknown</u>			

Use these commands to define/inquire the strings that will be transmitted in the CMR v2.0 message 2.

The argument *ShortID* is the short station ID. It can contain up to 8 characters in compliance with the CMR standard. If less than 8 characters are defined, the string will be right justified and padded with spaces.

The argument *LongID* is the long station ID. It can contain up to 50 characters in compliance with the CMR standard. If less than 50 characters are defined, the string will be right justified and padded with spaces.

The argument *COGO* is the COGO code. It can contain up to 16 characters in compliance with the CMR standard. If less than 16 characters are defined, the string will be right justified and padded with spaces.

Note that this command only defines the contents of message 2. To make the receiver actually output this message, use the **setCMRv2Output** and **setDataInOut** commands.

Example

To send the string "Hello" as short station ID and send CMR2 messages through COM2, use the following sequence:

```
COM1> sc2m, Hello <CR>
$R: sc2m, Hello
    CMRv2Message2, "Hello", "Unknown", "Unknown"
COM1> sc2o, COM2, CMR2 <CR>
$R: sc2o, COM2, CMR2
    CMRv2Output, COM2, CMR2
COM1> sdio, COM2, CMRv2 <CR>
$R: sdio, COM2, CMRv2
    DataInOut, COM2, auto, CMRv2
COM1>
```





sc2o	setCMRv2Output	Cd	Messages				
gc2o	getCMRv2Output	Cd					
		+ COM1	none				
		+ COM2	+ <u>CMR0</u>				
		+ COM3	+ CMR1				
		+ COM4	+ CMR2				
		+ USB1	+ <u>CMR3</u>				
		+ USB2	all				
		+ IP10 IP17					
		+NTR1					
		+NTR2					
		+ NTR3					
		+ IPS1					
		+ IPS2					
		+ IPS3					
		+ IPS4					
		+ IPS5					
		+ IPR1					
		+ IPR2					
		+ IPR3					
		all					

Use these commands to define/inquire which CMR v2.0 messages are enabled for output on a given connection descriptor (*Cd* - see 1.1.5). The *Messages* argument specifies the CMR message types to be enabled. Refer to appendix D for an overview of the supported CMR v2.0 messages.

Please make sure that the connection specified by *Cd* is configured to allow CMRv2 output, which can be done with the **setDataInOut** command. The interval at which each message is output is to be specified with the **setCMRv2Interval** command.

Example

To enable CMR v2.0 message 0 on COM2, use the following sequence:

```
COM1> sc2o, COM2, CMR0 <CR>
$R: sc2o, COM2, CMR0
   CMRv2Output, COM2, CMR0

COM1> sdio, COM2, , CMRv2 <CR>
$R: sdio, COM2, , CMRv2
   DataInOut, COM2, auto, CMRv2
COM1>
```





sc2u	setCMRv2Usage	MsgUsage				
gc2u	getCMRv2Usage					
		none				
		+ CMR0				
		+ CMR1				
		+ CMR2				
		+ CMR3				
		+ CMR0p				
		+ CMR0w				
		all				

Use this command to restrict the list of incoming CMR v2.0 messages that the receiver is allowed to use in its differential PVT computation. CMR0p and CMR0w refer to the CMR+ and CMR-W variants respectively.

A short description of the supported CMR v2.0 messages can be found in appendix D.

Example

To only accept CMR0 from the base station 12, use the following sequence:

```
COM1> sc2u, CMR0 <CR>
$R: sc2u, CMR0
   CMRv2Usage, CMR0

COM1> sdcu, , , manual, 12 <CR>
$R: sdcu, , , manual, 12
   DiffCorrUsage, LowLatency, 3600.0, manual, 12 ...
COM1>
```



3.2.21 Internal Disk Logging

sblp	setBINEXLoggingParameters	Cd	Duration	Compression			
gblp	getBINEXLoggingParameters	Cd					
			min15	<u>off</u>			
		LOG8	hour1	on			
		all	hour6				
			hour24				

RxControl: Logging > Internal Logging Settings > BINEX Logging and Upload

Use these commands to define the BINEX logging parameters.

The first argument defines the file duration: the receiver automatically starts a new file every 15 minutes, every hour, every 6 hours or every 24 hours according to the *Duration* argument.

The second argument enables or disables compression. Compression takes place when the file is complete, i.e. at the end of each *Duration* interval. After compression, the original (non-compressed) file is deleted.

The BINEX file name is <code>ssssdddfmm.yy.bnx</code>, where <code>ssssdddfmm.yy</code> follows the RINEX 2.11 definition. The 4-character station identifier is the first four letters of the station code as set by the <code>setMarkerParameters</code> command. If the station code is empty, the first four letters of the marker name are used. After compression, the <code>.gz</code> extension is appended to the file name.

If desired, it is also possible to add a log session ID prefix to all BINEX file names. This is enabled with the **setGlobalFileNamingOptions** command.

The BINEX files are put in daily directories, the directory name being of the form yyddd with yy the 2-digit year and ddd the day of year.

```
COM1> sblp, LOG1, hour1, on<CR>
$R: sblp, LOG1, hour1, on
   BINEXLoggingParameters, LOG1, hour1, on
COM1>
```



scgl	setCGGTTSLogging	Cd	FileTypes				
gcgl	getCGGTTSLogging	Cd					
		+ <u>LOG1</u>	<u>none</u>				
		+ LOG2 LOG8	+ GPS				
		all	+ GLONASS				
			+ GALILEO				
			+ BEIDOU				
			all				

RxControl: Logging > Internal CGGTTS Logging > CGGTTS File Logging

Use this command to enable/disable logging of CGGTTS files in one or more logging sessions.

The receiver can generate CGGTTS files for the GPS, GLONASS, Galileo and BeiDou constellations. These files can be logged in a single session, or in different sessions if preferred.

The CGGTTS files always cover a full day, and they are put in daily directories, the directory name being of the form yyddd with yy the 2-digit year and ddd the day of year.

The file name conforms to the CGGTTS-v2E convention: XFLLmodd.ddd, with X the constellation code, F the frequency type (always set to "Z"), LL the laboratory identifier set with **setTimeLabParameters**, mo the receiver identifier set with **setTimeLabParameters**, and dd.ddd the modified Julian date.

It is recommended to configure all CGGTTS parameters before enabling logging (see the setTimeLabParameters, setCGGTTSPosition, setCGGTTSTrackParameters, setINTDLY, setCABDLY and setREFDLY commands). If the CGGTTS parameters are changed while logging is ongoing, the CGGTTS file header information may not correspond to the actual content of the file.

Note that it can take up to 30 minutes between enabling CGGTTS logging and actually seeing the CGGTTS file on the disk. This is because CGGTTS data are generated at a very low rate (typically every 16 minutes).

```
COM1> scgl, LOG1, GPS+GALILEO<CR>
$R: scgl, LOG1, GPS+GALILEO
    CGGTTSLogging, LOG1, GPS+GALILEO
COM1>
```





	lde	IstDiskEvent	Disk	SessionName (60				
I			DSK1					
			DSK2					
			all					

Use this command to retrieve information about the disk identified by the Disk argument. DSK1 is the internal disk and DSK2 is the external disk (USB drive). The reply to this command lists the events that have occurred for a given log session in the context of the "preserve on event" feature. See also the **setPreserveOnEvent** command.

When only using the *Disk* argument and omitting the *SessionName* argument, the different log session names are listed.

When filling in both the *Disk* and the *SessionName* arguments, a list of events for the specified log session is generated.

The events are grouped per minute. The listed <etime> means that at least one event of type <Event type> happened between 30s before and 30s after <etime>. etime is a Unix timestamp. The fields <before> and <after> correspond to the applicable value of the TimeBefore and TimeAfter arguments of the setPreserveOnEvent command.

For the future events the Planned tag is diplayed.

```
COM1> lde, DSK1, LOG1_a_name <CR>
$R; lde, DSK1, LOG1_a_name
--->
$-- BLOCK 1 / 0
<?xml version="1.0" encoding="ISO-8859-1" ?>
<DiskEvent version="0.1">
  <Disk name="DSK1" total="15618400256" free="10437935104" >
    <Dir name="LOG1 a name">
      <Dir name="19260" mtime="1568764782" />
        <Event type="EventA" etime="1568727400" before="1440" after
           ="1440" />
        <Event type="EventB" etime="1568732640" before="1440" after</pre>
           ="1440" />
      <Dir name="19261" mtime="1568793582" />
        <Event type="EventA" etime="1568791150" before="1440" after</pre>
           ="1440" />
        <Event type="EventB" etime="1568796180" before="1440" after</pre>
        <Event type="EventA" etime="1568796190" before="1440" after</pre>
           ="1440" />
      </Dir>
    </Dir>
    <Planned>
      <Event type="Command" etime="1586529330" before="1440" after=
         "1440" />
      <Event type="Command" etime="1586615730" before="1440" after=
         "1440" />
```





sdfa	setDiskFullAction	Disk	Action				
gdfa	getDiskFullAction	Disk					
		+ DSK1	DeleteOldest				
		+ DSK2	StopLogging				
		all					

RxControl: Logging > Internal Logging Settings > Global Logging Options

Use these commands to define/inquire what the receiver should do when the disk identified by Disk is full. DSK1 is the internal disk and DSK2 is the external disk (USB drive).

The currently supported actions are as follows:

Action	Description
DeleteOldest	The receiver deletes old files from the disk that is becoming full. The files in unused or disabled log sessions (see the setLogSession command) are first to be deleted. Then the receiver scans the enabled low-priority sessions. The oldest file in these sessions is identified and deleted. If no file could be deleted, the receiver scans the medium-priority sessions, and finally it will scan the high-priority sessions. See the setLogSession command to define the log session priority.
StopLogging	All logging activity stops on the specified disk.

```
COM1> sdfa, DSK1, StopLogging <CR>
$R: sdfa, DSK1, StopLogging
   DiskFullAction, DSK1, StopLogging
COM1>

COM1> gdfa <CR>
$R: gdfa
   DiskFullAction, DSK1, StopLogging
COM1>
```





Ī	ldi	IstDiskInfo	Disk	Directory (60)				
ı			DSK1					
ı			DSK2					
ı			all					

Use this command to retrieve information about the disk identified by the Disk argument. DSK1 is the internal disk and DSK2 is the external disk (USB drive). The reply to this command contains the disk size and free space in bytes and the list of all recorded files and directories.

The content of directories is not shown by default. To list the content of a directory, use the second argument to specify the directory name.



sfn	setFileNaming	Cd	NamingType	FileName (20)	Compression			
gfn	getFileNaming	Cd						
		+LOG1 LOG8	<u>FileName</u>	log	<u>off</u>			
		all	Incremental		on			
			IGS15M					
			IGS1H					
			IGS6H					
			IGS24H					

RxControl: Logging > Internal Logging Settings > SBF Logging and Upload

Use these commands to define/inquire the file naming convention for the internal SBF files, and to enable compression.

If NamingType is FileName, the file name is given by the third argument FileName, followed by the extension .sbf.

If NamingType is Incremental, the receiver appends a 3-digit counter to the file name provided in the *FileName* argument. The counter increments each time logging is stopped and restarted. When the counter reaches 1000, it restarts at zero. If the resulting file name (*File-Name*+counter) already exists on the disk, the existing file is overwritten.

The set of allowed characters for the FileName argument is:

```
_0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefqhijklmnopqrstuvwxyz
```

If NamingType is IGS15M, IGS1H, IGS6H or IGS24H, the receiver automatically creates a new file every 15 minutes, every hour, every 6 hours or every 24 hours respectively, and the file name adheres to the IGS/RINEX2.11 naming convention.

The 4-character station identifier is the first four letters of the station code as set by the **setMarkerParameters** command. If the station code is empty, the first four letters of the marker name are used.

If desired, it is also possible to add a log session ID prefix to all file names logged in IGS naming mode. This is enabled with the **setGlobalFileNamingOptions** command.

In IGS naming mode, the files are put in daily directories, the directory name being of the form <code>yyddd</code> with <code>yy</code> the 2-digit year and <code>ddd</code> the day of year. If <code>NamingType</code> is <code>FileName</code> or <code>Incremental</code>, the file is put in the root directory of the log session.

If the *Compression* argument is set to on, the SBF files are compressed. Compression is only applied to files logged in one of the IGS naming modes, and takes place when the files are complete. After compression, the original (non-compressed) files are deleted.

If the naming convention is changed while logging is ongoing, the current file is closed and the logging continues in a new file with the name as specified.

Example

To have a fixed file name "mytest.sbf" in the first log session, use:

```
COM1> sfn, LOG1, FileName, mytest <CR>
$R: sfn, LOG1, FileName, mytest
  FileNaming, LOG1, FileName, "mytest", off
COM1>
```



sfno gfno	setGlobalFileNamingOptions getGlobalFileNamingOptions	BusyTag	SessionTag				
		off	<u>off</u>				
		<u>on</u>	on				

RxControl: Logging > Internal Logging Settings > Global Logging Options

By default, files names follow the convention described with the logging commands (setFileNaming, setBINEXLoggingParameters, setNMEALogging, setRTCMMSMLogging, setRINEXLogging).

By setting the BusyTag argument to on, a ".A" suffix is added to all files that are currently written to for easy identification. The suffix is removed when the file is closed.

By setting the *SessionTag* argument to on, the log session ID is prefixed to all file names, with the exception of the manually-specified SBF file names. This makes that all file names logged by the receiver are unique.

```
COM1> sfno, on, on<CR>
$R: sfno, on, on
  GlobalFileNamingOptions, on, on
COM1>
```



sls	setLogSession	Cd	State	Disk	Name (30)	AutoDelete	Priority	Туре	
gls	getLogSession	Cd							
		+LOG1 LOG8	Unused	DSK1		<u>Never</u>	Low	Continuous	
		all	Disabled	DSK2		After1Day	Medium	Scheduled	
			Enabled			After2Days	High	PreserveOnEvent	
						After3Days			
						After4Days			
						After7Days			
						After14Days			
						After21Days			
						After30Days			
						After60Days			
						After90Days			
						After180Days			
						After1 Year			
						After2Years			

RxControl: Logging > Internal Logging Settings > Log Sessions

This command defines the parameters of the log sessions. For each session, the user can specify where to log (DSK1: internal disk or DSK2: USB drive), the session name, when to auto-delete the files, and the session priority.

The state of each log session is set by the *State* argument. If *State* is Enabled, the log session is enabled for logging. If *State* is Unused or Disabled, the log session stops logging data.

Log files of session i are logged in a folder called "LOGi_Name" where Name is the session name provided in this command. If a folder named "LOGi_..." already exists on the disk, the existing folder is renamed to the new name without loosing its contents. If there is no "LOGi_..." folder yet, it is created.

The log files are automatically deleted after the interval specified in the *AutoDelete* argument (unless they are flagged as "to be preserved", see the *Type* argument below). If the *AutoDelete* argument is set to Never, files are never deleted automatically (except when the disk is full, see the **setDiskFullAction** command). It is the responsibility of the user to timely download and delete the files, or to timely stop the logging to avoid filling up the disk.

The *Priority* argument defines the session priority when the disk is full and the receiver starts to free-up disk space by deleting old files (see the **setDiskFullAction** command for details). Sessions with a low priority will be the first to be deleted upon a disk full condition.

Logging sessions can be of different types:

Туре	Description
Continuous	The log session is logging continuously and deleting old files as per the <i>AutoDelete</i> settings.
Scheduled	Logging is enabled/disabled according to the schedule set with the setLogSessionSchedule command. Auto-deletion is the same as in Continuous mode.





Type (Continued)	Description
	Logging is continuous, but auto-deletion will not delete files flagged as "to be preserved". The criterium to set the "to be preserved" flag must be defined with the setPreserveOnEvent command. Only files logged in one of the IGS naming modes can be preserved.
	When the disk is full and the receiver tries to delete old files to free-up space (see the setDiskFullAction command), preserved files will be the last to be deleted (starting from the session with lowest priority).

Example

COM1> sls, LOG1, Enabled, DSK1, MySession, After1Year, High,
 Continuous<CR>

\$R: sls, LOG1, Enabled, DSK1, MySession, AfterlYear, High,
 Continuous
LogSession, LOG1, Enabled, DSK1, MySession, AfterlYear, High,
 Continuous
COM1>



slss	setLogSessionSchedule	Cd	StartTime (30)	Duration	RepetitionIntrvl			
glss	getLogSessionSchedule	Cd						
		+LOG1 LOG8	000-01-01 00:00:0	<u>0</u> 2678400 s	<u>0</u> 2678400 s			
		all						

RxControl: Logging > Internal Logging Settings > Log Sessions

This command defines the logging schedule for log sessions configured in Scheduled mode with the **setLogSession** command.

The *StartTime* argument defines the epoch when the receiver should start logging the first time. It also serves as reference epoch for the *RepetitionIntrvI* argument. It refers to the GPS time scale. The format of the *StartTime* argument is "YYYY-MM-DD hh:mm:ss".

The *Duration* argument defines the period for which the receiver should stay logging. If this argument is set to 0 (the default value), the receiver will remain logging indefinitely.

The *RepetitionIntrvl* can be used to repeat the logging pattern at regular interval. *RepetitionIntrvl* should be at least 5 seconds longer than *Duration*. If *RepetitionIntrvl* is set to a value smaller than *Duration*, the repetition functionality is disabled.

Be aware that the receiver must know the time to automatically schedule the logging: if no antenna is connected to the receiver or if not enough satellites could be tracked since boot, the receiver will not log any data.

Example

If you want to log for one hour every day from 00:00:00 till 01:00:00 (GPS time), use:

```
COM1> sls, LOG1, Enabled, DSK1, "Example", After2Days, Medium,
    Scheduled <CR>
$R: sls, LOG1, Enabled, DSK1, "Example", After2Days, Medium,
    Scheduled
    LogSession, LOG1, Enabled, DSK1, "Example", After2Days, Medium,
        Scheduled

COM1> slss, , 3600, 86400 <CR>
$R: slss, , 3600, 86400
    LogSessionSchedule, "2000-01-01 00:00:00", 3600, 86400
COM1>
```





emd	exeManageDisk	Disk	Action				
gmd	getManageDisk						
		DSK1	<u>Unmount</u>				
		DSK2	Mount				
			Format				

RxControl: Logging > Disk(s) > Disk Management

Use this command to manage the disk identified by the *Disk* argument. DSK1 is the internal disk and DSK2 is the external disk (USB drive).

Specify the action Format to format the disk (all data will be lost).

The Mount and Unmount actions mount and unmount the disk respectively. Unmounting an internal disk makes it available as a mass-storage device when the USB cable is connected to a PC, i.e. it makes the disk appear as a drive on most file browsers. When the disk is mounted, it cannot be accessed as a mass-storage device. Internal logging is only possible when the disk is mounted.

Prior to formatting or unmounting the disk, make sure to stop all disk activities. If the specified action could not be performed, an error message is returned.

Example

To format the first disk (DSK1), use:

```
COM1> emd, DSK1, Format <CR>
    $R: emd, DSK1, Format
    ManageDisk, DSK1, Format
    COM1>
```





snlp	setNMEALogging	Cd	NamingType	FileName (20)	Compression			
gnlp	getNMEALogging	Cd						
		+LOG1 LOG8	<u>FileName</u>	log	<u>off</u>			
		all	Incremental		on			
			IGS15M					
			IGS1H					
			IGS6H					
			IGS24H					

RxControl: Logging > Internal Logging Settings > NMEA Logging and Upload

Use these commands to define/inquire the NMEA logging parameters.

If NamingType is FileName, the file name is given by the third argument FileName, followed by the extension .nma.

If NamingType is Incremental, the receiver appends a 3-digit counter to the file name provided in the *FileName* argument. The counter increments each time logging is stopped and restarted. When the counter reaches 1000, it restarts at zero. If the resulting file name (*File-Name*+counter) already exists on the disk, the existing file is overwritten.

The set of allowed characters for the *FileName* argument is:

```
_0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz
```

If NamingType is IGS15M, IGS1H, IGS6H or IGS24H, the receiver automatically creates a new file every 15 minutes, every hour, every 6 hours or every 24 hours respectively, and the file name adheres to the IGS/RINEX2.11 naming convention. The 4-character station identifier is the first four letters of the station code as set by the **setMarkerParameters** command. If the station code is empty, the first four letters of the marker name are used.

If desired, it is also possible to add a log session ID prefix to all file names logged in IGS naming mode. This is enabled with the **setGlobalFileNamingOptions** command.

In IGS naming mode, the files are put in daily directories, the directory name being of the form <code>yyddd</code> with <code>yy</code> the 2-digit year and <code>ddd</code> the day of year. If <code>NamingType</code> is <code>FileName</code> or <code>Incremental</code>, the file is put in the root directory of the log session.

If the *Compression* argument is set to on, the NMEA files are compressed. Compression is only applied to files logged in one of the IGS naming modes, and takes place when the files are complete. After compression, the original (non-compressed) files are deleted.

If the naming convention is changed while logging is ongoing, the current file is closed and the logging continues in a new file with the name as specified.

Example

To have a fixed file name "mytest.nma" in the first log session, use:

```
COM1> nlp, LOG1, FileName, mytest <CR>
$R: nlp, LOG1, FileName, mytest
  FileNaming, LOG1, FileName, "mytest", off
COM1>
```





epl	exePreserveLogging	EventTime (30)					
gpl	getPreserveLogging						
	2	2000-01-01 00:00:0	þ				

RxControl: Logging > Preserve Log Files

This command prevents the automatic deletion of a specified event's logs, pointed by *Event-Time*. Preserved files will not be deleted by the auto-delete functionality and they will also be the last to be deleted when the receiver attempts to free-up disk space when the disk is full. The command can add future events also and these can be viewed in the Planned tag using <code>lstDiskEvent</code> command. Refer to the <code>lstDiskEvent</code>, <code>setLogSession</code> and <code>PreserveOnEvent</code> commands for further details.

The *EventTime* argument defines the time of the event that the receiver should preserve. The format of the *EventTime* argument is "YYYY-MM-DD hh:mm:ss". Note: the Preserve-On-Event logic expects events to be marked at half-minute time, so *EventTime* argument is adjusted accordingly. When adding an already registered event this is updated using the current sessions params.

```
COM1> epl, 2019-01-01 00:00:00
$R: epl, 2019-01-01 00:00:00
PreserveLogging, 2019-01-01 00:00:00
COM1>
```





spoe	setPreserveOnEvent	Cd	Event	TimeBefore	TimeAfter			
gpoe	getPreserveOnEvent	Cd						
		+LOG1 LOG8	<u>none</u>	0 <u>15</u> 1440	0 <u>15</u> 1440			
		all	+ EventA	min	min			
			+ EventB					
			+ Command					

RxControl: Logging > Internal Logging Settings > Log Sessions

This command defines the criterium to use to preserve a file from automatic deletion. It is applicable to log sessions configured in PreserveOnEvent mode with the **setLogSession** command, and only to files logged in one of the IGS file naming modes.

Preserved files will not be deleted by the auto-delete functionality, and they will also be the last to be deleted when the receiver attempts to free-up disk space when the disk is full. Refer to the **setLogSession** command for further details.

The *Event* argument specifies the events that trigger files to be preserved. EventA and EventB refer to the two external event inputs of the receiver. Command refers to the on demand event log preserving command.

TimeBefore tells the receiver to preserve all the files that contain data for the last *TimeBefore* minutes before the event occurred.

TimeAfter tells the receiver to preserve all the files that contain data until *TimeAfter* minutes past the occurence of the event.

Note that only files that are logged under the IGS file naming can be preserved. Preserved files are marked as "preserve=on" when issuing the **lstDiskInfo** command. A list of events that occurred during logging can be seen with the **lstDiskEvent** command.

Example

If, for the LOG1 session, you want to preserve NMEA files that contain data at least 15 minutes before and 15 minutes after an EventA or EventB occurred, use:

```
COM1> sls, LOG1, Enabled, DSK1, "Example", After2Days, Medium,
    PreserveOnEvent <CR>
$R: sls, LOG1, Enabled, DSK1, "Example", After2Days, Medium,
    PreserveOnEvent
    LogSession, LOG1, Enabled, DSK1, "Example", After2Days, Medium,
        PreserveOnEvent

COM1> snlp, LOG1, IGS1H, "log", off <CR>
$R: snlp, LOG1, IGS1H, "log", off
    NMEALogging, LOG1, IGS1H, "log", off

COM1> spoe, LOG1, EventA+EventB <CR>
$R: spoe, LOG1, EventA+EventB
    PreserveOnEvent, LOG1, EventA+EventB, 15, 15
```



	Irf	IstRecordedFile	Disk	FileName (60)				
Ī			DSK1 DSK2					
			DSK2					

Use this command to retrieve the contents of one of the log files on the disk identified with the *Disk* argument. DSK1 is the internal disk and DSK2 is the external disk (USB drive).

The reply to this command consists in a succession of blocks starting with the "\$-- BLOCK" header, and terminating with the pseudo-prompt "---->" (see section Section 3.1.3, "Command Replies" for details). The decoding program must remove these headers and pseudo-prompts to recover the original file contents.

The download speed is highly influenced by the processor load. To speed up the download, it is recommended to stop the signal tracking, which can be done by typing the following command before starting the download: **setSatelliteTracking**, **none**.

The file download can be interrupted by sending ten uppercase "S" characters (simply by holding the "shift-S" key pressed) to the connection through which the download is taking place.

Examples

To output the contents of the internal log file named log.sbf on the first disk (DSK1), use:

```
COM1> lrf, DSK1, log.sbf <CR>
$R; lrf, DSK1, log.sbf
... Here comes the content of log.sbf ...
COM1>
```

If the file log.sbf does not exist, an error is returned:

```
COM1> lrf, DSK1, log.sbf <CR>
$R? lstRecordedFile: Argument 'FileName' could not be handled!
COM1>
```





erf	exeRemoveFile	Disk	FileName (200)				
grf	getRemoveFile						
		DSK1	<u>none</u>				
		DSK2	all				

RxControl: Logging > Remove Internal File

Use this command to remove one file or an entire directory from the disk identified by the Disk argument. DSK1 is the internal disk and DSK2 is the external disk (USB drive).

If *FileName* is the name of a file, only that single file is removed from the disk. Files in a directory can be specified using dirname/filename.

If *FileName* is the name of a directory, the entire directory is deleted, except the file currently written to, if any.

If the reserved string all is used for the *FileName* argument, all files are removed from the selected disk, except the file currently written to, if any.

If there is no file nor directory named *FileName* on the disk or if the file is currently written to, an error message is returned.

Examples

To remove the file "ATRX2980.03_" from directory "03298", use:

```
COM1> erf, DSK1, 03298/ATRX2980.03_ <CR>
$R: erf, DSK1, 03298/ATRX2980.03_
   RemoveFile, DSK1, "03298/ATRX2980.03_"
COM1>
```

To remove all files from DSK1, use:

```
COM1> erf, DSK1, all <CR>
$R: erf, DSK1, all
  RemoveFile, DSK1, all
COM1>
```



srxl	setRINEXLogging	Cd	FileDuration	ObsInterval	SignalTypes	ExtraObsTypes	RINEXVersion	MixedNav	FileTypes	Archiving
grxl	getRINEXLogging	Cd								
		+LOG1 LOG8	none	sec1	none	<u>none</u>	v211	off	+ <u>Obs</u>	<u>none</u>
		all	hour1	sec2	+ GPSL1CA	+ Dx	v304ShortName	<u>on</u>	+ <u>Nav</u>	+ Hatanaka
			hour6	sec5	+ GPSL1PY	+ Sx	<u>v304</u>		+ Met	+ GroupInTar
			hour24	sec10	+ GPSL2PY	+ Channel	v305		all	+ Compress
			minute15	sec15	+ GPSL2C	all	v400			
				sec30	+ GPSL5					
				sec60	+GPSL1C					
					+ GLOL1CA					
					+GLOL1P					
					+ GLOL2P					
					+ GLOL2CA					
					+ GLOL3					
					+ GALL1BC					
					+ GALE6BC					
					+ GALE5a					
					+ GALE5b					
					+ GALE5					
					+ GEOL1					
					+ GEOL5					
					+ BDSB1I					
					+ BDSB2I					
					+ BDSB3I					
					+BDSB1C					
					+BDSB2a					
					+ BDSB2b					
					+ QZSL1CA					
					+ QZSL2C					
					+ QZSL5					
					+QZSL1C					
					+QZSL1S					
					+ QZSL5S					
					+ QZSL1CB					
					+ NAVICL5					
					all					
					l un					
			1	·	·				·	

RxControl: Logging > Internal RINEX Logging > RINEX Logging Options

Use this command to configure RINEX file logging in the log session identified with the *Cd* argument.

The argument *FileDuration* specifies whether a new RINEX file should be started every 15 minutes, every hour, 6 hours or every day. When *FileDuration* is set to none, RINEX logging is disabled and all following arguments are ignored.

ObsInterval specifies the interval of the observation records.

SignalTypes sets the list of signals to encode in the RINEX observation files. The more signals are selected, the bigger the RINEX files.

By default, the RINEX files contain the code and carrier phase observables. The *ExtraObsTypes* argument allows to also include the Doppler (obs code Dx), the C/N_0 (obs code Sx), or the channel number (obs code X).

The argument *RinexVersion* selects which RINEX version to use. v304ShortName generates a v3.04 file, but still using the DOS file naming convention of v2.xx.

The argument $\it MixedNav$ specifies whether the navigation data is stored in separate files for each constellation ($\it MixedNav$ set to off), or in a single mixed file ($\it MixedNav$ set to on). This argument is ignored if $\it RINEXVersion$ is v211. Note that QZSS and BeiDou navigation data are only available in the mixed navigation file.



By default, all types of RINEX files will be logged (observation, navigation and meteo) if the relevant data is available. This can be changed with the *FileTypes* argument.

The Archiving argument defines the type of post-processing (archiving and/or compression) to apply at the end of each FileDuration interval. Hatanaka enables Hatanaka compression of the observation file, GroupInTar groups all RINEX files (possibly after Hatanaka compression) into a .tar archive, and Compress enables gzip compression. The different options can be enabled individually, or combined with the "+" sign. The order of execution is Hatanaka, GroupInTar and, finally, Compress. After post-processing, the original files are deleted.

In the RINEX file names, the 4-character station identifier is the first four letters of the station code as set by the **setMarkerParameters** command. If the station code is empty, the first four letters of the marker name are used instead. The monument index, receiver index and country code needed to generate long file names (used by the receiver for RINEX v3.04 or above) are also set with the **setMarkerParameters** command.

If desired, it is also possible to add a log session ID prefix to all RINEX file names. This is enabled with the **setGlobalFileNamingOptions** command.

RINEX files are put in daily directories, the directory name being of the form yyddd with yy the 2-digit year and ddd the day of year.

If a RINEX file is currently being logged when issuing this command, the new settings will only be applied when the next RINEX file will be started. This occurs at a rate specified by *FileDuration*. To force the new settings to be immediately applied, RINEX logging must be temporarily stopped (*FileDuration* set to none) and then re-enabled. Changing the RINEX settings (e.g. changing the list of signals to be stored in RINEX) results in the past data to be overwritten in the RINEX file.

Example

To create daily RINEX files with the observation file containing only GPS L1CA data at a 30-s interval, and to enable Hatanaka and gzip compression, use:

```
COM1> srx1, LOG1, hour24, sec30, GPSL1CA,,,, Hatanaka+Compress <CR>
$R: srx1, LOG1, hour24, sec30, GPSL1CA,,,, Hatanaka+Compress
RINEXLogging, LOG1, hour24, sec30, GPSL1CA, none, v304, on, Obs+
Nav+Met, Hatanaka+Compress
COM1>
```





smsl	setRTCMMSMLogging	Cd	FileDuration	Compression	Messages	ObsInterval		
gmsl	getRTCMMSMLogging	Cd	Thebaration	Compression	Wessuges	Obstitutival		
gilisi	geth i Civilia Sin Logging	+LOG1 LOG8	none	off	none	msec100		
		all	hour1	on	+ RTCM1006	msec200		
		all	hour6	011	+ RTCM1008	msec500		
			hour24		+ RTCM1013	sec1		
			minute15		+ RTCM1019	sec2		
			ininate 13		+ RTCM1020	sec5		
					+ RTCM1020 + RTCM1033			
					+ RTCM1033	sec10		
					+ RTCM1041 + RTCM1042	sec15		
						sec30		
					+ RTCM1044	sec60		
					+ RTCM1045			
					+ RTCM1046			
					+ RTCM1074			
					+ RTCM1075			
					+ RTCM1076			
					+ RTCM1077			
					+ RTCM1084			
					+ RTCM1085			
					+ RTCM1086			
					+ RTCM1087			
					+ RTCM1094			
					+ RTCM1095			
					+ RTCM1096			
					+ RTCM1097			
					+ RTCM1104			
					+ RTCM1105			
					+ RTCM1106			
					+ RTCM1107			
					+ RTCM1114			
					+ RTCM1115			
					+ RTCM1116			
					+ RTCM1117			
					+ RTCM1124			
					+ RTCM1125			
					+ RTCM1126			
					+ RTCM1127			
					+ RTCM1134			
					+ RTCM1135			
					+ RTCM1136			
					+ RTCM1137			
					+ RTCM1230			
					+ MSM4			
					+ MSM5			
					+ MSM6			
					+ MSM7			
					+ Nav			
					+ Station			

RxControl: Logging > Internal Logging Settings > RTCM-MSM Logging and Upload

Use this command to configure the logging of RTCM-MSM messages in the log session identified with the $\it Cd$ argument.

The *FileDuration* argument specifies whether a new RTCM-MSM file should be started every 15 minutes, every hour, 6 hours or every day. When *FileDuration* is set to none, RTCM logging is disabled and all following arguments are ignored.

If compression is enabled with the *Compression* argument, the RTCM files are compressed. Compression takes place at file completion and the original non-compressed file is deleted.

The *Messages* argument specifies the RTCM message types to be logged. A short description of the supported RTCM v3.x message types can be found in appendix D. MSMi enables the Multiple Signal Message - Type i from all constellations. Nav enables all navigation mes-



sages (ephemerides) and Station enables all station-related messages, as summarized in the table below.

Messages	Description
MSM4	+RTCM1074 +RTCM1084 +RTCM1094 +RTCM1104 +RTCM1114 +RTCM1124 +RTCM1134
MSM5	+RTCM1075 +RTCM1085 +RTCM1095 +RTCM1105 +RTCM1115 +RTCM1125 +RTCM1135
MSM6	+RTCM1076 +RTCM1086 +RTCM1096 +RTCM1116 +RTCM1116 +RTCM1126 +RTCM1136
MSM7	+RTCM1077 +RTCM1087 +RTCM1097 +RTCM1107 +RTCM1117 +RTCM1127 +RTCM1137
Nav	+RTCM1019 +RTCM1020 +RTCM1041 +RTCM1042 +RTCM1044 +RTCM1045 +RTCM1046
Station	+RTCM1006 +RTCM1008 +RTCM1013 +RTCM1033 +RTCM1230

The *ObsInterval* argument specifies the interval of the observation messages (RTCM1074 to RTCM1137). The ephemerides-related messages (eg. RTCM1019) are always logged onchange and the station messages are always logged once at the beginning of all files.

The RTCM-MSM file name follows the RINEX v3.02 convention, with the content characters being omitted and the format characters being set to <code>msm</code> (e.g. <code>SEPT00BEL_R_20173260000_06H_60S.msm</code>). The 4-character station identifier is the first four letters of the station code as set by the <code>setMarkerParameters</code> command. If the station code is empty, the first four letters of the marker name are used instead. The other elements of the file names (monument index, receiver index and country code) are also set with the <code>setMarkerParameters</code> command.

If desired, it is also possible to add a log session ID prefix to all RTCM-MSM file names. This is enabled with the **setGlobalFileNamingOptions** command.

RTCM-MSM files are put in daily directories, the directory name being of the form yyddd with yy the 2-digit year and ddd the day of year.

Example

To create daily RTCM-MSM files with the observation file containing all MSM7 messages at a 10-s interval, use:

COM1> sr31, LOG1, hour24, off, MSM7+Nav+Station, sec10 <CR>
\$R: sr31, LOG1, hour24, off, MSM7+Nav+Station, sec10
 RTCMMSMLogging, LOG1, Hour24, off, MSM7+Nav+Station, sec10
COM1>





3.2.22 FTP Push of Log Files

sbfp	setBINEXFTP	Cd	Enable	Server (40)	Path (64)	User (20)	Password (40)	FTPPort	RetryIntrvI	
gbfp	getBINEXFTP	Cd								
		+ LOG1 LOG8	<u>off</u>			anonymous		1 <u>21</u> 65535	<u>off</u>	
		all	on						min15	I
									min30	I
									hour1	I
									hour6	I
									day1	I
										į .

RxControl: Logging > Internal Logging Settings > BINEX Logging and Upload

Use this command to specify where to FTP BINEX files logged in the log session identified by the *Cd* argument (BINEX FTP push).

The FTP push configuration is done for each session independently. The *Enable* arguments enables or disables FTP push for a given session. The next arguments specify the FTP server hostname or IP address, the path to the remote directory where to put the BINEX files, the login and password to use, and the FTP port. Note that the receiver encrypts the password so that it cannot be read back with the command **getBINEXFTP**.

The files are FTPed when they are complete, as prescribed by the *Duration* settings in the **setBINEXLoggingParameters** command.

If BINEX file compression is enabled with the **setBINEXLoggingParameters** command, the compressed files are FTPed.

The files are put in the remote directory specified in the *Path* argument. Special character sequences can be used to encode the file date in the path: \S_Y is replaced with the 2-digit year, \S_Y with the 4-digit year, \S_M with the month, \S_M with the day of the month, \S_M with the day of the year (starting with 001) and \S_M with the 3-letter month indication (e.g. Apr for April). To put a literal " \S_M " in the path, use \S_M . After expansion, *Path* must not be longer than 80 characters.

If the directory specified in the *Path* argument does not exist on the remote server, it is created.

If the transfer or the directory creation fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the FTP retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Enable* argument is set to off, or when the *Server* is changed.

```
COM1> sbfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30<CR>
$R: sbfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
BINEXFTP, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
COM1>
```



scfp	setCGGTTSFTP	Cd	Enable	Server (40)	Path (64)	User (20)	Password (40)	FTPPort	RetryIntrvI	
gcfp	getCGGTTSFTP	Cd								
		+ LOG1 LOG8	<u>off</u>			anonymous		1 <u>21</u> 65535	<u>off</u>	
		all	on						min15	
									min30	
									hour1	
									hour6	
									day1	

RxControl: Logging > Internal CGGTTS Logging > CGGTTS FTP Push Options

Use this command to specify where to FTP CGGTTS files logged in the log session identified by the *Cd* argument (CGGTTS FTP push).

The FTP push configuration is done for each session independently. The *Enable* arguments enables or disables FTP push for a given session. The next arguments specify the FTP server hostname or IP address, the path to the remote directory where to put the CGGTTS files, the login and password to use, and the FTP port. Note that the receiver encrypts the password so that it cannot be read back with the command **getCGGTTSFTP**.

The CGGTTS files from a given day are FTPed within the first hour of the next day.

The files are put in the remote directory specified in the *Path* argument. Special character sequences can be used to encode the file date in the path: \$y is replaced with the 2-digit year, \$y with the 4-digit year, \$m with the month, \$d with the day of the month, and \$j with the day of the year (starting with 001). To put a literal "\$" in the path, use \$\$. After expansion, *Path* must not be longer than 80 characters.

If the directory specified in the *Path* argument does not exist on the remote server, it is created.

If the transfer or the directory creation fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the FTP retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Enable* argument is set to off, or when the *Server* is changed.

```
COM1> scfp, LOG1, on, tai.bipm.org, /data/UTC/xxxx/links/cggtts/,
    myname, mypwd, 21, min30<CR>
$R: scfp, LOG1, on, tai.bipm.org, /data/UTC/xxxx/links/cggtts/,
    myname, mypwd, 21, min30
    CGGTTSFTP, LOG1, on, tai.bipm.org, /data/UTC/xxxx/links/cggtts/,
    myname, mypwd, 21, min30
COM1>
```





efpt	exeFTPPushTest	Server (40)	Path (64)	User (20)	Password (40)	FTPPort		
gfpt	getFTPPushTest							
				anonymous		1 <u>21</u> 65535		

RxControl: Logging > Test FTP Push to Server

Use this command to test write access to a FTP server.

The arguments specify the FTP server hostname or IP address, the path to the remote directory where write access will be tested, and the login and password to use. The *Path* may contain variable fields as explained in the **setSBFFTP** command.

Upon receiving this command, the receiver tries to connect to the specified FTP server and to write a short file in the directory specified with the *Path* argument. The file is then deleted from the FTP server.

The process can take several minutes depending on the network latency. At the end, a report message is posted in the activity log. This message can be retrieved with the <code>lstInternalFile</code>, <code>RxMessages</code>, and is also available in the <code>RxMessage</code> SBF block.

Example

COM1> efpt, myftp.com, mydata/%Y%m%d, myname, mypwd, 21<CR> \$R: efpt, myftp.com, mydata/%Y%m%d, myname, mypwd, 21 FTPPushTest, myftp.com, mydata/%Y%m%d, myname, mypwd, 21 COM1>





snfp	setNMEAFTP	Cd	Enable	Server (40)	Path (64)	User (20)	Password (40)	FTPPort	RetryIntrvI	
gnfp	getNMEAFTP	Cd								
		+ LOG1 LOG8	<u>off</u>			anonymous		1 <u>21</u> 65535	<u>off</u>	
		all	on						min15	
									min30	
									hour1	
									hour6	
									day1	

RxControl: Logging > Internal Logging Settings > NMEA Logging and Upload

Use this command to specify where to FTP NMEA files logged in the log session identified by the *Cd* argument (NMEA FTP push).

The FTP push configuration is done for each session independently. The *Enable* arguments enables or disables FTP push for a given session. The next arguments specify the FTP server hostname or IP address, the path to the remote directory where to put the NMEA files, the login and password to use, and the FTP port. Note that the receiver encrypts the password so that it cannot be read back with the command **getnmeaftp**.

FTP push is only available in IGS file naming mode (see the *NamingType* argument of the **setNMEALogging** command). Each time an NMEA file is ready in a given log session, it is FTPed to the specified server. For example, in IGS1H file naming mode, files are FTPed every hour.

If NMEA file compression is enabled with the **setNMEALogging** command, the compressed files are FTPed.

The files are put in the remote directory specified in the *Path* argument. Special character sequences can be used to encode the file date in the path: \S_Y is replaced with the 2-digit year, \S_Y with the 4-digit year, \S_M with the month, \S_M with the day of the month, \S_M with the day of the year (starting with 001) and \S_M with the 3-letter month indication (e.g. Apr for April). To put a literal " \S_M " in the path, use \S_M . After expansion, *Path* must not be longer than 80 characters.

If the directory specified in the *Path* argument does not exist on the remote server, it is created.

If the transfer or the directory creation fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the FTP retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Enable* argument is set to off, or when the *Server* is changed.

```
COM1> snfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30<CR>
$R: snfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
    NMEAFTP, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
COM1>
```



srfp	setRINEXFTP	Cd	Enable	Server (40)	Path (64)	User (20)	Password (40)	FTPPort	RetryIntrvl	
grfp	getRINEXFTP	Cd								
		+ LOG1 LOG8	<u>off</u>			anonymous		1 <u>21</u> 65535	<u>off</u>	
		all	on						min15	
									min30	į
									hour1	
									hour6	1
									day1	

RxControl: Logging > Internal RINEX Logging > RINEX FTP Push Options

Use this command to specify where to FTP RINEX files logged in the log session identified by the *Cd* argument (RINEX FTP push).

The FTP push configuration is done for each session independently. The *Enable* arguments enables or disables FTP push for a given session. The next arguments specify the FTP server hostname or IP address, the path to the remote directory where to put the RINEX files, the login and password to use, and the FTP port. Note that the receiver encrypts the password so that it cannot be read back with the command **getRINEXFTP**.

The RINEX files are FTPed when they are complete, as prescribed by the *FileDuration* settings in the **setRINEXLogging** command.

If RINEX file compression is enabled with the **setRinexLogging** command, the compressed files are FTPed.

The files are put in the remote directory specified in the *Path* argument. Special character sequences can be used to encode the file date in the path: \$y is replaced with the 2-digit year, \$y with the 4-digit year, \$m with the month, \$d with the day of the month, and \$j with the day of the year (starting with 001) and \$b with the 3-letter month indication (e.g. Apr for April). To put a literal "\$" in the path, use \$\$. After expansion, *Path* must not be longer than 80 characters.

If the directory specified in the *Path* argument does not exist on the remote server, it is created

If the transfer or the directory creation fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the FTP retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Enable* argument is set to off, or when the *Server* is changed.

```
COM1> srfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30<CR>
$R: srfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
RINEXFTP, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
COM1>
```





smfp	setRTCMMSMFTP	Cd	Enable	Server (40)	Path (64)	User (20)	Password (40)	FTPPort	RetryIntrvl	
gmfp	getRTCMMSMFTP	Cd								
		+ LOG1 LOG8	<u>off</u>			anonymous		1 <u>21</u> 65535	<u>off</u>	
		all	on						min15	
									min30	
									hour1	
									hour6	
									day1	

RxControl: Logging > Internal Logging Settings > RTCM-MSM Logging and Upload

Use this command to specify where to FTP RTCM-MSM files logged in the log session identified by the *Cd* argument.

The FTP push configuration is done for each session independently. The *Enable* arguments enables or disables FTP push for a given session. The next arguments specify the FTP server hostname or IP address, the path to the remote directory where to put the RTCM-MSM files, the login and password to use, and the FTP port. Note that the receiver encrypts the password so that it cannot be read back with the command **getRTCMMSMFTP**.

The files are FTPed when they are complete, as prescribed by the *FileDuration* settings in the **setRTCMMSMLogging** command.

If file compression is enabled with the **setRTCMMSMLogging** command, the compressed files are FTPed.

The files are put in the remote directory specified in the *Path* argument. Special character sequences can be used to encode the file date in the path: \$y is replaced with the 2-digit year, \$y with the 4-digit year, \$m with the month, \$d with the day of the month, \$j with the day of the year (starting with 001) and \$b with the 3-letter month indication (e.g. Apr for April). To put a literal "\$" in the path, use \$\$. After expansion, *Path* must not be longer than 80 characters.

If the directory specified in the *Path* argument does not exist on the remote server, it is created

If the transfer or the directory creation fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the FTP retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Enable* argument is set to off, or when the *Server* is changed.

```
COM1> smfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30<CR>
$R: smfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
    RTCMMSMFTP, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd,
        21, min30
COM1>
```





ssfp	setSBFFTP	Cd	Enable	Server (40)	Path (64)	User (20)	Password (40)	FTPPort	RetryIntrvl	
gsfp	getSBFFTP	Cd								
		+ LOG1 LOG8	<u>off</u>			anonymous		1 <u>21</u> 65535	<u>off</u>	
		all	on						min15	
									min30	
									hour1	
									hour6	
									day1	

RxControl: Logging > Internal Logging Settings > SBF Logging and Upload

Use this command to specify where to FTP SBF files logged in the log session identified by the *Cd* argument (SBF FTP push).

The FTP push configuration is done for each session independently. The *Enable* arguments enables or disables FTP push for a given session. The next arguments specify the FTP server hostname or IP address, the path to the remote directory where to put the SBF files, the login and password to use, and the FTP port. Note that the receiver encrypts the password so that it cannot be read back with the command **getSBFFTP**.

FTP push is only available in IGS file naming mode (see the **setFileNaming** command). Each time an SBF file is ready in a given log session, it is FTPed to the specified server. For example, in IGS1H file naming mode, files are FTPed every hour.

If SBF file compression is enabled with the **setFileNaming** command, the compressed files are FTPed.

The files are put in the remote directory specified in the *Path* argument. Special character sequences can be used to encode the file date in the path: \$y is replaced with the 2-digit year, \$y with the 4-digit year, \$m with the month, \$d with the day of the month, \$j with the day of the year (starting with 001) and \$b with the 3-letter month indication (e.g. Apr for April). To put a literal "\$" in the path, use \$\$. After expansion, *Path* must not be longer than 80 characters.

If the directory specified in the *Path* argument does not exist on the remote server, it is created.

If the transfer or the directory creation fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the FTP retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Enable* argument is set to off, or when the *Server* is changed.

```
COM1> ssfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30<CR>
$R: ssfp, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
    SBFFTP, LOG1, on, myftp.com, mydata/%Y%m%d, myname, mypwd, 21,
    min30
COM1>
```



3.2.23 CloudIt Configuration

lal	IstAuthorizationLinkCloudIt	Server				
		+ Cloud1 + Cloud2 Cloud8 all				



CloudIt is a beta feature and the command description below is subject to change.

Use this command to get the authorization link of a specific CloudIt server defined by the Server argument. The selected server should be already configured using the **setCloudItConfig**. You need to visit the given link through a web browser.

If it is your first time to login, you should get a login web page. After entering your credentials and logging in, you should be directed to a "consent screen" where you give your consent to the receiver to access your storage server (you may not get this "consent screen" if your server administrator has configured the authorization server to skip this step).

The next page should display a code that you will need to copy back to the receiver using the exeAuthorizeCloudIt command.

The full workflow of CloudIt is described in section 1.24.

Example

To ouput the authorization link of Cloud1, use:

```
lstAuthorizationLinkCloudIt, Cloud1 <CR>
$R; lstAuthorizationLinkCloudIt, cloud1
--->
$-- BLOCK 1 / 1
http://myauthurl.com/auth?client_id=myclientid&scope=readwrite&
   response_type=code
COM1>
```





sbci	setBINEXCloudit	Cd	Server	Path (64)	Retry			
gbci	getBINEXCloudIt	Cd						
		+LOG1 LOG8	<u>off</u>		<u>off</u>			
		all	Cloud1 Cloud8		min15			
					min30			
					hour1			
					hour6			
					day1			

RxControl: Logging > Internal Logging Settings > BINEX Logging and Upload



! CloudIt is a beta feature and the command description below is subject to change.

Use this command to specify where to upload BINEX files logged in the log session identified by the Cd argument (BINEX CloudIt). CloudIt configuration is done for each session independently. The Server argument enables CloudIt for a given log session and specifies to which server the BINEX files will be uploaded to. The selected Server must have been already configured using **setCloudItConfig** command before enabling CloudIt for a given session. If a non-configured Server is selected, the upload attempt will fail. To disable CloudIt for a given session, the *Server* argument should be set to off.

The next argument specifies the path to the remote directory where to put the BINEX files in the remote server.

The RINEX files are uploaded when they are complete, as prescribed by the FileDuration settings in the **setBINEXLoggingParameters** command.

If BINEX file compression is enabled with the setBINEXLoggingParameters command, the compressed files are uploaded. The files are put in the remote directory specified in the Path argument.

Special character sequences can be used to encode the file date in the path: %y is replaced with the 2-digit year, %Y with the 4-digit year, %m with the month, %d with the day of the month, and % j with the day of the year (starting with 001). To put a literal "%" in the path, use %%. After expansion, Path must not be longer than 80 characters.

The Path argument is sent as a parameter to the Server according to the API description, and it is up to the server to manage the folder creation.

If the transfer fails, the receiver will periodically retry at a rate specified with the RetryIntrvI argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the CloudIt retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the State argument of **setLogSession**). Pending retries are also cancelled when the Server is changed or set to off.

```
COM1> sbci, LOG1, Cloud1, newfolder, min30<CR>
$R: sbci, LOG1, Cloud1, newfolder, min30
 BINEXCloudIt, LOG1, Cloud1, newfolder, min30
COM1>
```





scic	setCloudItConfig	Server	Name (32)	ClientID (128)	ClientSecret (128)	AuthURL (255)	TokenURL (255)	Endpoint (255)	Scope (64)	RedirectURI (255)
gcic	getCloudItConfig	Server								
		+ Cloud1 Cloud8 all								

RxControl: Logging > CloudIt > CloudIt Servers



CloudIt is a beta feature and the command description below is subject to change.

As described in the section 1.24, CloudIt uses the OAuth2 protocol to authorize a user to upload logged files to a resource server.

Use this command to configure a CloudIt server identified by the Server argument. The Server argument defines where the logged files will be uploaded.

The Name argument is optional and helps the user to identify the server during the configuration process.

All the next arguments are required. The ClientID and ClientSecret arguments identify the application to the authentication server as described in section 1.24. Note that the receiver encrypts the ClientSecret so that it cannot be read back with the command getCloudItConfig.

The AuthURL is the Authorization Endpoint. The TokenURL is the token endpoint that the receiver will use to obtain tokens. The Endpoint argument is the upload endpoint in the resource server where the files will be stored. The RedirectURI (optional) is the URI where the user will be redirected to after a successfull authentication to get the authorization code. All the endpoints should be valid http(s):// URLs.

The Scope defines the access scope of the receiver to the resource server. For example, if SBF files will be uploaded, the receiver should have the access to write files to the remote directory defined by the Path argument in setSBFCloudIt. If the receiver does not have the right to write to the remote directory, the upload attempts will fail.

When all the arguments are all set, the next step is authentication using the link given by the lstAuthorizationLinkCloudIt command.

The full workflow of CloudIt is described in section 1.24.

```
scic, Cloud1, MyServerName, myclientid, mysecret,
  http://www.mysauthserver.com/oauth2/auth/,
  http://www.mysauthserver.com/oauth2/token/,
  http://www.resourceserver.com/api/upload/, readwrite,
  http://www.myserver.com/api/<CR>
$R: scic, Cloud1, MyServerName, myclientid, mysecret, http://www.
  mysauthserver.com/oauth2/auth/, http://www.mysauthserver.com/
   oauth2/token/, http://www.resourceserver.com/api/upload/,
   readwrite, http://www.myserver.com/api/
 CloudItConfig, Cloud1, MyServerName, myclientid, mysecret, http
     ://www.mysauthserver.com/oauth2/auth/, http://www.
    mysauthserver.com/oauth2/token/, http://www.resourceserver.com
     /api/upload/, readwrite, http://www.myserver.com/api/
```



COM1>



edci	exeDisconnectCloudIt	Server				
gdci	getDisconnectCloudIt					
		Cloud1 Cloud8				

RxControl: Logging > CloudIt > Disconnect from CloudIt Server



Cloudit is a beta feature and the command description below is subject to change.

Use this command to disconnect the receiver from the resource server defined by the Server argument.

When the receiver is disconnected, it cannot upload files to the server anymore. If this command is used while a file is being uploaded, the upload will continue until it succeeds or fails. In case it succeeds, no additional files are uploaded. In case it fails, the next upload attempts for the same file will fail and the file will not be uploaded.

Example

COM1> edci, Cloud1<CR> \$R: edci, Cloud1 DisconnectCloudIt, Cloud1 COM1>





erac	exeAuthorizeCloudIt	Server	AuthCode (1024)				
		Cloud1 Cloud2 Cloud8					



CloudIt is a beta feature and the command description below is subject to change.

Use this command to authorize the receiver to access the resource server by setting the authorization code Authcode to the specified server defined by the Server argument.

The authorization code Authcode lifetime is usually short and depends on the admin configuration of the authorization server. If the lifetime of the authorization code is exceeded before executing **exeAuthorizeCloudIt**, the authorization will fail.

If an Authcode has been already used for a successful authorization, it cannot be used anymore. If the server needs to be reauthorized, the server will need a new code. This new code is generated by revisiting the link provided by the **lstAuthorizationLinkCloudIt**.

The process can take several minutes depending on the network latency. At the end, a report message is posted in the activity log. The result of the authorization attempt can be found in the receiver messages with the lstInternalFile, RxMessages command, and is also available in the RxMessage SBF block.

Example

COM1> erac, Cloud1, L2544MLKJLKJSDsd5444QSD<CR>

\$R: erac, Cloud1, L2544MLKJLKJSDsd5444QSD exeAuthorizeCloudIt, Cloud1, L2544MLKJLKJSDsd5444QSD COM1>





snci	setNMEACloudIt	Cd	Server	Path (64)	Retry			
gnci	getNMEACloudIt	Cd						
		+LOG1 LOG8	<u>off</u>		<u>off</u>			
		all	Cloud1 Cloud8		min15			
					min30			
					hour1			
					hour6			
					day1			

RxControl: Logging > Internal Logging Settings > NMEA Logging and Upload



CloudIt is a beta feature and the command description below is subject to change.

Use this command to specify where to upload NMEA files logged in the log session identified by the *Cd* argument (NMEA CloudIt). CloudIt configuration is done for each session independently. The *Server* argument enables CloudIt for a given log session and specifies to which server the NMEA files will be uploaded to. The selected *Server* must have been already configured using **setCloudItConfig** command before enabling CloudIt for a given session. If a non-configured *Server* is selected, the upload attempt will fail. To disable CloudIt for a given session, the *Server* argument should be set to off.

The next argument specifies the path to the remote directory where to put the NMEA files in the remote server.

CloudIt is only available in IGS file naming mode (see the setFileNaming command). Each time an NMEA file is ready in a given log session, it is uploaded with CloudIt to the specified server. For example, in IGS1H file naming mode, files are uploaded every hour.

If NMEA file compression is enabled with the **setFileNaming** command, the compressed files are uploaded. The files are put in the remote directory specified in the *Path* argument.

Special character sequences can be used to encode the file date in the path: \$y is replaced with the 2-digit year, \$y with the 4-digit year, \$m with the month, \$d with the day of the month, and \$j with the day of the year (starting with 001). To put a literal "\$" in the path, use \$\$. After expansion, Path must not be longer than 80 characters.

The *Path* argument is sent as a parameter to the *Server* according to the API description, and it is up to the server to manage the folder creation. If the transfer fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the Cloudlt retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Server* is changed or set to off.

Example

COM1> snci, LOG1, Cloud1, newfolder, min30<CR>
\$R: snci, LOG1, Cloud1, newfolder, min30
 NMEACloudIt, LOG1, Cloud1, newfolder, min30
COM1>





srci	setRINEXCloudIt	Cd	Server	Path (64)	Retry			
grci	getRINEXCloudIt	Cd						
		+LOG1 LOG8	<u>off</u>		<u>off</u>			
		all	Cloud1 Cloud8		min15			
					min30			
					hour1			
					hour6			
					day1			

RxControl: Logging > Internal RINEX Logging > RINEX CloudIt Options



CloudIt is a beta feature and the command description below is subject to change.

Use this command to specify where to upload RINEX files logged in the log session identified by the *Cd* argument (RINEX CloudIt). CloudIt configuration is done for each session independently. The *Server* argument enables CloudIt for a given log session and specifies to which server the RINEX files will be uploaded to. The selected *Server* must have been already configured using **setCloudItConfig** command before enabling CloudIt for a given session. If a non-configured *Server* is selected, the upload attempt will fail. To disable CloudIt for a given session, the *Server* argument should be set to off. The next argument specifies the path to the remote directory where to put the RINEX files in the remote server.

The RINEX files are uploaded when they are complete, as prescribed by the *FileDuration* settings in the **setRinexLogging** command.

If RINEX file compression is enabled with the **setRinexLogging** command, the compressed files are uploaded. The files are put in the remote directory specified in the *Path* argument.

Special character sequences can be used to encode the file date in the path: \$y is replaced with the 2-digit year, \$y with the 4-digit year, \$m with the month, \$d with the day of the month, and \$j with the day of the year (starting with 001). To put a literal "\$" in the path, use \$\$. After expansion, Path must not be longer than 80 characters.

The *Path* argument is sent as a parameter to the *Server* according to the API description, and it is up to the server to manage the folder creation.

If the transfer fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the Cloudlt retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Server* is changed or set to off.

```
COM1> srci, LOG1, Cloud1, newfolder, min30<CR>
$R: srci, LOG1, Cloud1, newfolder, min30
   RINEXCloudIt, LOG1, Cloud1, newfolder, min30
COM1>
```





srmi	setRTCMMSMCloudIt	Cd	Server	Path (64)	Retry			
grmi	getRTCMMSMCloudIt	Cd						
		+LOG1 LOG8	<u>off</u>		<u>off</u>			
		all	Cloud1 Cloud8		min15			
					min30			
					hour1			
					hour6			
					day1			

RxControl: Logging > Internal Logging Settings > RTCM-MSM Logging and Upload



CloudIt is a beta feature and the command description below is subject to change.

Use this command to specify where to upload RTCM-MSM files logged in the log session identified by the *Cd* argument (RTCM-MSM CloudIt). CloudIt configuration is done for each session independently. The *Server* argument enables CloudIt for a given log session and specifies to which server the RTCM-MSM files will be uploaded. The selected *Server* must have been already configured using **setCloudItConfig** command before enabling CloudIt for a given session. If a non-configured *Server* is selected, the upload attempt will fail. To disable CloudIt for a given session, the *Server* argument should be set to off.

The next argument specifies the path to the remote directory where to put the RTCM-MSM files in the remote server.

The files are uploaded when they are complete, as prescribed by the *FileDuration* settings in the **setRTCMMSMLogging** command.

If RTCM-MSM file compression is enabled with the **setRTCMMSMLogging** command, the compressed files are uploaded. The files are put in the remote directory specified in the *Path* argument.

Special character sequences can be used to encode the file date in the path: y is replaced with the 2-digit year, y with the 4-digit year, m with the month, d with the day of the month, and j with the day of the year (starting with 001). To put a literal "%" in the path, use k. After expansion, Path must not be longer than 80 characters.

The *Path* argument is sent as a parameter to the *Server* according to the API description, and it is up to the server to manage the folder creation.

If the transfer fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the CloudIt retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state (see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Server* is changed or set to off.

```
COM1> srmi, LOG1, Cloud1, newfolder, min30<CR>
$R: srmi, LOG1, Cloud1, newfolder, min30
   RTCMMSMCloudIt, LOG1, Cloud1, newfolder, min30
COM1>
```





ssci	setSBFCloudIt	Cd	Server	Path (64)	Retry			
gsci	getSBFCloudIt	Cd						
		+LOG1 LOG8	<u>off</u>		<u>off</u>			
		all	Cloud1 Cloud8		min15			
					min30			
					hour1			
					hour6			
					day1			

RxControl: Logging > Internal Logging Settings > SBF Logging and Upload



CloudIt is a beta feature and the command description below is subject to change.

Use this command to specify where to upload SBF files logged in the log session identified by the *Cd* argument (SBF Cloudlt). Cloudlt configuration is done for each session independently. The *Server* argument enables Cloudlt for a given log session and specifies to which server the SBF files will be uploaded. The selected *Server* must have been already configured using **setCloudItConfig** command before enabling Cloudlt for a given session. If a non-configured *Server* is selected, the upload attempt will fail. To disable Cloudlt for a given session, the *Server* argument should be set to off.

The next arguments specify the path to the remote directory where to put the SBF files in the remote server.

CloudIt is only available in IGS file naming mode (see the setFileNaming command). Each time an SBF file is ready in a given log session, it is uploaded with CloudIt to the specified server. For example, in IGS1H file naming mode, files are uploaded every hour.

If SBF file compression is enabled with the **setFileNaming** command, the compressed files are uploaded. The files are put in the remote directory specified in the *Path* argument.

Special character sequences can be used to encode the file date in the path: y is replaced with the 2-digit year, y with the 4-digit year, m with the month, d with the day of the month, and j with the day of the year (starting with 001). To put a literal "%" in the path, use k. After expansion, Path must not be longer than 80 characters.

The *Path* argument is sent as a parameter to the *Server* as described in section 1.24.2.2, and it is up to the server to manage the folder creation.

If the transfer fails, the receiver will periodically retry at a rate specified with the *RetryIntrvI* argument. The receiver will periodically retry the last 80 failed transfers for each log session. Setting the *RetryIntrvI* argument to off disables the CloudIt retries. Periodic retries continue for log sessions in disabled state, but are cancelled for log sessions in unused state(see the *State* argument of **setLogSession**). Pending retries are also cancelled when the *Server* is changed or set to off.

```
COM1> ssci, LOG1, Cloud1, newfolder, min30<CR>
$R: ssci, LOG1, Cloud1, newfolder, min30
   SBFCloudIt, LOG1, Cloud1, newfolder, min30
COM1>
```





3.2.24 MSS/L-Band Configuration

llbb	IstLBandBeams					

Use this command to retrieve the list of user-defined and auto-defined L-Band beams.

The list contains user-defined beams (User1, User2,...) defined with the **setLBandBeams** command and service-specific beams which are automatically updated by the L-Band service provider. Only the enabled user-defined beams are shown.

For each beam, the list contains the beam carrier frequency in Hz, the baud rate, the beam name and the region code. For service-specific beams, the satellite longitude in degrees (from -180 to 180, positive east of Greenwich) and the grant status are also provided. The last entry shows the SVID to which the beam is mapped.

This command is very similar to the command **getLBandBeams**, the only difference being that the latter only reports the list of user-defined beams.

```
COM1> llbb <CR>
$R; llbb
---->
$-- BLOCK 1 / 1
LBandBeams, User1, 1535165000, baud1200, "User", "E", Enabled, L13
...
COM1>
```



slbb	setLBandBeams	Beam	Frequency	Rate	Name (8)	Region (8)	Usage		
glbb	getLBandBeams	Beam							
		+ User1		baud600	<u>Unknown</u>	<u>Unknown</u>	<u>Disabled</u>		
		+ User2	1559000000 Hz	baud1200			Enabled		
		all		baud2400					
				baud4800					

RxControl: L-band > Generic L-Band Settings > Satellite Beam Configuration

This command can be used to define/inquire the parameters of user-defined L-Band beams. A beam is characterized by its frequency and baud rate (the *Frequency* and *Rate* arguments). Optionally, a beam name and region ID can also be associated to each beam, for information only. A beam can be enabled or disabled, as set by the *Usage* argument. Only enabled beams can be locked to.

Example

COM1> slbb, User1, 1537460000, baud1200, 25East, E, Enabled <CR>
\$R: slbb, User1, 1537460000, baud1200, 25East, E, Enabled
 LBandBeams, User1, 1537460000, baud1200, "25East", "E", Enabled
COM1>





slcs	setLBandCustomServiceID	ServiceID (4)	ScramblingVector	NDAUsage			
glcs	getLBandCustomServiceID						
		0000	0000	off			
				on			

RxControl: L-band > Generic L-Band Settings > Satellite Beam Configuration

This command can be used to define the Service ID, scrambling vector and Null-Data-Algorithm (NDA) usage of the L-Band service provider. The *ServiceID* and *ScramblingVector* are 4-digit hexadecimal numbers.

This command should only be used for test and maintenance purposes.

Example

COM1> slcs, A5A5, 0101, on<CR>
\$R: slcs, A5A5, 0101, on
 LBandCustomServiceID, A5A5, 0101, on
COM1>



sInd		Cd				
glnd	getLBandNTRIPDelivery					
		<u>none</u>				
		NTR1				
		NTR2				
		NTR3				
		DC1 SID08				
		DC2 SID08				
		·				

RxControl: L-band > Generic L-Band Settings > NTRIP Delivery

Use this command to enable reception of L-Band corrections over the NTRIP connection identified with the *Cd* argument.

The selected NTRIP connection (NTRi) must be configured in client mode with the **setNtripSettings** command.

The DC1|... and DC2|... connections should normally not be used. They are reserved for applications where the NTRIP client is running outside the receiver and the L-Band corrections are injected into one of the internal daisy-chain pipes (see the **setDataInOut** command for details on the daisy-chain pipes). In that case, the NTRIP mountpoint (SID08) must also be specified.

Example

COM1> slnd, NTR1<CR>
\$R: slnd, NTR1
 LBandNTRIPDelivery, NTR1
COM1>





slsm	setLBandSelectMode	Mode	Service	Beam1	Beam2			
glsm	getLBandSelectMode							
		<u>auto</u>	LBAS1	<u>User1</u>	User1			
		off	Inmarsat	User2	User2			
		manual		LBAS1 1	LBAS1 1			
				LBAS1 2	LBAS1 2			
				LBAS1 3	LBAS1 3			
				LBAS1 4	LBAS1 4			
				LBAS1 5	LBAS1 5			
				LBAS1 6	LBAS1 6			
				LBAS1 7	LBAS1 7			
				LBAS1 8	LBAS1 8			
				LBAS1 9	LBAS1 9			
				LBAS1 10	LBAS1 10			
				LBAS1 11	LBAS1 11			
				LBAS1 12	LBAS1 12			
				LBAS1 13	LBAS1 13			
				LBAS1 14	LBAS1 14			
				LBAS1 15	LBAS1 15			
				LBAS1 16	LBAS1 16			

RxControl: L-band > Generic L-Band Settings > Satellite Beam Configuration

This command can be used to define/inquire the main operation mode of the L-Band demodulator.

The following modes are available through the *Mode* argument:

Mode	Description
auto	The demodulator will try to lock to a visible beam, preferring beams to which access has been granted. The list of beams and their status can be retrieved by the command <code>lstlBandBeams</code> .
off	The demodulator will be disabled and will not attempt to lock to any beam.
manual	The demodulator will attempt to lock to the beams identified in the <i>Beami</i> arguments and ignore all other beams. The parameters of the beams (frequency and baud rate) can be retrieved by the command <code>lstlBandBeams</code> . Make sure that the beams identified in the <i>Beami</i> arguments are enabled (see command <code>setlBandBeams</code>).

The second argument *Service* specifies which service the demodulator has to lock to.

Example

```
COM1> slsm, manual, Inmarsat, User1, User2<CR>
$R: slsm, manual, Inmarsat, User1, User2
  LBandSelectMode, manual, Inmarsat, User1, User2
COM1>
```





Ilrs	IstLBAS1RefStations					

Use this LBAS1-specific command to inquire the list of the reference stations of which corrections are available in the LBAS1 L-Band beam currently locked to. Usage of the corrections from a given reference station can be granted or not, as indicated in the list.

Example

```
COM1>
       llrs <CR>
$R; llrs
--->
$-- BLOCK 1 / 1
LBAS1ReferenceStation, 0001, granted
LBAS1ReferenceStation, 0002, granted
LBAS1ReferenceStation, 0003, granted
LBAS1ReferenceStation, 0004, granted
LBAS1ReferenceStation, 0005, granted
LBAS1ReferenceStation, 0007, granted
LBAS1ReferenceStation, 0009, granted
LBAS1ReferenceStation, 0015, granted
LBAS1ReferenceStation, 0125, denied
LBAS1ReferenceStation, 0556, denied
COM1>
```





slrs	setLBAS1RefStations	Stream	StationID (255)				
glrs	getLBAS1RefStations	Stream					
		+ RTCMV	<u>all</u>				
		all					

RxControl: L-band > LBAS1-Specific Settings > Reference Stations

This LBAS1-specific command defines the set of reference stations from which differential corrections have to be demodulated from the L-Band beam and included in the decoded correction stream. Only one decoded stream is defined, the RTCMV stream. That stream is fed into the PVT algorithm and serves as source of differential corrections in DGPS-rover and in PPP positioning modes.

The argument *StationID* is a list of 4-digit reference station IDs, separated by the "+" or "-" sign. Use the keyword "none" to empty the selected decoded correction stream, and "all" to include all reference stations in the stream.

Examples

To restrain the decoded differential correction stream to reference stations 1, 2, 3 and 15, use:

```
COM1> slrs, RTCMV, 0001+0002+0003+0015 <CR>
$R: slrs, RTCMV, 0001+0002+0003+0015
  LBAS1RefStations, RTCMV, "0001+0002+0003+0015"
COM1>
```

To add reference station 4 to the set, use:


```
COM1> slrs, RTCMV, +0004 <CR>
$R: slrs, RTCMV, +0004
  LBAS1RefStations, RTCMV, "0001+0002+0003+0004+0015"
COM1>
```

To select all reference stations except the one with ID 0015, use:

```
COM1> slrs, RTCMV, all-0015 <CR>
$R: slrs, RTCMV, all-0015
  LBAS1RefStations, RTCMV, "all-0015"
COM1>
```

To empty the RTCMV stream, use:

```
COM1> slrs, RTCMV, none <CR>
$R: slrs, RTCMV, none
  LBAS1RefStations, RTCMV, "none"
COM1>
```



3.2.25 Cosmos Configuration

scoc	setCosmosConfig	Enable	CustomerID (24)				
gcoc	getCosmosConfig						
		<u>off</u>					
		on					

RxControl: Communication > Cosmos



Cosmos support is a beta feature and the command description below is subject to change.

Cosmos is a tool that makes it possible to visualize the health and status information of multiple GNSS receivers in a single dashboard, as well as to functionally manage these receivers.

To include the receiver in the Cosmos tool, among others the Cosmos service must be installed on the receiver, and this service must be correctly configured.

Use this command to configure the Cosmos service on the receiver.

The Enable argument determines whether or not the Cosmos service is executed on the receiver. The CustomerID argument is used to identify the customer in whose Cosmos dashboard the receiver must be included. This value is unique per customer and must be obtained from Septentrio.

Besides the configuration in this command, Cosmos certificate and key files must be uploaded to the receiver. These files must also be obtained from Septentrio and can be uploaded using the web interface (using the "Admin > About > Cosmos" page).

Please refer to the Cosmos documentation and/or to Septentrio sales/support for more information on deploying Cosmos.

Example

```
COM1> scoc, on, customerx<CR>
$R: scoc, on, customerx
 CosmosConfig, on, customerx
COM1>
```





Chapter 4

SBF Reference



4.1 SBF Outline

SBF is the binary output format of Septentrio receivers. In this format, the data are arranged in binary blocks referred to as SBF blocks.

Each SBF block consists of a sequence of numeric or alphanumeric fields of different types and sizes. The total block size is always a multiple of 4 bytes.

The fields of an SBF block may have one of the following types:

Type	Description
u1	Unsigned integer on 1 byte (8 bits)
u2	Unsigned integer on 2 bytes (16 bits)
u4	Unsigned integer on 4 bytes (32 bits)
u8	Unsigned integer on 8 bytes (64 bits)
i1	Signed integer on 1 byte (8 bits)
i2	Signed integer on 2 bytes (16 bits)
i4	Signed integer on 4 bytes (32 bits)
i8	Signed integer on 8 bytes (64 bits)
f4	IEEE float on 4 bytes (32 bits)
f8	IEEE float on 8 bytes (64 bits)
c1[X]	String of X ASCII characters, right padded with bytes set to 0 if needed.

Each multi-byte binary type is transmitted as little-endian, meaning that the least significant byte is the first one to be transmitted by the receiver. Signed integers are coded as two's complement.

Every SBF block begins with an 8-byte block header, which is followed by the block body.


4.1.1 SBF Block Header Format

Every SBF block starts with an 8-byte header having the following contents:

Parameter	Туре	Description
Sync		The Sync field is a 2-byte array always set to 0x24, 0x40. The first byte of every SBF block has hexadecimal value 24 (decimal 36, ASCII '\$'). The second byte of every SBF block has hexadecimal value 40 (decimal 64, ASCII '@'). These two bytes identify the beginning of any SBF block and can be used for synchronization.
CRC	u2	The CRC field is the 16-bit CRC of all the bytes in an SBF block from and including the ID field to the last byte of the block. The generator polynomial for this CRC is the so-called CRC-CCITT polynomial: $x^{16} + x^{12} + x^5 + x^0$. The CRC is computed in the forward direction using a seed of 0, no reverse and no final XOR.
ID	u2	The ID field is a 2-byte block ID, which uniquely identifies the block type and its contents. It is a bit field with the following definition: bits 0-12: block number;
		bits 13-15: block revision number, starting from 0 at the initial block definition, and incrementing each time backwards-compatible changes are performed to the block (see section 4.1.6).
Length	u2	The Length field is a 2-byte unsigned integer containing the size of the SBF block. It is the total number of bytes in the SBF block including the header. It is always a multiple of 4.

4.1.2 SBF Block Names and Numbers

The structure and contents of an SBF block are unambiguously identified by the block ID. For easier readability, a block name is also defined for each block. When invoking the **setSBFOutput** command to enable a given block, the block name should be specified.



The list of SBF blocks available on your receiver can be found in Appendix A.

4.1.3 SBF Block Time Stamp (TOW and WNc)

Each SBF header is directly followed by a time stamp, which consists of two fields: TOW and WNc:

Parame	ter Type	e Units & Sca	le Do-Not-Use	Description			
		Factor	Value				
TOW	u4	0.001 s		Time-Of-Week: Time-tag, expressed in whole milliseconds from the beginning of the current GPS week.			
WNc	u2	1 week		The GPS week number associated with the ${\tt TOW.\ WNC}$ is a continuous week count (hence the "c"). It is not affected by GPS week rollovers, which occur every 1024 weeks. By definition of the Galileo system time, ${\tt WNC}$ is also the Galileo week number plus 1024.			

In the SBF time stamps, the definition of the week always follows the GPS convention even if the block contains data for another constellation. This means that WNc 0, TOW 0 corresponds to Jan 06,1980 at 00:00:00 UTC.

If the time-of-week or the week number is unknown, which is typically the case for a few seconds after start-up, the corresponding field is set to its Do-Not-Use value (see section 4.1.7). It does not mean that the SBF block is unusable, but simply that the receiver could not time-tag it. It is typical that the ${\tt TOW}$ field becomes valid before the WNc field.

The interpretation to give to the time stamp is block-dependent. Three types of time stamps are possible:

- Receiver time stamp: this type of time stamp is used for the SBF blocks containing synchronous data, i.e. data generated at a given epoch in the receiver time scale. Examples of such blocks are the measurement and PVT blocks (MeasEpoch and PVTCartesian). The time stamp is always a multiple of the output interval as specified by the setSBFOutput command (see also section 4.1.8). As soon as the receiver time is aligned with the GNSS time, the receiver time stamp is guaranteed to never decrease in successive SBF blocks.
- SIS time stamp: it is used for asynchronous blocks containing navigation message data from the signal-in-space. The time stamp corresponds to the time of transmission of the end of the last navigation bit used to build the SBF block. It always follows the GPS convention, as explained above.
- External time stamp: this type of time stamp is used for SBF blocks triggered by external asynchronous events, such as the ExtEvent block.

For the blocks with a SIS or an external time stamp, there is no strict relation between the time stamp of the SBF blocks and their order of transmission. For example, the SBF stream may contain a ${\tt GPSNav}$ block with ephemeris parameters received one hour in the past (i.e. the time stamp is one hour in the past) followed by another block with a current receiver time stamp.

4.1.4 Sub-blocks

Some blocks contain sub-blocks. For example, the SatVisibility block contains NatInfo sub-blocks, each sub-block containing data for one particular satellite. Unless the



size of the sub-blocks is mentioned explicitly in the block description, SBF blocks that contain sub-blocks also contain a SBLength field, which indicates the size of the sub-blocks in bytes.

4.1.5 Padding Bytes

Padding bytes are foreseen at the end of most SBF blocks and sub-blocks, so that their total size is equal to Length or SBLength respectively. The padding bytes are just placeholders and should not be looked at by the decoding software. Their value is not defined.

4.1.6 SBF Revision Number

Each SBF block has an associated revision number. The revision number is incremented each time a backwards-compatible change is implemented.

As described in section 4.1.1, the block number is to be found in bits 0 to 12 of the ${\tt ID}$ field, and the revision is in bits 13 to 15 of that field.

A backwards-compatible change consists of adding one or more fields in the padding bytes, or in the fields marked as "reserved" in the block description. Such change should be unnoticed by properly written decoding software that ignore the contents of padding and reserved fields (see also section 4.1.12). Each time such change happens, the revision number is incremented. The revision at which a given field has been introduced is documented in the block description in chapter 4.2, unless that revision is 0 (see the ReceiverSetup block as an example). It is guaranteed that if a given field exists in revision N, it will also exist in all revisions after N: no fields are withdrawn from SBF.

4.1.7 Do-Not-Use Value

It might happen that one or more pieces of data in an SBF block are not known at block creation time. For example, when there are insufficient satellite measurements to compute a position solution, the position components found in the X, Y and Z fields of the PVTCartesian block will not be available. To indicate that a given data item is not available or is currently not provided by the receiver, the corresponding field is set to a 'Do-Not-Use' value that is never reached in normal operation.

When applicable, the Do-Not-Use value is mentioned in the block description. The Do-Not-Use value refers to the raw contents of the field, without applying the scale factor. A field set to its Do-Not-Use value should always be discarded by the decoding software.

4.1.8 Output Rate

In general, the default output rate for each SBF block is the renewal rate of the information. For instance, the <code>GPSNav</code> block is output each time a new ephemeris data set is received from a given GPS satellite. The default output rates of GNSS measurement blocks, PVT blocks and integrated INS/GNSS blocks depend on your permission set. These three rates can be checked by the command <code>getReceiverCapabilities</code>.



The default output rate is specified for each block in chapter 4.2. To instruct the receiver to output a given block at its default rate, the "OnChange" rate has to be specified in the setSBFOutput command.

Some blocks can only be output at their default rate (e.g. the GPSNav block). Others can be decimated to a user-selectable rate. A subset of blocks can also be output "once" using the **exeSBFOnce** command. This can be handy to get a one-shot overview of a particular receiver state. Whether a given block supports a user-selectable rate ("Flex Rate") and whether it belongs to the "output once" set is indicated in the SBF block list in Appendix A.

Attempting to force another rate than the default one for those blocks that do not support "Flex Rate" has no effect: those blocks are always output at their default rate.

Satellite ID and GLONASS Frequency Num-4.1.9 ber

Satellites are identified by the SVID (or PRN) and FreqNr fields, defined as in the table below.



This table is only valid for the currently-supported constellations and signal types (see 4.1.10). To ensure compatibility with future SBF upgrades, decoding software must ignore SBF blocks and sub-blocks of which the satellite ID field or the signal number field is undefined in this document.

Field	Туј	e Do-Not-Use		Description	RINEX satellite code
arra -		Value	C-+-II:+-	ID. The fallenting and are defined.	
SVID or E	PRN u	0		ID: The following ranges are defined:	
			1-37:	PRN number of a GPS satellite	Gnn (nn = SVID)
			38-61:	Slot number of a GLONASS satellite with an offset of 37 (R01 to R24) $$	Rnn (nn = SVID-37)
			62:	GLONASS satellite of which the slot number is not known	NA
			63-68:	Slot number of a GLONASS satellite with an offset of 38 (R25 to R30) $$	Rnn (nn = SVID-38)
			71-106:	PRN number of a GALILEO satellite with an offset of 70	<i>Enn</i> (<i>nn</i> = SVID-70)
			107-119:	L-Band (MSS) satellite. Corresponding satellite name can be found in the ${\tt LBandBeams}$ block.	NA
			120-140:	PRN number of an SBAS satellite (S120 to S140)	<i>Snn</i> (<i>nn</i> = SVID-100)
			141-180:	PRN number of a BeiDou satellite with an offset of 140	Cnn (nn = SVID-140)
			181-187:	PRN number of a QZSS satellite with an offset of 180	<i>Jnn (nn</i> = SVID-180)
			191-197:	PRN number of a NavIC/IRNSS satellite with an offset of 190 (l01 to l07) $$	<i>Inn</i> (<i>nn</i> = SVID-190)
			198-215:	PRN number of an SBAS satellite with an offset of 57 (S141 to S158)	Snn (nn = SVID-157)
			216-222:	PRN number of a NavIC/IRNSS satellite with an offset of 208 (108 to 114)	<i>Inn</i> (<i>nn</i> = SVID-208)
			223-245:	PRN number of a BeiDou satellite with an offset of 182 (C41 to C63)	Cnn (nn = SVID-182)
FreqNr	u'	0	from 1 (S frequency number, with an offset of 8. It ranges corresponding to an actual frequency number of (corresponding to an actual frequency number of	
				-GLONASS satellites, ${ t FreqNr}$ is reserved and ignored by the decoding software.	



4.1.10 Signal Type

Some sub-blocks contain a signal type field, which identifies the type of signal and modulation the sub-blocks applies to. The signal numbering is defined as follows:

Signal	Signal Type	Constellation	Carrier frequency (MHz)	RINEX
number			1	obs code
0	L1CA	GPS	1575.42	1C
1	L1P	GPS	1575.42	1W
2	L2P	GPS	1227.60	2W
3	L2C	GPS	1227.60	2L
4	L5	GPS	1176.45	5Q
5	L1C	GPS	1575.42	1L
6	L1CA	QZSS	1575.42	1C
7	L2C	QZSS	1227.60	2L
8	L1CA	GLONASS	1602.00+(FreqNr-8)*9/16, with FreqNr as defined in section 4.1.9.	1C
9	L1P	GLONASS	1602.00+(FreqNr-8)*9/16	1P
10	L2P	GLONASS	1246.00+(FreqNr-8)*7/16	2P
11	L2CA	GLONASS	1246.00+(FreqNr-8)*7/16	2C
12	L3	GLONASS	1202.025	3Q
13	B1C	BeiDou	1575.42	1P
14	B2a	BeiDou	1176.45	5P
15	L5	NavIC/IRNSS	1176.45	5A
16	Reserved			
17	E1	Galileo	1575.42	1C
18	Reserved			
19	E6	Galileo	1278.75	6C or 6B ^(*)
20	E5a	Galileo	1176.45	5Q
21	E5b	Galileo	1207.14	7Q
22	E5 AltBOC	Galileo	1191.795	8Q
23	LBand	MSS	L-band beam specific	NA
24	L1CA	SBAS	1575.42	1C
25	L5	SBAS	1176.45	51
26	L5	QZSS	1176.45	5Q
27	L6	QZSS	1278.75	
28	B1I	BeiDou	1561.098	21
29	B2I	BeiDou	1207.14	71
30	B3I	BeiDou	1268.52	61
31	Reserved			
32	L1C	QZSS	1575.42	1L
33	L1S	QZSS	1575.42	1Z
34	B2b	BeiDou	1207.14	7D
35-37	Reserved			
38 (Tentative!)	L1CB	QZSS	1575.42	1E
39	L5S	QZSS	1176.45	5P

^(*) See the E6B Used bit in the MeasEpoch SBF block.

4.1.11 Channel Numbering

Some blocks contain a reference to the receiver channel number. Channel numbering starts at one. The maximum value for the channel number depends on the receiver type.





4.1.12 Decoding of SBF Blocks

In order to decode an SBF block, one has to identify the block boundaries in the data stream coming from the receiver. This involves searching for the initial "\$@" characters that mark the beginning of each SBF block. Since the "\$@" sequence can occur in the middle of an SBF block as well, additional checking is needed to make sure that a given "\$@" is indeed the beginning of a block. The following procedure is recommended to decode SBF data stream.

- 1. Wait until the "\$@" character sequence appears in the data stream from the receiver. When it is found, go to point 2.
- 2. Read the next two bytes. It should be the block CRC. Store this value for future reference.
- 3. Read the next two bytes and store them in a buffer. It should be the block ID.
- 4. Read the next two bytes and append them to the buffer. It should be the Length field of the SBF block. It should be a multiple of 4. If not, go back to point 1.
- 5. Read the next (Length-8) bytes and append them to the buffer. Compute the CRC of the buffer. The computed CRC should be equal to the CRC stored at point 2. If not, go back to point 1, else a valid SBF block has been detected and can be interpreted by the reading software.
- 6. If the block number (bits 0 to 12 of the ${\tt ID}$ field decoded at point 3) is of interest to your application, decode the SBF block.
- 7. Go back to point 1 and search for the new occurrence of the "\$@" sequence after the end of the last byte of the block that was just identified.

To ensure compatibility with future upgrades of SBF, it is recommended that the decoding software observes the following rules:

- Only bits 0 to 12 of the ID field must be used to identify a block. Bits 13 to 15 represent the revision number.
- The lengths of SBF blocks and sub-blocks should not be considered constant and hard-coded in the decoding software. Instead, the decoding software must use the Length and SBLength fields encoded in the SBF block.
- · Padding bytes should be ignored.
- Reserved fields and reserved bits in bit-fields should be ignored.
- SBF blocks or sub-blocks of which the satellite ID field or the signal number field is undefined in this document should be ignored (see section 4.1.9).



4.2 SBF Block Definitions

4.2.1 Measurement Blocks

GNSS observables are available in the following SBF blocks:

- the legacy MeasEpoch block, possibly complemented by MeasExtra.
- the Meas3Ranges block, possibly complemented by Meas3Doppler and Meas3CNOHiRes.

The MeasEpoch block contains pseudorange, carrier phase, C/N0 and Doppler observables. The Meas3Ranges block contains pseudoranges, carrier phases and C/N0, while Doppler is available in the companion Meas3Doppler block. The observable resolution is shown in the table below.

	MeasEpoch	Meas3Ranges
Pseudorange	1mm	1mm
Carrier phase	0.001cycles	0.001cycles
C/N0	0.25dB-Hz	1dB-Hz
	0.03125dB-Hz with MeasExtra	0.0625dB-Hz with Meas3CNOHiRes
Doppler	0.0001Hz	No Doppler in Meas 3 Ranges
		1mm/s with Meas3Doppler

The main advantage of the Meas 3 blocks is their reduced size compared to the MeasEpoch blocks. As an illustration, the following table shows the disk space required to log the different measurement-related blocks over one day at a 1-s interval. In this example, measurements from all GPS L1/L2/L5, GLONASS L1/L2, Galileo E1/E6/E5a/E5b and BeiDou B1/B2/B3 signals have been logged (constellation status as of beginning of 2017).

SBF Block	Disk space (1 day, 1 Hz)
MeasEpoch	104MB
MeasExtra	110MB
Meas3Ranges	28MB
Meas3Doppler	10MB
Meas3CN0HiRes	5MB



MeasEpoch	Number:	4027				
	"OnChange"	interval: internal	measurement	rate	(receiver-type	depen-
		dent)				

This block contains all the GNSS measurements (observables) taken at the time given by the TOW and WNc fields.

For each tracked signal, the following measurement set is available:

- the pseudorange
- the carrier phase
- the Doppler
- the C/N0
- · the lock-time.

To decrease the block size, all the measurements from a given satellite are referenced to one master measurement set. For instance, the L2 pseudorange (C2) is not much different from the L1 pseudorange (C1), such that the difference between C2 and C1 is encoded, instead of the absolute value of C2.

This is done by using a two-level sub-block structure. All the measurements from a given satellite are stored in a MeasEpochChannelType1 sub-block. The first part of this sub-block contains the master measurements, encoded as absolute values. The second part contains slave measurements, for which only the delta values are encoded in smaller MeasEpochChannelType2 sub-blocks.

Every MeasEpochChannelType1 sub-block contains a field "N2", which gives the number of nested MeasEpochChannelType2 sub-blocks. If there is only one signal tracked for a given satellite, there are no slave measurements and ${\tt N2}$ is set to 0.

Decoding is done as follows:

- 1. Decode the master measurements and the the MeasEpochChannelType1 sub-block.
- 2. If N2 is not 0, decode the N2 nested MeasEpochChannelType2 sub-blocks.
- 3. Go back to 1 till the N1 MeasEpochChannelType1 sub-blocks have been decoded.



Note that measurements in this block are scrambled if the "Measurement Availability" permission is not granted on your receiver. See also bit 7 of the CommonFlags field.



Parameter	Туре	Units	Do-Not-Use	Description				
Sync1	c1							
Sync2	c1							
CRC	u2			Block Header, see 4.1.1				
ID	u2							
Length	u2	1 byte						
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3				
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5				
N1	u1			Number of MeasEpochChannelType1 sub-blocks in this MeasEpoch block.				
SB1Length	u1	1 byte		Length of a MeasEpochChannelType1 sub-block, excluding the nested MeasEpochChannelType2 sub-blocks				
SB2Length	u1	1 byte		Length of a MeasEpochChannelType2 sub-block				
CommonFlags	u1			Bit field containing flags common to all measurements.				
				 Bit 0: Multipath mitigation: if this bit is set, multipath mitigation is enabled. (see the setMultipathMitigation command). Bit 1: Smoothing of code: if this bit is set, at least one of the code measurements are smoothed values (see setSmoothingInterval command). Bit 2: Reserved 				
				Bit 3: Clock steering: this bit is set if clock steering is active (see setClockSyncThreshold command). Bit 4: Not applicable.				
				Bit 5: High dynamics: this bit is set when the receiver is in high- dynamics mode (either on request of the user using the setReceiverDynamics, high command, or based on the re- ceiver's built-in high-dynamics detection algorithms).				
				Bit 6: E6B used: this bit is set if the Galileo E6 measurements in this block are obtained using the E6B signal instead of the default E6C signal. This happens when E6C encryption is active on at least one of the Galileo satellites. Bit 7: Scrambling: bit set when the measurements are scrambled. Scrambling is applied when the "Measurement Availability" permission is not granted (see the lif, Permissions command).				
CumClkJumps	u1	0.001 s		Cumulative millisecond clock jumps since start-up, with an ambiguity of k*256 ms. For example, if two clock jumps of -1 ms have occurred since startup, this field contains the value 254.				
Reserved	u1			Reserved for future use, to be ignored by decoding software				
Туре1				A succession of N1 MeasEpochChannelType1 sub-blocks, see definition below				
Padding	u1[]			Padding bytes, see 4.1.5				

Rev 1



${\tt MeasEpochChannelType1} \ \ \textbf{sub-block definition:}$

Parameter	Туре	Units	Do-Not-Use	Description
RxChannel	u1			Receiver channel on which this satellite is currently tracked (see 4.1.11).
Туре	u1			Bit field indicating the signal type and antenna ID:
				Bits 0-4: SigIdxLo: if not 31, this is the signal number (see 4.1.10), otherwise the signal number can be found in the ObsInfo field below. Bits 5-7: Antenna ID: 0 for main, 1 for Aux1 and 2 for Aux2
SVID	u1			Satellite ID, see 4.1.9
Misc	u1			Bit field containing the MSB of the pseudorange.
		4294967.296 m	0 (1)	Bits 0-3: CodeMSB: MSB of the pseudorange (this is an unsigned value). Bits 4-7: Reserved
CodeLSB	u4	0.001 m	0 (1)	LSB of the pseudorange. The pseudorange expressed in meters is computed as follows: PR _{type1} [m] = (CodeMSB*4294967296+CodeLSB)*0.001 where CodeMSB is part of the Misc field.
Doppler	i4	0.0001 Hz	21/7/836/8	Carrier Doppler (positive for approaching satellites).
pobbiei	14	0.0001112	-2147403040	To compute the Doppler in Hz, use: $D_{\mathrm{type1}}[\mathrm{Hz}] = D_{\mathrm{Doppler}}^{*} \times 0.0001$
CarrierLSB	u2	0.001 cycles	0 (2)	LSB of the carrier phase relative to the pseudorange
CarrierMSB	i1	65.536 cycles	-128 ⁽²⁾	MSB of the carrier phase relative to the pseudorange. The full carrier phase can be computed by:
CN0	u1	0.25 dB-Hz	255	The C/N0 in dB-Hz is computed as follows, depending on the signal type in the Type field:
LockTime	u2	1 s	65535	Duration of continuous carrier phase. The lock-time is reset at the initial lock of the phase-locked-loop, and whenever a loss of lock condition occurs. If the lock-time is longer than 65534s, it is clipped to 65534s. If the carrier phase measurement is not available, this field is set to its Do-Not-Use value.



ObsInfo	u1		Bit field:	:
			Bit 0:	if set, the pseudorange measurement is smoothed
			Bit 1:	Reserved
			Bit 2:	this bit is set when the carrier phase (L) has a half-cycle ambiguity $ \\$
			Bits 3-7:	The interpretation of these bits depends on the value of ${\tt SigIdxLo}$ from the ${\tt Type}$ field.
				If $SigIdxLo$ equals 31, these bits contain the signal number with an offset of 32 (see 4.1.10). For example, a value of 1 corresponds to signal number 33 (QZSS L1S).
				If SigIdxLo is 8, 9, 10 or 11, these bits contain the GLONASS frequency number with an offset of 8. For example, a value of 1 corresponds to frequency number -7.
				Otherwise, these bits are reserved.
N2	u1	1		r of MeasEpochChannelType2 sub-blocks contained leasEpochChannelType1 sub-block.
Padding	u1[]		Padding	bytes, see 4.1.5
Туре2			A succes definitio	sion of N2 MeasEpochChannelType2 sub-blocks, see n below

MeasEpochChannelType2 sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description			
Type	u1			Bit field indicating the signal type and antenna ID:			
				Bits 0-4: SigIdxLo: if not 31, this is the signal number (see 4.1.10), otherwise the signal number can be found in the ObsInfo field below. Bits 5-7: Antenna ID: 0 for main, 1 for Aux1 and 2 for Aux2			
LockTime	u1	1 s	255	See corresponding field in the MeasEpochChannelType1 subblock above, except that the value is clipped to 254 instead of 65534.			
CN0	u1	0.25 dB-Hz	255	See corresponding field in the MeasEpochChannelType1 sulblock above.			
OffsetsMSB	u1			Bit field containing the MSB of the code and of the Doppler offsets with respect to the MeasEpochChannelType1 sub-block.			
		65.536 m	-4 ⁽³⁾	Bits 0-2: CodeOffsetMSB: MSB of the code offset.			
		6.5536 Hz	-16 ⁽⁴⁾	Bits 3-7: DopplerOffsetMSB: MSB of the Doppler offset.			
				CodeOffsetMSB and DopplerOffsetMSB are coded as two's complement. Refer to the CodeOffsetLSB and DopplerOffsetLSB fields to see how to use this field.			
CarrierMSB	i1	65.536 cycles	-128 ⁽⁵⁾	MSB of the carrier phase relative to the pseudorange.			
ObsInfo	u1			Bit field:			
				Bit 0: if set, the pseudorange measurement is smoothed			
				Bit 1: Reserved			
				Bit 2: this bit is set when the carrier phase (L) has a half-cycle ambiguity			
				Bits 3-7: If SigIdxLo from the Type field of this sub-block equals 31, these bits contain the signal number with an offset of 32 (see 4.1.10), e.g. 1 corresponds to signal number 33 (QZSS L1S). Otherwise they are reserved and must be ignored by the decoding software.			

The pseudorange is invalid if both CodeMSB is 0 and CodeLSB is 0.
The carrier phase is invalid if both CarrierMSB is -128 and CarrierLSB is 0.



CodeOffsetLSB	u2	0.001 m	0 (3)	LSB of the code offset with respect to pseudorange in the MeasEpochChannelType1 sub-block. To compute the pseudorange, use: $ PR_{\rm type2} \ [m] = PR_{\rm type1} [m] \\ + ({\tt CodeOffsetMSB*65536+CodeOffsetLSB})*0.001 $
CarrierLSB	u2	0.001 cycles	0 (5)	LSB of the carrier phase relative to the pseudorange. The full carrier phase can be computed by:
DopplerOffsetLSB	u2	0.0001 Hz	0 (4)	LSB of the Doppler offset relative to the Doppler in the MeasEpochChannelType1 sub-block. To compute the Doppler, use: $D_{type2}[Hz] = D_{type1}[Hz] * \alpha \\ + (DopplerOffsetMSB*65536+DopplerOffsetLSB) \\ *1e-4,$ where α is the ratio of the carrier frequency corresponding to the observable type in this MeasEpochChannelType2 sub-block, and that of the master observable type in the parent MeasEpochChannelType1 sub-block (see section 4.1.10 for a list of all carrier frequencies).
Padding	u1[]			Padding bytes, see 4.1.5

The pseudorange is invalid if both <code>CodeOffsetMSB</code> is -4 and <code>CodeOffsetLSB</code> is 0. The Doppler is invalid if both <code>DopplerOffsetMSB</code> is -16 and <code>DopplerOffsetLSB</code> is 0.


⁽⁵⁾ The carrier phase is invalid if both CarrierMSB is -128 and CarrierLSB is 0.



MeasExtra	Number:	4000				
	"OnChange"	interval: internal	measurement	rate	(receiver-type	depen-
		dent)				

This block contains extra information associated with the measurements contained in the MeasEpoch block, such as the internal corrections parameters applied during the measurement pre-processing, and the noise variances.

Parameter	Туре	Units	Do-Not-Use	Description				
Sync1	c1							
Sync2	c1			1				
CRC	u2			Block Header, see 4.1.1				
ID	u2							
Length	u2	1 byte						
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3				
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5				
N	u1			Number of sub-blocks in this MeasExtra block.				
SBLength	u1	1 byte		Length of a sub-block				
DopplerVarFactor	f4	1 Hz ² / cycle ²		Factor to be used to compute the Doppler variance from the carrier phase variance. More specifically, the Doppler variance in $\it mHz^2$ can be computed by: $\sigma^2_{\rm Doppler}[\rm mHz^2] = {\tt CarrierVariance*DopplerVarFactor},$ Where ${\tt CarrierVariance}$ can be found for each measurement type in the MeasExtraChannelSub sub-blocks.				
ChannelSub				A succession of N MeasExtraChannelSub sub-blocks, see definition below				
Padding	u1[]			Padding bytes, see 4.1.5				



MeasExtraChannelSub sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
RxChannel	u1			Receiver channel on which this satellite is currently tracked (see 4.1.11).
Type	u1			Bit field indicating the signal type and antenna ID:
				Bits 0-4: SigIdxLo: if not 31, this is the signal number (see 4.1.10), otherwise the signal number can be found in the Misc field below. A value of 31 can only happen on block revision 3 or above. Bits 5-7: Antenna ID: 0 for main, 1 for Aux1 and 2 for Aux2
MPCorrection	i2	0.001 m		Multipath correction applied to the pseudorange. This number has to be added to the pseudorange to recover the raw pseudorange as it would be if multipath mitigation was not used.
SmoothingCorr	i2	0.001 m		Smoothing correction applied to the pseudorange. This number has to be added to the pseudorange to recover the raw pseudorange as it would be if smoothing was disabled.
CodeVar	u2	0.0001 m ²	65535	Estimated code tracking noise variance. If the variance is larger than 65534 cm ² , it is clipped to 65534 cm ² .
CarrierVar	u2	1 mcycle ²	65535	Estimated carrier tracking noise variance. This value can be multiplied by DopplerVarFactor to compute the Doppler measurement variance.
				If the variance is larger than 65534 mcycles 2 , it is clipped to 65534 mcycles 2 .
LockTime	u2	1 s	65535	Duration of continuous carrier phase. The lock-time is reset at the initial lock after a signal (re)acquisition.
				If the lock-time is longer than 65534s, it is clipped to 65534s.
				If the carrier phase measurement is not available, this field is set to its Do-Not-Use value.
CumLossCont	u1			Carrier phase cumulative loss-of-continuity counter (modulo 256) for the signal type, antenna and satellite this sub-block refers to. This counter starts at zero at receiver start-up, and is incremented at each initial lock after signal (re)acquisition, or when a cycle slip is detected.
CarMPCorr	i1	1.953125 mcycle		Multipath correction applied to the carrier phase, in units of 1/512 cycles. This number has to be added to the carrier phase to recover the raw phase as it would be if multipath mitigation was not used.
Info	u1			Bit field:
				Bits 0-3: Reserved.
				Bits 4-7: Reserved.
Misc	u1	0.03125 dB-Hz		Bits 0-2: CN0HighRes: high-resolution extension of the C/N0 (unsigned value from 0 to 7). The C/N0 value in the MeasEpoch SBF block has a resolution of 0.25dB-Hz. CN0HighRes can be used to extend the resolution to 0.03125dB-Hz. The high-resolution C/N0, in dB-Hz, is computed as follows: C/N _{0,HighRes} = C/N _{0,MeasEpoch} +CN0HighRes*0.03129 where C/N _{0,MeasEpoch} is the C/N0 value coming from the MeasEpoch SBF block.
	45-			Bits 3-7: If SigIdxLo from the Type field equals 31, these bits contain the signal number with an offset of 32 (see 4.1.10). Otherwise they are reserved.
Padding	u1[]			Padding bytes, see 4.1.5

Rev 1

Rev 2

Rev 3



Meas3Ranges	Number:	4109				
	"OnChange"	interval: internal	measurement	rate	(receiver-type	de-
		pendent)			

This block contains all the code, carrier phase and C/N0 observables at a given measurement epoch. The resolution is 0.001m, 0.001cycles and 1dB-Hz for the code, carrier and C/N0 measurements respectively.

Applications requiring Doppler measurements can log the Meas3Doppler SBF block in addition to the Meas3Ranges block. Applications requiring extended C/N0 resolution (1/16dB-Hz) can log the Meas3CNOHiRes SBF block in addition to the Meas3Ranges block.

The advantage of this block compared to the MeasEpoch SBF block is its reduced size while offering the full resolution for the code and carrier measurements. One of the techniques used to reduce the size is to only encode full measurements (reference epochs) every N epochs. Between these reference epochs, Meas3Ranges contains delta epochs where the difference between the current measurements and the ones at the applicable reference epoch is encoded. The decoder must have received and stored the applicable reference epoch to be able to decode delta epochs. When streaming SBF over an unreliable communication link, if the reference epoch is lost, subsequent Meas3Ranges blocks cannot be decoded until the next reference epoch is received. The interval at which reference epochs are encoded can be controlled with the setMeas3MaxRefInterval command. A longer interval generally reduces the average block size, at the expense of a longer data gap in case a reference epoch is lost.

See also page 301 for additional information.



The format of this block and of the other Meas3 blocks is complex and is not provided here. Details can be obtained from Septentrio Support. The RxTools installation contains the complete source code of a decoder in C language, together with sbf2asc, a small application showing how to use it. All C files can be found under the sbf2asc folder in the RxTools installation. The main measurement decoding function is sbfread_MeasCollectAndDecode() in the sbfread_meas.c file. Users interested in decoding the Meas3 blocks are strongly advised to use the provided source code instead of writing their own decoder.



Meas3CN0HiRes	Number:	4110						
	"OnChange"	interval: internal	measurement	rate	(receiver-type			
	dependent)							

The Meas3CN0HiRes block is an extension of the Meas3Ranges block containing the fractional part of the C/N0 values. The resolution of the C/N0 value in the Meas3Ranges SBF block is 1dB-Hz. Applications requiring a finer C/N0 resolution (0.0625dB-Hz) must log the Meas3CN0HiRes block together with the Meas3Ranges block.



Meas3Doppler	Number:	4111
	"OnChange"	interval: internal measurement rate (receiver-type de-
		pendent)

The Meas3Doppler block is an extension of the Meas3Ranges block containing the range-rate (Doppler) values. Applications requiring range-rate or Doppler observables must log the Meas3Doppler block together with the Meas3Ranges block.



Meas3PP	Number:	4112	1
	"OnChange"	interval: internal measurement rate (receiver-type dependent)	

The Meas 3PP block is an extension of the Meas 3Ranges block containing various Septentrio-proprietary flags and values needed for accurate post-processing or re-processing of the PVT from the measurements in the Meas 3Ranges SBF block. This block must be logged together with Meas 3Ranges.



Meas3MP	Number:	4113
	"OnChange"	interval: internal measurement rate (receiver-type dependent)

The Meas3MP block is an extension of the Meas3Ranges block containing the multipath correction applied by the receiver. It can be used for research purposes to undo the receiver multipath mitigation and revert to unmitigated data. This block must be logged together with Meas3Ranges.



EndOfMeas	Number:	5922				
	"OnChange"	interval: internal	measurement	rate	(receiver-type	depen-
		dent)				

This block marks the end of the transmission of all measurement-related blocks belonging to a given epoch.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5
Padding	u1[]			Padding bytes, see 4.1.5



4.2.2 Navigation Page Blocks

GPSRawCA	Number:	4017	
	"OnChange"	interval: 6s	

This block contains the 300 bits of a GPS C/A subframe. It is generated each time a new subframe is received, i.e. every 6 seconds.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	1313 time stamp, see 4.1.3
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Not applicable
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as de-
				fined in 4.1.10 Bits 5-7: Reserved
FreqNr	u1			Not applicable
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 bits of a GPS C/A subframe.
				Encoding: For easier parsing, the bits are stored as a succession of 10 32-bit words. Since the actual words in the subframe are 30-bit long, two unused bits are inserted in each 32-bit word. More specifically, each 32-bit word has the following format:
				Bits 0-5: 6 parity bits (referred to as D_{25} to D_{30} in the GPS ICD), XOR-ed with the last transmitted bit of the previous word (D_{30}^*)).
				Bits 6-29: source data bits (referred to as d_n in the GPS ICD). The first received bit is the MSB. Bits 30-31: Reserved
Padding	u1[]			Padding bytes, see 4.1.5



GPSRawL2C	Number:	4018
	"OnChange"	interval: 12s

This block contains the 300 bits of a GPS L2C CNAV subframe (the so-called $\mathcal{D}_{c}(t)$ data stream).

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	and time stamp, see 4.1.5
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Viterbi decoder error count over the subframe
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved
FreqNr	u1			Not applicable
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 bits of a GPS CNAV subframe.
				Encoding: NAVBits contains all the bits of the frame, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[9] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



GPSRawL5	Number:	4019	
	"OnChange"	interval: 6s	

This block contains the 300 bits of a GPS L5 CNAV subframe (the so-called $\mathcal{D}_{c}(t)$ data stream).

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	1515 time stamp, see 4.1.5
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Viterbi decoder error count over the subframe
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved
FreqNr	u1			Not applicable
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 bits of a GPS CNAV subframe.
				Encoding: NAVBits contains all the bits of the frame, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[9] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



GPSRawL1C	Number:	4221
	"OnChange"	interval: 18s

This block contains the 1800 symbols of a GPS L1C navigation frame (itself containing three subframes).

The symbols are deinterleaved. The receiver attempts to correct bit errors using the LDPC parity bits, but unrecoverable errors are still possible at low C/N0. It is therefore always needed to check the CRC status before using the navigation bits. A separate CRC status is provided for subframe 2 and 3.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	and time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCSF2	u1			Status of the CRC check of subframe 2: 0: failed 1: passed	
CRCSF3	u1			Status of the CRC check of subframe 3: 0: failed 1: passed	
Source	u1			Signal type from which the bits have been received, as defined in 4.1.1	
Reserved	u1			Reserved for future use, to be ignored by decoding software.	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[57]			NAVBits contains the 1800 deinterleaved symbols of a GPS L1 navigation frame. Encoding: NAVBits contains all the symbols of the frame. The first received symbol (i.e. the first symbol of subframe 1) is stored a	
				the MSB of NAVBits[0]. The 24 unused bits in NAVBits[56] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



This block contains the 85 bits of a GLONASS L1CA or L2CA navigation string.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	or all the stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Not applicable	
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved	
FreqNr	u1			Frequency number, with an offset of 8. See 4.1.9	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[3]			NAVBits contains the first 85 bits of a GLONASS C/A string (i.e. all bits of the string with the exception of the time mark). Encoding: The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[2] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



GALRawFNAV	Number:	4022	
	"OnChange"	interval: 10s	

This block contains the 244 bits of a Galileo F/NAV navigation page, after deinterleaving and Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	isis time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the page	
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-6: Reserved Bit 7: Reserved	
FreqNr	u1			Not applicable	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[8]			NavBits contains the 244 bits of a Galileo F/NAV page. Encoding: NAVBits contains all the bits of the frame, with the exception of the synchronization field. The first received bit is stored at the MSB of NAVBits[0]. The unused bits in NAVBits[7] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



GALRawINAV	Number:	4023	
	"OnChange"	interval: 2s	

This block contains the 234 bits of a Galileo I/NAV navigation page, after deinterleaving and Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	313 time stamp, see 4.1.3	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the page	
Source	u1			Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bit 5: Set when the nav page is the concatenation of a sub-page received from E5b, and a sub-page received from L1BC. In that case, bits 0-4 are set to L1BC. Bit 6: Reserved Bit 7: Reserved	
FreqNr	u1			Not applicable	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[8]			NAVBits contains the 234 bits of an I/NAV navigation page (in nominal or alert mode). Note that the I/NAV page is transmitted as two sub-pages (the so-called even and odd pages) of duration 1 second each (120 bits each). In this block, the even and odd pages are concatenated, even page first and odd page last. The 6 tails bits at the end of the even page are removed (hence a total of 234 bits). If the even and odd pages have been received from two different carriers (E5b and L1), bit 5 of the Source field is set. Encoding: NAVBits contains all the bits of the frame, with the exception of the synchronization field. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[7] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	
L			1		



GALRawCNAV	Number:	4024	
	"OnChange"	interval: 1s	

This block contains the 492 bits of a Galileo C/NAV navigation page, after deinterleaving and Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	and time stamp, see 4.1.3	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the page	
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-6: Reserved	
	+			Bit 7: Reserved	
FreqNr	u1			Not applicable	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[16]			NAVBits contains the 492 bits of a Galileo C/NAV page. Encoding: NAVBits contains all the bits of the frame, with the exception of the synchronization field. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[15] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



GEORawL1	Number:	4020	
	"OnChange"	interval: 1s	

This block contains the 250 bits of a SBAS L1 navigation frame, after Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	Job time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the navigation frame	
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved	
FreqNr	u1			Not applicable	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[8]			NAVBits contains the 250 bits of a SBAS navigation frame. Encoding: NAVBits contains all the bits of the frame, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[7] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



GEORawL5	Number:	4021	
	"OnChange"	interval: 1s	

This block contains the 250 bits of a SBAS L5 navigation frame, after Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			Block Header, see 4.1.1
Sync2	c1			
CRC	u2			
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Viterbi decoder error count over the navigation frame
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved
FreqNr	u1			Not applicable
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[8]			NAVBits contains the 250 bits of a SBAS navigation frame. Encoding: NAVBits contains all the bits of the frame, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[7] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



BDSRaw Number: 4047
"OnChange" interval: 6 seconds (non GEOs), 0.6 s (GEOs)

This block contains the 300 bits of a BeiDou navigation page, as received from the B1I, B2I or B3I signal.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	on time stamp, see 4.1.5
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Not applicable
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10
Reserved	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 deinterleaved bits of a BeiDou navigation subframe.
				Encoding: NAVBits contains all the bits of the subframe, including the preamble and the parity bits. The first received bit is stored as the MSB of NAVBits[0]. The 20 unused bits in NAVBits[9] must be ignored by the decoding software. The bits are deinterleaved.
Padding	u1[]			Padding bytes, see 4.1.5



BDSRawB1C	Number:	4218
	"OnChange"	interval: 18s

This block contains the 1800 symbols of a BeiDou B-CNAV1 navigation frame (itself containing three subframes), as received from the B1C signal.

The symbols are deinterleaved. The receiver attempts to correct bit errors using the LDPC parity bits, but unrecoverable errors are still possible at low C/N0. It is therefore always needed to check the CRC status before using the navigation bits. A separate CRC check is provided for subframe 2 and 3.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	and time stamp, see 4.1.5
SVID	u1			Satellite ID, see 4.1.9
CRCSF2	u1			Status of the CRC check of subframe 2: 0: failed 1: passed
CRCSF3	u1			Status of the CRC check of subframe 3: 0: failed 1: passed
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10
Reserved	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[57]			NAVBits contains the 1800 deinterleaved symbols of a BeiDou B1C (B-CNAV1) navigation frame. Encoding: NAVBits contains all the symbols of the frame. The first received symbol (i.e. the first symbol of subframe 1) is stored as
				the MSB of NAVBits[0]. The 24 unused bits in NAVBits[56] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



BDSRawB2a	Number:	4219		
	"OnChange"	interval: 3s		

This block contains the 576 symbols of a BeiDou B-CNAV2 navigation frame, as received from the B2a signal.

The receiver attempts to correct bit errors using the LDPC parity bits, but unrecoverable errors are still possible at low C/N0. It is therefore always needed to check the CRC status before using the navigation bits.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Not applicable
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10
Reserved	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[18]			${\tt NAVBits}$ contains the 576 symbols of a BeiDou B2a (B-CNAV2) navigation frame.
				Encoding: NAVBits contains all the symbols of the frame, excluding the preamble. The first received symbol (i.e. the MSB of the PRN field) is stored as the MSB of NAVBits [0].
Padding	u1[]			Padding bytes, see 4.1.5



BDSRawB2b	Number:	4242
	"OnChange"	interval: 1s

This block contains the raw symbols of a BeiDou B-CNAV3 or PPP-B2b_I navigation frame, as received from the B2b signal.

The receiver attempts to correct bit errors using the LDPC parity bits, but unrecoverable errors are still possible at low C/N0. It is therefore always needed to check the CRC status before using the navigation bits.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC check on the 486 bits of the message: 0: CRC check failed 1: CRC check passed
Reserved1	u1			Reserved for future use, to be ignored by decoding software.
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10
Reserved2	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[31]			NAVBits contains the 984 symbols of a BeiDou B2b navigation frame. Encoding: NAVBits contains all the symbols of the frame, excluding the preamble. The first received symbol (i.e. the MSB of the PRN field) is stored as the MSB of NAVBits[0]. The 8 unused bits in NAVBits[30] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



QZSRawL1CA Number: 4066
"OnChange" interval: 6s

This block contains the 300 bits of a QZSS L1C/A or L1C/B subframe.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	and time stamp, see 4.1.3
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
Reserved	u1			Reserved
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10
Reserved2	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 bits of a QZSS C/A subframe.
				Encoding: Same as GPSRawCA block.
Padding	u1[]			Padding bytes, see 4.1.5



QZSRawL2C Number:	4067	
"OnChang	re" interval: 12s	

This block contains the 300 bits of a QZSS L2C CNAV subframe.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	313 time stamp, see 4.1.3
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Viterbi decoder error count over the subframe
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved
Reserved	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 bits of a QZSS CNAV subframe. Encoding: NAVBits contains all the bits of the frame, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[9] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



QZSRawL5	Number:	4068	
	"OnChange"	interval: 6s	

This block contains the 300 bits of a QZSS L5 CNAV subframe.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	313 time stamp, see 4.1.3
SVID	u1			Satellite ID, see 4.1.9
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed
ViterbiCnt	u1			Viterbi decoder error count over the subframe
Source	u1			Bit field: Bits 0-4: Signal type from which the bits have been received, as defined in 4.1.10 Bits 5-7: Reserved
Reserved	u1			Reserved for future use, to be ignored by decoding software.
RxChannel	u1			Receiver channel (see 4.1.11).
NAVBits	u4[10]			NAVBits contains the 300 bits of a QZSS CNAV subframe. Encoding: NAVBits contains all the bits of the frame, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[9] must be ignored by the decoding software.
Padding	u1[]			Padding bytes, see 4.1.5



QZSRawL6	Number:	4069	
	"OnChange"	interval: 1s	

This block contains the 2000 bits of a QZSS L6 message.

The receiver attempts to correct bit errors using the Reed-Solomon parity symbols. The block contains the corrected bits and there is no need to have a Reed-Solomon decoder at the user side. The Parity field indicates whether the error recovery was successful or not.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	1515 time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
Parity	u1			Status of the Reed-Solomon decoding: 0: Failed: unrecoverable errors found. There is at least one wrong bit in NavBits. 1: Passed: all bit errors could be recovered, or the message was received without bit error.	
RSCnt	u1			Number of symbol errors that were successfully corrected by the Reed-Solomon decoder.	
Source	u1			Source of the message: 0: Unknown 1: QZSS L6D 2: OZSS L6E	
Reserved	u1			Reserved	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[63]			NAVBits contains the 2000 bits of a QZSS L6 message. Encoding: NAVBits contains all the bits of the message after Reed-Solomon decoding, including the preamble and the Reed-Solomon parity symbols themselves. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[63] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



QZSRawL1C	Number:	4227
	"OnChange"	interval: 18s

This block contains the 1800 symbols of a QZSS L1C navigation frame (itself containing three subframes).

The symbols are deinterleaved. The receiver attempts to correct bit errors using the LDPC parity bits, but unrecoverable errors are still possible at low C/N0. It is therefore always needed to check the CRC status before using the navigation bits. A separate CRC status is provided for subframe 2 and 3.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	and time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCSF2	u1			Status of the CRC check of subframe 2: 0: failed 1: passed	
CRCSF3	u1			Status of the CRC check of subframe 3: 0: failed 1: passed	
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10	
Reserved	u1			Reserved for future use, to be ignored by decoding software.	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[57]			NAVBits contains the 1800 deinterleaved symbols of a QZSS L1C navigation frame. Encoding: NAVBits contains all the symbols of the frame. The	
				first received symbol (i.e. the first symbol of subframe 1) is stored as the MSB of <code>NAVBits[0]</code> . The 24 unused bits in <code>NAVBits[56]</code> must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



This block contains the 250 bits of a QZSS L1S navigation message, after Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	515 time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the navigation message	
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10	
FreqNr	u1			Not applicable	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[8]			NAVBits contains the 250 bits of a QZSS L1S navigation message. Encoding: NAVBits contains all the bits of the message, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[7] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



QZSRawL5S Number:	4246	
"OnChange"	interval: 1s	

This block contains the 250 bits of a QZSS L5S navigation message, after Viterbi decoding.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	or anne stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the navigation message	
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10	
FreqNr	u1			Not applicable	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[8]			NAVBits contains the 250 bits of a QZSS L5S navigation message. Encoding: NAVBits contains all the bits of the message, including the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[7] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



NAVICRaw	Number:	4093	
	"OnChange"	interval: 12s	

This block contains the 292 bits of a NavIC/IRNSS subframe.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	and time stamp, see 4.1.5	
SVID	u1			Satellite ID, see 4.1.9	
CRCPassed	u1			Status of the CRC or parity check: 0: CRC or parity check failed 1: CRC or parity check passed	
ViterbiCnt	u1			Viterbi decoder error count over the subframe	
Source	u1			Signal type from which the bits have been received, as defined in 4.1.10	
Reserved	u1			Reserved for future use, to be ignored by decoding software.	
RxChannel	u1			Receiver channel (see 4.1.11).	
NAVBits	u4[10]			NavBits contains the 292 bits of a NavIC/IRNSS subframe. Encoding: NAVBits contains all the bits of the frame, with the exception of the preamble. The first received bit is stored as the MSB of NAVBits[0]. The unused bits in NAVBits[9] must be ignored by the decoding software.	
Padding	u1[]			Padding bytes, see 4.1.5	



4.2.3 GPS Decoded Message Blocks

GPSNav	Number:	5891	
	"OnChange"	interval: block generated each time a new navigation data set i	s
		received from a GPS satellite	

The \mathtt{GPSNav} block contains the decoded navigation data for one GPS satellite. These data are conveyed in subframes 1 to 3 of the satellite navigation message. Refer to GPS ICD for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	-515 time stamp, see 4.1.5
PRN	u1			ID of the GPS satellite of which the ephemeris is given in this block (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
MM	u2	1 week	65535	Week number (10 bits from subframe 1, word 3)
CAorPonL2	u1			Code(s) on L2 channel (2 bits from subframe 1, word 3)
URA	u1			User Range accuracy index (4 bits from subframe 1 word 3)
health	u1			6-bit health from subframe 1, word 3 (6 bits from subframe 1, word 3)
L2DataFlag	u1			Data flag for L2 P-code (1 bit from subframe 1, word 4)
IODC	u2			Issue of data, clock (10 bits from subframe 1)
IODE2	u1			Issue of data, ephemeris (8 bits from subframe 2)
IODE3	u1			Issue of data, ephemeris (8 bits from subframe 3)
FitIntFlg	u1			Curve Fit Interval, (1 bit from subframe 2, word 10)
Reserved2	u1			unused, to be ignored by decoding software
T_gd	f4	1 s		Estimated group delay differential
t_oc	u4	1 s		clock data reference time
a_f2	f4	1 s / s ²		SV clock aging
a_f1	f4	1 s / s		SV clock drift
a_f0	f4	1 s		SV clock bias
C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit ra- dius
DEL_N	f4	1 semi-circle / s		Mean motion difference from computed value
M_0	f8	1 semi-circle		Mean anomaly at reference time
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude
е	f8			Eccentricity
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude
SQRT_A	f8	1 m ^{1/2}		Square root of the semi-major axis
t_oe	u4	1 s		Reference time ephemeris
C_ic	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination
OMEGA_0	f8	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch
C_is	f4	1 rad		Amplitude of the sine harmonic correction term to the angle of inclination



i_0	f8	1 semi-circle	Inclination angle at reference time
C_rc	f4	1 m	Amplitude of the cosine harmonic correction term to the orbit radius
omega	f8	1 semi-circle	Argument of perigee
OMEGADOT	f4	1 semi-circle / s	Rate of right ascension
IDOT	f4	1 semi-circle / s	Rate of inclination angle
WNt_oc	u2	1 week	WN associated with t_oc, modulo 1024
WNt_oe	u2	1 week	WN associated with t_oe, modulo 1024
Padding	u1[]		Padding bytes, see 4.1.5



GPSAlm	Number:	5892
	"OnChange"	interval: block generated each time a new almanac data set is re-
		ceived from a GPS satellite

The \mathtt{GPSAlm} block contains the decoded almanac data for one GPS satellite. These data are conveyed in subframes 4 and 5 of the satellite navigation message. Refer to GPS ICD for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	ors time stamp, see 4.1.5
PRN	u1			ID of the GPS satellite of which the almanac is given in this block (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
е	f4			Eccentricity
t_oa	u4	1 s		almanac reference time of week
delta_i	f4	1 semi-circle		Inclination angle at reference time, relative to $i_0 = 0.3$ semicircles
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
SQRT_A	f4	1 m ^{1/2}		Square root of the semi-major axis
OMEGA_0	f4	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch
omega	f4	1 semi-circle		Argument of perigee
M_0	f4	1 semi-circle		Mean anomaly at reference time
a_f1	f4	1 s / s		SV clock drift
a_f0	f4	1 s		SV clock bias
WN_a	u1	1 week		Almanac reference week, to which t_oa is referenced
config	u1			Anti-spoofing and satellite configuration (4 bits from subframe 4, page 25)
health8	u1			health on 8 bits from the almanac page
health6	u1			health summary on 6 bits (from subframe 4, page 25 and subframe 5 page 25)
Padding	u1[]			Padding bytes, see 4.1.5



GPSIon	Number:	5893
	"OnChange"	interval: block generated each time subframe 4, page 18, is re-
		ceived from a GPS satellite

The GPSIon block contains the decoded ionosphere data (the Klobuchar coefficients). These data are conveyed in subframes 4, page 18 of the satellite navigation message. Refer to GPS ICD for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or time stamp, see 4.1.5
PRN	u1			ID of the GPS satellite from which the coefficients have been received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
alpha_0	f4	1 s		vertical delay coefficient 0
alpha_1	f4	1 s / semi-circle		vertical delay coefficient 1
alpha_2	f4	1 s / semi-circle ²		vertical delay coefficient 2
alpha_3	f4	1 s / semi-circle ³		vertical delay coefficient 3
beta_0	f4	1 s		model period coefficient 0
beta_1	f4	1 s / semi-circle		model period coefficient 1
beta_2	f4	1 s / semi-circle ²		model period coefficient 2
beta_3	f4	1 s / semi-circle ³		model period coefficient 3
Padding	u1[]			Padding bytes, see 4.1.5



GPSUtc	Number:	5894
	"OnChange"	interval: block generated each time subframe 4, page 18, is re-
		ceived from a GPS satellite

The \mathtt{GPSUtc} block contains the decoded UTC data. These data are conveyed in subframes 4, page 18 of the satellite navigation message. Refer to GPS ICD for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	515 time stamp, see 4.1.5
PRN	u1			ID of the GPS satellite from which these UTC parameters have been received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
A_1	f4	1 s / s		first order term of polynomial
A_0	f8	1 s		constant term of polynomial
t_ot	u4	1 s		reference time for UTC data
WN_t	u1	1 week		UTC reference week number, to which t_ot is referenced
DEL_t_LS	i1	1 s		Delta time due to leap seconds whenever the effectivity time is not in the past
WN_LSF	u1	1 week		Effectivity time of leap second (week)
DN	u1	1 day		Effectivity time of leap second (day, from 1 to 7)
DEL_t_LSF	i1	1 s		Delta time due to leap seconds whenever the effectivity time is in the past
Padding	u1[]			Padding bytes, see 4.1.5



GPSCNav	Number:	4042
	"OnChange"	interval: block generated at each change of ephemeris, clock or
		group delay parameters

The $\mathtt{GPSCNav}$ block contains the decoded CNAV navigation data for one GPS satellite. The ephemeris and health parameters are extracted from message types (MT) 10 and 11. The clock correction and group delay correction parameters are extracted from MT30.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	Sis time stamp, see 4.1.5
PRN	u1			ID of the GPS satellite of which the parameters are given in this block (see 4.1.9)
Flags	u1			Bit field:
				Bit 0: Alert: Set to 1 if at least one of the message types of which the contents is included in this block had its alert bit (bit 38) set to 1. Set to 0 otherwise. Bit 1: Integrity Status Flag (bit 272 of MT10).
				Bit 2: L2C Phasing (bit 273 of MT10).
				Bits 3-5: Reserved
				Bit 6: L2C used: bit set if at least part of the navigation data has been decoded from L2C. Bit 7: L5 used: bit set if at least part of the navigation data
WN	u2	1 week		has been decoded from L5. Week number (<i>WN_n</i> , 13 bits from MT10)
Health	u1			L1, L2 and L5 signal health (3 bits from MT10). LSB is L5 health.
URA_ED	i1			Elevation-Dependant accuracy index (<i>URA_{ED}</i> , 5 bits from MT10)
t_op	u4	1 s		Data predict time of week (300 $*t_{op}$, 11 bits from MT10/30)
t_oe	u4	1 s		Ephemeris data reference time of week (300 $*t_{oe}$, 11 bits from MT10/11)
A	f8	1 m		Semi-major axis at reference time (ΔA , 26 bits from MT10, plus $A_{\rm ref}$)
A_DOT	f8	1 m / s		Change rate in semi-major axis (Å, 25 bits from MT10)
DELTA_N	f4	1 semi-circle / s		Mean motion difference from computed value at reference time (Δn_0 , 17 bits from MT10)
DELTA_N_DOT	f4	1 semi-circle / s ²		Rate of mean motion difference from computed value (Δn_0 , 23 bits from MT10)
M_0	f8	1 semi-circle		Mean anomaly at reference time (M_{0-n} , 33 bits from MT10)
е	f8			Eccentricity (<i>e_n</i> , 33 bits from MT10)
omega	f8	1 semi-circle		Argument of perigee (ω_n , 33 bits from MT10)
OMEGA_0	f8	1 semi-circle		Reference right ascension angle (Ω_{0-n} , 33 bits from MT11)
OMEGADOT	f8	1 semi-circle / s		Rate of right ascension ($\Delta\dot{\Omega}$, 17 bits from MT11, plus $\dot{\Omega}_{ref}$)
i_0	f8	1 semi-circle		Inclination angle at reference time (i_{0-n} , 33 bits from MT11)
IDOT	f4	1 semi-circle / s		Rate of inclination angle (i_{0-n} , 15 bits from MT11)
C_is	f4	1 rad		Amplitude of the sine harmonic correction term to the angle of inclination (C_{is-n} , 16 bits from MT11)
C_ic	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination (C_{ic-n} , 16 bits from MT11)



C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit radius (C_{rs-n} , 24 bits from MT11)
C_rc	f4	1 m		Amplitude of the cosine harmonic correction term to the orbit radius (C_{rc-n} , 24 bits from MT11)
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude (C_{us-n} , 21 bits from MT11)
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude (C_{uc-n} , 21 bits from MT11)
t_oc	u4	1 s		Clock data reference time (300 $*t_{oc}$, 11 bits from MT30)
URA_NED0	i1			Non-Elevation-Dependant accuracy index (URA_{NED0} , 5 bits from MT30)
URA_NED1	u1			Non-Elevation-Dependant accuracy change index (<i>URA_{NED1}</i> , 3 bits from MT30)
URA_NED2	u1			Non-Elevation-Dependant accuracy change rate index (<i>URA</i> _{NED2} , 3 bits from MT30)
WN_op	u1	1 week		Week number associated with t_op, modulo 256 (WN_{op} , 8 bits from MT30)
a_f2	f4	1 s / s ²		Clock drift rate correction coefficient (a_{f2-n} , 10 bits from MT30)
a_f1	f4	1 s / s		Clock drift correction coefficient (a_{f1-n} , 20 bits from MT30)
a_f0	f8	1 s		Clock bias correction coefficient (a_{f0-n} , 26 bits from MT30)
T_gd	f4	1 s	-2·10 ¹⁰ (6)	Group delay differential (T_{GD} , 13 bits from MT30)
ISC_L1CA	f4	1 s	-2·10 ¹⁰ (6)	Group delay differential L1C/A ($ISC_{L1C/A}$, 13 bits from MT30)
ISC_L2C	f4	1 s	-2·10 ¹⁰ (6)	Group delay differential L2C (<i>ISC_{L2C}</i> , 13 bits from MT30)
ISC_L5I5	f4	1 s	-2·10 ¹⁰ (6)	Group delay differential L5I (<i>ISC</i> _{L5/5} , 13 bits from MT30)
ISC_L5Q5	f4	1 s	-2·10 ¹⁰ (6)	Group delay differential L5Q (<i>ISC</i> _{L5Q5} , 13 bits from MT30)
Padding	u1[]			Padding bytes, see 4.1.5

 $^{^{(6)}}$ $\;$ The Do-Not-Use value is used when the bit string is "1000000000000".





4.2.4 GLONASS Decoded Message Blocks

GLONav	Number:	4004
	"OnChange"	interval: block generated each time a new navigation data set is
		received from a GLONASS satellite

The GLONav block contains the decoded ephemeris data for one GLONASS satellite.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or time stamp, see 4.1.5
SVID	u1			ID of the GLONASS satellite for which ephemeris is provided in this block (see 4.1.9).
FreqNr	u1			Frequency number of the GLONASS satellite for which ephemeris is provided in this block (see 4.1.9).
Х	f8	1000 m		x-component of satellite position in PZ-90
Y	f8	1000 m		y-component of satellite position in PZ-90
Z	f8	1000 m		z-component of satellite position in PZ-90
Dx	f4	1000 m / s		x-component of satellite velocity in PZ-90
Dy	f4	1000 m / s		y-component of satellite velocity in PZ-90
Dz	f4	1000 m / s		z-component of satellite velocity in PZ-90
Ddx	f4	1000 m / s ²		x-component of satellite acceleration in PZ-90
Ddy	f4	1000 m / s ²		y-component of satellite acceleration in PZ-90
Ddz	f4	1000 m / s ²		z-component of satellite acceleration in PZ-90
gamma	f4	1 Hz / Hz		$\gamma_{ m n}({ m t_b})$:relative deviation of predicted carrier frequency
tau	f4	1 s		$ au_{ m n}({ m t_b})$: time correction to GLONASS time
dtau	f4	1 s		$\Delta au_{ m n}$: time difference between L2 and L1 sub-band
t_oe	u4	1 s		reference time-of-week in GPS time frame
WN_toe	u2	1 week		reference week number in GPS time frame (modulo 1024)
P1	u1	1 minute		time interval between adjacent values of t _b
P2	u1			1-bit odd/even flag of $t_{\rm b}$
Е	u1	1 day		age of data
В	u1			3-bit health flag, satellite unhealthy if MSB set
tb	u2	1 minute		time of day (center of validity interval)
М	u1			2-bit GLONASS-M satellite identifier (01, otherwise 00)
P	u1			2-bit mode of computation of time parameters
1	u1			1-bit health flag, 0=healthy, 1=unhealthy
P4	u1			1-bit 'updated' flag of ephemeris data
N_T	u2	1 day		current day number within 4-year interval
F_T	u2	0.01 m		predicted user range accuracy at time t _b
С	u1		255	1-bit health Cn flag from the almanac. This field is set to the last 'Cn' flag received from the almanac. If no 'Cn' flag has been received yet, it is set to its do-not-use value.
Padding	u1[]			Padding bytes, see 4.1.5

Rev 1





GLOAlm	Number:	4005
	"OnChange"	interval: block generated each time a new almanac data set is re-
		ceived from a GLONASS satellite

The ${\tt GLOAlm}$ block contains the decoded navigation data for one GLONASS satellite.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or time stamp, see 1.1.5
SVID	u1			ID of the GLONASS satellite for which almanac is provided in this block (see 4.1.9).
FreqNr	u1			Frequency number of the GLONASS satellite for which almanac is provided in this block (see 4.1.9). This number corresponds to the H^A_n parameter in the GLONASS ICD.
epsilon	f4			$\epsilon_{ m n}^{ m A}$: orbit eccentricity
t_oa	u4	1 s		Reference time-of-week in GPS time frame
Delta_i	f4	1 semi-circle		Δ i $_{ m n}^{ m A}$: correction to inclination
lambda	f4	1 semi-circle		λ_n^A : Longitude of first ascending node
t_ln	f4	1 s		t_{λ}^{A} : time of first ascending node passage
omega	f4	1 semi-circle		$\omega_{ m n}^{ m A}$: argument of perigee
Delta_T	f4	1 s / orbit-period		Δ T $_{n}^{A}$: correction to mean Draconian period
dDelta_T	f4	1 s / orbit-period ²		$\mbox{d}\Delta\mbox{T}_{n}^{A};$ rate of change correction to mean Draconian period
tau	f4	1 s		$ au_n^A$: coarse correction to satellite time
WN_a	u1	1 week		Reference week in GPS time frame (modulo 256)
С	u1			$C_{ m n}{}^{ m A}$: 1-bit general health flag (1 indicates healthy)
N	u2	1 day		N ^A : calendar day number within 4 year period
М	u1			M_n^A : 2-bit GLONASS-M satellite identifier
N_4	u1			N ₄ : 4 year interval number, starting from 1996
Padding	u1[]			Padding bytes, see 4.1.5



GLOTime	Number:	4036
	"OnChange"	interval: block generated at the end of each GLONASS super-
		frame, i.e. every 2.5 minutes.

The ${\tt GLOTime}$ block contains the decoded non-immediate data related to the difference between GLONASS and GPS, UTC and UT1 time scales.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	one stamp, see 4.1.5
SVID	u1			ID of the GLONASS satellite from which the data in this block has been decoded (see 4.1.9).
FreqNr	u1			Frequency number of the GLONASS satellite from which the data in this block has been decoded (see 4.1.9).
N_4	u1			4 year interval number, starting from 1996
KP	u1			notification of leap second
N	u2	1 day		calendar day number within 4 year period
tau_GPS	f4	1 · 10 ⁹ ns		difference with respect to GPS time
tau_c	f8	1 · 10 ⁹ ns		GLONASS time scale correction to UTC(SU)
B1	f4	1 s		difference between UT1 and UTC(SU)
B2	f4	1 s / msd		daily change of B1
Padding	u1[]			Padding bytes, see 4.1.5



4.2.5 Galileo Decoded Message Blocks

GALNav	Number:	4002	
	"OnChange"	interval: output each time a new navigation data batch is dec	oded.

The GalNav block contains the following decoded navigation data for one Galileo satellite:

- orbital elements and clock corrections
- health, Signal-In-Space Accuracy (SISA) indexes and Broadcast Group Delays (BGDs) for each carrier or carrier combinations.

The interpretation of the clock correction parameters (t_oc , a_f0 , a_f1 , a_f2) depends on the value of the Source field:

Source	Message type	Applicable Clock Model
2	I/NAV	(L1,E5b)
16	F/NAV	(L1,E5a)

If the receiver is decoding both the I/NAV and the F/NAV data stream, it will output a <code>GalNav</code> block for the I/NAV stream, containing the (L1, E5b) clock model, and a different <code>GalNav</code> block for the F/NAV stream, containing the (L1, E5a) clock model.

Depending on the message type being decoded, some health, SISA or BGD values may not be available (in that case they are set to their respective Do-Not-Use values). The following health, SISA and BGD values are guaranteed to be available for a given value of the Source field:

Source	Health, SISA and BGD availability
2 (I/NAV)	At least L1-B $_{ m DVS}$, L1-B $_{ m HS}$, E5b $_{ m DVS}$,E5b $_{ m HS}$, SISA_L1E5b and BGD_L1E5b are available
16 (F/NAV)	At least E5a $_{ m DVS}$,E5a $_{ m HS}$, SISA_L1E5a and BGD_L1E5a are available

The IODNav field identifies the issue of data. All orbital elements, clock parameters and SISA values in the block are guaranteed to refer to the same data batch identified by IODNav. The fields ${\tt Health_OSSOL}$, ${\tt BGD_L1E5a}$, ${\tt BGD_L1E5b}$ and ${\tt CNAVenc}$ are not covered by the issue of data, and the block simply contains the latest received value.

Please refer to the Galileo Signal-In-Space ICD for the interpretation and usage of the parameters contained in this SBF block.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	-SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	-515 time stamp, see 4.1.5
SVID	u1			SVID of the Galileo satellite (see 4.1.9)
Source	u1			See table above: this field indicates how to interpret the clock correction parameters.



SQRT_A	f8	1 m ^{1/2}		Square root of the semi-major axis
M_0	f8	1 semi-circle		Mean anomaly at reference time
e	f8			Eccentricity
i_0	f8	1 semi-circle		Inclination angle at reference time
omega	f8	1 semi-circle		Argument of perigee
OMEGA_0	f8	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
IDOT	f4	1 semi-circle / s		Rate of inclination angle
DEL_N	f4	1 semi-circle / s		Mean motion difference from computed value
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude
C_rc	f4	1 m		Amplitude of the cosine harmonic correction term to the orbit radius
C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit radius
C_ic	f4	1 rad		Amplitude of the sine harmonic correction term to the angle of inclination
C_is	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination
t_oe	u4	1 s		Reference time, ephemeris
t_oc	u4	1 s		Reference time, clock. The Source field indicates which clock model t_oc refers to.
a_f2	f4	1 s / s ²		SV clock aging. The Source field indicates which clock model a_f2 refers to.
a_f1	f4	1 s / s		SV clock drift. The <code>Source</code> field indicates which clock model <code>a_f1</code> refers to.
a_f0	f8	1 s		SV clock bias. The Source field indicates which clock model a_f0 refers to.
WNt_oe	u2	1 week		WN associated with t_oe, in GPS time frame, modulo 4096
WNt_oc	u2	1 week		WN associated with t_oc, in GPS time frame, modulo 4096
IODnav	u2			Issue of data, navigation (10 bits)
Health_OSSOL	u2			Bit field indicating the last received Health Status (HS) and Data Validity Status (DVS) of the E5a, E5b and L1-B signals:
				Bit 0: If set, bits 1 to 3 are valid, otherwise they must be ignored. Bit 1: 1-bit L1-B $_{ m DVS}$
				Bits 2-3: 2-bit L1-B _{HS}
				Bit 4: If set, bits 5 to 7 are valid, otherwise they must be ignored. Bit 5: 1-bit $E5b_{\rm DVS}$
				Bits 6-7: 2 -bit E5b $_{ m HS}$
				Bit 8: If set, bits 9 to 11 are valid, otherwise they must be ignored.
				Bit 9: 1-bit E5a _{DVS}
				Bits 10-11: 2-bit E5a _{HS}
				Bits 12-15: Reserved
Health_PRS	u1		055	Reserved
SISA_L1E5a	u1		255	Signal-In-Space Accuracy Index (L1, E5a)
SISA_L1E5b	u1		255	Signal-In-Space Accuracy Index (L1, E5b)
SISA_L1AE6A	u1		255	Reserved
BGD_L1E5a	f4	1 s	$-2 \cdot 10^{10}$	Last received broadcast group delay (L1, E5a)
BGD_L1E5b	f4	1 s	-2·10 ¹⁰	Last received broadcast group delay (L1, E5b)
BGD_L1AE6A	f4	1 s	$-2 \cdot 10^{10}$	Reserved



CNAVenc	u1	255	2-bit C/NAV encryp	otion status:
			Bit 0: Bit set i	f E6B is unencrypted
			Bit 1: Bit set i	f E6C is unencrypted
			Bits 2-7: Reserve	ed
Padding	u1[]		Padding bytes, see	4.1.5



GALAlm	Number:	4003		
	"OnChange"	interval: output each	ach time a new almanac set is received f	or a
		satellite.		

The GalAlm block contains the decoded almanac data for one Galileo satellite.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			·
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	CIS time stamp see 4.1.2
WNc	u2	1 week	65535	SIS time stamp, see 4.1.3
SVID	u1			SVID of the Galileo satellite from which these almanac parameters have been received (see 4.1.9)
Source	u1			See corresponding field in the GalNav block. Source can take the value 18 to indicate that the almanac data contained in this block has been merged from INAV and FNAV pages.
е	f4			Eccentricity
t_oa	u4	1 s		almanac reference time of week
delta_i	f4	1 semi-circle		Inclination angle at reference time, relative to nominal
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
SQRT_A	f4	1 m ^{1/2}		Square root of the semi-major axis, relative to nominal
OMEGA_0	f4	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch
omega	f4	1 semi-circle		Argument of perigee
M_0	f4	1 semi-circle		Mean anomaly at reference time
a_f1	f4	1 s / s		SV clock drift
a_f0	f4	1 s		SV clock bias
WN_a	u1	1 week		2-bit almanac reference week
SVID_A	u1			SVID of the Galileo satellite of which the almanac parameters are provided in this block (see 4.1.9 for the SVID numbering convention).
health	u2			Bit field indicating the health status (HS) of the E5a, E5b, L1-B, L1-A and E6-A signals:
				Bit 0: If set, bits 1 and 2 are valid, otherwise they must be ignored. Bits 1-2: 2-bit L1-B _{HS}
				Bit 3: If set, bits 4 and 5 are valid, otherwise they must be ignored.
				Bits 4-5: 2-bit E5b _{HS}
				Bit 6: If set, bits 7 and 8 are valid, otherwise they must be ignored. Bits 7-8: 2-bit $E5a_{\rm HS}$
				Bit 9: Not applicable
				Bits 10-11: Not applicable
				Bit 12: Not applicable
				Bits 13-14: Not applicable
				Bit 15: Reserved
IODa	u1			4-bit Issue of Data for the almanac.
Padding	u1[]			Padding bytes, see 4.1.5



GALIon	Number:	4030		
	"OnChange"	interval: output each time the ionospheric parameters	are	re-
		ceived from a Galileo satellite.		

The Gallon block contains the decoded ionosphere model parameters of the Galileo system.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	one stamp, see 4.1.5
SVID	u1			SVID of the Galileo satellite from which these parameters have been received (see 4.1.9)
Source	u1			Message type from which the data has been decoded: 2: I/NAV 16: F/NAV
a_i0	f4	1 · 10 ⁻²² W / (m ² Hz)		Effective ionization level, a _{i0}
a_i1	f4	1 · 10 ⁻²² W / (m ² Hz) / deg		Effective ionization level, a_{i1}
a_i2	f4	1 · 10 ⁻²² W / (m ² Hz) / deg ²		Effective ionization level, a_{i2}
StormFlags	u1			Bit field containing the five ionospheric storm flags:
				Bit 0: SF5
				Bit 1: SF4
				Bit 2: SF3
				Bit 3: SF2
				Bit 4: SF1
				Bits 5-7: Reserved
Padding	u1[]			Padding bytes, see 4.1.5



GALUtc	Number:	4031
	"OnChange"	interval: output each time the UTC offset parameters are received
		from a Galileo satellite.

The ${\tt GalUtc}$ block contains the decoded UTC parameter information.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	Job time stamp, see 4.1.5
SVID	u1			SVID of the Galileo satellite from which these parameters have been received (see 4.1.9)
Source	u1			Message type from which the data has been decoded: 2: I/NAV 16: F/NAV
A_1	f4	1 s / s	$-2 \cdot 10^{10}$	first order term of polynomial
A_0	f8	1 s	-2·10 ¹⁰	constant term of polynomial
t_ot	u4	1 s		reference time of week for UTC data
WN_ot	u1	1 week		UTC reference week number, to which t_ot is referenced
DEL_t_LS	i1	1 s		Delta time due to leap seconds whenever the effectivity time is not in the past
WN_LSF	u1	1 week		Effectivity time of leap second (week)
DN	u1	1 day		Effectivity time of leap second (day, from 1 to 7)
DEL_t_LSF	i1	1 s		Delta time due to leap seconds whenever the effectivity time is in the past
Padding	u1[]			Padding bytes, see 4.1.5



GALGstGps	Number:	4032
	"OnChange"	interval: output each time valid GST-GPS offset parameters
		are received from a Galileo satellite.

This block contains the decoded GPS to Galileo System Time offset parameters. This block is only output if these parameters are valid in the navigation page (i.e. if they are not set to "all ones").

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	1313 time stamp, see 4.1.3	
SVID	u1			SVID of the Galileo satellite from which these parameters have been received (see 4.1.9)	
Source	u1			Message type from which the data has been decoded: 2: I/NAV 16: F/NAV	
A_1G	f4	1 · 10 ⁹ ns / s		Rate of change of the offset	
A_0G	f4	1 · 10 ⁹ ns		Constant term of the offset	
t_oG	u4	1 s		Reference time of week	
WN_oG	u1	1 week		6-bit reference week number.	
Padding	u1[]			Padding bytes, see 4.1.5	



GALSARRLM	Number:	4034								
	"OnChange"	interval: generated	each	time	a SA	ιR	RLM	message	is	de-
		coded.								

 $This block contains \ a \ decoded \ Galileo \ search-and-rescue \ (SAR) \ return \ link \ message \ (RLM).$

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1			Block Header, see 4.1.1	
CRC	u2				
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3	
WNc	u2	1 week	65535	or anne scamp, see 4.1.5	
SVID	u1			SVID of the Galileo satellite from which this RLM has been received.	
Source	u1			Message type from which the data has been decoded: 2: I/NAV 16: F/NAV	
RLMLength	u1			Length of the RLM message in bits. RLMLength can be either 80 for a short message or 160 for a long message.	
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software	
RLMBits	u4[<i>N</i>]			Bits in the RLM message, with the first bit being the MSB of RLMBits[0]. N is 3 for a short message (i.e. if RLMLength is 80), and 5 for a long message (i.e. if RLMLength is 160). The 16 unused bits of a short message are set to 0. These bits correspond to the 16 LSBs of RLMBits[2].	
Padding	u1[]			Padding bytes, see 4.1.5	



4.2.6 BeiDou Decoded Message Blocks

BDSNav	Number:	4081	
	"OnChange"	interval: block generated each time a new navigation data set is	l
		received from a BeiDou satellite	l

The ${\tt BDSNav}$ block contains the decoded navigation data for one BeiDou satellite, as received from the D1 or D2 nav message.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			·
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	CIS time stamp see 4.1.2
WNc	u2	1 week	65535	SIS time stamp, see 4.1.3
PRN	u1			ID of the BeiDou satellite of which the ephemeris is given in this block (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
MN	u2	1 week		BeiDou week number as received from the navigation message (from 0 to 8191)
URA	u1			User range accuracy index (4-bit value)
SatH1	u1			1-bit autonomous health
IODC	u1			Age of data, clock (5 bits)
IODE	u1			Age of data, ephemeris (5 bits)
Reserved2	u2			unused, to be ignored by decoding software
T_GD1	f4	1 s		B1l equipment group delay differential
T_GD2	f4	1 s	-2·10 ¹⁰	B2I equipment group delay differential (set to the Do-Not-Use value when unknown)
t_oc	u4	1 s		clock data reference time, in BeiDou system time (lagging GPS time by 14 seconds).
a_f2	f4	1 s / s ²		SV clock aging
a_f1	f4	1 s / s		SV clock drift
a_f0	f4	1 s		SV clock bias
C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit radius
DEL_N	f4	1 semi-circle / s		Mean motion difference from computed value
M_0	f8	1 semi-circle		Mean anomaly at reference time
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude
е	f8			Eccentricity
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude
SQRT_A	f8	1 m ^{1/2}		Square root of the semi-major axis
t_oe	u4	1 s		Reference time ephemeris, in BeiDou system time (lagging GPS time by 14 seconds).
C_ic	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination
OMEGA_0	f8	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch
C_is	f4	1 rad		Amplitude of the sine harmonic correction term to the angle of inclination
i_0	f8	1 semi-circle		Inclination angle at reference time



C_rc	f4	1 m	Amplitude of the cosine harmonic correction term to the orbit radius
omega	f8	1 semi-circle	Argument of perigee
OMEGADOT	f4	1 semi-circle / s	Rate of right ascension
IDOT	f4	1 semi-circle / s	Rate of inclination angle
WNt_oc	u2	1 week	BeiDou week number associated with t_oc, modulo 8192. Note that this value relates to the BeiDou system time.
WNt_oe	u2	1 week	BeiDou week number associated with t_oe, modulo 8192. Note that this values relates to the BeiDou system time.
Padding	u1[]		Padding bytes, see 4.1.5



BDSCNav2	Number:	4252
	"OnChange"	interval: block generated when a new data set is received

The ${\tt BDSCNav2}$ block contains the B-CNAV2 navigation data decoded from the B2a signal of a BeiDou satellite.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			·
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	and time stamp, see 4.1.5
PRNidx	u1			PRN number of the satellite in the BeiDou constellation (1 for C01, 2 for C02, etc). Warning: this is the index within the constellation and not the global PRN number defined in 4.1.9.
Flags	u1			Bit field: Bits 0-1: Satellite type (1: GEO, 2: IGSO, 3: MEO). Bits 2-7: Reserved
t_oe	u4	1 s		Ephemeris reference time of week
A	f8	1 m		Semi-major axis at reference time (ΔA plus A_{ref})
A_DOT	f8	1 m / s		Change rate in semi-major axis (Å)
DELTA_n0	f4	1 semi-circle / s		Mean motion difference from computed value at reference time
DELTA_n0_DOT	f4	1 semi-circle / s ²		Rate of mean motion difference from computed value
M_0	f8	1 semi-circle		Mean anomaly
е	f8			Eccentricity
omega	f8	1 semi-circle		Argument of perigee
OMEGA_0	f8	1 semi-circle		Longitude of ascending node
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
i_0	f8	1 semi-circle		Inclination angle
IDOT	f4	1 semi-circle / s		Rate of inclination angle
C_is	f4	1 rad		Amplitude of the sine harmonic correction term to the angle of inclination
C_ic	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination
C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit radius
C_rc	f4	1 m		Amplitude of the cosine harmonic correction term to the orbit radius
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude
t_oc	u4	1 s		Clock correction parameters reference time
a_2	f4	1 s / s ²		Clock drift rate
a_1	f4	1 s / s		Clock drift
a_0	f8	1 s		Clock bias
t_op	u4	1 s		Time of week for data prediction
SISAI_ocb	u1			Satellite orbit radius and fixed satellite clock bias accuracy index



SISAI_oc12	u1			Bit field:
				Bits 0-2: SISAI_oc2: Satellite clock drift accuracy index
				Bits 3-5: SISAI_oc1: Satellite clock bias accuracy index
				Bits 6-7: Reserved
SISAI_oe	u1			Satellite orbit along-track and cross-track accuracy index
SISMAI	u1			Signal in space monitoring accuracy index
HealthIF	u1			Health and integrity flags from the last message type used in this SBF block:
				Bit 0: Accuracy integrity flag $(AIF_{(B1C)})$
				Bit 1: Signal integrity flag $(SIF_{(B1C)})$
				Bit 2: Data integrity flag ($DIF_{(B1C)}$)
				Bit 3: Accuracy integrity flag ($AIF_{(B2a)}$)
				Bit 4: Signal integrity flag (SIF _(B2a))
				Bit 5: Data integrity flag (<i>DIF</i> _(B2a))
				Bits 6-7: Satellite health status (0 if healthy)
IODE	u1			Issue Of Data Ephemeris
IODC	u2			Issue Of Data Clock
ISC_B2ad	f4	1 s	-2·10 ¹⁰	Group delay differential between the B2a data and pilot components
T_GDB2ap	f4	1 s	$-2 \cdot 10^{10}$	Group delay differential of the B2a pilot component
T_GDB1Cp	f4	1 s	$-2 \cdot 10^{10}$	Group delay differential of the B1C pilot component
Padding	u1[]			Padding bytes, see 4.1.5



BDSAlm	Number:	4119
	"OnChange"	interval: block generated each time a new almanac data set is re-
		ceived from a BeiDou satellite

The BDSAlm block contains the decoded almanac data for one BeiDou satellite.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	ors time stamp, see 4.1.5
PRN	u1			ID of the BeiDou satellite of which the almanac is given in this block (see 4.1.9)
WN_a	u1	1 week		Almanac week number
t_oa	u4	1 s		Almanac reference time
SQRT_A	f4	1 m ^{1/2}		Square root of the semi-major axis
е	f4			Eccentricity
omega	f4	1 semi-circle		Argument of perigee
M_0	f4	1 semi-circle		Mean anomaly at reference time
OMEGA_0	f4	1 semi-circle		Longitude of ascending node of orbital plane computed according to reference time
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
delta_i	f4	1 semi-circle		Correction of orbit reference inclination at reference time
a_f0	f4	1 s		Satellite clock bias
a_f1	f4	1 s / s		Satellite clock drift
Health	u2			Satellite health information (9 bits)
Reserved	u1[2]			Reserved for future use, to be ignored by decoding software
Padding	u1[]			Padding bytes, see 4.1.5



BDSIon	Number:	4120		
	"OnChange"	interval: output each time the ionospheric parameters	are	re-
		ceived from a BeiDou satellite		

The ${\tt BDSIon}$ block contains the BeiDou ionosphere data (the Klobuchar coefficients), as received from the D1 or D2 nav message.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or time stamp, see 4.1.5
PRN	u1			ID of the BeiDou satellite from which the coefficients have been received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
alpha_0	f4	1 s		vertical delay coefficient 0
alpha_1	f4	1 s / semi-circle		vertical delay coefficient 1
alpha_2	f4	1 s / semi-circle ²		vertical delay coefficient 2
alpha_3	f4	1 s / semi-circle ³		vertical delay coefficient 3
beta_0	f4	1 s		model period coefficient 0
beta_1	f4	1 s / semi-circle		model period coefficient 1
beta_2	f4	1 s / semi-circle ²		model period coefficient 2
beta_3	f4	1 s / semi-circle ³		model period coefficient 3
Padding	u1[]			Padding bytes, see 4.1.5



BDSUtc	Number:	4121
	"OnChange"	interval: output each time the UTC offset parameters are received
		from a BeiDou satellite

The BDSUtc block contains the BeiDou UTC data, as received from the D1 or D2 nav message.

Note that BDT (BeiDou time) started on January 1st, 2006 (GPS week 1356). Therefore the delta time between BDT and UTC due to leap seconds is 14 less than the value in ${\tt GPSUtc.}$

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	1313 time stamp, see 4.1.3
PRN	u1			ID of the BeiDou satellite from which the coefficients have been received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
A_1	f4	1 s / s		first order term of polynomial
A_0	f8	1 s		constant term of polynomial
DEL_t_LS	i1	1 s		Delta time due to leap seconds whenever the effectivity time is not in the past
WN_LSF	u1	1 week		Effectivity time of leap second (week)
DN	u1	1 day		Effectivity time of leap second (day, from 0 to 6)
DEL_t_LSF	i1	1 s		Delta time due to leap seconds whenever the effectivity time is in the past
Padding	u1[]			Padding bytes, see 4.1.5



4.2.7 QZSS Decoded Message Blocks

QZSNav	Number:	4095	
	"OnChange"	interval: block generated each time a new navigation dat	a set is
		received from a QZSS satellite	

The QZSNav block contains the decoded navigation data for one QZSS satellite. The data is decoded from the navigation message transmitted by the L1C/A or L1C/B signal. Refer to the QZSS ICD for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			·
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	1515 time stamp, see 4.1.5
PRN	u1			ID of the QZSS satellite of which the ephemeris is given in this block (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
WN	u2	1 week	65535	Week number (10 bits from subframe 1, word 3)
CAorPonL2	u1			Code(s) on L2 channel (2 bits from subframe 1, word 3). Always 2 for QZSS satellites.
URA	u1			User Range accuracy index (4 bits from subframe 1 word 3)
health	u1			6-bit health from subframe 1, word 3 (6 bits from subframe 1, word 3)
L2DataFlag	u1			Data flag for L2 P-code (1 bit from subframe 1, word 4). Always 1 for QZSS satellites.
IODC	u2			lssue of data, clock (10 bits from subframe 1)
IODE2	u1			Issue of data, ephemeris (8 bits from subframe 2)
IODE3	u1			Issue of data, ephemeris (8 bits from subframe 3)
FitIntFlg	u1			Curve Fit Interval, (1 bit from subframe 2, word 10)
Reserved2	u1			unused, to be ignored by decoding software
T_gd	f4	1 s	$-2 \cdot 10^{10}$	Estimated group delay differential
t_oc	u4	1 s		clock data reference time
a_f2	f4	1 s / s ²		SV clock aging
a_f1	f4	1 s / s		SV clock drift
a_f0	f4	1 s		SV clock bias
C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit radius
DEL_N	f4	1 semi-circle / s		Mean motion difference from computed value
M_0	f8	1 semi-circle		Mean anomaly at reference time
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude
е	f8			Eccentricity
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude
SQRT_A	f8	1 m ^{1/2}		Square root of the semi-major axis
t_oe	u4	1 s		Reference time ephemeris
C_ic	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination
OMEGA_0	f8	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch



C_is	f4	1 rad	Amplitude of the sine harmonic correction term to the angle of inclination
i_0	f8	1 semi-circle	Inclination angle at reference time
C_rc	f4	1 m	Amplitude of the cosine harmonic correction term to the orbit radius
omega	f8	1 semi-circle	Argument of perigee
OMEGADOT	f4	1 semi-circle / s	Rate of right ascension
IDOT	f4	1 semi-circle / s	Rate of inclination angle
WNt_oc	u2	1 week	WN associated with t_oc, modulo 1024
WNt_oe	u2	1 week	WN associated with t_oe, modulo 1024
Padding	u1[]		Padding bytes, see 4.1.5



QZSAlm	Number:	4116
	"OnChange"	interval: block generated each time a new almanac data set is re-
		ceived from a QZSS satellite

The QZSAlm block contains the decoded almanac data for one QZSS satellite. These data are conveyed in subframes 4 and 5 of the satellite navigation message. Refer to QZSS ICD for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	Sis time stamp, see 1.1.5
PRN	u1			ID of the QZSS satellite of which the almanac is given in this block (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
е	f4			Difference from reference eccentricity
t_oa	u4	1 s		almanac reference time of week
delta_i	f4	1 semi-circle		Difference from reference angle of inclination
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
SQRT_A	f4	1 m ^{1/2}		Square root of the semi-major axis
OMEGA_0	f4	1 semi-circle		Longitude of ascending node of orbit plane at weekly epoch
omega	f4	1 semi-circle		Argument of perigee
M_0	f4	1 semi-circle		Mean anomaly at reference time
a_f1	f4	1 s / s		SV clock drift
a_f0	f4	1 s		SV clock bias
WN_a	u1	1 week		Almanac reference week, to which t_oa is referenced
Reserved2	u1			Reserved for future use, to be ignored by decoding software
health8	u1			health on 8 bits from the almanac page
health6	u1			health summary on 6 bits (from subframe 4, page 25 and subframe 5 page 25)
Padding	u1[]			Padding bytes, see 4.1.5



4.2.8 NavIC/IRNSS Decoded Message Blocks

NavICLNav	Number:	4254
	"OnChange"	interval: block generated each time a new navigation data set
		is received from a NavIC satellite

The ${\tt NavICLNav}$ block contains the decoded LNAV navigation data for one NavIC/IRNSS satellite.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	CIC time stamp see 4.1.2
WNc	u2	1 week	65535	SIS time stamp, see 4.1.3
PRNidx	u1			PRN number of the satellite in the NavIC/IRNSS constellation (1 for I01, 2 for I02, etc). Warning: this is the index within the constellation and not the global PRN number defined in 4.1.9.
IODEC	u1			Issue of data, ephemeris and clock
t_oe	u4	1 s		Ephemeris reference time of week
SQRT_A	f8	1 m ^{1/2}		Square root of the semi-major axis
DELTA_N	f4	1 semi-circle / s		Mean motion difference from computed value at reference time
M_0	f8	1 semi-circle		Mean anomaly
e	f8			Eccentricity
omega	f8	1 semi-circle		Argument of perigee
OMEGA_0	f8	1 semi-circle		Longitude of ascending node
OMEGADOT	f4	1 semi-circle / s		Rate of right ascension
i_0	f8	1 semi-circle		Inclination angle
IDOT	f4	1 semi-circle / s		Rate of inclination angle
C_is	f4	1 rad		Amplitude of the sine harmonic correction term to the angle of inclination
C_ic	f4	1 rad		Amplitude of the cosine harmonic correction term to the angle of inclination
C_rs	f4	1 m		Amplitude of the sine harmonic correction term to the orbit radius
C_rc	f4	1 m		Amplitude of the cosine harmonic correction term to the orbit radius
C_us	f4	1 rad		Amplitude of the sine harmonic correction term to the argument of latitude
C_uc	f4	1 rad		Amplitude of the cosine harmonic correction term to the argument of latitude
t_oc	u4	1 s		Clock correction parameters reference time
a_f0	f4	1 s		Clock bias
a_f1	f4	1 s / s		Clock drift
a_f2	f4	1 s / s ²		Clock drift rate
T_GD	f4	1 s		Total group delay between L5-SPS and S-SPS signals
Flags	u1			Health, Alert and AutoNav flags:
				Bit 0: S-SPS health flag (0 if healthy)
				Bit 1: L5-SPS health flag (0 if healthy)
				Bit 2: Current value of the Alert flag
				Bit 3: Current value of the AutoNav flag
				Bits 4-7: Reserved
URA	u1			User Range accuracy index
Padding	u1[]			Padding bytes, see 4.1.5
	1	l	l	<u> </u>



4.2.9 SBAS L1 Decoded Message Blocks

GEOMT00	Number:	5925
	"OnChange"	interval: block generated each time an empty MT00 is received
		from an SBAS satellite on the L1 signal

This block is sent to indicate that an empty SBAS message type 0 has been received.

Depending on the SBAS operational mode, message type 0 can contain the contents of message type 2. Upon reception of a message type 0, the receiver checks whether the message is empty (it contains only 0's) or whether it contains the message type 2 contents. In the former case, a GEOMT00 block will be generated. In the latter case, a GEOFastCorr block will be generated. Refer to section A.4.4.1 of the DO 229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	ois time stamp, see 4.1.5
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
Padding	u1[]			Padding bytes, see 4.1.5



GEOPRNMask	Number:	5926
	"OnChange"	interval: block generated each time MT01 is received from
		an SBAS satellite

This block contains the decoded PRN mask transmitted in SBAS message type 1. Refer to section A.4.4.2 of the DO 229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	and time stamp, see 4.1.5
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
IODP	u1			Issue of data - PRN.
NbrPRNs	u1			Number of PRNs designated in the mask.
PRNMask	u1[NbrPRNs]			List of the PRNs in the PRN mask. $ PRNMask \cite{Mask} Mas$
Padding	u1[]			Padding bytes, see 4.1.5



GEOFastCorr	Number:	5927
	"OnChange"	interval: block generated each time MT02, MT03, MT04,
		MT05, MT24 and possibly MT00 is received from
		an SBAS satellite

This block contains the decoded fast corrections transmitted in the SBAS message types 2, 3, 4, 5, 24 and possibly 0 if the type 0 message contains the type 2 contents. Refer to section A.4.4.3 and A.4.4.8 of the DO 229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description		
Sync1	c1					
Sync2	c1					
CRC	u2			Block Header, see 4.1.1		
ID	u2					
Length	u2	1 byte				
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3		
WNc	u2	1 week	65535	515 time stamp, see 4.1.5		
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)		
MT	u1			Message type from which these fast corrections come, either 0, 2, 3, 4, 5 or 24.		
IODP	u1			Issue of data - PRN.		
IODF	u1			Issue of data - fast corrections.		
N	u1			Number of fast correction sets in this message. This is the number of FastCorr sub-blocks. N depends on the message type as follows. Message type MT00, MT02, MT03, MT04 MT05 12 MT24 6		
SBLength	u1			Length of the FastCorr sub-blocks in bytes		
FastCorr				A succession of N FastCorr sub-blocks, see definition below		
Padding	u1[]			Padding bytes, see 4.1.5		

FastCorr sub-block definition:

Parameter	Туре	Units	Description			
PRNMaskNo	u1		Sequence number in the PRN mask. This field may be set to zero. In that case, all following fields in this sub-block must be discarded.			
UDREI	u1		ser Differential Range Error Indicator for the PRN at index PRNMaskNo.			
Reserved	u1[2]		eserved for future use, to be ignored by decoding software			
PRC	f4	1 m	seudorange correction for the PRN at index PRNMaskNo.			
Padding	u1[]		adding bytes, see 4.1.5			



GEOIntegrity	Number:	5928				
	"OnChange"	interval: block generated	each tir	ne MT06	is	received
		from an SBAS sat	ellite			

This block contains the decoded integrity information transmitted in SBAS message type 6. Refer to section A.4.4.4 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	and time stamp, see 4.1.5
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
IODF	u1[4]			Issue of data - fast corrections for MT02, MT03, MT04 and MT05.
UDREI	u1[51]			User Differential Range Error Indicator for each of the 51 slots in the PRN mask.
Padding	u1[]			Padding bytes, see 4.1.5



GEOFastCorrDegr	Number:	5929
	"OnChange"	interval: block generated each time MT07 is re-
		ceived from an SBAS satellite

This block contains the decoded fast correction degradation factors transmitted in SBAS message type 7. Refer to section A.4.4.5 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week		Jos time stamp, see 4.1.5
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
IODP	u1			Issue of data - PRN.
t_lat	u1	1 s		System latency.
ai	u1[51]			Degradation factor indicator (from 0 to 15) for each of the 51 slots in the PRN mask.
Padding	u1[]			Padding bytes, see 4.1.5



GEONav	Number:	5896
	"OnChange"	interval: block generated each time MT09 is received from an SBAS
		satellite

This block contains the decoded navigation data transmitted in SBAS message type 9. Refer to section A.4.4.11 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	с1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	 SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or time stamp, see 1.1.5
PRN	u1			ID of the SBAS satellite of which the navigation data is provided here (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
IODN	u2			lssue of data - navigation (DO 229-B) Spare (DO 229-C)
URA	u2			Accuracy exponent
t0	u4	1 s		Time of applicability (time-of-day)
Xg	f8	1 m		X position at time-of-day t 0
Yg	f8	1 m		Y position at time-of-day t 0
Zg	f8	1 m		Z position at time-of-day t0
Xgd	f8	1 m / s		X velocity at time-of-day t 0
Ygd	f8	1 m / s		Y velocity at time-of-day t0
Zgd	f8	1 m / s		Z velocity at time-of-day t 0
Xgdd	f8	1 m / s ²		X acceleration at time-of-day t 0
Ygdd	f8	1 m / s ²		Y acceleration at time-of-day t 0
Zgdd	f8	1 m / s ²		Z acceleration at time-of-day t 0
aGf0	f4	1 s		Time offset with respect to SBAS network time
aGf1	f4	1 s / s		Time drift with respect to SBAS network time
Padding	u1[]			Padding bytes, see 4.1.5



GEODegrFactors	Number:	5930						
	"OnChange"	interval: block	generated	each	time	MT10	is	re-
		ceived	from an SE	BAS sa	tellite			

This block contains the decoded degradation factors transmitted in SBAS message type 10. Refer to section A.4.5 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or anno stamp, see time
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
Brrc	f8	1 m		A parameter associated with the relative estimation noise and round-off error.
Cltc_lsb	f8	1 m		Maximum round-off error due to the LSB resolution of the orbit and clock information.
Cltc_v1	f8	1 m / s		Velocity error bound on the maximum range rate difference of missed messages due to clock and orbit rate differences.
Iltc_v1	u4	1 s		Update interval for long term corrections when the velocity code is 1.
Cltc_v0	f8	1 m		Bound on the update delta between successive long term corrections.
Iltc_v0	u4	1 s		Minimum update interval for long term messages when the velocity code is 0.
Cgeo_lsb	f8	1 m		Maximum round-off error due to the LSB resolution of the orbit and clock information.
Cgeo_v	f8	1 m / s		Velocity error bound on the maximum range rate difference of missed messages due to clock and orbit rate differences.
Igeo	u4	1 s		Update interval for GEO navigation messages.
Cer	f4	1 m		A degradation parameter.
Ciono_step	f8	1 m		Bound on the difference between successive ionospheric grid delay values.
Iiono	u4	1 s		Minimum update interval for ionospheric correction messages.
Ciono_ramp	f8	1 m / s		Rate of change of the ionospheric corrections.
RSSudre	u1			Root-sum-square flag (UDRE)
RSSiono	u1			Root-sum-square flag (IONO)
Reserved2	u1[2]			Reserved for future use, to be ignored by decoding software
Ccovariance	f8			A parameter used to compensate for the errors introduced by quantization (introduced in DO 229-C). To be multiplied by the SF parameter from the GEOClockEphCovMatrix block.
Padding	u1[]			Padding bytes, see 4.1.5



GEONetworkTime	Number:	5918						
	"OnChange"	interval: block	generated	each	time	MT12	is	re-
		ceived	from an SE	BAS sat	tellite			

This block contains the decoded network time offset parameters transmitted in SBAS message type 12. Refer to section A.4.4.15 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	515 time stamp, see 4.1.5
PRN	u1			ID of the SBAS satellite from which this Network Time data was received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
A_1	f4	1 s / s		first order term of polynomial
A_0	f8	1 s		constant term of polynomial
t_ot	u4	1 s		reference time for UTC data (time of week)
WN_t	u1	1 week		UTC reference week number, to which t_ot is referenced
DEL_t_LS	i1	1 s		Delta time due to leap seconds whenever the effectivity time is not in the past
WN_LSF	u1	1 week		Effectivity time of leap second (week)
DN	u1	1 day		Effectivity time of leap second (day)
DEL_t_LSF	i1	1 s		Delta time due to leap seconds whenever the effectivity time is in the past
UTC_std	u1			UTC Standard Identifier
GPS_WN	u2	1 week		GPS week number (modulo 1024)
GPS_TOW	u4	1 s		GPS time-of-week
GlonassID	u1			Glonass Indicator
Padding	u1[]			Padding bytes, see 4.1.5



GEOAlm	Number:	5897
	"OnChange"	interval: block generated each time MT17 is received from an SBAS
		satellite

This block contains the decoded almanac data for one SBAS satellite, as transmitted in SBAS message type 17. A different GEOAlm block is generated for each of the up to three almanac data sets in MT17. Refer to section A.4.4.12 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	 SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or arms scamp, see 4.1.5
PRN	u1			ID of the SBAS satellite of which the almanac is provided here (see 4.1.9)
Reserved0	u1			Reserved for future use, to be ignored by decoding software
DataID	u1			Data ID
Reserved1	u1			Reserved for future use, to be ignored by decoding software
Health	u2			Health bits
t_oa	u4	1 s		Time of applicability with the day ambiguity resolved. This is the time in GPS seconds from Jan 6th, 1980.
Xg	f8	1 m		X position at t_oa
Yg	f8	1 m		Y position at t_oa
Zg	f8	1 m		Z position at t_oa
Xgd	f8	1 m / s		X velocity at t_oa
Ygd	f8	1 m / s		Y velocity at t_oa
Zgd	f8	1 m / s		Z velocity at t_oa
Padding	u1[]			Padding bytes, see 4.1.5



GEOIGPMask	Number:	5931
	"OnChange"	interval: block generated each time MT18 is received from
		an SBAS satellite

This block contains the decoded ionospheric grid point mask transmitted in SBAS message type 18. Refer to section A.4.4.9 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	-313 time stamp, see 4.1.3
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
NbrBands	u1			Number of bands being broadcast.
BandNbr	u1			Band number.
IODI	u1			Issue of data - ionosphere.
NbrIGPs	u1			Number of ionospheric grid points (IGP) designated in the mask.
IGPMask	u1[NbrlGPs]			List of the IGPs in the IGP mask. $ \label{eq:IGPMask} \begin{subarray}{l} IGPMask [0] is the first IGP designated in the IGP mask (from 1 to 201), \\ IGPMask [1] is the 2^{nd} IGP designated in the IGP mask, etc $
Padding	u1[]			Padding bytes, see 4.1.5



GEOLongTermCorr	Number:	5932
	"OnChange"	interval: block generated each time MT24 or MT25
		is received from an SBAS satellite

This block contains the decoded long term corrections transmitted in SBAS message types 24 and 25. Refer to section A.4.4.7 and A.4.4.8 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description			
Sync1	c1						
Sync2	c1						
CRC	u2			Block Header, see 4.1.1			
ID	u2						
Length	u2	1 byte					
TOW	u4	0.001 s	4294967295	SIS time stamp see 4.1.2			
WNc	u2	1 week	65535	–SIS time stamp, see 4.1.3			
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)			
N	u1			Number of long-term corrections in this message. This is the number of LTCorr sub-blocks. $\mathbb N$ can be 0, 1, 2, 3 or 4.			
SBLength	u1	1 byte		Length of the LTCorr sub-blocks in bytes			
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software			
LTCorr				A succession of N LTCorr sub-blocks, see definition below			
Padding	u1[]			Padding bytes, see 4.1.5			

LTCorr sub-block definition:

Parameter	Туре	Units	Description	
VelocityCode	u1		Velocity code (0 or 1)	
PRNMaskNo	u1		Sequence in the PRN mask, from 1 to 51. Note that if the PRN mask No. from the original message is 0, the corresponding long term corrections are ignored, and hence not included in the GEOLONGTermCorr block.	
IODP	u1		Issue of data - PRN.	
IODE	u1		lssue of data - ephemeris.	
dx	f4	1 m	Satellite position offset (x).	
dy	f4	1 m	Satellite position offset (y).	
dz	f4	1 m	Satellite position offset (z).	
dxRate	f4	1 m / s	Satellite velocity offset (x), or 0.0 if VelocityCode is 0.	
dyRate	f4	1 m / s	Satellite velocity offset (y), or 0.0 if VelocityCode is 0.	
dzRate	f4	1 m / s	Satellite velocity offset (z), or 0.0 if VelocityCode is 0.	
da_f0	f4	1 s	Satellite clock offset.	
da_f1	f4	1 s / s	Satellite drift correction, or 0.0 if VelocityCode is 0.	
t_oe	u4	1 s	Time-of-day of applicability, or 0 if VelocityCode is 0.	
Padding	u1[]		Padding bytes, see 4.1.5	



GEOIonoDelay	Number:	5933
	"OnChange"	interval: block generated each time MT26 is received
		from an SBAS satellite

This block contains the decoded ionospheric delays transmitted in SBAS message type 26. Refer to section A.4.4.10 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	1313 time stamp, see 4.1.3
PRN	u1			ID of the SBAS satellite from which the message has been received (see 4.1.9)
BandNbr	u1			Band number
IODI	u1			Issue of data - ionosphere.
N	u1			Number of ionospheric delay corrections in this message. This is the number of ${\tt IDC}$ sub-blocks. ${\tt N}$ is always 15.
SBLength	u1	1 byte		Length of the IDC sub-blocks in bytes.
Reserved	u1			Reserved for future use, to be ignored by decoding software
IDC				A succession of N IDC sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

IDC sub-block definition:

Parameter	Туре	Units	Description
IGPMaskNo	u1		Sequence number in the IGP mask (see <code>GEOIGPMask</code> block), from 1 to 201.
GIVEI	u1		Grid lonospheric Vertical Error Indicator, from 0 to 15
Reserved	u1[2]		Reserved for future use, to be ignored by decoding software
VerticalDelay	f4	1 m	IGP vertical delay estimate.
Padding	u1[]		Padding bytes, see 4.1.5



GEOServiceLevel	Number:	5917
	"OnChange"	interval: block generated each time MT27 is received from an SBAS satellite

This block contains a decoded service level message for a geostationary SBAS satellite as sent in message type 27. Refer to section A.4.4.13 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	or time stamp, see 4.1.5
PRN	u1			ID of the SBAS satellite from which this service level message was received (see 4.1.9)
Reserved	u1			Reserved for future use, to be ignored by decoding software
IODS	u1			Issue of Data Service level, ranging from 0 to 7
nrMessages	u1			Number of service messages (MT27), from 1 to 8
MessageNR	u1			Service message number, from 1 to 8
PriorityCode	u1			Priority Code, from 0 to 3
dUDREI_In	u1			δ UDRE Indicator for users inside the service region, from 0 to 15
dUDREI_Out	u1			δ UDRE Indicator for users outside the service region, from 0 to 15
N	u1			Number of Regions in this message. This is the number of ServiceRegion sub-blocks. Ranging from 0 to 7
SBLength	u1	1 byte		Length of the ServiceRegion sub-blocks in bytes
Regions				A succession of N ServiceRegion sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

ServiceRegion sub-block definition:

Parameter	Туре	Units	Description	
Latitude1	i1	1 degree	Coordinate 1 latitude, from -90 to +90	
Latitude2	i1	1 degree	Coordinate 2 latitude, from -90 to +90	
Longitude1	i2	1 degree	Coordinate 1 longitude, from -180 to +180	
Longitude2	i2	1 degree	Coordinate 2 longitude, from -180 to +180	
RegionShape	u1		Region Shape: 0=triangular, 1=square	
Padding	u1[]		Padding bytes, see 4.1.5	



GEOClockEphCovMatrix	Number:	5934
	"OnChange"	interval: block generated each time MT28
		is received from an SBAS satel-
		lite

This block contains the decoded clock-ephemeris covariance Cholesky factor matrix transmitted in SBAS message type 28. Refer to section A.4.4.16 of the DO-229 standard for further details.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	SIS time stamp, see 4.1.3
WNc	u2	1 week	65535	313 time stamp, see 4.1.3
PRN	u1			Satellite ID, see 4.1.9
IODP	u1			Issue of data - PRN.
N	u1			Number of covariance matrices in this message. This is the number of $CovMatrix$ sub-blocks. N can be 1 or 2.
SBLength	u1	1 byte		Length of the CovMatrix sub-blocks in bytes
Reserved	u1[2]			Reserved for future use, to be ignored by decoding software
CovMatrix				A succession of N CovMatrix sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

CovMatrix sub-block definition:

Parameter	Туре	Units	Description
PRNMaskNo	u1		Sequence number in the PRN mask, from 1 to 51. Note that if the PRN mask No. from the original message is 0, the corresponding matrix is ignored, and hence not included in the GEOClockEphCovMatrix block.
Reserved	u1[2]		Reserved for future use, to be ignored by decoding software
ScaleExp	u1		Scale exponent; scale factor (= $2^{\text{(scale exponent - 5)}}$)
E11	u2		E _{1,1}
E22	u2		E _{2,2}
E33	u2		E _{3,3}
E44	u2		E _{4,4}
E12	i2		E _{1,2}
E13	i2		E _{1,3}
E14	i2		E _{1,4}
E23	i2		E _{2,3}
E24	i2		E _{2,4}
E34	i2		E _{3,4}
Padding	u1[]		Padding bytes, see 4.1.5





4.2.10 GNSS Position, Velocity and Time Blocks

PVTCartesian	Number:	4006
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the GNSS-based position, velocity and time (PVT) solution at the time specified in the ${\tt TOW}$ and ${\tt WNC}$ fields. The time of applicability is specified in the receiver time frame.

The computed position (x, y, z) and velocity (v_x, v_y, v_z) are reported in a Cartesian coordinate system using the datum indicated in the Datum field. The position is that of the marker. The ARP-to-marker offset is set through the command **setAntennaOffset**.

The PVT solution is also available in ellipsoidal form in the PVTGeodetic block.

The variance-covariance information associated with the reported PVT solution can be found in the PosCovCartesian and VelCovCartesian blocks.

If no PVT solution is available, the Error field indicates the cause of the unavailability and all fields after the Error field are set to their respective Do-Not-Use values.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	т.
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and
				Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
X	f8	1 m	-2·10 ¹⁰	X coordinate in coordinate frame specified by Datum
Y	f8	1 m	-2·10 ¹⁰	Y coordinate in coordinate frame specified by Datum
Z	f8	1 m	$-2 \cdot 10^{10}$	Z coordinate in coordinate frame specified by Datum
Undulation	f4	1 m	$-2 \cdot 10^{10}$	Geoid undulation. See the setGeoidUndulation command.
Vx	f4	1 m / s	$-2 \cdot 10^{10}$	Velocity in the X direction
Vy	f4	1 m / s	$-2 \cdot 10^{10}$	Velocity in the Y direction
Vz	f4	1 m / s	$-2 \cdot 10^{10}$	Velocity in the Z direction
COG	f4	1 degree		Course over ground: this is defined as the angle of the vehicle with
				respect to the local level North, ranging from 0 to 360, and increasing towards east. Set to the Do-Not-Use value when the speed is lower than 0.1m/s.
RxClkBias	f8	1 ms	-2·10 ¹⁰	Receiver clock bias relative to the GNSS system time reported in the $\texttt{TimeSystem}$ field. Positive when the receiver time is ahead of the system time. To transfer the receiver time to the system time, use: $t_{GPS/GST} = t_{rx} - \texttt{RxClkBias}$
RxClkDrift	f4	1 ppm	−2·10 ¹⁰	Receiver clock drift relative to the GNSS system time (relative frequency error). Positive when the receiver clock runs faster than the system time.



TimeSystem	u1	255	Time system of which the offset is provided in this sub-block: 0: GPS time 1: Galileo time 3: GLONASS time 4: BeiDou time 5: QZSS time
Datum	u1	255	This field defines in which datum the coordinates are expressed: 0: WGS84/ITRS 19: Datum equal to that used by the DGNSS/RTK base station 30: ETRS89 (ETRF2000 realization) 31: NAD83(2011), North American Datum (2011) 32: NAD83(PA11), North American Datum, Pacific plate (2011) 33: NAD83(MA11), North American Datum, Marianas plate (2011) 34: GDA94(2010), Geocentric Datum of Australia (2010) 35: GDA2020, Geocentric Datum of Australia 2020 36: JGD2011, Japanese Geodetic Datum 2011 250: First user-defined datum 251: Second user-defined datum
NrSV	u1	255	Total number of satellites used in the PVT computation.
WACorrInfo	u1	0	Bit field providing information about which wide area corrections have been applied:
			Bit 0: set if orbit and satellite clock correction information is used
			Bit 1: set if range correction information is used
			Bit 2: set if ionospheric information is used
			Bit 3: set if orbit accuracy information is used (UERE/SISA)
			Bit 4: set if DO229 Precision Approach mode is active
			Bits 5-7: Reserved
ReferenceID	u2	65535	This field indicates the reference ID of the differential information used. In case of DGPS or RTK operation, this field is to be interpreted as the base station identifier. In SBAS operation, this field is to be interpreted as the PRN of the geostationary satellite used (from 120 to 158). If multiple base stations or multiple geostationary satellites are used the value is set to 65534.
MeanCorrAge	u2 C	0.01 s 65535	In case of DGPS or RTK, this field is the mean age of the differential corrections. In case of SBAS operation, this field is the mean age of the 'fast corrections' provided by the SBAS satellites. In case of PPP, this is the age of the last received clock or orbit correction message.
SignalInfo	u4	0	Bit field indicating the type of GNSS signals having been used in the PVT computations. If a bit i is set, the signal type having index i has been used. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.
AlertFlag	u1	0	Bit field indicating integrity related information:
			Bits 0-1: RAIM integrity flag: 0: RAIM not active (integrity not monitored) 1: RAIM integrity test successful 2: RAIM integrity test failed 3: Reserved Bit 2: set if integrity has failed as per Galileo HPCA (HMI Probability
			Computation Algorithm) Bit 3: set if Galileo ionospheric storm flag is active
	1 1		
			Bit 4: Reserved Bits 5-7: Reserved

Rev 1





PPPInfo u2 Bit field containing PPP-related information: Bits 0-11: Age of the last seed, in seconds. The age is clipped to 4091s. 1 s This field must be ignored when the seed type is 0 (see bits 13-15 below). Bit 12: Reserved Rev 1 Bits 13-15: Type of last seed: Not seeded or not in PPP positioning mode Manual seed 1: Seeded from DGPS 2: Seeded from RTKFixed 0.0001 s 65535 Latency u2 Time elapsed between the time of applicability of the position fix and the generation of this SBF block by the receiver. This time includes the receiver processing time, but not the communication latency. 65535 0.01 m 2DRMS horizontal accuracy: twice the root-mean-square of the hor-HAccuracy u2 izontal distance error. The horizontal distance between the true position and the computed position is expected to be lower than HAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m 65535 VAccuracy u2 0.01 m 2-sigma vertical accuracy. The vertical distance between the true position and the computed position is expected to be lower than VAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m. u1 Misc Bit field containing miscellaneous flags: In DGNSS or RTK mode, set if the baseline points to the base Bit 0: station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the rover, unset if not or unknown. Bit 2: Proprietary. Bit 3: Proprietary. Bits 4-5: Proprietary. Bits 6-7: Flag indicating whether the marker position reported in this block is also the ARP position (i.e. whether the ARP-tomarker offset provided with the setAntennaOffset command is zero or not) 0: Unknown The ARP-to-marker offset is zero 1: 2: The ARP-to-marker offset is not zero

Padding bytes, see 4.1.5

Rev 2

Padding

u1[..]



PVTGeodetic	Number:	4007
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the GNSS-based position, velocity and time (PVT) solution at the time specified in the ${\tt TOW}$ and ${\tt WNC}$ fields. The time of applicability is specified in the receiver time frame.

The computed position (ϕ, λ, h) and velocity (v_n, v_e, v_u) are reported in an ellipsoidal coordinate system using the datum indicated in the Datum field. The velocity vector is expressed relative to the local-level Cartesian coordinate frame with north-, east-, up-unit vectors. The position is that of the marker. The ARP-to-marker offset is set through the command **setAntennaOffset**.

The PVT solution is also available in Cartesian form in the PVTCartesian block.

The variance-covariance information associated with the reported PVT solution can be found in the PosCovGeodetic and VelCovGeodetic blocks.

If no PVT solution is available, the Error field indicates the cause of the unavailability and all fields after the Error field are set to their respective Do-Not-Use values.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	т.
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution: 0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution)
				1: Stand-Alone PVT 2: Differential PVT 3: Fixed location
				4: RTK with fixed ambiguities
				5: RTK with float ambiguities 6: SBAS aided PVT
				7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP)
				12: Reserved
				Bits 4-5: Reserved
				Bit 6: Set if the user has entered the command setPVTMode , Static , , auto and the receiver is still in the process of determining its fixed position.
				Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error
				1: Not enough measurements
				Not enough ephemerides available DOP too large (larger than 15)
				4: Sum of squared residuals too large
				5: No convergence 6: Not enough measurements after outlier rejection
				6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws
				8: Not enough differential corrections available
				9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-
				fixed positions
Latitude	f8	1 rad	−2·10 ¹⁰	Latitude, from $-\pi/2$ to $+\pi/2$, positive North of Equator
Longitude	f8	1 rad	$-2 \cdot 10^{10}$	Longitude, from $-\pi$ to $+\pi$, positive East of Greenwich
Height	f8	1 m	$-2 \cdot 10^{10}$	Ellipsoidal height (with respect to the ellipsoid specified by Datum)
Undulation	f4	1 m	$-2 \cdot 10^{10}$	Geoid undulation. See the setGeoidUndulation command.
Vn	f4	1 m / s	$-2 \cdot 10^{10}$	Velocity in the North direction
Ve	f4	1 m / s	-2·10 ¹⁰	Velocity in the East direction
Vu	f4	1 m / s	$-2 \cdot 10^{10}$	Velocity in the 'Up' direction
COG	f4	1 degree	−2·10 ¹⁰	Course over ground: this is defined as the angle of the vehicle with respect to the local level North, ranging from 0 to 360, and increasing towards east. Set to the Do-Not-Use value when the speed is lower than 0.1m/s.
RxClkBias	f8	1 ms	−2·10 ¹⁰	Receiver clock bias relative to the GNSS system time reported in the $\texttt{TimeSystem}$ field. Positive when the receiver time is ahead of the system time. To transfer the receiver time to the system time, use: $t_{GPS/GST} = t_{rx} \cdot \texttt{RxClkBias}$
RxClkDrift	f4	1 ppm	−2·10 ¹⁰	Receiver clock drift relative to the GNSS system time (relative frequency error). Positive when the receiver clock runs faster than the system time.





TimeSystem	u1	255	Time system of which the offset is provided in this sub-block: 0: GPS time 1: Galileo time 3: GLONASS time 4: BeiDou time 5: QZSS time
Datum	u1	255	This field defines in which datum the coordinates are expressed: 0: WGS84/ITRS 19: Datum equal to that used by the DGNSS/RTK base station 30: ETRS89 (ETRF2000 realization) 31: NAD83(2011), North American Datum (2011) 32: NAD83(PA11), North American Datum, Pacific plate (2011) 33: NAD83(MA11), North American Datum, Marianas plate (2011) 34: GDA94(2010), Geocentric Datum of Australia (2010) 35: GDA2020, Geocentric Datum of Australia 2020 36: JGD2011, Japanese Geodetic Datum 2011 250: First user-defined datum 251: Second user-defined datum
NrSV	u1	255	Total number of satellites used in the PVT computation.
WACorrInfo	u1	0	Bit field providing information about which wide area corrections have been applied:
			Bit 0: set if orbit and satellite clock correction information is used
			Bit 1: set if range correction information is used
			Bit 2: set if ionospheric information is used
			Bit 3: set if orbit accuracy information is used (UERE/SISA)
			Bit 4: set if DO229 Precision Approach mode is active
			Bits 5-7: Reserved
ReferenceID	u2	65535	This field indicates the reference ID of the differential information used. In case of DGPS or RTK operation, this field is to be interpreted as the base station identifier. In SBAS operation, this field is to be interpreted as the PRN of the geostationary satellite used (from 120 to 158). If multiple base stations or multiple geostationary satellites are used the value is set to 65534.
MeanCorrAge	u2 C	0.01 s 65535	In case of DGPS or RTK, this field is the mean age of the differential corrections. In case of SBAS operation, this field is the mean age of the 'fast corrections' provided by the SBAS satellites. In case of PPP, this is the age of the last received clock or orbit correction message.
SignalInfo	u4	0	Bit field indicating the type of GNSS signals having been used in the PVT computations. If a bit i is set, the signal type having index i has been used. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.
AlertFlag	u1	0	Bit field indicating integrity related information:
			Bits 0-1: RAIM integrity flag: 0: RAIM not active (integrity not monitored) 1: RAIM integrity test successful 2: RAIM integrity test failed 3: Reserved Bit 2: set if integrity has failed as per Galileo HPCA (HMI Probability
			Computation Algorithm) Bit 3: set if Galileo ionospheric storm flag is active
	1 1		
			Bit 4: Reserved Bits 5-7: Reserved

Rev 1





PPPInfo u2 Bit field containing PPP-related information: Bits 0-11: Age of the last seed, in seconds. The age is clipped to 4091s. 1 s This field must be ignored when the seed type is 0 (see bits 13-15 below). Bit 12: Reserved Rev 1 Bits 13-15: Type of last seed: Not seeded or not in PPP positioning mode Manual seed 1: Seeded from DGPS 2: Seeded from RTKFixed 0.0001 s 65535 Latency u2 Time elapsed between the time of applicability of the position fix and the generation of this SBF block by the receiver. This time includes the receiver processing time, but not the communication latency. 65535 0.01 m 2DRMS horizontal accuracy: twice the root-mean-square of the hor-HAccuracy u2 izontal distance error. The horizontal distance between the true position and the computed position is expected to be lower than HAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m 65535 VAccuracy u2 0.01 m 2-sigma vertical accuracy. The vertical distance between the true position and the computed position is expected to be lower than VAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m. u1 Misc Bit field containing miscellaneous flags: In DGNSS or RTK mode, set if the baseline points to the base Bit 0: station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the rover, unset if not or unknown. Bit 2: Proprietary. Bit 3: Proprietary. Bits 4-5: Proprietary. Bits 6-7: Flag indicating whether the marker position reported in this block is also the ARP position (i.e. whether the ARP-tomarker offset provided with the setAntennaOffset command is zero or not) 0: Unknown The ARP-to-marker offset is zero 1: 2: The ARP-to-marker offset is not zero

Padding bytes, see 4.1.5

Rev 2

Padding

u1[..]



PosCovCartesian	Number:	5905	1
	"OnChange"	interval: default PVT output rate (see 4.1.8)	١

This block contains the elements of the symmetric variance-covariance matrix of the position expressed relative to the Cartesian axes of the coordinate system datum requested by the user:

$$\begin{pmatrix}
\sigma_{x}^{2} & \sigma_{xy} & \sigma_{xz} & \sigma_{xb} \\
\sigma_{yx} & \sigma_{y}^{2} & \sigma_{yz} & \sigma_{yb} \\
\sigma_{zx} & \sigma_{zy} & \sigma_{z}^{2} & \sigma_{zb} \\
\sigma_{bx} & \sigma_{by} & \sigma_{bz} & \sigma_{b}^{2}
\end{pmatrix}$$

This variance-covariance matrix contains an indication of the accuracy of the estimated parameters (see diagonal elements) and the correlation between these estimates (see off-diagonal elements). Note that the variances and covariances are estimated: they are not necessarily indicative of the actual scatter of the position estimates at a given site.

The position variance results from the propagation of all pseudorange variances using the observation geometry. The receiver implements a stochastic error model for individual measurements, based on parameters such as the C/N_0 , the satellite elevation, the pseudorange type, the URA of the broadcast ephemeris and the ionospheric model.

If the ellipsoidal height is not estimated (2D-mode), all components of the variance-covariance matrix are undefined and set to their Do-Not-Use value.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Description there are 44.2
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).



Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
Cov_xx	f4	1 m ²	-2·10 ¹⁰	Variance of the x estimate
Cov_yy	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the y estimate
Cov_zz	f4	1 m ²	-2·10 ¹⁰	Variance of the z estimate
Cov_bb	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the clock bias estimate
Cov_xy	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the x and y estimates
Cov_xz	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the x and z estimates
Cov_xb	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the x and clock bias estimates
Cov_yz	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the y and z estimates
Cov_yb	f4	1 m ²	-2·10 ¹⁰	Covariance between the y and clock bias estimates
Cov_zb	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the z and clock bias estimates
Padding	u1[]			Padding bytes, see 4.1.5



PosCovGeodetic	Number:	5906
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the elements of the symmetric variance-covariance matrix of the position expressed in the geodetic coordinates in the datum requested by the user:

$$\begin{pmatrix} \sigma_{\phi}^{2} & \sigma_{\phi\lambda} & \sigma_{\phi h} & \sigma_{\phi b} \\ \sigma_{\lambda\phi} & \sigma_{\lambda}^{2} & \sigma_{\lambda h} & \sigma_{\lambda b} \\ \sigma_{h\phi} & \sigma_{h\lambda} & \sigma_{h}^{2} & \sigma_{hb} \\ \sigma_{b\phi} & \sigma_{b\lambda} & \sigma_{bh} & \sigma_{b}^{2} \end{pmatrix}$$

Please refer to the PosCovCartesian block description for a general explanation of the contents.

Note that the units of measure for all the variances and covariances, for height as well as for latitude and longitude, are m^2 for ease of interpretation.

If the ellipsoidal height is not estimated (2D-mode), all height related components of the variance-covariance matrix are undefined and set to their Do-Not-Use value.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	с1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	receiver time stamp, see 4.1.5
Mode	u1			Bit field indicating the GNSS PVT mode, as follows: Bits 0-3: type of PVT solution:
Error	u1			0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed). PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15)
				 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
Cov_latlat	f4	1 m ²	-2·10 ¹⁰	Variance of the latitude estimate
Cov_lonlon	f4	1 m ²	-2·10 ¹⁰	Variance of the longitude estimate
Cov_hgthgt	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the height estimate
Cov_bb	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the clock-bias estimate
Cov_latlon	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the latitude and longitude estimates
Cov_lathgt	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the latitude and height estimates
Cov_latb	f4	1 m ²	-2·10 ¹⁰	Covariance between the latitude and clock-bias estimates
	f4	1 m ²	-2·10 ¹⁰	Covariance between the longitude and height estimates
Cov_lonb	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the longitude and clock-bias estimates
	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the height and clock-bias estimates
	u1[]			Padding bytes, see 4.1.5



VelCovCartesian	Number:	5907
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the elements of the symmetric variance-covariance matrix of the velocity expressed in the Cartesian coordinates of the coordinate system datum requested by the user:

$$\begin{pmatrix} \sigma_{v_x}^2 & \sigma_{v_x v_y} & \sigma_{v_x v_z} & \sigma_{v_x d} \\ \sigma_{v_y v_x} & \sigma_{v_y}^2 & \sigma_{v_y v_z} & \sigma_{v_y d} \\ \sigma_{v_z v_x} & \sigma_{v_z v_y} & \sigma_{v_z}^2 & \sigma_{v_z d} \\ \sigma_{d v_x} & \sigma_{d v_y} & \sigma_{d v_z} & \sigma_{d}^2 \end{pmatrix}$$


Please refer to the ${\tt PosCovCartesian}$ block description for a general explanation of the contents.

If the up-velocity is not estimated (2D-mode), all components of the variance-covariance matrix are undefined and set to their Do-Not-Use value.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Possiver time stamp, see 4.1.2
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows: Bits 0-3: type of PVT solution: 0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved
				Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions



Cov_VxVx	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the x-velocity estimate
Cov_VyVy	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the y-velocity estimate
Cov_VzVz	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the z-velocity estimate
Cov_DtDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the clock drift estimate
Cov_VxVy	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the x- and y-velocity estimates
Cov_VxVz	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the x- and z-velocity estimates
Cov_VxDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the x-velocity and the clock drift estimates
Cov_VyVz	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the y- and z-velocity estimates
Cov_VyDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the y-velocity and the clock drift estimates
Cov_VzDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the z-velocity and the clock drift estimates
Padding	u1[]			Padding bytes, see 4.1.5



VelCovGeodetic	Number:	5908
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the elements of the symmetric variance-covariance matrix of the velocity expressed in the geodetic coordinates in the datum requested by the user:

$$\begin{pmatrix} \sigma_{V_N}^2 & \sigma_{V_N V_E} & \sigma_{V_N V_U} & \sigma_{V_N d} \\ \sigma_{V_E V_N} & \sigma_{V_E}^2 & \sigma_{V_E V_U} & \sigma_{V_E d} \\ \sigma_{V_U V_N} & \sigma_{V_U V_E} & \sigma_{V_U}^2 & \sigma_{V_U d} \\ \sigma_{d V_N} & \sigma_{d V_E} & \sigma_{d V_U} & \sigma_{d}^2 \end{pmatrix}$$

Please refer to the PosCovCartesian block description for a general explanation of the contents.

If the up-velocity is not estimated (2D-mode), all up-velocity related components of the variance-covariance matrix are undefined and set to their Do-Not-Use value.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Passiver time stamp, see 4.1.2
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows: Bits 0-3: type of PVT solution: 0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved
				Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions



Cov_VnVn	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the north-velocity estimate
Cov_VeVe	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the east-velocity estimate
Cov_VuVu	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the up-velocity estimate
Cov_DtDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Variance of the clock drift estimate
Cov_VnVe	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the north- and east-velocity estimates
Cov_VnVu	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the north- and up-velocity estimates
Cov_VnDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the north-velocity and clock drift estimates
Cov_VeVu	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the east- and up-velocity estimates
Cov_VeDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the east-velocity and clock drift estimates
Cov_VuDt	f4	1 m ² / s ²	$-2 \cdot 10^{10}$	Covariance between the up-velocity and clock drift estimates
Padding	u1[]			Padding bytes, see 4.1.5



DOP Number: 4001
"OnChange" interval: default PVT output rate (see 4.1.8)

This block contains both Dilution of Precision (DOP) values and SBAS protection levels. The DOP values result from a trace of the unit position variance-covariance matrices:

Position Dilution of Precision: $PDOP = \sqrt{\mathbf{Q}_{xx} + \mathbf{Q}_{yy} + \mathbf{Q}_{zz}}$

Time Dilution of Precision: $TDOP = \sqrt{\mathbf{Q}_{bb}}$

Horizontal Dilution of Precision: $HDOP = \sqrt{\mathbf{Q}_{\lambda\lambda} + \mathbf{Q}_{\phi\phi}}$

Vertical Dilution of Precision: $VDOP = \sqrt{\mathbf{Q}_{hh}}$

In these equations, the matrix \mathbf{Q} is the inverse of the unweighted normal matrix used for the computation of the position. The normal matrix equals the product of the geometry matrix A with its transpose (A^tA). The term "unweighted" implies that the DOP factor only addresses the effect of the geometric factors on the quality of the position.

The DOP values can be used to interpret the current constellation geometry. This is an important parameter for the quality of the position fix: the DOP parameter is the propagation factor of the pseudorange variance. For example, if an error of 5 m is present in the pseudorange, it will propagate into the horizontal plane with a factor expressed by the HDOP. Hence a low DOP value indicates that the satellites used for the position fix result in a low multiplication of the systematic ranging errors. A value of six (6) for the PDOP is generally considered as the maximum value allowed for an acceptable position computation.

The horizontal and vertical protection levels (HPL and VPL) indicate the integrity of the computed horizontal and vertical position components as per the DO 229 specification. In SBAS-aided PVT mode (see the Mode field of the PVTCartesian SBF block), HPL and VPL are based upon the error estimates provided by SBAS. Otherwise they are based upon internal position-mode dependent error estimates.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	Acceiver time stamp, see 4.1.5	
NrSV	u1		0	Total number of satellites used in the DOP computation, or 0 if the DOP information is not available (in that case, the $xDOP$ fields are all set to 0)	
Reserved	u1			Reserved for future use, to be ignored by decoding software	
PDOP	u2	0.01	0	If 0, PDOP not available, otherwise divide by 100 to obtain PDOP.	
TDOP	u2	0.01	0	If 0, TDOP not available, otherwise divide by 100 to obtain TDOP.	
HDOP	u2	0.01	0	If 0, HDOP not available, otherwise divide by 100 to obtain HDOP.	
VDOP	u2	0.01	0	If 0, VDOP not available, otherwise divide by 100 to obtain VDOP.	
HPL	f4	1 m	-2·10 ¹⁰	Horizontal Protection Level (see the DO 229 standard).	
VPL	f4	1 m	$-2 \cdot 10^{10}$	Vertical Protection Level (see the DO 229 standard).	
Padding	u1[]			Padding bytes, see 4.1.5	



PosCart Numbe	r: 4044	
"OnCha	ange" interval: default PVT output rate (see 4.1.8)	

This block contains the absolute and relative (relative to the nearest base station) position at the time specified in the ${\tt TOW}$ and ${\tt WNC}$ fields. The time of applicability is specified in the receiver time frame.

The absolute position (X, Y, \mathbb{Z}) is reported in a Cartesian coordinate system using the datum indicated in the Datum field. The position is that of the marker. The ARP-to-marker offset is set through the command **setAntennaOffset**.

For highest accuracy, the receiver tries to compute the baseline (Base2RoverX, Base2RoverY, Base2RoverZ) from rover ARP to base ARP. See the description of the BaseVectorCart block for details.

Accurate ARP-to-ARP baseline is guaranteed only if both bits 0 and 1 of the Misc field are set. Otherwise, centimeter-level offsets may arise because the receiver cannot make the distinction between phase center and ARP positions. See section 2.5 for a discussion on the phase center and ARP positions.

This block also contains the variance-covariance information and DOP factors associated with the position.



Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	receiver time stamp, see 1.1.3	
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:	
				Bits 0-3: type of PVT solution:	
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not	
				computed).	
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions	
Х	f8	1 m	-2·10 ¹⁰	X coordinate in coordinate frame specified by Datum	
Y	f8	1 m	-2·10 ¹⁰	Y coordinate in coordinate frame specified by Datum	
Z	f8	1 m	-2·10 ¹⁰	Z coordinate in coordinate frame specified by Datum	
Base2RoverX	f8	1 m	-2·10 ¹⁰	X baseline component (from base to rover)	
Base2RoverY	f8	1 m	-2·10 ¹⁰	Y baseline component (from base to rover)	
Base2RoverZ	f8	1 m	$-2 \cdot 10^{10}$	Z baseline component (from base to rover)	
Cov_xx	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the x estimate	
Cov_yy	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the y estimate	
Cov_yy	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of the z estimate	
Cov_xy	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the x and y estimates	
	f4	1 m ²	$-2 \cdot 10^{10}$	Covariance between the x and y estimates Covariance between the x and z estimates	
Cov_xz		1 m ²	$-2 \cdot 10^{10}$ $-2 \cdot 10^{10}$		
Cov_yz				Covariance between the y and z estimates	
PDOP		0.01	0	If 0, PDOP not available, otherwise divide by 100 to obtain PDOP.	
HDOP		0.01	0	If 0, HDOP not available, otherwise divide by 100 to obtain HDOP.	
VDOP	u2	0.01	0	If 0, VDOP not available, otherwise divide by 100 to obtain VDOP.	



Misc	u1			Bit field containing miscellaneous flags:
				Bit 0: In DGNSS or RTK mode, set if the baseline points to the base station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the rover, unset if not or unknown.
				Bit 2: Proprietary.
				Bit 3: Proprietary.
				Bits 4-5: Proprietary.
				Bits 6-7: Flag indicating whether the marker position reported in this block is also the ARP position (i.e. whether the ARP-to-marker offset provided with the setAntennaOffset command is zero or not)
				0: Unknown 1: The ARP-to-marker offset is zero
				2: The ARP-to-marker offset is not zero
Reserved	u1			Reserved for future use.
AlertFlag	u1		0	Bit field indicating integrity related information:
				Bits 0-1: RAIM integrity flag: 0: RAIM not active (integrity not monitored) 1: RAIM integrity test successful 2: RAIM integrity test failed 3: Reserved
				Bit 2: set if integrity has failed as per Galileo HPCA (HMI Probability Computation Algorithm) Bit 3: set if Galileo ionospheric storm flag is active
				Bit 4: Reserved
				Bits 5-7: Reserved
Datum	u1		255	This field defines in which datum the coordinates are expressed: 0: WGS84/ITRS
				 19: Datum equal to that used by the DGNSS/RTK base station 30: ETRS89 (ETRF2000 realization) 31: NAD83(2011), North American Datum (2011) 32: NAD83(PA11), North American Datum, Pacific plate (2011) 33: NAD83(MA11), North American Datum, Marianas plate (2011) 34: GDA94(2010), Geocentric Datum of Australia (2010) 35: GDA2020, Geocentric Datum of Australia 2020 36: JGD2011, Japanese Geodetic Datum 2011 250: First user-defined datum 251: Second user-defined datum
NrSV	u1		255	Total number of satellites used in the PVT computation.
WACorrInfo	u1		0	Bit field providing information about which wide area corrections have been applied:
				Bit 0: set if orbit and satellite clock correction information is used
				Bit 1: set if range correction information is used
				Bit 2: set if ionospheric information is used
				Bit 3: set if orbit accuracy information is used (UERE/SISA)
				Bit 4: set if DO229 Precision Approach mode is active
				Bits 5-7: Reserved
ReferenceId	u2		65535	This field indicates the reference ID of the differential information used. In case of DGPS or RTK operation, this field is to be interpreted as the base station identifier. In SBAS operation, this field is to be interpreted as the PRN of the geostationary satellite used (from 120 to 158). If multiple base stations or multiple geostationary satellites are used the value is set to 65534.
MeanCorrAge	u2	0.01 s	65535	In case of DGPS or RTK, this field is the mean age of the differential corrections. In case of SBAS operation, this field is the mean age of the 'fast corrections' provided by the SBAS satellites. In case of PPP, this is the age of the last received clock or orbit correction message.



SignalInfo	u4	0	Bit field indicating the type of GNSS signals having been used in the PVT computations. If a bit i is set, the signal type having index i has been used. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.
Padding	u1[]		Padding bytes, see 4.1.5



PosLocal	Number:	4052
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the position at the time specified in the TOW and WNc fields. The time of applicability is specified in the receiver time frame.

The position (Lat, Lon, Alt) relates to the local datum identified with the <code>Datum</code> field. The coordinate transformation to the local datum is done using parameters transmitted by the RTK service provider in RTCM message types MT1021 to MT1023.

The position is that of the marker. The ARP-to-marker offset is set through the command **setAntennaOffset**.

If no position is available, the Error field indicates the cause of the unavailability and all fields after the Error field are set to their respective Do-Not-Use values.

To be able to output a position in the PosLocal block, the receiver needs to have received the relevant RTCM transformation messages (at least either MT1021 or MT1022 is required). If they have not been received yet, the local position is not available and the Error field is set to value 17. See also section 2.4.6.

The corresponding RTCMDatum block provides information on the local datum name and transformation quality indicators. The corresponding RTCMDatum block is the one of which the Datum field matches the Datum field in the PosLocal block.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	receiver time stamp, see 1.7.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved
				Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions 17: Datum transformation parameters unknown
Lat	f8	1 rad	-2·10 ¹⁰	Latitude, from $-\pi/2$ to $+\pi/2$, positive North of Equator
Lon	f8	1 rad	$-2 \cdot 10^{10}$	Longitude, from $-\pi$ to $+\pi$, positive East of Greenwich
Alt	f8	1 m	−2·10 ¹⁰	Height. See the HeightType field of the corresponding RTCMDatum block for the interpretation of the height.
Datum	u1			Reference frame to which the position relate. If the value is in the 20 to 24 range, the corresponding datum parameters can be found in the RTCMDatum block having a matching Datum field.
Padding	u1[]	-		Padding bytes, see 4.1.5



PosProjected	Number:	4094
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the projected coordinates at the time specified in the TOW and WNC fields. The time of applicability is specified in the receiver time frame.

The coordinates (Northing, Easting, Alt) relate to the local datum identified with the <code>Datum</code> field. The coordinate transformation and projection is done using parameters transmitted by the RTK service provider in RTCM message types MT1021 to MT1027.

The position is that of the marker. The ARP-to-marker offset is set through the command **setAntennaOffset**.

If no position is available, the Error field indicates the cause of the unavailability and all fields after the Error field are set to their respective Do-Not-Use values.

To be able to output a position in the PosProjected block, the receiver needs to have received at least one RTCM message in the MT1025 to MT1027 range. If none of these messages is sent out by the service provider, or if they have not been received yet, the projected position is not available and the Error field is set to value 17. See also section 2.4.6.

The corresponding RTCMDatum block provides information on the local datum name and transformation/projection quality indicators. The corresponding RTCMDatum block is the one of which the Datum field matches the Datum field in the PosProjected block.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Descriver time stamp see 4.1.2
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode,
				Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions 17: Datum transformation parameters unknown
Northing	f8	1 m	-2·10 ¹⁰	Northing coordinate in the plane grid representation.
Easting	f8	1 m	-2·10 ¹⁰	Easting coordinate in the plane grid representation.
Alt	f8	1 m	-2·10 ¹⁰	Height. If the Datum field is in the 20 to 24 range, see the HeightType field of the corresponding RTCMDatum block for the interpretation of the height.
Datum	u1			Reference frame to which the position relate. If the value is in the 20 to 24 range, the corresponding datum parameters can be found in the RTCMDatum block having a matching Datum field.
Padding	u1[]			Padding bytes, see 4.1.5



PVTSatCartesian	Number:	4008
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the position and velocity of all the satellites used in the PVT solution, together with slant ionospheric and tropospheric delays. Coordinates are referred to the time of signal transmission computed by the receiver and are corrected for the Sagnac effect.

The reference frame the coordinates are related to is the one specified in the respective ICDs (WGS84 for GPS satellites, GTRF for Galileo satellites, PZ90 for GLONASS satellites, etc).

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	receiver time stamp, see 4.1.5	
N	u1			Number of satellites for which satellite position is provided in this SBF block, i.e. number of SatPos sub-blocks. If $\mathbb N$ is 0, there are no satellite positions available for this epoch.	
SBLength	u1	1 byte		Length of one sub-block	
SatPos				A succession of N SatPos sub-blocks, see definition below	
Padding	u1[]			Padding bytes, see 4.1.5	



SatPos sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
SVID	u1			Satellite ID, see 4.1.9
FreqNr	u1		0	For GLONASS FDMA signals, this is the frequency number, with an offset of 8. It ranges from 1 (corresponding to an actual frequency number of -7) to 21 (corresponding to an actual frequency number of 13). Otherwise, ${\tt FreqNr}$ is reserved and must be ignored by the decoding software.
IODE	u2			IODE of the data set used to compute the values in this sub-block.
х	f8	1 m	$-2 \cdot 10^{10}$	X coordinate
У	f8	1 m	$-2 \cdot 10^{10}$	Y coordinate
z	f8	1 m	$-2 \cdot 10^{10}$	Z coordinate
Vx	f4	1 m / s	$-2 \cdot 10^{10}$	Satellite velocity in the X direction
Vy	f4	1 m / s	$-2 \cdot 10^{10}$	Satellite velocity in the Y direction
Vz	f4	1 m / s	$-2 \cdot 10^{10}$	Satellite velocity in the Z direction
IonoMSB	i2	1 dm	-32768 ⁽⁷⁾	Total slant ionospheric delay at the L1 carrier frequency (1575.42MHz), with a decimeter resolution.
TropoMSB	i2	1 dm	-32768 ⁽⁸⁾	Total slant tropospheric delay, with a decimeter resolution.
IonoLSB	u1	1.0/256.0 dm	0 (7)	Sub-decimeter part of the slant ionospheric delay. The high-resolution ionospheric delay, expressed in meters, can be computed as: lonoDelay[m] = 0.1*(IonoMSB + IonoLSB/256)
TropoLSB	u1	1.0/256.0 dm	0 (8)	Sub-decimeter part of the slant tropospheric delay. The high-resolution tropospheric delay, expressed in meters, can be computed as: TropoDelay[m] = 0.1*(TropoMSB + TropoLSB/256)
IonoModel	u1			Model used to compute the ionospheric delay: 0: Not applicable 1: Klobuchar 2: DO229 3: NeQuick 4: Measured (from dual frequency measurements) 5: Estimated 6: KlobucharBeiDou
Padding	u1[]			Padding bytes, see 4.1.5

Rev 1

The ionospheric delay should not be used when IonoMSB is -32768.
 The tropospheric delay should not be used when TropoMSB is -32768.



PVTResiduals	Number:	4009
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the residuals of all measurements used in PVT solution computed at the epoch specified in the TOW and WNc fields. The PVT solution itself can be found in the PVTCartesian or PVTGeodetic blocks.

For each measurement from each satellite and each modulation used in the PVT solution, detailed PVT residual information is output for each observable type (code phase, carrier phase and Doppler):

- a-posteriori measurement residual (*e_i*)
- absolute value of the w-test statistic (w_i)
- Minimal detectable bias (MDB).

In case of multi-base differential operation, a set of residuals is provided for all base stations.

This block uses a two-level sub-block structure analogous to that of the MeasEpoch block. It contains one SatSignalInfo sub-block for each satellite/signal type pair used in the PVT or attitude computation. Each SatSignalInfo sub-block contains a number of ResidualInfo sub-blocks, each of them containing the residuals of a given observable type.

The standard deviation of the residual (σ_e) for satellite i and the "a priori" measurement standard deviation (σ_y) can be computed from e_i , w_i and MDB by using the following formulas (see also section 2.7):

$$\sigma_{e_i} = \frac{|e_i|}{w_i}$$
 and $\sigma_{y_i} = \sqrt{\frac{MDB}{\sqrt{\lambda_0}}}.\sigma_{e_i}$

where λ_0 is the non-centrality parameter and:

$$\sqrt{\lambda_0} = \sqrt{2}[\text{erfinv}(1 - P_{fa}) + \text{erfinv}(1 - 2P_{md})]$$


with P_{fa} and P_{md} being the probability of false alarm and of missed detection respectively, as set by the **setRAIMLevels** command, and the "erfinv" function being the inverse error function. The output of erfinv(x) is the value y that satisfies the following equality:

$$x = \frac{2}{\sqrt{\pi}} \int_{0}^{y} e^{-t^2} dt$$

This block can be used to monitor the quality of the measurements. Under normal circumstances, the residuals lie within -2 and +2 times the a-priori variance of the corresponding measurements.



Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5
N	u1			Number of satellite/signal pairs for which residual blocks are provided in this SBF block, i.e. number of $SatSignalInfo$ sub-blocks. If N is 0, there are no satellite residuals available for this epoch.
SB1Length	u1	1 byte		Length of a SatSignalInfo sub-block, excluding the nested ResidualInfoCode, ResidualInfoPhase and ResidualInfoDoppler sub-blocks
SB2Length	u1	1 byte		Length of a ResidualInfoCode, ResidualInfoPhase and ResidualInfoDoppler sub-block
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software
Residuals				A succession of N SatSignalInfo sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5



${\tt SatSignalInfo} \ \ {\tt sub-block} \ \ {\tt definition:}$

Parameter	Туре	Units	Do-Not-Use	Description
SVID	u1			Satellite ID, see 4.1.9
FreqNr	u1		0	For GLONASS FDMA signals, this is the frequency number, with an offset of 8. It ranges from 1 (corresponding to an actual frequency number of -7) to 21 (corresponding to an actual frequency number of 13). Otherwise, $FreqNr$ is reserved and must be ignored by the decoding software.
Type	u1			Bit field indicating the signal type and antenna ID:
				Bits 0-4: Signal number, see 4.1.10.
				Bits 5-7: Antenna ID: 0 for the main antenna
RefSVID	u1		255, 62	Satellite ID of the reference satellite used for double differencing, see 4.1.9.
				Set to 255 if not in double difference mode, or set to 62 if in double difference mode, and GLONASS slot number unknown.
RefFreqNr	u1		255, 0	GLONASS frequency number for the reference satellite, see 4.1.9.
				Set to 255 if not in double difference mode, or set to 0 if in double difference mode, but non-GLONASS satellite.
MeasInfo	u1			Bit field:
				Bits 0-1: Type of residual this sub-block refers to: 0: zero-difference residual (standalone) 1: single-difference residual (SBAS, DGPS) 2: double-difference residual. If the antenna ID is 0 (see the Type field above), this sub-block contains an RTK residual, else it contains an attitude residual.
				Bit 2: Set if a ResidualInfoCode sub-block containing pseudorange residuals follows.
				Bit 3: Set if a ResidualInfoPhase sub-block containing carrier-phase residuals follows.
				Bit 4: Set if a ResidualInfoDoppler sub-block containing Doppler residuals follows.
				Bits 5-6: Reserved
				Bit 7: Set if ambiguity is fixed for the signal type identified by the Type field.
				The number of ResidualInfo sub-blocks to follow is equal to the number of bits set to 1 between bit 2 and bit 4. The order of these
				ResidualInfo sub-blocks is fixed: the code-phase residuals come first (if any), then the carrier phase residuals (if any), and the Doppler residuals as last.
IODE	u2			Issue of Data Ephemeris used for the satellite and signal type identified by ${\tt SVID}$ and ${\tt Type}.$ For GLONASS satellites, this is the t_b value in minutes.
CorrAge	u2	0.01 s	65535	Age of corrections, either from SBAS, DGPS, RTK etc, truncated to 655.34 seconds.
ReferenceID	u2		65535	ID of the base station the residuals apply to. Set to 65535 in case of standalone operation.
Padding	u1[]			Padding bytes, see 4.1.5
If the Pseudorange res	idual	s field i	s 1 then this s	sub block is available:
ResidualInfoCode				A ResidualInfoCode sub-block, see definition below
If the Carrier-phase r	esidu	als fie	ld is 1 then th	is sub block is available:
ResidualInfoPhase]			A ResidualInfoPhase sub-block, see definition below
	1	Γ		
If the Doppler residua	ıls field	d is 1 th	en this sub bl	ock is available:
ResidualInfoDopple				A ResidualInfoDoppler sub-block, see definition below
	•	•	•	

Rev 1



ResidualInfoCode sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
Residual	f4	1 m		Code Residual with respect to PVT solution reported in PVTCartesian and/or PVTGeodetic block.
W	u2	0.001		Absolute value of the <i>w</i> -test statistic based on probability of false alarm set by user
MDB	u2	0.1 m	65535	Minimal detectable bias based on probability of missed detection set by user
Padding	u1[]			Padding bytes, see 4.1.5

ResidualInfoPhase sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
Residual	f4	1 cycle		Phase Residual with respect to PVT solution reported in PVTCartesian and/or PVTGeodetic block. Double-difference carrier phase residuals include the double difference ambiguity as long as the ambiguity is not fixed (i.e. as long as bit 7 of MeasInfo is not set). When the ambiguity is fixed, e_i does not contain the ambiguity anymore.
W	u2	0.001	I	Absolute value of the <i>w</i> -test statistic based on probability of false alarm set by user
MDB	u2	0.01 cycles	I	Minimal detectable bias based on probability of missed detection set by user
Padding	u1[]			Padding bytes, see 4.1.5

${\tt ResidualInfoDoppler} \ \ \textbf{sub-block definition:}$

Parameter	Туре	Units	Do-Not-Use	Description
Residual	f4	1 m / s		Doppler Residual with respect to PVT solution reported in PVTCartesian and/or PVTGeodetic block.
W	u2	0.001		Absolute value of the <i>w</i> -test statistic based on probability of false alarm set by user
MDB	u2	0.01 m/s	65535	Minimal detectable bias based on probability of missed detection set by user
Padding	u1[]			Padding bytes, see 4.1.5



RAIMStatistics	Number:	4011
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the integrity statistics that are computed by the receiver RAIM algorithm.

The output of the RAIM algorithm contains integrity information, which can be used in user applications. First, the RAIM algorithm generates its own integrity flag based on the probability of false-alarm, which can be used by a user as a receiver-level indication of positional integrity. If the internal integrity test is successful, a user has an opportunity to introduce a more stringent application-specific integrity criterion by using External Reliability Levels (XERL). The positional solution is deemed as passed an application-level integrity test if the XERLs are within user-defined (and application-dependent) alarm limits. This comparison (and the definition of alarm limits as well) takes place in a user application and is outside of the receiver scope. Please also refer to section 2.7.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5
IntegrityFlag	u1			RAIM integrity flag: 0: Integrity test successful 1: Integrity test failed 2: Integrity not available
Reserved1	u1			Reserved for future use, to be ignored by decoding software
HERL-position	f4	1 m	-2·10 ¹⁰	Horizontal external reliability level of the position
VERL-position	f4	1 m	$-2 \cdot 10^{10}$	Vertical external reliability level of the position
HERL-velocity	f4	1 m / s	-2·10 ¹⁰	Horizontal external reliability level of the velocity
VERL-velocity	f4	1 m / s	-2·10 ¹⁰	Vertical external reliability level of the velocity
OverallModel	u2	1/50000	65535 ⁽⁹⁾	Overall model test statistic for the estimated PVT parameters divided by the test threshold
Padding	u1[]			Padding bytes, see 4.1.5



⁽⁹⁾ This field is clipped to 65534, i.e. if the actual value is larger than 65534, it is set to 65534.



GEOCorrections	Number:	5935
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains the SBAS corrections that the receiver has applied to the pseudoranges used in the PVT computation computed at the epoch specified in the TOW and WNc fields. The PVT solution itself can be found in the PVTCartesian or PVTGeodetic blocks.

The corrections are based on the messages received from an SBAS satellite. They compensate for the following errors:

- Satellite orbit
- Satellite clock
- Ionospheric delay.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N	u1			Number of satellites for which corrections are provided in this SBF block, i.e. number of SatCorr sub-blocks. If $\mathbb N$ is 0, there are no corrections available for this epoch.
SBLength	u1	1 byte		Length of one sub-block in bytes
SatCorr				A succession of N SatCorr sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

SatCorr sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
SVID	u1			Satellite ID, see 4.1.9
IODE	u1			lssue of Data Ephemeris related to the orbit and clock corrections
Reserved	u1[2]			Reserved for future use, to be ignored by decoding software
PRC	f4	1 m		Applied pseudorange correction based on the fast correction data received in MT02-MT05 or MT24
CorrAgeFC	f4	1 s	$-2 \cdot 10^{10}$	Age of applied fast correction
DeltaX	f4	1 m		X-component of applied orbit correction based on the long term correction data received in MT24 or MT25
DeltaY	f4	1 m		Y-component of applied orbit correction based on the long term correction data received in MT24 or MT25
DeltaZ	f4	1 m		Z-component of applied orbit correction based on the long term correction data received in MT24 or MT25
DeltaClock	f4	1 s		Satellite clock correction based on the long term correction data received in MT24 or MT25
CorrAgeLT	f4	1 s	$-2 \cdot 10^{10}$	Age of applied long term correction
IonoPPlat	f4	1 rad	$-2 \cdot 10^{10}$	Latitude of ionospheric pierce point
IonoPPlon	f4	1 rad	−2·10 ¹⁰	Longitude of ionospheric pierce point
SlantIono	f4	1 m	−2·10 ¹⁰	Slant ionospheric delay at the L1 carrier at the ionosphere pierce point based on the data received in MT18 and MT26
CorrAgeIono	f4	1 s		Maximum of the ionospheric correction age at each of the grid locations used for the interpolation of the ionospheric delay.



VarFLT	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of fast and long-term corrections (used for XPL computation)
VarUIRE	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of ionospheric delay corrections (used for XPL computation)
VarAir	f4	1 m ²	-2·10 ¹⁰	Variance of unmodeled receiver errors, such as tracking noise and multipath (used for XPL computation)
VarTropo	f4	1 m ²	$-2 \cdot 10^{10}$	Variance of tropospheric delay corrections (used for XPL computation)
Padding	u1[]			Padding bytes, see 4.1.5



BaseVectorCart	Number:	4043
	"OnChange"	interval: default PVT output rate (see 4.1.8)

The BaseVectorCart block contains the relative position and orientation of one or more base stations, as seen from the rover (i.e. this receiver). The relative position is expressed in the Cartesian X, Y, Z directions.


For highest accuracy, the receiver tries to compute the baseline from rover antenna reference point (ARP) to base ARP. This requires to compensate for the phase center offset at both the base and the rover antennas. This is possible if two conditions are met:

- the base station must transmit its antenna parameters in RTCM2 message types 23 and 24 or in RTCM3 message types 1005/1006 and 1007/1008. Older RTCM2 messages and CMR do not allow phase center offset compensation.
- the base and rover antenna types must belong to the list returned by the command lstAntennaInfo, overview. (see the description of the commands setAntennaOffset and lstAntennaInfo for details).

Accurate ARP-to-ARP baseline is guaranteed only if both bits 0 and 1 of the Misc field are set. Otherwise, centimeter-level offsets may arise because the receiver cannot make the distinction between phase center and ARP positions. See section 2.5 for a discussion on the phase center and ARP positions.

The block supports multi-base operation. It contains as many sub-blocks as available base stations, each sub-block containing the baseline relative to a single base station identified by the ReferenceID field.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Descriver time stamp see 4.1.2
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N	u1			Number of baselines for which relative position, velocity and direction are provided in this SBF block, i.e. number of $VectorInfoCart$ subblocks. If N is 0, there are no baseline available for this epoch.
SBLength	u1	1 byte		Length of one sub-block
VectorInfoCart				A succession of N VectorInfoCart sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5



VectorInfoCart sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
nrSV	u1			Number of satellites for which corrections are available from the base station identified by the ReferenceID field.
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
Misc	u1			Bits 0-3: type of PVT solution: 0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static,, auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed). Bit field containing miscellaneous flags: Bit 0: Set if the baseline points to the base station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the
				rover (i.e. the baseline starts from the antenna ARP), unset if not or unknown. Bit 2: Proprietary. Bit 3: Proprietary. Bits 4-5: Proprietary.
Do1+ 2V	f8	1 m	-2·10 ¹⁰	Bits 6-7: Reserved Y haseline component (from rover to base)
DeltaY	f8	1 m	$-2 \cdot 10^{10}$	X baseline component (from rover to base) Y baseline component (from rover to base)
	f8	1 m	$-2 \cdot 10^{10}$	·
DeltaZ	f4		$-2 \cdot 10^{10}$	Z baseline component (from rover to base)
DeltaVx	-	1 m / s		X velocity of base with respect to rover
DeltaVy	f4	1 m / s	$-2 \cdot 10^{10}$	Y velocity of base with respect to rover
DeltaVz	f4	1 m / s	-2·10 ¹⁰	Z velocity of base with respect to rover
Azimuth	u2	0.01 degrees		Azimuth of the base station (from 0 to 360° , increasing towards east)
Elevation	i2	0.01 degrees	-32768	Elevation of the base station (from -90° to 90°)
ReferenceID	u2			Base station ID
CorrAge	u2	0.01 s	65535	Age of the oldest differential correction used for this baseline computation.



SignalInfo	u4	0	Bit field indicating the GNSS signals for which differential corrections are available from the base station identified by ReferenceID. If bit <i>i</i> is set, corrections for the signal type having index <i>i</i> are available. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.
Padding	u1[]		Padding bytes, see 4.1.5



BaseVectorGeod	Number:	4028
	"OnChange"	interval: default PVT output rate (see 4.1.8)

The <code>BaseVectorGeod</code> block contains the relative position and orientation of one or more base stations, as seen from the rover (i.e. this receiver). The relative position is expressed in the <code>East-North-Up</code> directions.

For highest accuracy, the receiver tries to compute the baseline from rover antenna reference point (ARP) to base ARP. See the description of the BaseVectorCart block for details.

Accurate ARP-to-ARP baseline is guaranteed only if both bits 0 and 1 of the Misc field are set. Otherwise, centimeter-level offsets may arise because the receiver cannot make the distinction between phase center and ARP positions. See section 2.5 for a discussion on the phase center and ARP positions.

The block supports multi-base operation. It contains as many sub-blocks as available base stations, each sub-block containing the baseline coordinates relative to a single base station identified by the ReferenceID field.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N	u1			Number of baselines for which relative position, velocity and direction are provided in this SBF block, i.e. number of ${\tt VectorInfoGeod\ subblocks}$. If ${\tt N}$ is 0, there are no baseline available for this epoch.
SBLength	u1	1 byte		Length of one sub-block
VectorInfoGeod				A succession of N VectorInfoGeod sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

VectorInfoGeod sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
NrSV	u1			Number of satellites for which corrections are available from the base station identified by the ReferenceID field.
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions



Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved
				Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Misc	u1			Bit field containing miscellaneous flags:
				Bit 0: Set if the baseline points to the base station ARP. Unset if it points to the antenna phase center, or if unknown.
				Bit 1: Set if the phase center offset is compensated for at the rover (i.e. the baseline starts from the antenna ARP), unset if not or unknown. Bit 2: Proprietary.
				Bit 3: Proprietary.
				Bits 4-5: Proprietary.
				Bits 6-7: Reserved
DeltaEast	f8	1 m	-2·10 ¹⁰	East baseline component (from rover to base)
DeltaNorth	f8	1 m	-2·10 ¹⁰	North baseline component (from rover to base)
DeltaUp	f8	1 m	-2·10 ¹⁰	Up baseline component (from rover to base)
DeltaVe	f4	1 m / s	-2·10 ¹⁰	East velocity of base with respect to rover
DeltaVn	f4	1 m / s	-2·10 ¹⁰	North velocity of base with respect to rover
DeltaVu	f4	1 m / s	-2·10 ¹⁰	Up velocity of base with respect to rover
Azimuth	u2	0.01 degrees	65535	Azimuth of the base station (from 0 to 360° , increasing towards east)
Elevation	i2	0.01 degrees	-32768	Elevation of the base station (from -90° to 90°)
ReferenceID	u2			Base station ID
CorrAge	u2	0.01 s	65535	Age of the oldest differential correction used for this baseline computation.
SignalInfo	u4		0	Bit field indicating the GNSS signals for which differential corrections are available from the base station identified by ReferenceID. If bit <i>i</i> is set, corrections for the signal type having index <i>i</i> are available. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.
Padding	u1[]			Padding bytes, see 4.1.5



PVTSupport Number	r: 4076	
"OnCha	ange" interval: default PVT output rate (see 4.1.8)	

This block contains various internal parameters that can be used for maintenance and support.

The detailed definition of this block is not available in this document.



PVTSupportA	Number:	4079
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block contains various internal parameters that can be used for maintenance and support.

The detailed definition of this block is not available in this document.



EndOfPVT	Number:	5921
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block marks the end of transmission of all PVT related blocks belonging to the same epoch.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5
Padding	u1[]			Padding bytes, see 4.1.5



4.2.11 Receiver Time Blocks

ReceiverTime	Number:	59	14
	"OnChange"	interval: 1s	

The ReceiverTime block provides the current time with a 1-second resolution in the receiver time scale and UTC.

The level of synchronization of the receiver time with the satellite system time is provided in the SyncLevel field.

UTC time is provided if the UTC parameters have been received from at least one GNSS satellite. If the UTC time is not available, the corresponding fields are set to their Do-Not-Use value.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	receiver time stamp, see 1.1.5
UTCYear	i1	1 year	_128	Current year in the UTC time scale (2 digits). From 0 to 99, or -128 if not available
UTCMonth	i1	1 month	-128	Current month in the UTC time scale. From 1 to 12, or -128 if not available
UTCDay	i1	1 day	-128	Current day in the UTC time scale. From 1 to 31, or -128 if not available
UTCHour	i1	1 hour	-128	Current hour in the UTC time scale. From 0 to 23, or -128 if not available
UTCMin	i1	1 minute	-128	Current minute in the UTC time scale. From 0 to 59, or -128 if not available
UTCSec	i1	1 s	-128	Current second in the UTC time scale. From 0 to 59, or -128 if not available
DeltaLS	i1	1 s	-128	Integer second difference between UTC time and GPS system time. Positive if GPS time is ahead of UTC. Set to -128 if not available.
SyncLevel	u1			Bit field indicating the synchronization level of the receiver time. If bits 0 to 2 are set, full synchronization is achieved:
				Bit 0: WNSET: if this bit is set, the receiver week number is set.
				Bit 1: TOWSET: if this bit is set, the receiver time-of-week is set to within 20ms. Bit 2: FINETIME: if this bit is set, the receiver time-of-week is within the limit specified by the setClockSyncThreshold command. Bit 3: Reserved
				Bit 4: Reserved
				Bits 5-7: Reserved
Padding	u1[]			Padding bytes, see 4.1.5



xPPSOffset Numbe	5911	
"OnCha	ge" interval: PPS rate	

The xPPSOffset block contains the offset between the true xPPS pulse and the actual pulse output by the receiver. It is output right after each xPPS pulse.

On receivers with more than one independent PPS outputs, this block always refers to the first PPS output.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
SyncAge	u1	1 s		Age of the last synchronization to system time. The xPPS pulse is regularly resynchronized with system time. This field indicates the number of seconds elapsed since the last resynchronization. SyncAge is constrained to the 0-255s range. If the age is higher than 255s, SyncAge is set to 255. If the PPS is synchronized with the internal receiver time (Timescale = 3), SyncAge is always set to 0.
TimeScale	u1			Time scale to which the xPPS pulse is referenced, as set with the setPPSParameters command: 1: GPS time 2: UTC 3: Receiver time 4: GLONASS time 5: Galileo time 6: BeiDou time
Offset	f4	1 · 10 ⁻⁹ s		Offset of the xPPS output by the receiver with respect to its true position. Offset is negative when the xPPS pulse is in advance with respect to its true position. See also section 1.27 for an explanation of the xPPS generation principle, and for a description of the xPPS offset.
Padding	u1[]			Padding bytes, see 4.1.5



4.2.12 External Event Blocks

These blocks report the state of the receiver applicable at the instant of a level transition on one of its "Event" pins. The receiver time is reported in the <code>ExtEvent SBF</code> block, and the receiver position is reported in the <code>ExtEventPVTCartesian</code> and the <code>ExtEventPVTGeodetic</code> blocks.

If enabled, upon detection of an event, these three blocks are output in the following order, with no other SBF blocks in between them:

- ExtEvent;
- 2. ExtEventPVTCartesian;
- 3. ExtEventPVTGeodetic.

All blocks referring to the same event contain the same time stamp in the TOW and WNc fields.



ExtEvent	Number:	5924
	"OnChange"	interval: each time an event is detected

The ${\tt ExtEvent}$ block contains the time tag of a voltage transition on one of the "Event" input pins.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	External time stamp, see 4.1.3
WNc	u2	1 week	65535	external time stamp, see 4.1.5
Source	u1			Input pin where this external event has been detected. The following values are defined: 1: EventA 2: EventB
Polarity	u1			0: rising edge event 1: falling edge event
Offset	f4	1 s		Event time offset with respect to <code>TOW</code> , including the potential delay specified with the <code>setEventParameters</code> command. The time of week of the external event is given by: $t_{\rm ext,rx} \ [s] = {\tt TOW}/1000 + {\tt Offset}$ $t_{\rm ext,rx} \ \text{refers to the receiver system time scale.} \ \text{Use the } {\tt RxClkBias}$ field to convert this time to the GNSS time scale.
RxClkBias	f8	1 s	-2·10 ¹⁰	Receiver clock bias at the time of event. The clock bias is relative to the time system of the last PVT computation (see the $\mathtt{TimeSystem}$ field of the $\mathtt{PVTCartesian}$ or $\mathtt{PVTGeodetic}$ blocks). To get the time of week of the external event in GNSS time, use: $t_{\mathrm{ext,GNSS}}$ [s] = $\mathtt{ToW}/1000 + \mathtt{Offset} - \mathtt{RxClkBias}$. The accuracy of the clock bias is dependent on the age of the last PVT solution. When the receiver has been unable to compute a PVT during the last 10 minutes, this field is set to its Do-Not-Use value.
PVTAge	u2	1 s		Age of the last PVT solution. If the PVT age is larger than 10 minutes (600s), this value is clipped to 600.
Padding	u1[]			Padding bytes, see 4.1.5

Rev 1



ExtEventPVTCartesian	Number:	4037	
	"OnChange"	interval: each time an	external event is
		detected	

This block contains the position, velocity and time (PVT) solution applicable at the time of an external event, in a Cartesian coordinate system.

This block has the same structure and description as the PVTCartesian block, except that the TOW and WNc fields refer to the time at which the electrical transition on the event pin has been detected (with a millisecond resolution), and that the position is computed at the event time, taking into account a possible user-defined delay set by the **setEventParameters** command.

A user needing the sub-millisecond part of the event time must refer to the Offset field of the corresponding <code>ExtEvent</code> block. The corresponding <code>ExtEvent</code> block is the last of the <code>ExtEvent</code> blocks having been output by the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Extraordal disease at the second seco
WNc	u2	1 week	65535	External time stamp, see 4.1.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
Х	f8	1 m	$-2 \cdot 10^{10}$	X coordinate in coordinate frame specified by <code>Datum</code>



Y	f8	1 m	$-2 \cdot 10^{10}$	Y coordinate in coordinate frame specified by Datum
Z	f8	1 m	$-2 \cdot 10^{10}$	Z coordinate in coordinate frame specified by Datum
	f4	1 m	$-2 \cdot 10^{10}$	Geoid undulation. See the setGeoidUndulation command.
Undulation	f4	1 m / s	$-2 \cdot 10^{10}$	
Vx		-	$-2 \cdot 10^{10}$	Not applicable
Vy	f4	1 m / s		Not applicable
Vz	f4	1 m / s	$-2 \cdot 10^{10}$	Not applicable
COG	f4	1 degree	−2·10 ¹⁰	Course over ground: this is defined as the angle of the vehicle with respect to the local level North, ranging from 0 to 360, and increasing towards east. Set to the Do-Not-Use value when the speed is lower than 0.1m/s.
RxClkBias	f8	1 ms	−2·10 ¹⁰	Receiver clock bias relative to the GNSS system time reported in the $ \begin{tabular}{ll} TimeSystem field. Positive when the receiver time is ahead of the system time. To transfer the receiver time to the system time, use: t_{GPS/GST} = t_{rx} \cdot \texttt{RxClkBias} $
RxClkDrift	f4	1 ppm	−2·10 ¹⁰	Receiver clock drift relative to the GNSS system time (relative frequency error). Positive when the receiver clock runs faster than the system time.
TimeSystem	u1		255	Time system of which the offset is provided in this sub-block: 0: GPS time 1: Galileo time 3: GLONASS time 4: BeiDou time 5: QZSS time
Datum	u1		255	This field defines in which datum the coordinates are expressed: 0: WGS84/ITRS 19: Datum equal to that used by the DGNSS/RTK base station 30: ETRS89 (ETRF2000 realization) 31: NAD83(2011), North American Datum (2011) 32: NAD83(PA11), North American Datum, Pacific plate (2011) 33: NAD83(MA11), North American Datum, Marianas plate (2011) 34: GDA94(2010), Geocentric Datum of Australia (2010) 35: GDA2020, Geocentric Datum of Australia 2020 36: JGD2011, Japanese Geodetic Datum 2011 250: First user-defined datum 251: Second user-defined datum
NrSV	u1		255	Total number of satellites used in the PVT computation.
WACorrInfo	u1		0	Bit field providing information about which wide area corrections have been applied:
				Bit 0: set if orbit and satellite clock correction information is used Bit 1: set if range correction information is used Bit 2: set if ionospheric information is used Bit 3: set if orbit accuracy information is used (UERE/SISA) Bit 4: set if DO229 Precision Approach mode is active Bits 5-7: Reserved
ReferenceID	u2		65535	This field indicates the reference ID of the differential information used. In case of DGPS or RTK operation, this field is to be interpreted as the base station identifier. In SBAS operation, this field is to be interpreted as the PRN of the geostationary satellite used (from 120 to 158). If multiple base stations or multiple geostationary satellites are used the value is set to 65534.
MeanCorrAge	u2	0.01 s	65535	In case of DGPS or RTK, this field is the mean age of the differential corrections. In case of SBAS operation, this field is the mean age of the 'fast corrections' provided by the SBAS satellites. In case of PPP, this is the age of the last received clock or orbit correction message.
SignalInfo	u4		0	Bit field indicating the type of GNSS signals having been used in the PVT computations. If a bit i is set, the signal type having index i has been used. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.



Rev 1

Rev 2

AlertFlag	u1		0	Bit field indicating integrity related information:
				Bits 0-1: RAIM integrity flag: 0: RAIM not active (integrity not monitored) 1: RAIM integrity test successful 2: RAIM integrity test failed 3: Reserved
				Bit 2: set if integrity has failed as per Galileo HPCA (HMI Probability Computation Algorithm) Bit 3: set if Galileo ionospheric storm flag is active
				Bit 4: Reserved
				Bits 5-7: Reserved
NrBases	u1		0	Number of base stations used in the PVT computation.
PPPInfo	u2		0	Bit field containing PPP-related information:
		1 s		Bits 0-11: Age of the last seed, in seconds. The age is clipped to 4091s. This field must be ignored when the seed type is 0 (see bits 13-15 below). Bit 12: Reserved
				Bits 13-15: Type of last seed:
				O: Not seeded or not in PPP positioning mode Hanual seed Seeded from DGPS Seeded from RTKFixed
Latency	u2	0.0001 s	65535	Time elapsed between the time of applicability of the position fix and the generation of this SBF block by the receiver. This time includes the receiver processing time, but not the communication latency.
HAccuracy	u2	0.01 m	65535	2DRMS horizontal accuracy: twice the root-mean-square of the horizontal distance error. The horizontal distance between the true position and the computed position is expected to be lower than HAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m
VAccuracy	u2	0.01 m	65535	2-sigma vertical accuracy. The vertical distance between the true position and the computed position is expected to be lower than VAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m.
Misc	u1			Bit field containing miscellaneous flags:
				Bit 0: In DGNSS or RTK mode, set if the baseline points to the base station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the rover, unset if not or unknown. Bit 2: Proprietary.
				Bit 3: Proprietary.
				Bits 4-5: Proprietary.
				Bits 6-7: Flag indicating whether the marker position reported in this block is also the ARP position (i.e. whether the ARP-to-marker offset provided with the setAntennaOffset command is zero or not) 0: Unknown 1: The ARP-to-marker offset is zero 2: The ARP-to-marker offset is not zero
Padding	u1[]			Padding bytes, see 4.1.5

3



ExtEventPVTGeodetic	Number:	4038
	"OnChange"	interval: each time an external event is de- tected
		tecteu

This block contains the position, velocity and time (PVT) solution applicable at the time of an external event, in an ellipsoidal coordinate system.

This block has the same structure and description as the PVTGeodetic block, except that the TOW and WNc fields refer to the time at which the electrical transition on the event pin has been detected (with a millisecond resolution), and that the position is computed at the event time, taking into account a possible user-defined delay set by the **setEventParameters** command.

A user needing the sub-millisecond part of the event time must refer to the Offset field of the corresponding <code>ExtEvent</code> block. The corresponding <code>ExtEvent</code> block is the last of the <code>ExtEvent</code> blocks having been output by the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Estamal time atoms and 44.2
WNc	u2	1 week	65535	External time stamp, see 4.1.3
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and not computed).
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
Latitude	f8	1 rad	$-2 \cdot 10^{10}$	Latitude, from $-\pi/2$ to $+\pi/2$, positive North of Equator



Longitude	f8	1 rad	$-2 \cdot 10^{10}$	Longitude, from $-\pi$ to $+\pi$, positive East of Greenwich
Height	f8	1 m	−2·10 ¹⁰	Ellipsoidal height (with respect to the ellipsoid specified by Datum)
Undulation	f4	1 m	-2·10 ¹⁰	Geoid undulation. See the setGeoidUndulation command.
Vn	f4	1 m / s	−2·10 ¹⁰	Not applicable
Ve	f4	1 m / s	$-2 \cdot 10^{10}$	Not applicable
Vu	f4	1 m / s	-2·10 ¹⁰	Not applicable
COG	f4	1 degree		Course over ground: this is defined as the angle of the vehicle with respect to the local level North, ranging from 0 to 360, and increasing towards east. Set to the Do-Not-Use value when the speed is lower than 0.1m/s.
RxClkBias	f8	1 ms	-2·10 ¹⁰	Receiver clock bias relative to the GNSS system time reported in the $\texttt{TimeSystem}$ field. Positive when the receiver time is ahead of the system time. To transfer the receiver time to the system time, use: $t_{GPS/GST} = t_{rx} - \texttt{RxClkBias}$
RxClkDrift	f4	1 ppm	-2·10 ¹⁰	Receiver clock drift relative to the GNSS system time (relative frequency error). Positive when the receiver clock runs faster than the system time.
TimeSystem	u1		255	Time system of which the offset is provided in this sub-block: 0: GPS time 1: Galileo time 3: GLONASS time 4: BeiDou time 5: QZSS time
Datum	u1		255	This field defines in which datum the coordinates are expressed: 0: WGS84/ITRS 19: Datum equal to that used by the DGNSS/RTK base station 30: ETRS89 (ETRF2000 realization) 31: NAD83(2011), North American Datum (2011) 32: NAD83(PA11), North American Datum, Pacific plate (2011) 33: NAD83(MA11), North American Datum, Marianas plate (2011) 34: GDA94(2010), Geocentric Datum of Australia (2010) 35: GDA2020, Geocentric Datum of Australia 2020 36: JGD2011, Japanese Geodetic Datum 2011 250: First user-defined datum 251: Second user-defined datum
NrSV	u1		255	Total number of satellites used in the PVT computation.
WACorrInfo	u1		0	Bit field providing information about which wide area corrections have been applied:
				Bit 0: set if orbit and satellite clock correction information is used Bit 1: set if range correction information is used Bit 2: set if ionospheric information is used Bit 3: set if orbit accuracy information is used (UERE/SISA) Bit 4: set if DO229 Precision Approach mode is active Bits 5-7: Reserved
ReferenceID	u2		65535	This field indicates the reference ID of the differential information used. In case of DGPS or RTK operation, this field is to be interpreted as the base station identifier. In SBAS operation, this field is to be interpreted as the PRN of the geostationary satellite used (from 120 to 158). If multiple base stations or multiple geostationary satellites are used the value is set to 65534.
MeanCorrAge	u2	0.01 s	65535	In case of DGPS or RTK, this field is the mean age of the differential corrections. In case of SBAS operation, this field is the mean age of the 'fast corrections' provided by the SBAS satellites. In case of PPP, this is the age of the last received clock or orbit correction message.
SignalInfo	u4		0	Bit field indicating the type of GNSS signals having been used in the PVT computations. If a bit i is set, the signal type having index i has been used. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.



Rev 1

Rev 2

AlertFlag	u1		0	Bit field indicating integrity related information:
				Bits 0-1: RAIM integrity flag: 0: RAIM not active (integrity not monitored) 1: RAIM integrity test successful 2: RAIM integrity test failed 3: Reserved
				Bit 2: set if integrity has failed as per Galileo HPCA (HMI Probability Computation Algorithm) Bit 3: set if Galileo ionospheric storm flag is active
				Bit 4: Reserved
				Bits 5-7: Reserved
NrBases	u1		0	Number of base stations used in the PVT computation.
PPPInfo	u2		0	Bit field containing PPP-related information:
		1 s		Bits 0-11: Age of the last seed, in seconds. The age is clipped to 4091s. This field must be ignored when the seed type is 0 (see bits 13-15 below). Bit 12: Reserved
				Bits 13-15: Type of last seed:
				0: Not seeded or not in PPP positioning mode 1: Manual seed 2: Seeded from DGPS 3: Seeded from RTKFixed
Latency	u2	0.0001 s	65535	Time elapsed between the time of applicability of the position fix and the generation of this SBF block by the receiver. This time includes the receiver processing time, but not the communication latency.
HAccuracy	u2	0.01 m	65535	2DRMS horizontal accuracy: twice the root-mean-square of the horizontal distance error. The horizontal distance between the true position and the computed position is expected to be lower than HAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m
VAccuracy	u2	0.01 m	65535	2-sigma vertical accuracy. The vertical distance between the true position and the computed position is expected to be lower than VAccuracy with a probability of at least 95%. The value is clipped to 65534 =655.34m.
Misc	u1			Bit field containing miscellaneous flags:
				Bit 0: In DGNSS or RTK mode, set if the baseline points to the base station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the rover, unset if not or unknown. Bit 2: Proprietary.
				Bit 3: Proprietary.
				Bits 4-5: Proprietary.
				Bits 6-7: Flag indicating whether the marker position reported in this block is also the ARP position (i.e. whether the ARP-to-marker offset provided with the setAntennaOffset command is zero or not) 0: Unknown 1: The ARP-to-marker offset is zero 2: The ARP-to-marker offset is not zero
Padding	u1[]			Padding bytes, see 4.1.5

3




ExtEventBaseVectGeod	Number:	4217	
	"OnChange"	interval: each time an	external event is
		detected	

This block contains the relative position and orientation of one or more base stations at the time of an external event. The relative position is expressed in the East-North-Up directions.

This block has the same structure and description as the <code>BaseVectorGeod</code> block, except that the <code>TOW</code> and <code>WNc</code> fields refer to the time at which the electrical transition on the event pin has been detected (with a millisecond resolution), and that the position is computed at the event time, taking into account a possible user-defined delay set by the <code>setEventParameters</code> command.

A user needing the sub-millisecond part of the event time must refer to the Offset field of the corresponding ExtEvent block. The corresponding ExtEvent block is the last of the ExtEvent blocks having been output by the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	External time stamp, see 4.1.3
WNc	u2	1 week	65535	External time stamp, see 4.1.5
N	u1			Number of baselines for which relative position, velocity and direction are provided in this SBF block, i.e. number of <code>ExtEventVectorInfoGeod</code> sub-blocks. If N is 0, there are no baseline available for this epoch.
SBLength	u1	1 byte		Length of one sub-block
ExtEventVectorInfoGeod				A succession of N ExtEventVectorInfoGeod sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5



ExtEventVectorInfoGeod sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
NrSV	u1			Number of satellites for which corrections are available from the base station identified by the ReferenceID field.
Error	u1			PVT error code. The following values are defined: 0: No Error 1: Not enough measurements 2: Not enough ephemerides available 3: DOP too large (larger than 15) 4: Sum of squared residuals too large 5: No convergence 6: Not enough measurements after outlier rejection 7: Position output prohibited due to export laws 8: Not enough differential corrections available 9: Base station coordinates unavailable 10: Ambiguities not fixed and user requested to only output RTK-fixed positions
Mode	u1			Bit field indicating the GNSS PVT mode, as follows:
				Bits 0-3: type of PVT solution:
				0: No GNSS PVT available (the Error field indicates the cause of the absence of the PVT solution) 1: Stand-Alone PVT 2: Differential PVT 3: Fixed location 4: RTK with fixed ambiguities 5: RTK with float ambiguities 6: SBAS aided PVT 7: moving-base RTK with fixed ambiguities 8: moving-base RTK with float ambiguities 10: Precise Point Positioning (PPP) 12: Reserved Bits 4-5: Reserved Bit 6: Set if the user has entered the command setPVTMode, Static, , auto and the receiver is still in the process
				of determining its fixed position. Bit 7: 2D/3D flag: set in 2D mode (height assumed constant and
261	1			not computed).
Misc	u1			 Bit field containing miscellaneous flags: Bit 0: Set if the baseline points to the base station ARP. Unset if it points to the antenna phase center, or if unknown. Bit 1: Set if the phase center offset is compensated for at the rover (i.e. the baseline starts from the antenna ARP), unset if not or unknown. Bit 2: Proprietary.
				Bit 3: Proprietary.
				Bits 4-5: Proprietary.
				Bits 6-7: Reserved
DeltaEast	f8	1 m	-2·10 ¹⁰	East baseline component (from rover to base)
DeltaNorth	f8	1 m	−2·10 ¹⁰	North baseline component (from rover to base)
DeltaUp	f8	1 m	-2·10 ¹⁰	Up baseline component (from rover to base)
DeltaVe	f4	1 m / s	-2·10 ¹⁰	East velocity of base with respect to rover
DeltaVn	f4	1 m / s	-2·10 ¹⁰	North velocity of base with respect to rover
DeltaVu	f4	1 m / s	-2·10 ¹⁰	Up velocity of base with respect to rover
Azimuth	u2	0.01 degrees	65535	Azimuth of the base station (from 0 to 360° , increasing towards east)
Elevation	i2	0.01 degrees	-32768	Elevation of the base station (from -90° to 90°)
ReferenceID	u2			Base station ID
CorrAge	u2	0.01 s	65535	Age of the oldest differential correction used for this baseline computation.



SignalInfo	u4	Bit field indicating the GNSS signals for which differential corrections are available from the base station identified by ReferenceID. If bit i is set, corrections for the signal type having index i are available. The signal numbers are listed in section 4.1.10. Bit 0 (GPS-C/A) is the LSB of SignalInfo.
Padding	u1[]	Padding bytes, see 4.1.5



4.2.13 Differential Correction Blocks

DiffCorrIn	Number:	5919
	"OnChange"	interval: each time a RTCM or CMR message is received

The $\mbox{DiffCorrIn}$ block contains incoming RTCM or CMR messages. The length of the block depends on the message type and contents.

Parameter	Type	Units	Do-Not-Use	Description			
Sync1	c1			·			
Sync2	c1						
CRC	u2			Block Header, see 4.1.1			
ID	u2						
Length	u2	1 byte					
TOW	u4		4294967295				
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3			
Mode	u1			0: RTCMv2 1: CMRv2 2: RTCMv3 3: RTCMV (a proprietary variant of RTCM2) 4: SPARTN 5: Reserved			
Source	u1		255	Indicates the receiver connection from which the message has been received: 0: COM1 1: COM2 2: COM3 3: COM4 4: USB1 5: USB2 6: IP connection 7: SBF file 8: L-Band (message decoded by the built-in L-band demodulator) 9: NTRIP 10: OTG1 11: OTG2 12: Bluetooth 15: UHF modem 16: IPR connection 17: Direct call port 18: IPS connection			
If the Mode field is 0 the	en this	field is a	available:				
RTCM2Words	u4[<i>N</i>]			30-bit words of the RTCM2 message. The Data Word Length (number of 32 bit words) is variable and depends on the RTCM2 message contents. It can be computed by the following piece of C code: N = 2 + ((RTCM2Words[1]»9) & 0x1f); N can range from 2 to 33. The first two words are the RTCM2 message header and they are always present. Each of the words is organized as follows: Bits 0-5: 6 parity bits. They are provided for the sake of completeness. Parity doesn't need to be checked, since the DiffCorrIn block only contains valid words. Bits 6-29: 24 information-containing bits of the word. The first received bit is the MSB. Bits 30-31: bit 0 and 1 of the preceding word			
If the Mode field is 1 the	If the Mode field is 1 then this field is available:						
CMRMessage	u1[N]			N depends on the CMR message type.			
If the Mode field is 2 then this field is available:							



RTCM3Message	u1[<i>N</i>]		N depends on the RTCM 3 message type.			
If the Mode field is 3 then this field is available:						
RTCMVMessage	u1[<i>N</i>]		N depends on the RTCMV message type.			
	•		•			
Padding	u1[]		Padding bytes, see 4.1.5			



BaseStation	Number:	5949
	"OnChange"	interval: block generated each time a differential correc-
		tion message related to the base station coordi-
		nates is received

The BaseStation block contains the ECEF coordinates of the base station the receiver is currently connected to. This block helps users accessing the base station coordinates via SBF instead of having to decode the specific differential correction message (see the DiffCorrIn SBF block above).

The interpretation to give to the X, Y, Z ECEF coordinates is dependent on the value of the Source field:

Value of Source	Interpretation of X, Y, Z
0, 4 or 10	Coordinate of the L1 phase center
2 or 8	Antenna reference point
9	Proprietary

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	neceiver time stamp, see 4.1.3
BaseStationID	u2			The base station ID
BaseType	u1			Base station type: 0: Fixed 1: Moving (reserved for future use) 255: Unknown
Source	u1			Source of the base station coordinates: 0: RTCM 2.x (Msg 3) 2: RTCM 2.x (Msg 24) 4: CMR 2.x (Msg 1) 8: RTCM 3.x (Msg 1005 or 1006) 9: RTCMV (Msg 3) 10: CMR+ (Type 2)
Datum	u1		255	Not applicable
Reserved	u1			Reserved for future use, to be ignored by decoding software
Х	f8	1 m		Antenna X coordinate expressed in the datum specified by the <code>Datum</code> field
Y	f8	1 m		Antenna Y coordinate
Z	f8	1 m		Antenna Z coordinate
Padding	u1[]			Padding bytes, see 4.1.5



RTCMDatum	Number:	4049
	"OnChange"	interval: block generated each time a set of transformation
		parameters is received

This block reports the source and target datum names as transmitted in RTCM 3.x message types 1021 or 1022. It also reports the corresponding height and quality indicators.

If a service provider only sends out message types 1021 or 1022, this block is transmitted immediately after reception of MT1021 or MT1022. If message types 1023 or 1024 are also sent out, this block is transmitted after the reception of these messages and the QualityInd field is set accordingly.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5
SourceCRS	c1[32]			Name of the source Coordinate Reference System, right-padded with zeros.
TargetCRS	c1[32]			Name of the target Coordinate Reference System, right-padded with zeros.
Datum	u1			See the Datum field in the PosLocal and PosProjected SBF blocks.
				Datum is set to 255 if this SourceCRS/TargetCRS pair is currently not used by the receiver.
HeightType	u1			Height Indicator field from MT1021 and MT1022. This field indicates how to interpret the height reported in the PosLocal and the PosProjected SBF blocks: 0: Geometrical height 1: Physical height (height definition in target CRS) 2: Physical height (height definition in source CRS)
QualityInd	u1			Bit field indicating the maximum approximation error after applying the transformation: Bits 0-3: horizontal quality indicator: 0: Unknown quality 1: Quality better than 21 mm (from MT1021/1022) 2: Quality 21 to 50 mm (from MT1021/1022) 3: Quality 51 to 200 mm (from MT1021/1022) 4: Quality 201 to 500 mm (from MT1021/1022) 5: Quality 501 to 2000 mm (from MT1021/1022) 6: Quality 2001 to 5000 mm (from MT1021/1022) 7: Quality worse than 5001 mm (from MT1021/1022) 9: Quality 0 to 10 mm (from MT1023/1024) 10: Quality 11 to 20 mm (from MT1023/1024) 11: Quality 21 to 50 mm (from MT1023/1024) 12: Quality 51 to 100 mm (from MT1023/1024) 13: Quality 101 to 200 mm (from MT1023/1024) 14: Quality 201 to 500 mm (from MT1023/1024) 15: Quality worse than 501 mm (from MT1023/1024) 15: Quality indicator, same definition as bits 0-3.
Padding	u1[]			Padding bytes, see 4.1.5





4.2.14 L-Band Demodulator Blocks

LBandTrackerStatus	Number:	4201	
	"OnChange"	interval: 1s	

The ${\tt LBandTrackerStatus}$ block provides general information on the tracking status of the L-band signals.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5
N	u1			Number of L-band trackers for which data is provided in this SBF block, i.e. number of TrackData sub-blocks.
SBLength	u1	1 byte		Length of one sub-block
TrackData				A succession of N TrackData sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

TrackData sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
Frequency	u4	1 Hz	0	Nominal frequency of the beam for which data is provided in this sub-block.
Baudrate	u2	1 baud	0	Baudrate of the beam
ServiceID	u2			Service ID of the beam. Set to 0 for the LBAS1 beam. Set to 1 for the LBAS2 beam when received through an NTRIP connection.
				This field must be ignored if the Status field is set to anything else than 3 (Locked).
FreqOffset	f4	1 Hz	$-2 \cdot 10^{10}$	Frequency offset of the demodulator, if available
CN0	u2	0.01 dB-Hz	0	Current C/N ₀ value
AvgPower	i2	0.01 dB	-32768	Not applicable.
AGCGain	i1	1 dB	-128	L-band AGC gain, in dB.
Mode	u1			Current operation mode: 0: normal
Status	u1			Current status: 0: Idle 1: Search 2: FrameSearch 3: Locked
SVID	u1			Satellite ID, see 4.1.9
LockTime	u2	1 s		Lock time to the L-band signal, clipped to 65535 seconds.
Source	u1			L-band tracking module: 0: Unknown 1: Internal 2: LBR board 3: NTRIP. L-band data received over NTRIP. In that case, the other fields in this sub-block are not applicable and set to their Do-Not-Use value.
Padding	u1[]			Padding bytes, see 4.1.5

Rev 2 | Rev 1 |



LBAS1DecoderStatus	Number:	4202
	"OnChange"	interval: Block generated each time a status
		update is received from the LBAS1
		decoder

The LBAS1DecoderStatus block provides general information on the LBAS1 L-band decoder.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5
Reserved	u1[2]			Reserved for future use. to be ignored by decoding software
Status	u1			Status of the Decoder: 0: No Signal (more than 30 seconds no valid data) 1: Search 2: Locked 3: Locked w Error
Access	u1			Access status: 0: Access disabled 1: Access enabled
GeoGatingMode	u1			GeoGating mode 0: N/A 1: Non-maritime usage 2: Maritime and non-maritime usage 3: Coastal and non-maritime usage 4: 60 km nearshore and non-maritime usage
GeoGatingStatus	u1			GeoGating status.
Event	u4			Bit field indicating whether an event occurred previously. If this field is not equal to zero, at least one event has occurred. Bit 0: Beamtable Update
				Bit 1: Station List Update
				Bit 2: Access Changed
				Bit 3: Message Received
				Bit 4: Subscription Error
				Bits 5-31: Reserved
LeaseTime	u4	1 s	4294967295	Allocated lease time
LeaseRemaining	u4	1 s	4294967295	Remaining lease time
LocalAreaLat	i4	1.0/3600.0 degrees	-2147483648	Local area center latitude, positive North.
LocalAreaLon	i4	1.0/3600.0 degrees	-2147483648	Local area center longitude, positive East of Greenwich.
LocalAreaRadius	u2	1000 m	65535	Local area radius.
LocalAreaStatus	u1			Local area status: 0: Local area disabled 1: Waiting for position 16: Range check 129: User is in range 130: User is out of range 255: Position is too old
Reserved1	u1			Reserved for future use, to be ignored by decoding software.
SubscrEndYear	i1	1 year	-128	Subscription end date, year (2 digits). From 0 to 99.
SubscrEndMonth	i1	1 month	-128	Subscription end date, month. From 1 to 12.



Rev 1

SubscrEndDay	i1	1 day	-128	Subscription end date, day. From 1 to 31.
SubscrEndHour	i1	1 hour	-128	Subscription end date, hour (UTC). From 0 to 23.
PAC	c1[20]			Product activation code, right padded with zeros.
VelocityLimit	u1	1 m / s		Speed Gating : Velocity Limit.
SpeedGatingStatus	u1			Speed Gating status: 0: Speed Gating disabled 1: Waiting for velocity 129: User is in speed limit 130: Speed limit exceeded 255: Velocity error
Padding	u1[]			Padding bytes, see 4.1.5



LBAS1Messages	Number:	4203		
	"OnChange"	interval: Block generated	each time	an over-the-air
		message is recei	ved by the L	BAS1 decoder

The ${\tt LBAS1Messages}$ block contains the over-the-air message decoded from LBAS1.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	inceiver time stamp, see 4.1.3
MessageLength	u2	1 byte		Length of the message in this block. Maximum message length is 512 bytes
Message	c1[MessageLength]			Over-The-Air message
Padding	u1[]			Padding bytes, see 4.1.5



LBandBeams	Number:	4204
	"OnChange"	interval: Block generated each time beam status data is de-
		coded

This block contains the name, longitude and beam frequency of the L-band geostationary satellites known by the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week		Neceiver time stamp, see 4.1.5
N	u1			Number of L-band beams for which data is provided in this SBF block, i.e. number of BeamInfo sub-blocks.
SBLength	u1	1 byte		Length of one sub-block
BeamInfo				A succession of N BeamInfo sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

BeamInfo sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
SVID	u1			SVID associated to the satellite for which information is provided in this sub-block. SVID ranges from 107 to 119. See also section 4.1.9.
SatName	c1[9]			Satellite Name, right padded with zeros
SatLongitude	i2	0.01 degrees	-32768	Satellite Longitude (positive east of Greenwich)
BeamFreq	u4	1 Hz	0	L-band beam center frequency
Padding	u1[]			Padding bytes, see 4.1.5



4.2.15 Status Blocks

ChannelStatus	Number:	4013
	"OnChange"	interval: default PVT output rate (see 4.1.8)

This block describes the current satellite allocation and tracking status of the active receiver channels. Active channels are channels to which a satellite has been allocated.

This block uses a two-level sub-block structure analogous to that of the MeasEpoch block. For each active channel, a ChannelSatInfo sub-block contains all satellite-dependent information such as health, azimuth and elevation. Each of these sub-blocks contains N2 ChannelStateInfo sub-blocks, N2 being the number of active antennas in a given channel (for single-antenna receivers, N2 is one). The ChannelStateInfo reports information such as the tracking status and PVT usage of a given signal type tracked on a given antenna.

Inactive channels are not contained in the Channel Status block.

Health, tracking and PVT status fields are available for each satellite. These status fields consist of a sequence of up to 8 two-bit fields. Each 2-bit field contains the status of one of the signals transmitted by the satellite. The position of the 2 bits corresponding to a given signal is dependent on the constellation, but is otherwise fixed. It is indicated in the tables below.

GPS:															
Reserv	ed	Rese	erved	L'	1C	L	.5	l	_2C	F	P2(Y)	P1	l(Y)		L1CA
15 14	1	13	12	11	10	9	8	7	6	5	4	3	2	1	0
GLONAS	GLONASS:														
Reserv	1	Rese	erved	Rese	erved	L	.3	L	2CA		L2P	L	1P		L1CA
15 14	1	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Galileo:															
Reserv	ed	E5-Al	tBOC	E	5b	E	5a	E	6BC		E6A	L1	BC		L1A
15 14	4	13	12	11	10	9	8	7	6	5	4	3	2	1	0
SBAS:															
Reserv	ed	Rese	erved	Rese	erved	Rese	erved	Res	erved	Re	served	[_5		L1
15 14	4	13	12	11	10	9	8	7	6	5	4	3	2	1	0
BeiDou:															
Reserv		Rese	erved	B:	2b	B	2a	E	31C		B3I	B	32I		B1I
15 14	4	13	12	11	10	9	8	7	6	5	4	3	2	1	0
QZSS:															
L5S		L1	СВ	L	1S	L	1C	1	L6		L5	L	2C		L1CA
15 14	4	13	12	11	10	9	8	7	6	5	4	3	2	1	0
NavIC/IF	SVIC	ς.				•			•		•				•
Reserv	- 1		erved	Rese	rved	Rese	erved	Res	erved	Re	served	Rese	erved		L5
15 14	4	13	12	11	10	9	8	7	6	5	4	3	2	1	0



Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	Neceiver time staffip, see 4.1.5	
N	u1			Number of channels for which status are provided in this SBF block, i.e. number of ChannelSatInfo sub-blocks. If N is 0, there are no active channels available for this epoch.	
SB1Length	u1	1 byte		Length of a ChannelSatInfo sub-block, excluding the nested ChannelStateInfo sub-blocks	
SB2Length	u1	1 byte		Length of a ChannelStateInfo sub-block	
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software	
SatInfo				A succession of N ChannelSatInfo sub-blocks, see definition below	
Padding	u1[]			Padding bytes, see 4.1.5	

ChannelSatInfo sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
SVID	u1			Satellite ID, see 4.1.9
FreqNr	u1		0	For GLONASS FDMA signals, this is the frequency number, with an offset of 8. It ranges from 1 (corresponding to an actual frequency number of -7) to 21 (corresponding to an actual frequency number of 13). Otherwise, ${\tt FreqNr}$ is reserved and must be ignored by the decoding software.
Reserved1	u1[2]			Reserved for future use, to be ignored by decoding software
Azimuth/RiseSet	u2			bit field:
		1 degree	511	Bits 0-8: Azimuth [0,359]. 0 is North, and Azimuth increases towards East. Bits 9-13: Reserved
			3	Bits 14-15: Rise/Set Indicator:
				0: Satellite setting 1: Satellite rising 3: Elevation rate unknown
HealthStatus	u2			Sequence of 2-bit health status fields, each of them taking one of the following values: 0 : health unknown, or not applicable 1 : healthy 3 : unhealthy
				The 2-bit health status is a condensed version of the health status as sent by the satellite. For SBAS, the health status is set from the almanac data (MT17).
Elevation	i1	1 degree	-128	Elevation [-90,90] relative to local horizontal plane
N2	u1			Number of ChannelStateInfo blocks following this ChannelSatInfo block. There is one ChannelStateInfo subblock per antenna.
RxChannel	u1			Channel number, see section 4.1.11.
Reserved2	u1			Reserved for future use, to be ignored by decoding software.
Padding	u1[]			Padding bytes, see 4.1.5
StateInfo				A succession of N2 Channel State Info sub-blocks, see definition below





ChannelStateInfo sub-block definition:

Parameter	Туре	Units	Description
Antenna	u1		Antenna number (0 for main antenna)
Reserved	u1		Reserved for future use, to be ignored by decoding software
TrackingStatus	u2		Sequence of 2-bit tracking status fields, each of them taking one of the following values: 0: idle or not applicable 1: Search 2: Sync 3: Tracking
PVTStatus	u2		Sequence of 2-bit PVT status fields, each of them taking one of the following values: 0: not used 1: waiting for ephemeris 2: used 3: rejected
PVTInfo	u2		Internal info
Padding	u1[]		Padding bytes, see 4.1.5



ReceiverStatus	Number:	4014	
	"OnChange"	interval: 1s	

The ReceiverStatus block provides general information on the status of the receiver.

Parameter	Туре	Units	Do-Not-Use	Description				
Sync1	c1							
Sync2	c1							
CRC	u2			Block Header, see 4.1.1				
ID	u2							
Length	u2	1 byte						
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3				
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5				
CPULoad	u1	1 %	255	Load on the receiver's CPU. The load should stay below 80% in normal operation. Higher loads might result in data loss.				
ExtError	u1			Bit field reporting external errors, i.e. errors detected in external data. Upon detection of an error, the corresponding bit is set for a duration of one second, and then resets. Bit 0: SISERROR: set if a violation of the signal-in-space ICD has been detected for at least one satellite while that satellite is reported as healthy. Use the command "lif,SisError" for details. Bit 1: DIFFCORRERROR: set when an anomaly has been detected in an incoming differential correction stream, causing the receiver to fail to decode the corrections. Use the command "lif,DiffCorrError" for details. Bit 2: EXTSENSORERROR: set when a malfunction has been detected on at least one of the external sensors connected to the receiver. Use the command "lif, ExtSensorError" for details. Bit 3: SETUPERROR: set when a configuration/setup error has been detected. An example of such error is when a remote NTRIP Caster is not reachable. Use the command "lif, SetupError" for details. Bits 4-7: Reserved				
UpTime	u4	1 s		Bits 4-7: Reserved Number of seconds elapsed since the start-up of the receiver, or since the last reset.				



RxState	u4	Bit field indicating the status of key components of the receiver:
		Bit 0: Reserved
		Bit 1: ACTIVEANTENNA: this bit is set when an active GNSS antenna is sensed, i.e. when current is drawn from the antenna connector. In dual-antenna receivers, this bit alternatively reports the status of the main and the auxiliary antenna in intervals of 10 seconds. For example, if only the main antenna is drawing current, the bit will be cyclically set for 10s and unset for 10s.
		Bit 2: EXT_FREQ: this bit is set if an external frequency reference is detected at the 10 MHz input, and cleared if the receiver uses its own internal clock.
		Bit 3: EXT_TIME: this bit is set if a pulse has been detected on the PPS IN connector.
		Bit 4: WNSET: see corresponding bit in the SyncLevel field of the ReceiverTime block.
		Bit 5: TOWSET: see corresponding bit in the SyncLevel field of the ReceiverTime block.
		Bit 6: FINETIME: see corresponding bit in the SyncLevel field of the ReceiverTime block.
		Bit 7: INTERNALDISK_ACTIVITY: this bit is set for one second each time data is logged to the internal disk (DSK1). If the logging rate is larger than 1 Hz, set continuously.
		Bit 8: INTERNALDISK_FULL: this bit is set when the internal disk (DSK1) is full. A disk is full when it is filled to 95% of its total capacity.
		Bit 9: INTERNALDISK_MOUNTED: this bit is set when the internal disk (DSK1) is mounted.
		Bit 10: INT_ANT: this bit is set when the GNSS RF signal is taken from the internal antenna input, and cleared when it comes from the external antenna input (only applicable on receiver models featuring an internal antenna input).
		Bit 11: REFOUT_LOCKED: if set, the 10-MHz frequency provided at the REF OUT connector is locked to GNSS time. Otherwise it is free-running.
		Bit 12: Reserved
		Bit 13: EXTERNALDISK_ACTIVITY: this bit is set for one second each time data is logged to the external disk (DSK2). If the logging rate is larger than 1 Hz, set continuously.
		Bit 14: EXTERNALDISK_FULL: this bit is set when the external disk (DSK2) is full. A disk is full when it is filled to 95% of its total capacity.
		Bit 15: EXTERNALDISK_MOUNTED: this bit is set when the external disk (DSK2) is mounted.
		Bit 16: PPS_IN_CAL: this bit is set when PPS IN delay calibration is ongoing. Only applicable to PolaRx5TR receivers.
		Bit 17: DIFFCORR_IN: this bit is set for one second each time differential corrections are decoded. If the input rate is larger than 1 Hz, set continuously.
		Bit 18: INTERNET: this bit is set when the receiver has internet access. If not set, there is either no internet access, or the receiver could not reliably determine the status.
		Bits 19-31: Reserved



Rev 1

RxError	u4				ndicating whether an error occurred previously. If this field is to zero, at least one error has been detected.
				Bit 0:	Reserved
				Bit 1:	Reserved
				Bit 2:	Reserved
				Bit 3:	SOFTWARE: set upon detection of a software warning or error. This bit is reset by the command "lif, error".
				Bit 4:	WATCHDOG: set when the watchdog expired at least once since the last power-on.
				Bit 5:	ANTENNA: set when antenna overcurrent condition is detected.
				Bit 6:	CONGESTION: set when an output data congestion has been detected on at least one of the communication ports of the receiver during the last second.
				Bit 7:	Reserved
				Bit 8:	MISSEDEVENT: set when an external event congestion has been detected during the last second. It indicates that the receiver is receiving too many events on its EVENTx pins.
				Bit 9:	CPUOVERLOAD: set when the CPU load is larger than 90%.
				Bit 10:	INVALIDCONFIG: set if one or more configuration file (e.g. permissions) is invalid or absent.
				Bit 11:	OUTOFGEOFENCE: set if the receiver is currently out of its permitted region of operation (geofencing).
				Bit 12:	Reserved
				Bit 13:	Reserved
				Bit 14:	Reserved
				Bit 15:	Reserved
				Bit 16:	Reserved
				Bits 17-31	: Reserved
N	u1			Number o	of AGCState sub-blocks this block contains.
SBLength	u1	1 byte		Length of	a AGCState sub-block.
CmdCount	u1		0		d cyclic counter, incremented each time a command is entered ges the receiver configuration. After the counter has reached lets to 1.
Temperature	u1	1 °C	0		remperature with an offset of 100. Remove 100 to get the temin degree Celsius.
AGCState				A succession	on of N AGCState sub-blocks, see definition below
Padding	u1[]			Padding b	oytes, see 4.1.5

AGCState sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description		
FrontEndID	u1			Bit field indicating the frontend code and antenna ID:		
				Bits 0-4: fronter	nd code:	
				0: 1: 2: 3: 4: 5: 6: 7: 8: 9:	GPSL1/E1 GLOL1 E6 GPSL2 GLOL2 L5/E5a E5b/B2I E5(a+b) Combined GPS/GLONASS/SBAS/Galileo L1 Combined GPS/GLONASS L2	
				10:	MSS/L-band	
				11: 12:	B1I B3I	
				13:	S-band	
				Bits 5-7: Antenr	a ID: 0 for main, 1 for Aux1 and 2 for Aux2	



Gain	i1	1 dB	-128	AGC gain, in dB.
				The Do-Not-Use value is used to indicate that the frontend PLL is not locked.
SampleVar	u1			Normalized variance of the IF samples. The nominal value for this variance is 100.
BlankingStat	u1	1 %		Current percentage of samples being blanked by the pulse blanking unit. This field is always 0 for receiver without pulse blanking unit.
Padding	u1[]			Padding bytes, see 4.1.5



SatVisibility	Number:	4012	
	"OnChange"	interval: 1s	

This block contains the azimuth and elevation of all the satellites above the horizon for which the ephemeris or almanac is available.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5	
N	u1			Number of satellites for which information is provided in this SBF block, i.e. number of SatInfo sub-blocks.	
SBLength	u1	1 byte		Length of one SatInfo sub-block	
SatInfo				A succession of N SatInfo sub-blocks, see definition below	
Padding	u1[]			Padding bytes, see 4.1.5	

SatInfo sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
SVID	u1			Satellite ID, see 4.1.9
FreqNr	u1		0	For GLONASS FDMA signals, this is the frequency number, with an offset of 8. It ranges from 1 (corresponding to an actual frequency number of -7) to 21 (corresponding to an actual frequency number of 13). Otherwise, ${\tt FreqNr}$ is reserved and must be ignored by the decoding software.
Azimuth	u2	0.01 degrees	65535	Azimuth. 0 is North, and azimuth increases towards East.
Elevation	i2	0.01 degrees	-32768	Elevation relative to local horizontal plane.
RiseSet	u1			Rise/set indicator: 0: satellite setting 1: satellite rising 255: elevation rate unknown
SatelliteInfo	u1			Satellite visibility info based on: 1: almanac 2: ephemeris 255: unknown
Padding	u1[]			Padding bytes, see 4.1.5



InputLink	Number:	4090	
	"OnChange"	interval: 1s	

The InputLink block reports statistics of the number of bytes and messages received and accepted on each active connection descriptor.


Per connection descriptor, the receiver maintains two byte counters (NrBytesReceived and NrBytesAccepted) and two message counters (NrMsgReceived and NrMsgAccepted), which are reported in the sub-blocks. These counters provide useful information on the quality of the transmission link, and of the bandwidth efficiency.

These counters (as well as the age of the last message) are reset simultaneously on the following events:

- start-up of the receiver
- overflow of one of the counters
- change of input type
- deactivation of a connection descriptor, e.g. on disconnection of USB or IP ports.

There is one sub-block per connection descriptor for which statistics is available.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		1
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N	u1			Number of connection descriptors for which communication link statistics are included
SBLength	u1	1 byte		Length of one InputStatsSub sub-block.
InputStats				A succession of N InputStatsSub sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5



InputStatsSub sub-block definition:

Parameter	Туре	Units	Do-Not-Use		Description	
CD	u1			Identifier	of the connection to which this information app	olies:
				Value of CD	Connection type	Example
				0-31	COMx, with x=CD	1: COM1
				32-47	USBx, with x=CD-32	33: USB1
				48-63	OTGx, with x=CD-48	49: OTG1
				64-95	IPx, with x=CD-54	64:IP10
				96-127	DSKx, with <i>x</i> =CD-96	97:DSK1
				128-159	NTRx, with <i>x</i> =CD-128 (NTRIP connections)	129:NTR1
				160-191	IPSx, with <i>x</i> =CD-160 (IP server connections)	161:IPS1
				192	BT01 (Bluetooth connection)	
				193	BT02 (Bluetooth connection)	
				196	UHF1 (UHF Modem)	
				200-205	IPRx, with x =CD-200 (IP receive connections)	201:IPR1
				210	DCL1 (cellular data-call connection)	
				214	CAN1 (CAN stream interface)	
				215-219	Reserved	
				220	SPI1 (SPI interface)	
				221-255	Reserved	
	u1			Type of d		
				1: D 32: Cl 33: Sl 34: A: 35: R 36: Cl 40: B 64: N 96: R 97: R 98: Cl 99: R 100: Sl 111: ra 111: ra 112: ra 112: ra 112: ra 121: ra 122: R 129: R 130: R	BMP aw LBAS1 from e.g. NTRIP aw LBAS2 from e.g. NTRIP aw LBAND data from Beam1 aw LBAND data from Beam2 aw LBAND data from Beam3 aw LBAND data from Beam4 eserved eserved eserved BG (IMU sensor) eserved eserved eserved eserved eserved eserved eserved	
AgeOfLastMessage	u2	1 s	65535		e last accepted message.	
					is older than 65534s, it is clipped to 65534s.	
NrBytesReceived	u4	1 byte	4294967295	Total nun	nber of bytes received ⁽¹⁰⁾	



NrBytesAccepted	u4	1 byte	Total number of bytes $^{(10)}$ in messages that passed the check for this type of input (CRC, parity check,).
			The ratio of NrBytesAccepted to NrBytesReceived gives an indication of the quality of the communication link.
NrMsgReceived	u4	1 message	Total number of messages of type Type received.
NrMsgAccepted	u4	1 message	Total number of messages of type \mathtt{Type} that were interpreted and used by the receiver.
			The ratio of NrMsgAccepted to NrMsgReceived gives an indication of the bandwidth usage efficiency
Padding	u1[]		Padding bytes, see 4.1.5

 $^{^{(10)}\,\,}$ Note that, for RTCM 2.x, one 8-bit byte contains 6 RTCM data bits.



OutputLink Nun	nber:	4091
"On	Change " interval:	:1s

The OutputLink block reports statistics of the number of bytes sent on each active connection descriptor.


Per connection descriptor, the receiver maintains two byte counters <code>NrBytesProduced</code> and <code>NrBytesSent</code>, which are reported in the sub-block. They provide an indication of the amount of data output and data lost on a given connection.

These counters are reset simultaneously on the following events:

- start-up of the receiver
- overflow of one of the counters
- deactivation of a connection descriptor, e.g. on disconnection of USB or IP ports
- · change of COM port settings.

There is one <code>OutputStatsSub</code> sub-block per connection descriptor for which statistics is available. Each <code>OutputStatsSub</code> sub-block contains a number of <code>OutputTypeSub</code> sub-blocks. These sub-blocks indicate which data type has been output through the connection in question during the last second. If no output happened during the last second, there is no <code>OutputTypeSub</code> sub-block.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	neceiver time stamp, see 4.1.5	
N1	u1			Number of OutputStatsSub sub-blocks in this OutputLink block.	
SB1Length	u1	1 byte		Length of an OutputStatsSub sub-block, excluding the nested OutputTypeSub sub-block	
SB2Length	u1	1 byte		Length of an OutputTypeSub sub-block	
Reserved	u1[3]			Reserved for future use	
OutputStats				A succession of N1 OutputStatsSub sub-blocks, see definition below	
Padding	u1[]			Padding bytes, see 4.1.5	



OutputStatsSub sub-block definition:

Parameter	Туре	Units	Description		
CD	u1		Identifier	of the connection to which this information applies:	
			Value of	Connection type	Example
			CD		
			0-31	COMx, with <i>x</i> =CD	1: COM1
			32-47	USBx, with x=CD-32	33: USB1
			48-63	OTGx, with x=CD-48	49: OTG1
			64-95	IPx, with x=CD-54	64:IP10
			96-127	DSKx, with x=CD-96	97:DSK1
			128-159	NTRx, with <i>x</i> =CD-128 (NTRIP connections)	129:NTR1
			160-191	IPSx, with x =CD-160 (IP server connections)	161:IPS1
			192	BT01 (Bluetooth connection)	
			193	BT02 (Bluetooth connection)	
			196	UHF1 (UHF Modem)	
			200-205	IPRx, with <i>x</i> =CD-200 (IP receive connections)	201:IPR1
			210	DCL1 (cellular data-call connection)	
			214	CAN1 (CAN stream interface)	
			215-219	Reserved	
			220	SPI1 (SPI interface)	
			221-255	Reserved	
N2	u1			of OutputTypeSub sub-blocks included at the endtatsSub sub-block	d of this
AllowedRate	u2	1 kbyte / s	Maximun	n datarate recommended on this connection	
NrBytesProduced	u4	1 byte	Total nun	nber of bytes produced by the receiver. See also the <code>NrBytes</code>	Sent field.
NrBytesSent	u4	1 byte	Total nur errors).	nber of bytes actually sent (i.e. without congestions or tra	ansmission
			The ratio	of NrBytesSent to NrBytesProduced gives an indicat	ion of the
			amount c	f bandwidth overload.	
				Sent and NrBytesProduced are 32-bit counters. If on both counters are reset to zero.	e of them
NrClients	u1		can only	of clients currently connected to this connection. Most connesserve one client at a time, but each IP server (IPS) port can sultaneous clients.	
				t when NrClients is more than one, the fields NrBytes rtesSent are the number of bytes produced and sent to each	
Reserved	u1[3]		Reserved for future use		
Padding	u1[]		Padding b	oytes, see 4.1.5	
OutputType			A successi	on of N2 OutputTypeSub sub-blocks, see definition below	



${\tt OutputTypeSub} \ \ \textbf{sub-block definition:}$

Parameter	Туре	Units	Description
Туре	u1		Type of data: 0: none 1: DaisyChain (includes "echo" messages) 32: CMD 33: SBF 34: AsciiDisplay (see setDataInOut command) 35: RINEX 36: CGGTTS 40: BINEX 64: NMEA 96: RTCMv2 97: RTCMv3 98: CMRv2 99: RTCMV (a proprietary variant of RTCMv2) 118: raw LBAND data from Beam1 119: raw LBAND data from Beam2 120: raw LBAND data from Beam3 121: raw LBAND data from Beam4
Percentage	u1	1 %	Percentage of the produced bytes that belong to this type (during the last second)
Padding	u1[]		Padding bytes, see 4.1.5



NTRIPClientStatus	Number:	4053	
	"OnChange"	interval: 1s	

This block reports the current status of the NTRIP client connections.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Neceiver time stamp, see 4.1.5
N	u1			Number of NTRIP client connections for which status is provided in this block, i.e. number of NTRIPClientConnection sub-blocks.
SBLength	u1	1 byte		Length of one NTRIPClientConnection sub-block
NTRIPClientConnection				A succession of N NTRIPClientConnection sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

NTRIPClientConnection sub-block definition:

Parameter	Туре	Units	Description
CDIndex	u1		Index of the NTRIP connection (1 for NTR1, 2 for NTR2, etc) for which status is provided in this sub-block.
Status	u1		NTRIP client status: 0: Connection disabled 1: Initializing 2: Running, differential corrections are being received and the link statistics is available in the InputLink block. 3: Error detected, the error code is provided in the next field. 4: Retrying, client encountered an error, we are trying to reconnect. The error code is provided in the next field. 5: Disabled since the settings are a duplicate of another active NTRIP connection.
ErrorCode	u1		NTRIP error code: 0: No error 1: Initialization error (e.g. source table retrieval failure) 2: Authentication error 3: Connection error 4: Mountpoint does not exist 5: Mountpoint unavailable 6: Waiting for GGA 7: GGA sending disabled when required by mountpoint 8: Resolving host failed 9: Out of region 10: TLS setup error 11: TLS handshake error 12: TLS fingerprint error 13: TLS time not known 254: Unknown error
Info	u1		Bit field indicating miscellaneous info about the Connection status: Bit 0: TLS was used to make secure NTRIP connection if this bit is set Bits 1-7: Reserved
Padding	u1[]		Padding bytes, see 4.1.5



NTRIPServerStatus	Number:	4122	
	"OnChange"	interval: 1s	

This block reports the current status of the NTRIP server connections.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N	u1			Number of NTRIP server connections for which status is provided in this block, i.e. number of NTRIPServerConnection sub-blocks.
SBLength	u1	1 byte		Length of one NTRIPServerConnection sub-block
NTRIPServerConnection				A succession of N NTRIPServerConnection sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

NTRIPServerConnection sub-block definition:

Parameter	Туре	Units	Description			
CDIndex	u1		Index of the NTRIP connection (1 for NTR1, 2 for NTR2, etc) for which status is provided in this sub-block.			
Status	u1		NTRIP server status: 0: Connection disabled 1: Initializing 2: Running, differential corrections are being sent and the link statistics is as able in the OutputLink block. 3: Error detected, the error code is provided in the next field. 4: Error detected. Currently trying to reconnect. The error code is provided in next field. 5: Disabled since the settings are a duplicate of another active NTRIP connections.			
ErrorCode	u1		NTRIP error code: 0: No error 1: Initialization error 2: Authentication error 3: Connection error 4: Mountpoint does not exist 5: Configuration conflict error 6: Resolving host failed 7: TLS setup error 8: TLS handshake error 9: TLS fingerprint error 10: TLS time not known 254: Unknown error			
Info	u1		Bit field indicating miscellaneous info about the Connection status: Bit 0: TLS was used to make secure NTRIP connection if this bit is set Bits 1-7: Reserved			
Padding	u1[]		Padding bytes, see 4.1.5			



IPStatu	s Number:	4058
	"OnChange"	interval: output each time one or more IP parameters change

This block contains information on the receiver's Ethernet interface (hostname, IP address, gateway, netmask and MAC address).

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	neceiver time stamp, see 4.1.5
MACAddress	u1[6]			MAC address. The first byte corresponds to the MSB of the address.
IPAddress	u1[16]		All elements set to 0	IP address. For future upgradability, this field can contain a 128-bit IPv6 address. In the current firmware version, the first 12 bytes are always set to 0, and the last 4 bytes contain the IPv4 IP address, or are set to zero if the IP address is not known or not applicable.
Gateway	u1[16]		All elements set to 0	Gateway address. For future upgradability, this field can contain a 128-bit IPv6 address. In the current firmware version, the first 12 bytes are always set to 0, and the last 4 bytes contain the IPv4 IP address, or are set to zero if the gateway address is not known or not applicable.
Netmask	u1		255	Number of bits used to identify the network (CIDR notation).
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software.
HostName	c1[32]			Receiver hostname on the Ethernet interface, or empty if not known.
Padding	u1[]			Padding bytes, see 4.1.5



WiFiAPStatus	Number:	4054	
	"OnChange"	interval: 1s	

This block contains the IP address of the receiver when configured in WiFi access point. It also contains the list of all connected clients.

The current WiFi mode is reported in the Mode argument. When the receiver is configured in WiFi client mode or when WiFi is disabled, many fields are not applicable and are set to their Do-Not-Use value.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5
N	u1			Number of WiFi clients currently connected to the receiver.
SBLength	u1	1 byte		Length of one WiFiClient sub-block
APIPAddress	u1[16]			IP address of the WiFi access point. For future upgradability, this field can contain a 128-bit IPv6 address. In the current firmware version, the first 12 bytes are always set to 0, and the last 4 bytes contain the IPv4 IP address, or are set to zero if the IP address is not known or not applicable.
Mode	u1			WiFi mode: 0: WiFi disabled 1: WiFi enabled in access point mode 2: WiFi enabled in client mode
Hotspot	u1			WiFi hotspot: 0: Hotspot disabled 1: Hotspot enabled and no Internet access 2: Hotspot enabled and Internet access 255: Hotspot not supported
Reserved	u1[2]			Reserved for future use, to be ignored by decoding software
WiFiClient				A succession of N WiFiClient sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

WiFiClient sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description
ClientHostName	c1[32]			Hostname of a WiFi client connected to the receiver, or empty if not known.
ClientMACAddress	u1[6]			MAC address of a WiFi client connected to the receiver. The first byte corresponds to the MSB of the address.
ClientIPAddress	u1[16]			IP address of a WiFi client connected to the receiver. For future upgradability, this field can contain a 128-bit IPv6 address. In the current firmware version, the first 12 bytes are always set to 0, and the last 4 bytes contain the IPv4 IP address, or are set to zero if the IP address is not known or not applicable.
Padding	u1[]			Padding bytes, see 4.1.5



WiFiClientStatus	Number:	4096	
	"OnChange"	interval: 1s	

This block contains WiFi status information of the receiver when configured in WiFi client mode.

When the receiver is not configured in WiFi client mode, many fields are not applicable and are set to their Do-Not-Use value.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	receiver time stamp, see 4.1.5
SSID_AP	c1[32]			SSID of the access point the receiver is currently connected to. Empty when not connected.
IPAddress	u1[16]		All elements set to 0	IP address of the receiver as WiFi client. For future upgradability, this field can contain a 128-bit IPv6 address. In the current firmware version, the first 12 bytes are always set to 0, and the last 4 bytes contain the IPv4 IP address. All bytes are set to zero if the IP address is not applicable or not known yet (e.g. when the receiver is currently obtaining its IP address from the access point).
APFrequency	u1			The frequency of the WIFI access point the receiver is connected to. Possible WiFi AP Frequencies: 0: Unknown frequency of access point 1: 2.4GHz 2: 5GHz
SigLevel	i1	1 dBm	-128	WiFi signal power level
Status	u1			Bit field: Bits 0-3: WiFi client connection status: 0: Not connected, see the ErrorCode field for reason 1: Connecting 2: Connected Bits 4-7: Reserved
ErrorCode	u1			WiFi client error code: 0: No error 1: WiFi disabled or not in client mode 2: No reachable WiFi access point found 3: No known access point in reach (use the exeAddwiFiAccessPoint command to add an access point to the list of known access points) 4: Known access points were found but the receiver could not connect to them 5: Failed to connect to access point, wrong credentials
Padding	u1[]			Padding bytes, see 4.1.5



DynDNSStatus	Number:	41	05
	"OnChange"	interval: 1s	5

This block contains dynamic DNS (DynDNS) status information.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Descriver time stamp, see 4.1.2
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
Status	u1			DynDNS status: 0: DynDNS disabled 1: Updating IP address 2: IP address updated at the DynDNS server. DynDNS is ready to use. 254: Error detected, the error code is provided in the next field.
ErrorCode	u1			DynDNS error code: 0: No error 1: Unspecified error 2: Abusive update 3: User name and password mismatch 4: Not a credited user 5: Hostname is not a fully-qualified domain name 6: Hostname does not exist in this user account 7: Hostname blocked for update abuse 8: Bad agent 9: DNS error 10: DynDNS server problem or maintenance 11: DynDNS server not reachable
IPAddress	u1[16]		All elements set to 0	IP address that has been registered at the DynDNS server. For future upgradability, this field can contain a 128-bit IPv6 address. In the current firmware version, the first 12 bytes are always set to 0, and the last 4 bytes contain the IPv4 IP address, or are set to zero if the IP address is not known or not applicable (e.g. because registration failed).
Padding	u1[]			Padding bytes, see 4.1.5



PowerStatus	Number:	4101	
	"OnChange"	interval: 1s	

This block contains information on the power supply (source and voltage).

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week			
PowerInfo	u2			Bit field:	
		0.025 V	4095	Bits 0-3: Current power source: 0: Unknown 1: Vin: DC supply through the Vin pins 2: PoE: Power over Ethernet 3: USB: Supply through VBUS 4: Battery: Supply from battery Bits 4-15: Voltage at the Vin pins	
Padding	u1[]			Padding bytes, see 4.1.5	



QualityInd	Number:	4082	
	"OnChange"	interval: 1s	

The QualityInd block contains quality indicators for the main functions of the receiver. Each quality indicator is a value from 0 to 10, 0 corresponding to poor quality and 10 to very high quality.

Туре	Units	Do-Not-Use	Description
c1			
c1			
u2			Block Header, see 4.1.1
u2			
u2	1 byte		
u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
u2	1 week	65535	neceiver time stamp, see 4.1.5
u1			Number of quality indicators contained in this block
u1			Reserved for future use, to be ignored by decoding software.
u2[N]			N successive quality indicators, coded as follows:
		All elements set to 15	Bits 0-7: Quality indicator type: 0: Overall quality 1: GNSS signals from main antenna 2: GNSS signals from aux1 antenna 11: RF power level from the main antenna 12: RF power level from the aux1 antenna 21: CPU headroom 25: OCXO stability (only available on PolaRx5S receivers) 30: Base station measurements. This indicator is only available in RTK mode. A low value could for example hint at severe multipath or interference at the base station, or also at ionospheric scintillation. 31: RTK post-processing. This indicator is only available when the position mode is not RTK. It indicates the likelihood of getting a cmaccurate RTK position when post-processing the current data. Bits 8-11: Value of this quality indicator (from 0 for low quality to 10 for high quality, or 15 if unknown) Bits 12-15: Reserved for future use, to be ignored by decoding software.
u1[]			Padding bytes, see 4.1.5
	c1 c1 u2 u2 u4 u2 u1 u1 u2[N]	c1	c1



DiskStatus	Number:	4059	
	"OnChange"	interval: 1s	

This block reports the size and usage of the disks mounted on the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N	u1			Number of DiskData sub-blocks this block contains.
SBLength	u1	1 byte		Length of one DiskData sub-blocks in bytes.
Reserved	u1[4]			Reserved for future use
DiskData				A succession of N DiskData sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

DiskData sub-block definition:

	Parameter	Type	Units	Do-Not-Use	Description
	DiskID	u1			ID of the disk, starting at 1 for the internal SD Memory Card.
	Status	u1			Bit field:
					Bit 0: DISK_MOUNTED: bit set when the disk is mounted.
					Bit 1: DISK_FULL: bit set when the disk is full. A disk is full when it is filled to 95% of its total capacity.
					Bit 2: DISK_ACTIVITY: bit set for one second each time data is written to the disk. If the logging rate is larger than 1 Hz, set continuously.
					Bit 3: LOGGING_ENABLED: bit set when at least one file is open on the disk, regardless of the logging rate.
					Bit 4: MOUNTING: bit set when disk is being mounted.
l					Bit 5: FORMATTING: bit set when disk is being formatted.
					Bits 6-7: Reserved
	DiskUsageMSB	u2		65535 ⁽¹¹⁾	16 MSB of the total disk usage. The disk usage in bytes is given by DiskUsageMSB*4294967296+DiskUsageLSB.
	DiskUsageLSB	u4		4294967295 ⁽¹¹⁾	32 LSB of the total disk usage. The disk usage in bytes is given by DiskUsageMSB*4294967296+DiskUsageLSB.
	DiskSize	u4	1 Mbyte	0	Total size of the disk, in megabytes.
	CreateDeleteCount	u1			Counter incremented by one each time a file or a folder is created or deleted on this disk. This counter starts at zero at receiver start-up and restarts at zero after having reached 255.
	Error	u1		255	Disk error: 0: No error 1: Disk partition is too large 2: Disk does not have any partition 3: File system check and recovery failed 4: Disk in use over USB 254: Disk mount failed due to unknown error
	Padding	u1[]			Padding bytes, see 4.1.5

The disk usage is invalid if both <code>DiskUsageMSB</code> is 65535 and <code>DiskUsageLSB</code> is 4294967295.

Rev 1



LogStatus	Number:	4102
	"OnChange"	interval: 1s

This block reports the status of the different log sessions, including the status of the FTP push and CloudIt.

There is one LogSession sub-block per active log session. Each of these sub-blocks contains a number of FileUploadStatus sub-blocks that report the status of the uploads of SBF, RINEX, BINEX, NMEA, RTCMv3 and/or CGGTTS files logged in the corresponding log session.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
N1	u1			Number of LogSession sub-blocks this block contains.
SB1Length	u1	1 byte		Length of one LogSession sub-block, excluding the nested FileUploadStatus sub-blocks.
SB2Length	u1	1 byte		Length of an FileUploadStatus sub-block
Reserved	u1[3]			Reserved for future use
LogSessions				A succession of N1 LogSession sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

LogSession sub-block definition:

Parameter	Туре	Units	Description	
SessionID	u1		ID of the log session of which the status is provided in this sub-block, starting at 1 for the ${\tt LOG1}$ session.	
SessionStatus	u1		Bit field: Bit 0: DISK_UNMOUNTED: bit set when the disk where the log session is supposed to write is not mounted. Bit 1: DISK_FULL: bit set when the disk where the log session is supposed to write is full. A disk is full when it is filled to 95% of its total capacity. Bit 2: WAITING: bit set when the log session is currently disabled (see the setLogSession command) or, in the case of scheduled sessions, is waiting for the "start event". Bit 3: DISK_ACTIVITY: bit set for one second each time data is effectively written to the log session. If the logging rate is larger than 1 Hz, set continuously. Bits 4-7: Reserved	
N2	u1		Number of FileUploadStatus sub-blocks included at the end of this LogSession sub-block	
Reserved	u1		Reserved for future use	
Padding	u1[]		Padding bytes, see 4.1.5	
FileUploadStatus			A succession of N2 FileUploadStatus sub-blocks, see definition below	



${\tt FileUploadStatus} \ \ {\tt sub-block} \ \ {\tt definition:}$

Parameter	Type	Units	Description		
Туре	u1		File upload type: 0: This sub-block contains information on SBF FTP push 1: This sub-block contains information on RINEX FTP push 2: This sub-block contains information on BINEX FTP push 3: This sub-block contains information on NMEA FTP push 4: This sub-block contains information on RTCMv3 FTP push 5: This sub-block contains information on CGGTTS FTP push 10: This sub-block contains information on SBF CloudIt 11: This sub-block contains information on RINEX CloudIt 12: This sub-block contains information on BINEX CloudIt 13: This sub-block contains information on NMEA CloudIt 14: This sub-block contains information on RTCMv3 CloudIt		
ErrorCode	u1		Latest error code reported by FTP push or CloudIt: 0: No error 1: FTP: Connection to FTP server failed 2: FTP: Wrong credentials 3: FTP: Only part of the file could be transferred 4: FTP: The local file is not available (e.g. it has been deleted by the user before being FTP pushed). 5: FTP: Server permissions prohibit file creation 6: FTP: Server permissions prohibit folder creation 7: FTP: The disk is not accessible. This can for example happen when a past FTP transfer did not succeed and the receiver tries it again but the disk has been unmounted in the meantime. 8: Unexpected error 11: CloudIt: Not authorized to upload files to CloudIt server 12: CloudIt: Timeout while trying to reach server 13: CloudIt: The redirect_uri does not match the one registered in the authentication server 14: CloudIt: Client error server response, see RxMessages for more information 15: CloudIt: Server unreachable or bad response 20: CloudIt: An internal incorrect configuration of CloudIt 21: CloudIt: One or more parameters are invalid 22: CloudIt: One or more parameters are missing 40: CloudIt: The local file is not available (e.g. it has been deleted by the user before being uploaded). 41: CloudIt: Failed to upload file to server		
RetryQueueSize	u1		Number of files of the type identified in the \mathtt{Type} field that could not be uploaded but that will be retried by the receiver at a later time.		
NrFailedTransfers	u1		Number of files of the type identified in the \mathtt{Type} field that could not be uploaded and for which the receiver will not retry anymore. This number is clipped to 254 if larger than 254.		
Padding	u1[]		Padding bytes, see 4.1.5		



RFStatus	Number:	4092
	"OnChange"	interval: 1s

The RFStatus block reports on the quality of the radio-frequency (RF) signal received by the antenna(s). The RFBand sub-blocks provide a list of the frequency bands where interferences have been detected and/or mitigated, and the Flags field contains warnings that the receiver's output may be affected by non-authentic RF signals.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5	
N	u1			Number of RF bands for which data is provided in this SBF block, i.e number of RFBand sub-blocks.	
SBLength	u1	1 byte		Length of one sub-block	
Flags	u1			Bit field:	
				Bit 0: Set when the receiver determined that its output (position or raw measurements) may be affected by a spoofer, and may therefore be misleading. This bit is based on a set of built-in tests to check the authenticity of the GNSS signals. Note that this bit may be set even if no interference is detected (i.e. with no associated RFBand sub-blocks). Bit 1: Set when spoofing is detected by Galileo OSNMA.	
				Bits 2-7: Reserved	
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software.	
RFBand				A succession of N RFBand sub-blocks, see definition below	
Padding	u1[]			Padding bytes, see 4.1.5	

RFBand sub-block definition:

Parameter	Туре	Units	Description		
Frequency	u4	1 Hz	enter frequency of the RF band addressed by this sub-block.		
Bandwidth	u2	1 kHz	Bandwidth of the RF band.		
Info	u1		nfo on this RF band: Bits 0-3: Mode:		
			 This RF band is suppressed by a notch filter set manually with the command setNotchFiltering. The receiver detected interference in this band, and successfully canceled it. The receiver detected interference in this band. No mitigation applied. Bits 4-5: Reserved Bits 6-7: Antenna ID: 0 for main, 1 for Aux1 and 2 for Aux2 		
Padding	u1[]		Padding bytes, see 4.1.5		



P2PPStatus	Number:	4238	
	"OnChange"	interval: 1s	

This block reports the status of the active P2PP (Point-to-Point Protocol) sessions. See the **setPointToPoint** command for details.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5	
N	u1			Number of active P2PP sessions for which status is provided in this bloc i.e. number of P2PPSession sub-blocks.	
SBLength	u1	1 byte		Length of one P2PPSession sub-block	
P2PPSession				A succession of N P2PPSession sub-blocks, see definition below	
Padding	u1[]			Padding bytes, see 4.1.5	

P2PPSession sub-block definition:

Parameter	Туре	Units	Description		
SessionID	u1		Index of the P2PP session (1 for P2PP1, 2 for P2PP2, etc) for which status is provided in this sub-block.		
Port	u1		Index for the COM port the P2PP session is configured on (1 for COM1, 2 for COM2, etc).		
Status	u1		Bit field: Bit 0: Mode: Bit set if the P2PP session is in Server mode, and unset if it is in Client mode (future functionality). Bits 1-7: P2PP status: 0: Initializing 1: Waiting for Connection 2: Connected 3: Disconnecting 4: Error, see ErrorCode field below		
ErrorCode	u1		P2PP error: 1: No error 2: Configuration 3: Port Acquisition 4: Port Lock 5: Start Daemon 6: Server Authentication 7: Client Authentication 8: Timeout on Activity 9: Timeout on Negotiation 10: Link Negotiation 255: Unspecified		
Padding	u1[]		Padding bytes, see 4.1.5		



CosmosStatus	Number:	4243	
	"OnChange"	interval: 1s	

The ${\tt CosmosStatus}$ block provides information on the status of the Cosmos receiver service.

Parameter	Туре	Units	Do-Not-Use	Description	
Sync1	c1				
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3	
WNc	u2	1 week	65535		
Status	u1			The status of Cosmos receiver service: 0: Disabled 1: Running	
Padding	u1[]			Padding bytes, see 4.1.5	



GALAuthStatus	Number:	4245	
	"OnChange"	interval: 1s	

The ${\tt GALAuthStatus}$ block contains the current status of the Galileo OSNMA authentication.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3
OSNMAStatus	u2			Bits 0-2: status: 0: Disabled 1: Initializing 2: Waiting on NTP 3: Init failed - inconsistent time 4: Init failed - KROOT signature invalid 5: Init failed - invalid param received 6: Authenticating Bits 3-10: OSNMA initialization progress, expressed in percent [0-100]. This value will only be encoded when the OSNMA Status is initializing. Bits 11-15: Reserved
TrustedTimeDelta	f4	1 s	-2·10 ¹⁰	Time difference between external trusted and receiver time, positive when receiver time lags trusted time.
GalActiveMask	u8			Bit field indicating the Galileo satellites for which OSNMA results are available. If bit i is set, OSNMA authentication is available for Galileo satellite $i+1$.
GalAuthenticMask	u8			Bit field indicating the Galileo satellites successfully authenticated by OSNMA. If bit i is set, the navigation message from Galileo satellite $i+1$ is authentic. If bit i is not set and the corresponding bit is set in $GalActiveMask$, the navigation message from that satellite is non-authentic.
GpsActiveMask	u8			Bit field indicating the GPS satellites for which OSNMA results are available. If bit i is set, OSNMA authentication is available for GPS satellite $i+1$.
GpsAuthenticMask	u8			Bit field indicating the GPS satellites successfully authenticated by OSNMA. If bit i is set, the navigation message from GPS satellite $i+1$ is authentic. If bit i is not set and the corresponding bit is set in GpsActiveMask, the navigation message from that satellite is non-authentic.
Padding	u1[]			Padding bytes, see 4.1.5



4.2.16 Miscellaneous Blocks

ReceiverSetup	Number:	5902
	"OnChange"	interval: Block generated each time a user-command
		is entered to change one or more val-
		ues in the block (e.g. when entering the
		setMarkerParameters command)

The ReceiverSetup block contains parameters related to the receiver and its installation. When generating RINEX files, this block defines the RINEX file name and the contents of the header.

For all fields containing a string, if the length of the string is lower than the size of the corresponding field, the unused bytes are set to zero.

Parameter	Tyne	Units	Do-Not-Use	Description	
Sync1	c1	Offics	D0-140t-03c	Description	
Sync2	c1				
CRC	u2			Block Header, see 4.1.1	
ID	u2				
Length	u2	1 byte			
TOW	u4		4294967295		
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.3	
Reserved	u1[2]			2 bytes reserved for future use, to be ignored by decoding software	
MarkerName	c1[60]			Marker name (set with setMarkerParameters).	
MarkerNumber	c1[20]			Marker number (set with setMarkerParameters).	
Observer	c1[20]			Observer name (set with setObserverParameters).	
Agency	c1[40]			Observer agency (set with setObserverParameters).	
RxSerialNumber	c1[20]			Receiver serial number.	
RxName	c1[20]			Receiver GNSS engine name.	
RxVersion	c1[20]			Receiver firmware version.	
AntSerialNbr	c1[20]			Serial number of the main antenna (set with setAntennaOffset).	
AntType	c1[20]			Type of the main antenna (set with setAntennaOffset).	
deltaH	f4	1 m		δ H offset of the main antenna (set with setAntennaOffset).	
deltaE	f4	1 m		δE offset of the main antenna (set with setAntennaOffset).	
deltaN	f4	1 m		δN offset of the main antenna (set with setAntennaOffset).	
MarkerType	c1[20]			Marker type (set with the setMarkerParameters command).	
GNSSFWVersion	c1[40]			Version the firmware installed on the receiver.	
ProductName	c1[40]			Product name.	
Latitude	f8	1 rad	-2·10 ¹⁰	Latitude of the reference position, from $-\pi/2$ to $+\pi/2$, positive North of Equator. Use the setPVTMode command to set the reference position.	
Longitude	f8	1 rad	-2·10 ¹⁰	Longitude of the reference position, from $-\pi$ to $+\pi$, positive East of Greenwich. Use the setPVTMode command to set the reference position.	
Height	f4	1 m	-2·10 ¹⁰	Ellipsoidal height of the reference position (with respect to WGS84 ellipsoid). Use the setPVTMode command to set the reference position.	
StationCode	c1[10]			Station code (set with setMarkerParameters). This field can for example contains the four-letter IGS station code assigned to the receiver.	
MonumentIdx	u1			Monument index (set with setMarkerParameters). This index is used to identify the monument when there are multiple monuments at the same station.	

Rev 4

Rev 1 | Rev 2 | Rev 3 |



Rev 4

ReceiverIdx	u1		Receiver index (set with setMarkerParameters). This index is used to identify the receiver when there are multiple receivers at the same monument.
CountryCode	c1[3]		ISO 3-character country code (set with the setMarkerParameters command).
Reserved1	c1[21]		Reserved.
Padding	u1[]		Padding bytes, see 4.1.5



RxComponents	Number:	4084	
	"OnChange"	interval: 10s	

This block contains information on various hardware and software components of the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	neceiver time stamp, see 4.1.5
N	u1		Number of components for which information is provided in this	
SBLength	u1	1 byte		Length of one Component sub-block
Reserved	u1[4]			Reserved for future use, to be ignored by decoding software
Component				A succession of N Component sub-blocks, see definition below
Padding	u1[]			Padding bytes, see 4.1.5

Component sub-block definition:

Parameter	Туре	Units	Do-Not-Use	Description		
Туре	u1			Type of component described in this sub-block: 1: Motherboard 2: GNSS module 3: WiFi module 4: Cellular module 5: Bluetooth module 6: L-Band module 7: UHF module 8: Reserved 9: Reserved 10: Library		
CPULoad	u1	1 %	255	Load on the component CPU, if applicable.		
Reserved	u1[2]			Reserved for future use, to be ignored by decoding software		
Name	c1[40]			Component name.		
SerialNumber	c1[20]			Component serial number. Empty if not applicable.		
FWVersion	c1[40]			Component firmware version. Empty if not applicable.		
MACAddress	u1[6]			MAC address if applicable. The first byte corresponds to the MSB of the address. All bytes set to 0 for components for which no MAC address applies.		
Padding	u1[]			Padding bytes, see 4.1.5		



RxMessage	Number:	4103	
	"OnChange"	interval: block generated	each time a message needs to be
		sent	

The receiver generates ASCII messages to help users follow the progress of processes such as file logging or FTP push (activity log). These messages are output in the RxMessage block, and they can also be retrieved from the command line using the lif, RxMessages command.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	neceiver time stamp, see 4.1.5
Туре	u1		255	Type of message contained in this block: 1: Asynchronous command reply 2: Message about internal logging 3: Message about FTP push 4: Message about Receiver Status 5: Message from slave GNSS receiver 6: Message about CloudIt
Severity	u1		255	Message severity: 1: Info 2: Warning 3: Error
MessageID	u4		0	A unique value associated to each message. This is a counter starting at 1 for the first message after boot and incrementing at each message.
StringLn	u2			Length of Message in characters, including the terminating \0.
Reserved2	u1[2]			Reserved, contents to be ignored.
Message	c1[StringLn]			Receiver message terminated by \0.
Padding	u1[]			Padding bytes, see 4.1.5



Commands	Number:	4015	
	"OnChange"	interval: each time a user command is entered	

Every time the user sends a command, a Commands block is output on all ports for which this block is enabled. The Commands SBF block is inserted in the SBF stream at the very moment when the command starts to take effect.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week	65535	Receiver time stamp, see 4.1.5
Reserved	u1[2]			Reserved for future use, to be ignored by decoding software.
CmdData	u1[<i>N</i>]		l	Command data, this is the command in the SNMP' format (reserved for maintenance and support only).
Padding	u1[]			Padding bytes, see 4.1.5



Comment	Number:	5936
	"OnChange"	interval: block generated each time a comment is entered with
		setObserverComment

The Comment block contains a comment string as entered with the **setObserverComment** command.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	Receiver time stamp, see 4.1.3
WNc	u2	1 week		receiver time stamp, see 4.1.5
CommentLn	u2			Length of the Comment string, in characters. The maximum length of a comment is 120 characters.
Comment	c1[CommentLn]			Comment string, as entered with the setObserverComment command. Note that this string is not terminated by the "\0" character.
Padding	u1[]			Padding bytes, see 4.1.5



BBSamples	Number:	4040
	"OnChange"	interval: block generated each time new baseband samples
		are ready (typically at 2Hz)

The BBSamples block contains a series of successive complex baseband samples. These samples can be used for signal monitoring and for spectral analysis of the GNSS bands supported by the receiver.

Parameter	Туре	Units	Do-Not-Use	Description
Sync1	c1			
Sync2	c1			
CRC	u2			Block Header, see 4.1.1
ID	u2			
Length	u2	1 byte		
TOW	u4	0.001 s	4294967295	External time stamp, see 4.1.3
WNc	u2	1 week	65535	external time stamp, see 4.1.5
N	u2			Number of complex baseband samples contained in this block
Info	u1			Bit field as follows:
				Bits 0-2: Antenna ID: antenna from which the samples have been taken: 0 for main, 1 for <i>Aux1</i> and 2 for <i>Aux2</i> . Bits 3-7: Reserved
Reserved	u1[3]			Reserved for future use, to be ignored by decoding software.
SampleFreq	u4	1 Hz		Sampling frequency in Hz.
LOFreq	u4	1 Hz		Frequency of the local oscillator (LO) used to down-convert the RF signal to baseband.
Samples	u2[N]			N successive complex baseband samples (I+jQ), coded as follows:
				Bits 0-7: 8-bit Q component, two's complement.
				Bits 8-15: 8-bit I component, two's complement.
Padding	u1[]			Padding bytes, see 4.1.5



ASCIIIn Number:	4075
"OnChange"	interval: block generated each time an ASCII string is received

The ASCIIIn block contains a string that has been received on one of the receiver's connection ports.

More specifically, this block is output each time an end-of-line character is received on a communication port configured to receive ASCIIIn input (with the **setDataInOut** command). The string reported in this block contains all characters received since the previous occurrence of an end-of-line character.

The maximum length of the string is 2000 characters. If there are more than 2000 characters between the occurrence of two successive end-of-line characters, the string is discarded

Parameter	Туре	Units	Do-Not-Use		Description	
Sync1	c1					
Sync2	c1					
CRC	u2			Block Header, see 4.1.1		
ID	u2					
Length	u2	1 byte				
TOW	u4	0.001 s	4294967295	Receiver 1	time stamp, see 4.1.3	
WNc	u2	1 week	65535	Receiver	ame stamp, see 4.1.5	
CD	u1			Identifier ceived:	of the connection from which the data has	s been re-
				Value of CD	Connection type	Example
				0-31	COMx, with <i>x</i> =CD	1: COM1
				32-47	USBx, with x=CD-32	33: USB1
				48-63	OTGx, with x=CD-48	49: OTG1
				64-95	IPx, with <i>x</i> =CD-54	64:IP10
				128-159	NTRx, with <i>x</i> =CD-128 (NTRIP connections)	129:NTR1
				192	BT01 (Bluetooth connection)	
				193	BT02 (Bluetooth connection)	
				196	UHF1 (UHF Modem)	
				200-205	IPRx, with x =CD-200 (IP receive connections)	201:IPR1
				210	DCL1 (cellular data-call connection)	
				214	CAN1 (CAN stream interface)	
				215-255	Reserved	
Reserved1	u1[3]			Reserved	, contents to be ignored.	
StringLn	u2			Length of	ASCIIString in characters.	
SensorModel	c1[20]			Not supp	orted, reserved for future use.	
SensorType	c1[20]			Not supp	orted, reserved for future use.	
Reserved2	u1[20]			Reserved, contents to be ignored.		
ASCIIString	c1[StringLn]			ASCII string. Note that this string is not terminated by the "\0" character. The string does not include the end-of-line character(s) (carrier return and/or line feed).		
Padding	u1[]			Padding b	oytes, see 4.1.5	



4.2.17 Advanced Blocks

SystemInfo	Number:	6000	
	"OnChange"	interval: 1s	

This block contains various system parameters that can be used for maintenance and support.

The detailed definition of this block is not available in this document.



4.3 SBF Change Log

Date	Change Description
Oct 01, 2021	Added the QZSRawL5S block containing the raw QZSS L5S navigation bits
Apr 10, 2020	Added the NTRIPServerStatus block for the NTRIP server connection
	status
Feb 11, 2020	Added the BDSRawB2b block containing the raw BeiDou B2b navigation
	symbols
May 16, 2019	Added the P2PPStatus block to report the status of the Point-to-Point ses-
	sions
Apr 26, 2019	Added the QZSAlm block containing QZSS almanac parameters
Apr 8, 2019	Renamed IRNSSRaw to NAVICRaw
Mar 12, 2019	Added the BDSAlm block containing BeiDou almanac parameters
Aug 07, 2018	Added the QZSRawL1S block containing the raw QZSS L1S navigation bits
Aug 07, 2018	Added the QZSRawL1C block containing the raw QZSS L1C navigation sym-
	bols
May 31, 2018	Added the GPSRawL1C block containing the raw GPS L1C navigation sym-
10.0010	bols
Apr 19, 2018	Added the BDSRawB1C block containing the raw BeiDou B1C navigation
A = = 10, 2010	symbols
Apr 19, 2018	Added the BDSRawB2a block containing the raw BeiDou B2a navigation
lun 20 2017	symbols
Jun 20, 2017	Added the BDSIon and BDSUtc blocks containing BeiDou ionospheric and
h 15 2017	UTC offset parameters
Jun 15, 2017	Added the Meas3PP and Meas3MP blocks to supplement the
Mar 6, 2017	Meas3Ranges block Added the Meas3Ranges, Meas3CNOHiRes and Meas3Doppler blocks
IVIAI 0, 2017	containing GNSS measurements
Mar 1, 2017	Renamed CMPNav to BDSNav and CMPRaw to BDSRaw
Nov 15, 2016	Added the QZSRawL6 block containing raw QZSS L6 navigation bits
July 13, 2016	Added the SystemInfo block containing raw Q255 to Havigation bits
July 13, 2010	tems
Nov 10, 2015	Added the RxMessage block containing the receiver activity log
Nov 5, 2015	Added the LogStatus block to report the status of the log sessions
Sep 29, 2015	Added the PowerStatus block to report the voltage of the power supply
Feb 04, 2015	Added the QZSNav block containing decoded QZSS navigation data
Jan 13, 2015	Added the PosProjected block containing plane grid coordinates
Dec 12, 2014	Added the base measurements quality indicator
Nov 6, 2014	Added the RFStatus block for interference mitigation monitoring
	Added new values for the Datum field
April 30, 2014	
April 22, 2014	Added the DiskStatus block reporting the disk usage and free space of the disks available on the receiver
Fob 21 2014	Added the NTRIPClientStatus block for the NTRIP client connection sta-
Feb 21, 2014	tus
June 24, 2013	Added the RxComponents block containing information on the various re-
Julie 24, 2013	ceiver's components
June 24 2012	·
	Added the WiFiAPStatus block for the WiFi status in access point mode Added the QualityInd block containing various quality indicators
reb 19, 2013	Added the CMPNav block containing decoded BeiDou navigation data



Feb 8, 2013	Fixed typo: field t_oG of GALGstGps changed to type u4 and units of sec-				
	onds				
Jan 8, 2013	Added fields HAccuracy, VAccuracy and Misc to the PVTCartesian				
	and PVTGeodetic blocks				
Dec 19, 2012	Added PRNs 139 and 140 to the list of SBAS satellites				
Oct 25, 2012	Added RTCMDatum and PosLocal blocks				
Oct 19, 2012	Added GEORawL5 block				
Oct 1, 2012	Added new signal type for L-band and SBAS L5 signals (value 23 and 25)				
Sep 29, 2012	Added LBandBeams block and added SVID field to				
	LBandTrackerStatus block				
Sep 20, 2012	Added field PPPInfo to the PVTCartesian and PVTGeodetic blocks				
Jun 27, 2012	Added fields to the LBAS1DecoderStatus block to report various service				
	subscription parameters				
Feb 28, 2012	Added GALSARRLM block				
Feb 6, 2012	Added QZSS signals and QZSRawL1CA, QZSRawL2C and QZSRawL5 blocks				



Appendix A

List of SBF Blocks

The following table provides the list of the SBF block names and numbers available on PolaRx5TR and a short description of the associated contents. The block number is contained in bits 0 to 12 of the block ID field (see section 4.1.1).

The "Flex Rate" column indicates whether a given block can be output at a user-defined rate and the "esoc" column whether it can be used as an argument of the **exeSBFOnce** command (see also section 4.1.8). The "Time stamp" column indicates which type of time is encoded in the block time stamp (see section 4.1.3 for details).

Block name		Content description			Time
Measurement Blocks	No		Rate		Stamp
MeasEpoch	14027	Measurement set of one epoch	•	•	R
MeasExtra		Additional info such as observable variance		_	R
		Code, phase and CN0 measurements	•	•	R
Meas3Ranges Meas3CN0HiRes			•	•	R
		Extension of Meas3Ranges containing fractional C/N0 values	•	•	R
Meas3Doppler		Extension of Meas3Ranges containing Doppler values	•	•	R
Meas3PP	4112	Extension of Meas3Ranges containing proprietary flags for data post- processing.	•	•	K
Meas3MP		Extension of Meas3Ranges containing multipath corrections applied by the receiver.	•	•	R
EndOfMeas	5922	Measurement epoch marker	•	•	R
Navigation Page Blocks					
GPSRawCA	4017	GPS CA navigation subframe			S
GPSRawL2C	4018	GPS L2C navigation frame			S
GPSRawL5		GPS L5 navigation frame			S
GPSRawL1C	4221	GPS L1C navigation frame			S
GLORawCA		GLONASS CA navigation string			S
GALRawFNAV	4022	Galileo F/NAV navigation page			S
GALRawINAV	4023	Galileo I/NAV navigation page			S
GALRawCNAV	4024	Galileo C/NAV navigation page			S
GEORawL1	4020	SBAS L1 navigation message			S
GEORawL5	4021	SBAS L5 navigation message			S
BDSRaw	4047	BeiDou navigation page			S
BDSRawB1C	4218	BeiDou B1C navigation frame			S
BDSRawB2a		BeiDou B2a navigation frame			S
BDSRawB2b	4242	BeiDou B2b navigation frame			S
QZSRawL1CA	4066	QZSS L1C/A or L1C/B navigation frame			S
QZSRawL2C		QZSS L2C navigation frame			S
QZSRawL5	4068	QZSS L5 navigation frame			S
QZSRawL6	4069	QZSS L6 navigation message			S
QZSRawL1C	4227	QZSS L1C navigation frame			S
QZSRawL1S		QZSS L1S navigation message			S
QZSRawL5S		QZSS L5S navigation message			S
NAVICRaw	4093	NavIC/IRNSS subframe			S
GPS Decoded Message B	locks				
GPSNav	5891	GPS ephemeris and clock		•	S



Block name		Content description			Time
GPSAlm	No	Almanac data for a GPS satellite	Rate	•	Stamp
GPSION		Ionosphere data from the GPS subframe 5		-	S
GPSUtc		GPS-UTC data from GPS subframe 5		•	S
GPSCNav		CNAV Ephemeris data for one satellite.		•	S
GLONASS Decoded M					
GLONav		GLONASS ephemeris and clock		•	S
GLOAlm		Almanac data for a GLONASS satellite		•	S
GLOTime		GLO-UTC, GLO-GPS and GLO-UT1 data		•	S
Galileo Decoded Mess					
GALNav		Galileo ephemeris, clock, health and BGD		•	S
GALAlm		Almanac data for a Galileo satellite		•	S
GALIon	4030	NeQuick Ionosphere model parameters		•	S
GALUtc	4031	GST-UTC data		•	S
GALGstGps	4032	GST-GPS data		•	S
GALSARRLM		Search-and-rescue return link message			S
BeiDou Decoded Mess	sage Block	ks			
BDSNav		BeiDou ephemeris and clock		•	S
BDSCNav2	4252	BeiDou B-CNAV2 ephemeris data for one satellite.		•	S
BDSAlm		Almanac data for a BeiDou satellite		•	S
BDSIon	4120	BeiDou lonospheric delay model parameters		•	S
BDSUtc		BDT-UTC data		•	S
QZSS Decoded Messa					
QZSNav		QZSS ephemeris and clock		•	S
QZSAlm		Almanac data for a QZSS satellite		•	S
NavIC/IRNSS Decoded	Message	Blocks			
NavICLNav		NavIC/IRNSS ephemeris and clock		•	S
SBAS L1 Decoded Me	ssage Blo	cks			
GEOMT00	5925	MT00 : SBAS Don't use for safety applications			S
GEOPRNMask	5926	MT01 : PRN Mask assignments			S
GEOFastCorr	5927	MT02-05/24: Fast Corrections			S
GEOIntegrity		MT06 : Integrity information			S
GEOFastCorrDegr		MT07 : Fast correction degradation factors			S
GEONav		MT09 : SBAS navigation message		•	S
GEODegrFactors		MT10 : Degradation factors			S
GEONetworkTime		MT12 : SBAS Network Time/UTC offset parameters			S
GEOAlm		MT17 : SBAS satellite almanac		•	S
GEOIGPMask		MT18 : lonospheric grid point mask			S
GEOLongTermCorr		MT24/25 : Long term satellite error corrections			S
GEOIonoDelay		MT26 : lonospheric delay corrections			S
GEOServiceLevel		MT27 : SBAS Service Message			S
		MT28 : Clock-Ephemeris Covariance Matrix			S
GNSS Position, Veloci					
PVTCartesian		GNSS position, velocity, and time in Cartesian coordinates	•	•	R
PVTGeodetic		GNSS position, velocity, and time in geodetic coordinates	•	•	R
PosCovCartesian		Position covariance matrix (X,Y, Z)	•	•	R
PosCovGeodetic		Position covariance matrix (Lat, Lon, Alt)	•	•	R
VelCovCartesian		Velocity covariance matrix (X, Y, Z)	•	•	R
VelCovGeodetic		Velocity covariance matrix (North, East, Up)	•	•	R
DOP		Dilution of precision	•	•	R
PosCart		Position, variance and baseline in Cartesian coordinates	•	•	R
PosLocal		Position in a local datum	•	•	R
PosProjected		Plane grid coordinates	•	•	R
PVTSatCartesian		Satellite positions	•	•	R
PVTResiduals		Measurement residuals	•	•	R
RAIMStatistics		Integrity statistics	•	•	R
GEOCorrections		Orbit, Clock and pseudoranges SBAS corrections	•	•	R
BaseVectorCart		XYZ relative position and velocity with respect to base(s)	•	•	R R
BaseVectorGeod		ENU relative position and velocity with respect to base(s) Internal parameters for maintenance and support	•	•	
PVTSupport			•	•	R
PVTSupportA		Internal parameters for maintenance and support	•	•	R R
EndOfPVT		PVT epoch marker	•	•	K
Receiver Time Blocks		Current receiver and LITC time			D
ReceiverTime		Current receiver and UTC time	•	•	R
xPPSOffset External Event Blocks		Offset of the xPPS pulse with respect to GNSS time			R
		Time at the instant of an external event			С
ExtEvent		Time at the instant of an external event		-	E
ExtEventPVTCartes:		Cartesian position at the instant of an event		-	E
ExtEventPVTGeodet:	LC 4038	Geodetic position at the instant of an event			E



Block name		Content description		esoc	Time
Evrt Evront Dogovio at Cood	No 4217	ENU relative position with respect to base(s) at the instant of an event	Rate		Stamp E
Differential Correction Bloom		ENO relative position with respect to base(s) at the instant or an event			
DiffCorrIn		Incoming RTCM or CMR message			R
BaseStation		Base station coordinates			R
RTCMDatum	1	Datum information from the RTK service provider			R
L-Band Demodulator Blo		Datum mornation from the KTK service provider			I N
LBandTrackerStatus		Status of the L-band signal tracking	•	•	R
LBAS1DecoderStatus		Status of the LBAS1 L-band service	+	_	R
LBAS1Messages		LBAS1 over-the-air message			R
LBandBeams		L-band satellite/beam information		•	R
Status Blocks	4204	L-Dand Satellite/Dearn Information		•	IX.
ChannelStatus	<i>1</i> 013	Status of the tracking for all receiver channels	•	•	R
ReceiverStatus		Overall status information of the receiver	+	•	R
SatVisibility		Azimuth/elevation of visible satellites	+ :	•	R
InputLink		Statistics on input streams	+ -	•	R
OutputLink		Statistics on output streams	+		R
NTRIPClientStatus	1	NTRIP client connection status	+ -	•	R
NTRIPCIIentStatus NTRIPServerStatus		NTRIP client connection status	•	•	R
IPStatus			•	•	R
		IP address, gateway and MAC address of Ethernet interface WiFi status in access point mode	-	•	R
WiFiAPStatus			•	•	
WiFiClientStatus		WiFi status in client mode	•	•	R
DynDNSStatus		DynDNS status	•	•	R
PowerStatus		Power supply source and voltage	•	•	R
QualityInd		Quality indicators	•	•	R
DiskStatus		Internal logging status	•	•	R
LogStatus		Log sessions status	•	•	R
RFStatus		Radio-frequency interference mitigation status	•	•	R
P2PPStatus		P2PP client/server status	•	•	R
CosmosStatus		Cosmos receiver service status	•	•	R
GALAuthStatus	4245	Galileo OSNMA authentication status		•	R
Miscellaneous Blocks					
ReceiverSetup		General information about the receiver installation		•	R
RxComponents		Information on various receiver components	•	•	R
RxMessage		Receiver message		•	R
Commands		Commands entered by the user		•	R
Comment		Comment entered by the user		•	R
BBSamples	4040	Baseband samples			E
ASCIIIn	4075	ASCII input from external sensor			R
Advanced Blocks					
SystemInfo	6000	System parameters for maintenance and support	•	•	R



Appendix B

List of BINEX Records

The following table provides a list of BINEX records supported by your receiver. The first column is the record identifier to be used in the **setBINEXOutput** and the **exeBINEXOnce** commands.

The "OnChange Rate" column indicates the rate at which each record is output when the OnChange interval is selected with the **setBINEXOutput** command, and the "Flex Rate" column indicates whether the record can be output at a different rate than its OnChange rate.

Message Identifier	Short Description		Flex
Rec00	Site metadata	at the beginning of each log file, and when contents is changed by user with the setAntennaOffset, setMarkerParameters or the setObserverParameters command	Rate
Rec0101	Decoded GPS Ephemeris	when a new GPS dataset is decoded	
Rec0102	Decoded GLONASS Ephemeris	when a new GLONASS dataset is decoded	
Rec0103	Decoded SBAS Ephemeris	when a new SBAS dataset is decoded	
Rec0114	Decoded Galileo Ephemeris	when a new Galileo dataset is decoded	
Rec0105	Decoded BeiDou Ephemeris	when a new BeiDou dataset is decoded	
Rec0106	Decoded QZSS Ephemeris	when a new QZSS dataset is decoded	
Rec0107	Decoded NavIC/IRNSS Ephemeris	when a new NavIC dataset is decoded	
Rec0141	Raw GPS navigation subframe	at the end of each subframe	
Rec0142	Raw GLONASS navigation string	at the end of each string	
Rec0143	Raw SBAS navigation block	at the end of each block	
Rec0144	Raw Galileo navigation page	at the end of each page	
Rec0145	Raw BeiDou navigation subframe	at the end of each subframe	
Rec0146	Raw QZSS navigation subframe	at the end of each subframe	
Rec0147	Raw NavIC/IRNSS navigation sub- frame	at the end of each subframe	
Rec05Geod	Geodetic position and velocity	0.1s	•
Rec7D00	Receiver internal state	1s	•
Rec7E01	Raw ASCII string from ancillary device	when a new string is received	
Rec7F05	GNSS measurements (empty epochs are encoded as record 0x7F-04)	0.1s	•





Appendix C

List of NMEA Sentences

The following table provides a list of the NMEA messages supported by your receiver. The first column is the message identifier to be used in the **setNMEAOutput** and the **exeNMEAOnce** commands.

For a full description of the NMEA messages, please refer to the NMEA 0183 standard.

Message	NMEA For-	Short Description	Comment
Identifier	matter		
ALM	ALM	GPS Almanac Data	
AVR	AVR	Trimble Navigation proprietary	
		\$PTNL, AVR sentence	
DTM	DTM	Datum Reference	
GBS	GBS	GNSS Satellite Fault Detection	
GFA	GFA	GNSS Fix Accuracy and Integrity	
GGA	GGA	GPS Fix Data	GPS Quality Indicator field is set to 5 in PPP mode
GGK	GGK	Trimble Navigation proprietary	
		\$PTNL, GGK sentence	
GGQ	GGQ	Leica Real-Time Position with CQ	
GLL	GLL	Geographic Position - Latitude/Longi-	
		tude	
GMP	GMP	GNSS Map Projection Fix Data	
GNS	GNS	GNSS Fix Data	
GRS	GRS	GNSS Range Residuals	
GSA	GSA	GNSS DOP and Active Satellites	
GST	GST	GNSS Pseudorange Error Statistics	
GSV	GSV	GNSS Satellites in View	
HDT	HDT	Heading, True	
LLK	LLK	Leica Local Position and GDOP	
LLQ	LLQ	Leica Local Position and Quality	
PUMRD	PUMRD	Septentrio proprietary	Septentrio proprietary, not documented here
RBD	RBD	Rover-Base Direction	Septentrio proprietary, see section C.1.1
RBP	RBP	Rover-Base Position	Septentrio proprietary, see section C.1.2
RBV	RBV	Rover-Base Velocity	Septentrio proprietary, see section C.1.3
RMC	RMC	Recommended Minimum Specific GNSS	
		Data	
ROT	ROT	Rate of Turn	
SDI	SDI	Disk Status	Septentrio proprietary, see section C.1.4
SNC	SNC	NTRIP Client Status	Septentrio proprietary, see section C.1.5
SPW	SPW	Power Status	Septentrio proprietary, see section C.1.6
SRX	SRX	Receiver Status	Septentrio proprietary, see section C.1.7



Message Identifier	matter	Short Description	Comment
TFM	TFM	Used Coordinate Transformation Messages	Septentrio proprietary, see section C.1.8
TXTbase	ТХТ		Text from a base station in RTCM message type 1029. The text identifier is set to 1, and the text message is in the form "nnnn: base txt>", where nnnn is the base station ID.
VTG	VTG	Course Over Ground and Ground Speed	
ZDA	ZDA	Time and Date	

Note: in sentences containing satellite-per-satellite data, data for BeiDou satellites are encoded using System ID 4 (BD) and satellite ID 1-36. Data for NavIC/IRNSS, QZSS and SBAS satellites with a PRN>151 are not encoded in NMEA.

Appendix C.1 Proprietary NMEA Sentences

C.1.1 RBD: Rover-Base Direction

Field	Description
\$PSSN,RBD,	Start of sentence
hhmmss.ss,	UTC of RBD (HoursMinutesSeconds.DecimalSeconds)
xxxxxx,	Date: ddmmyy
x.x,	Azimuth of the base as seen from rover (0 to 360 increasing towards east), degrees True
x.x,	Elevation of the base as seen from rover (-90 to 90), degrees
xx,	Number of satellites used for baseline computation
x, x,	Quality indicator: 0: Invalid 2: DPGS 4: RTK 5: Float RTK Base motion indicator: 0: Static base 1: Moving base
x.x,	Correction Age, seconds
C-C,	Rover serial number
xxxx	Base station ID
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence





C.1.2 RBP: Rover-Base Position

Field	Description
\$PSSN,RBP,	Start of sentence
hhmmss.ss,	UTC of RBP (HoursMinutesSeconds.DecimalSeconds)
xxxxxx,	Date: ddmmyy
x.x,	North (True) baseline component (positive when base is north of rover), meters
x.x,	East baseline component (positive when base is east of rover), meters
x.x,	Up baseline component (positive when base is higher than rover), meters
XX,	Number of satellites used for baseline computation
x, x,	Quality indicator: 0: Invalid 2: DPGS 4: RTK 5: Float RTK Base motion indicator: 0: Static base 1: Moving base
x.x,	Correction Age, seconds
C-C,	Rover serial number
xxxx	Base station ID
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

C.1.3 RBV : Rover-Base Velocity

Field	Description
\$PSSN,RBV,	Start of sentence
hhmmss.ss,	UTC of RBV (HoursMinutesSeconds.DecimalSeconds)
xxxxxx,	Date: ddmmyy
x.x,	Rate of change of baseline vector (rover to base), north component, m/s
x.x,	Rate of change of baseline vector (rover to base), east component, m/s
x.x,	Rate of change of baseline vector (rover to base), up component, m/s
xx,	Number of satellites used for baseline computation
x, x,	Quality indicator: 0: Invalid 2: DPGS 4: RTK 5: Float RTK Base motion indicator: 0: Static base 1: Moving base
x.x,	Correction Age, seconds
C-C,	Rover serial number
XXXX	Base station ID
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

C.1.4 SDI: Disk Status

This proprietary sentence is the NMEA equivalent of the <code>DiskStatus</code> SBF block.



Field	Description
\$PSSN,SDI,	Start of sentence
[
х,	message revision
xxxxxxxxx,	time of week, milliseconds
xxxx,	week number
,	Reserved
<sdisub></sdisub>	a succession of SDISub sub-messages, see definition below
]	
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

SDISub definition:

Field	Description
[
x.x,	DiskID field of the DiskStatus SBF block
x.x,	Status field of the DiskStatus SBF block
x.x,	Disk usage in bytes
x.x,	DiskSize field of the DiskStatus SBF block, in MBytes
x.x,	Percentage of disk used
x.x,	CreateDeleteCounter field of the DiskStatus SBF block
x.x	Error field of the DiskStatus SBF block
]	

Example:

\$PSSN, SDI, [1,314558000,1985,,[1,13,14616641536,15472,90,5,0]] *77

C.1.5 SNC: NTRIP Client Status

This proprietary sentence is the NMEA equivalent of the NTRIPClientStatus SBF block.

Field	Description
\$PSSN,SNC,	Start of sentence
[
х,	message revision
xxxxxxxxx,	time of week, milliseconds
xxxx,	week number
<sncsub></sncsub>	a succession of SNCSub sub-messages, see definition below
]	
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

SNCSub definition:

Field	Description
[
х,	CDIndex field of the NTRIPClientStatus SBF block
х,	Status field of the NTRIPClientStatus SBF block
х,	ErrorCode field of the NTRIPClientStatus SBF block
Х	Info field of the NTRIPClientStatus SBF block
]	

Example:

\$PSSN, SNC, [0, 379359000, 1840, [1, 2, 0, 0]] *68





C.1.6 SPW: Power Status

This proprietary sentence is the NMEA equivalent of the PowerStatus SBF block.

Field	Description
\$PSSN,SPW,	Start of sentence
[
х,	message revision
xxxxxxxxx,	time of week, milliseconds
xxxx,	week number
x.x,	PowerSource. See PowerInfo field of the PowerStatus SBF block
x.x	Voltage at the Vin pins, in Volts
]	
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

Example:

\$PSSN, SPW, [0,314389000,1985,1,12.25] *56

C.1.7 SRX: Receiver Status

This proprietary sentence is the NMEA equivalent of the ReceiverStatus SBF block.

Field	Description
\$PSSN,SRX,	Start of sentence
[
x,	message revision
xxxxxxxxx,	time of week, milliseconds
xxxx,	week number
x.x,	CPULoad field of the ReceiverStatus SBF block
x.x,	ExtError field of the ReceiverStatus SBF block
x.x,	UpTime field of the ReceiverStatus SBF block
x.x,	RxState field of the ReceiverStatus SBF block
x.x,	RxError field of the ReceiverStatus SBF block
x.x,	CmdCount field of the ReceiverStatus SBF block
x.x,	Temperature field of the ReceiverStatus SBF block, in degC
<srxsub></srxsub>	a succession of SRXSub sub-messages, see definition below
]	
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

SRXSub definition:

Field	Description
[
x.x,	FrontendID field of the ReceiverStatus SBF block
x.x,	Gain field of the ReceiverStatus SBF block, in dB
x.x,	SampleVar field of the ReceiverStatus SBF block
X.X	BlankingStat field of the ReceiverStatus SBF block, in percent
]	

Example:

\$PSSN, SRX, [1,316618000,1985,41,0,25,754,8,6,43.00,[0,49,102,0], [1,52,96,0], [11,52,104,0], [10,36,98,0], [5,48,96,0], [6,45,98,0], [3,38,93,0], [4,39,100,0], [12,36,102,0], [2,36,104,0]] *4B





C.1.8 TFM: Used RTCM Coordinate Transformation Messages

This proprietary sentence indicates which RTCM coordinate transformation messages have been received and used in the position computation.

Field	Description
\$PSSN,TFM,	Start of sentence
hhmmss.ss,	UTC time (HoursMinutesSeconds.DecimalSeconds)
х,	Height indicator, a copy of the Height Indicator field in RTCM message 1021 or 1022. Null if unknown.
xxxx,	Message 1021/1022 usage (they are exclusive). Possible field values: 1021: Message type 1021 used; 1022: Message type 1022 used; null: neither 1021 nor 1022 used.
xxxx,	Message 1023/1024 usage (they are exclusive). Possible field values: 1023: Message type 1023 used; 1024: Message type 1024 used; null: neither 1023 nor 1024 used.
xxxx	Message 1025/1026/1027 usage (they are exclusive). Possible field values: 1025: Message type 1025 used; 1026: Message type 1026 used; 1027: Message type 1027 used; null: neither 1025 nor 1026 nor 1027 used.
*hh	Checksum delimiter and checksum field
<cr><lf></lf></cr>	End of sentence

Example:

\$PSSN, TFM, 104751.00, 2, 1021, 1023, 1025*5F



Appendix D

List of CMR and RTCM Messages

This appendix provides a list of all the CMR and RTCM (v2.x and v3.x) messages supported by the receiver.

Appendix D.1 CMR Messages

Message Ide	en- Short Description
CMR0	Observables
CMR1	Reference Station Coordinates
CMR2	Reference Station Description
CMR3	GLONASS Observables
CMR0p	CMR+ variant
CMR0w	CMR-W variant

Appendix D.2 RTCM v2.x Messages

	- Short Description
tifier RTCM1	Differential GPS Corrections
RTCM3	GPS Reference Station Parameters
RTCM9	GPS Partial Correction Set
RTCM15	lonospheric Delay
RTCM16	GPS Special Message
RTCM17	GPS Ephemerides Message
RTCM18	RTK Uncorrected Carrier Phases
RTCM19	RTK Uncorrected Pseudoranges
RTCM20	RTK Carrier Phase Corrections
RTCM21	RTK/Hi-Accuracy Pseudorange Corrections
RTCM22	Extended Reference Station Parameters
RTCM23	Antenne Type Definition Record
RTCM24	Antenna Reference Point (ARP)
RTCM31	Differential GLONASS Corrections
RTCM32	GLONASS Reference Station Parameters
RTCM34	GLONASS Partial Correction Set
RTCM59	Proprietary Message

Appendix D.3 RTCM v3.x Messages



Message Iden- Short Description		
tifier RTCM1001	L1-Only GPS RTK Observables	
RTCM1002	Extended L1-Only GPS RTK Observables	
RTCM1003	L1&L2 GPS RTK Observables	
RTCM1004	Extended L1&L2 GPS RTK Observables	
RTCM1005	Stationary RTK Reference Station ARP	
RTCM1006	Stationary RTK Reference Station ARP with Antenna Height	
RTCM1007	Antenna Descriptor	
RTCM1008	Antenna Descriptor and Serial Number	
RTCM1009	L1-Only GLONASS RTK Observables	
RTCM1010	Extended L1-Only GLONASS RTK Observables	
RTCM1011	L1&L2 GLONASS RTK Observables	
RTCM1012	Extended L1&L2 GLONASS RTK Observables	
RTCM1013	System Parameters	
RTCM1015	Network RTK (MAC), GPS Ionospheric Correction Differences	
RTCM1016	Network RTK (MAC), GPS Geometric Correction Differences	
RTCM1017	Network RTK (MAC), GPS Combined Geometric and Ionospheric Correction Differences	
RTCM1019	GPS Satellite Ephemeris Data	
RTCM1020	Glonass Satellite Ephemeris Data	
RTCM1021	Helmert-Abridged Molodenski Transformation Parameters	
RTCM1022	Molodenski-Badekas Transformation Parameters	
RTCM1023	Residuals, Ellipsoidal Grid Representation	
RTCM1024	Residuals, Plane Grid Representation	
RTCM1025	Projection Parameters, Projection Types other than Lambert Conic Conformal (2 SP) and	
	Oblique Mercator	
RTCM1026	Projection Parameters, Projection Type LCC2SP (Lambert Conic Conformal (2 SP))	
RTCM1027	Projection Parameters, Projection Type OM (Oblique Mercator)	
RTCM1029	Unicode Text String	
RTCM1033	Receiver and Antenna Descriptors	
RTCM1037	Network RTK (MAC), GLONASS Ionospheric Correction Differences	
RTCM1038	Network RTK (MAC), GLONASS Geometric Correction Differences	
RTCM1039	Network RTK (MAC), GLONASS Combined Geometric and Ionospheric Correction Differences	
RTCM1041	NavIC/IRNSS Satellite Ephemeris Data	
RTCM1042	BDS Satellite Ephemeris Data	
RTCM1044	QZSS Satellite Ephemeris Data	
RTCM1045	Galileo F/NAV Satellite Ephemeris Data	
RTCM1046	Galileo I/NAV Satellite Ephemeris Data	
RTCM1071	GPS MSM1, Compact Pseudoranges	
RTCM1072	GPS MSM2, Compact PhaseRanges	
RTCM1073	GPS MSM3, Compact Pseudoranges and PhaseRanges	
RTCM1074	GPS MSM4, Full Pseudoranges and PhaseRanges plus CNR	
RTCM1075	GPS MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR	
RTCM1076	GPS MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)	
RTCM1077	GPS MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolution)	
RTCM1081	GLONASS MSM1, Compact Pseudoranges	
RTCM1082	GLONASS MSM2, Compact PhaseRanges	
RTCM1083	GLONASS MSM3, Compact Pseudoranges and PhaseRanges	
RTCM1084	GLONASS MSM4, Full Pseudoranges and PhaseRanges plus CNR	
RTCM1085	GLONASS MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR	
RTCM1086	GLONASS MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)	
RTCM1087	GLONASS MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolution)	
RTCM1091	Galileo MSM1, Compact Pseudoranges	
RTCM1092	Galileo MSM2, Compact PhaseRanges	
RTCM1093	Galileo MSM3, Compact Pseudoranges and PhaseRanges	
RTCM1094	Galileo MSM4, Full Pseudoranges and PhaseRanges plus CNR	
RTCM1095	Galileo MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR	
RTCM1096	Galileo MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)	
RTCM1097	Galileo MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolution)	
RTCM1101	SBAS MSM1, Compact Pseudoranges	



Message Iden-	Short Description
tifier	
RTCM1102	SBAS MSM2, Compact PhaseRanges
RTCM1103	SBAS MSM3, Compact Pseudoranges and PhaseRanges
RTCM1104	SBAS MSM4, Full Pseudoranges and PhaseRanges plus CNR
RTCM1105	SBAS MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR
RTCM1106	SBAS MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)
RTCM1107	SBAS MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolution)
RTCM1111	QZSS MSM1, Compact Pseudoranges
RTCM1112	QZSS MSM2, Compact PhaseRanges
RTCM1113	QZSS MSM3, Compact Pseudoranges and PhaseRanges
RTCM1114	QZSS MSM4, Full Pseudoranges and PhaseRanges plus CNR
RTCM1115	QZSS MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR
RTCM1116	QZSS MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)
RTCM1117	QZSS MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolution)
RTCM1121	BeiDou MSM1, Compact Pseudoranges
RTCM1122	BeiDou MSM2, Compact PhaseRanges
RTCM1123	BeiDou MSM3, Compact Pseudoranges and PhaseRanges
RTCM1124	BeiDou MSM4, Full Pseudoranges and PhaseRanges plus CNR
RTCM1125	BeiDou MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR
RTCM1126	BeiDou MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)
RTCM1127	BeiDou MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolution)
RTCM1131	NavIC/IRNSS MSM1, Compact Pseudoranges
RTCM1132	NavIC/IRNSS MSM2, Compact PhaseRanges
RTCM1133	NavIC/IRNSS MSM3, Compact Pseudoranges and PhaseRanges
RTCM1134	NavIC/IRNSS MSM4, Full Pseudoranges and PhaseRanges plus CNR
RTCM1135	NavIC/IRNSS MSM5, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR
RTCM1136	NavIC/IRNSS MSM6, Full Pseudoranges and PhaseRanges plus CNR (high resolution)
RTCM1137	NavIC/IRNSS MSM7, Full Pseudoranges, PhaseRanges, PhaseRangeRate and CNR (high resolu-
	tion)
RTCM1230	GLONASS L1&L2 Code-Phase Biases



Index of Commands

```
Α
AddWiFiAccessPoint
   exeAddWiFiAccessPoint, getAddWiFiAccessPoint
     eawa, gawa, 203
AGCMode
   setAGCMode, getAGCMode
     sam, gam, 119
Antennalnfo
   IstAntennaInfo
     lai, 79
AntennaOffset
   setAntennaOffset, getAntennaOffset
     sao, gao, 123
AuthorizationLinkCloudIt
   IstAuthorizationLinkCloudIt
     lal, 276
В
BBSamplingMode
   setBBSamplingMode, getBBSamplingMode
     sbbs, gbbs, 120
BINEXCloudIt
   setBINEXCloudIt, getBINEXCloudIt
     sbci, gbci, 277
BINEXFormatting
   setBINEXFormatting, getBINEXFormatting
     sbfm, gbfm, 222
BINEXFTP
   setBINEXFTP, getBINEXFTP
     sbfp, gbfp, 269
BINEXLoggingParameters
   setBINEXLoggingParameters, getBINEXLoggingParameters
     sblp, gblp, 248
BINEXOnce
   exeBINEXOnce, getBINEXOnce
     ebio, gbio, 224
BINEXOutput
   setBINEXOutput, getBINEXOutput
     sbo, gbo, 225
C
```



CABDLY



setCABDLY, getCABDLY scdy, gcdy, 167 **CGGTTSFTP** setCGGTTSFTP, getCGGTTSFTP scfp, gcfp, 270 CGGTTSLogging setCGGTTSLogging, getCGGTTSLogging scgl, gcgl, 249 CGGTTSPosition setCGGTTSPosition, getCGGTTSPosition scpo, gcpo, 168 CGGTTSTrackParameters setCGGTTSTrackParameters, getCGGTTSTrackParameters scgt, gcgt, 169 ChannelAllocation setChannelAllocation, getChannelAllocation sca, gca, 107 ClockSyncThreshold setClockSyncThreshold, getClockSyncThreshold scst, gcst, 160 CloudItConfig setCloudItConfig, getCloudItConfig scic, gcic, 278 CMRv2Formatting setCMRv2Formatting, getCMRv2Formatting sc2f, gc2f, 243 CMRv2Interval setCMRv2Interval, getCMRv2Interval sc2i, gc2i, 244 CMRv2Message2 setCMRv2Message2, getCMRv2Message2 sc2m, gc2m, 245 CMRv2Output setCMRv2Output, getCMRv2Output sc2o, gc2o, 246 CMRv2Usage setCMRv2Usage, getCMRv2Usage sc2u, gc2u, 247 CN0Mask setCN0Mask, getCN0Mask scm, gcm, 109 CommandHelp IstCommandHelp help, 80 COMSettings setCOMSettings, getCOMSettings scs, gcs, 178 ConfigFile IstConfigFile lcf, 81 CopyConfigFile

exeCopyConfigFile, getCopyConfigFile



eccf, gccf, 82 CosmosConfig setCosmosConfig, getCosmosConfig scoc, gcoc, 293 CrossDomainWebAccess set Cross Domain Web Access, get Cross Domain Web Accessscda, gcda, 179 CurrentUser IstCurrentUser Icu, 102 D DaisyChainMode setDaisyChainMode, getDaisyChainMode sdcm, gdcm, 180 DataInOut setDataInOut, getDataInOut sdio, gdio, 181 DefaultAccessLevel setDefaultAccessLevel, getDefaultAccessLevel sdal, gdal, 103 DiffCorrMaxAge setDiffCorrMaxAge, getDiffCorrMaxAge sdca, gdca, 124 DiffCorrUsage setDiffCorrUsage, getDiffCorrUsage sdcu, gdcu, 125 DisconnectCloudIt exeDisconnectCloudIt, getDisconnectCloudIt edci, gdci, 280 DiskEvent IstDiskEvent lde, 250 DiskFullAction setDiskFullAction, getDiskFullAction sdfa, gdfa, 252 DiskInfo IstDiskInfo ldi, 253 DynamicDNS setDynamicDNS, getDynamicDNS sdds, gdds, 183 E EchoMessage exeEchoMessage, getEchoMessage eecm, gecm, 184 ElevationMask setElevationMask, getElevationMask sem, gem, 126 EthernetMode setEthernetMode, getEthernetMode



```
seth, geth, 83
EventParameters
   setEventParameters, getEventParameters
     sep, gep, 161
exeAuthorizeCloudIt
   exeAuthorizeCloudIt
     erac, 281
F
FileNaming
   setFileNaming, getFileNaming
     sfn, gfn, 254
FTPPushTest
   exeFTPPushTest, getFTPPushTest
     efpt, gfpt, 271
FTPUpgrade
   exeFTPUpgrade, getFTPUpgrade
     efup, gfup, 84
G
GalOSNMAPublicKeys
   IstGalOSNMAPublicKeys
     lopk, 152
   setGalOSNMAPublicKeys, getGalOSNMAPublicKeys
     sopk, gopk, 153
GalOSNMAUsage
   setGalOSNMAUsage, getGalOSNMAUsage
     sou, gou, 154
GeodeticDatum
   set Geodetic Datum, get Geodetic Datum\\
     sgd, ggd, 155
GeoidUndulation
   setGeoidUndulation, getGeoidUndulation
     sgu, ggu, 127
GlobalFileNamingOptions
   setGlobalFileNamingOptions, getGlobalFileNamingOptions
     sfno, gfno, 255
GPIOFunctionality
   setGPIOFunctionality, getGPIOFunctionality
     sgpf, ggpf, 85
Н
HealthMask
   setHealthMask, getHealthMask
     shm, ghm, 128
HttpsSettings
   setHttpsSettings, getHttpsSettings
     shs, ghs, 185
I
INTDLY
   setINTDLY, getINTDLY
     sidy, gidy, 170
```



```
InternalFile
    IstInternalFile
      lif. 86
IonosphereModel
    setIonosphereModel, getIonosphereModel
      sim, gim, 129
IPFiltering
    setIPFiltering, getIPFiltering
      sipf, gipf, 186
IPKeepAlive
    setIPKeepAlive, getIPKeepAlive
      sipk, gipk, 187
IPPortSettings
    setIPPortSettings, getIPPortSettings
      sipp, gipp, 188
IPReceiveSettings
    setIPReceiveSettings, getIPReceiveSettings
      sirs, girs, 189
IPServerSettings
    setIPServerSettings, getIPServerSettings
      siss, giss, 190
IPSettings
    setIPSettings, getIPSettings
      sips, gips, 191
L
L6CLASSource
    setL6CLASSource, getL6CLASSource
      scls, gcls, 131
LBandBeams
   IstLBandBeams
      Ilbb, 286
    setLBandBeams, getLBandBeams
      slbb, glbb, 287
LBandCustomServiceID
    setLBandCustomServiceID, getLBandCustomServiceID
      slcs, glcs, 288
LBandNTRIPDelivery
    setLBandNTRIPDelivery, getLBandNTRIPDelivery
      slnd, glnd, 289
LBandSelectMode
    setLBandSelectMode, getLBandSelectMode
      slsm, glsm, 290
LBAS1RefStations
   IstLBAS1RefStations
      Ilrs, 291
    setLBAS1RefStations, getLBAS1RefStations
      slrs, glrs, 292
LEDMode
    setLEDMode, getLEDMode
      slm, glm, 87
LogIn
```



LogIn login, 104 LogOut LogOut logout, 105 LogSession setLogSession, getLogSession sls, gls, 256 LogSessionSchedule setLogSessionSchedule, getLogSessionSchedule slss, glss, 258 M MagneticVariance setMagneticVariance, getMagneticVariance smv, gmv, 132 ManageDisk exeManageDisk, getManageDisk emd, gmd, 259 ManageWiFiAccessPoint exeManageWiFiAccessPoint, getManageWiFiAccessPoint emwa, gmwa, 204 MarkerParameters setMarkerParameters, getMarkerParameters smp, gmp, 175 Meas3MaxRefInterval setMeas3MaxRefInterval, getMeas3MaxRefInterval smrf, gmrf, 214 MIBDescription IstMIBDescription Imd, 88 MultipathMitigation setMultipathMitigation, getMultipathMitigation smm, gmm, 110 N NetworkRTKConfig setNetworkRTKConfig, getNetworkRTKConfig snrc, gnrc, 133 **NMEACloudIt** setNMEACloudIt, getNMEACloudIt snci, gnci, 282 **NMEAFTP** setNMEAFTP, getNMEAFTP snfp, gnfp, 272 **NMEALogging** setNMEALogging, getNMEALogging snlp, gnlp, 260 **NMEAOnce** exeNMEAOnce, getNMEAOnce enoc, gnoc, 208 **NMEAOutput**



```
setNMEAOutput, getNMEAOutput
     sno, gno, 209
NMEAPrecision
   setNMEAPrecision, getNMEAPrecision
     snp, gnp, 211
NMEATalkerID
   setNMEATalkerID, getNMEATalkerID
     snti, gnti, 212
NMEAVersion
   setNMEAVersion, getNMEAVersion
     snv, gnv, 213
NotchFiltering
   setNotchFiltering, getNotchFiltering
     snf, gnf, 121
NtpClient
   setNtpClient, getNtpClient
     snc, gnc, 162
NTPServer
   setNTPServer, getNTPServer
     sntp, gntp, 163
NtripCasterMountPoints
   setNtripCasterMountPoints, getNtripCasterMountPoints
     snmp, gnmp, 196
NtripCasterMPFormat
   setNtripCasterMPFormat, getNtripCasterMPFormat
     smpf, gmpf, 197
NtripCasterSettings
   setNtripCasterSettings, getNtripCasterSettings
     sncs, gncs, 198
NtripCasterUsers
   setNtripCasterUsers, getNtripCasterUsers
     sncu, gncu, 199
NtripSettings
   setNtripSettings, getNtripSettings
     snts, gnts, 200
NTRIPSourceTable
   IstNTRIPSourceTable
     Inst, 201
NtripTlsSettings
   setNtripTlsSettings, getNtripTlsSettings
     sntt, gntt, 202
0
ObserverComment
   setObserverComment, getObserverComment
     soc, goc, 176
ObserverParameters
   setObserverParameters, getObserverParameters
     sop, gop, 177
P
```

PeriodicEcho



setPeriodicEcho, getPeriodicEcho spe, gpe, 192 PointToPoint setPointToPoint, getPointToPoint sp2p, gp2p, 194 **PortFirewall** setPortFirewall, getPortFirewall spfw, gpfw, 195 PowerMode exePowerMode, getPowerMode epwm, gpwm, 97 PowerThresholds setPowerThresholds, getPowerThresholds spth, gpth, 98 **PPPAutoSeed** setPPPAutoSeed, getPPPAutoSeed spas, gpas, 134 PPPSetSeedGeod exePPPSetSeedGeod, getPPPSetSeedGeod epss, gpss, 135 **PPSINMonitor** setPPSINMonitor, getPPSINMonitor spim, gpim, 171 **PPSINParameters** setPPSINParameters, getPPSINParameters spin, gpin, 172 **PPSParameters** setPPSParameters, getPPSParameters spps, gpps, 164 PreserveLogging exePreserveLogging, getPreserveLogging epl, gpl, 261 PreserveOnEvent setPreserveOnEvent, getPreserveOnEvent spoe, gpoe, 262 **PVTMode** setPVTMode, getPVTMode spm, gpm, 137 R **RAIMLevels** setRAIMLevels, getRAIMLevels srl, grl, 138 ReceiverCapabilities getReceiverCapabilities grc, 89 ReceiverDynamics setReceiverDynamics, getReceiverDynamics srd, grd, 139 ReceiverInterface getReceiverInterface gri, 92



RTCMv2IntervalObs

```
RecordedFile
   IstRecordedFile
     Irf. 263
REFDLY
   setREFDLY, getREFDLY
     srdy, grdy, 173
REFOUTMode
   setREFOUTMode, getREFOUTMode
     srom, grom, 165
RegisteredApplications
   exeRegisteredApplications, getRegisteredApplications
     era, gra, 93
RemoveFile
   exeRemoveFile, getRemoveFile
     erf, grf, 264
ResetNavFilter
   exeResetNavFilter, getResetNavFilter
     ernf, grnf, 140
ResetReceiver
   exeResetReceiver, getResetReceiver
     erst, grst, 94
RINEXCloudIt
   setRINEXCloudIt, getRINEXCloudIt
     srci, grci, 283
RINEXFTP
   setRINEXFTP, getRINEXFTP
     srfp, grfp, 273
RINEXLogging
   setRINEXLogging, getRINEXLogging
     srxl, grxl, 265
RTCMMSMCloudIt
   setRTCMMSMCloudIt, getRTCMMSMCloudIt
     srmi, grmi, 284
RTCMMSMFTP
   setRTCMMSMFTP, getRTCMMSMFTP
     smfp, gmfp, 274
RTCMMSMLogging
   setRTCMMSMLogging, getRTCMMSMLogging
     smsl, gmsl, 267
RTCMv2Compatibility
   setRTCMv2Compatibility, getRTCMv2Compatibility
     sr2c, gr2c, 226
RTCMv2EphemerisHoldoff
   setRTCMv2EphemerisHoldoff, getRTCMv2EphemerisHoldoff
     sr2h, gr2h, 227
RTCMv2Formatting
   setRTCMv2Formatting, getRTCMv2Formatting
     sr2f, gr2f, 228
RTCMv2Interval
   setRTCMv2Interval, getRTCMv2Interval
     sr2i, gr2i, 229
```



setRTCMv2IntervalObs, getRTCMv2IntervalObs sr2b, gr2b, 230 RTCMv2Message16 setRTCMv2Message16, getRTCMv2Message16 sr2m, gr2m, 231 RTCMv2Output setRTCMv2Output, getRTCMv2Output sr2o, gr2o, 232 RTCMv2Usage setRTCMv2Usage, getRTCMv2Usage sr2u, gr2u, 233 RTCMv3CRSTransfo setRTCMv3CRSTransfo, getRTCMv3CRSTransfo sr3t, gr3t, 234 RTCMv3Delay setRTCMv3Delay, getRTCMv3Delay sr3d, gr3d, 235 RTCMv3Formatting setRTCMv3Formatting, getRTCMv3Formatting sr3f, gr3f, 236 RTCMv3Interval setRTCMv3Interval, getRTCMv3Interval sr3i, gr3i, 238 RTCMv3Message1029 setRTCMv3Message1029, getRTCMv3Message1029 sr3m, gr3m, 239 RTCMv3Output setRTCMv3Output, getRTCMv3Output sr3o, gr3o, 240 RTCMv3Usage setRTCMv3Usage, getRTCMv3Usage sr3u, gr3u, 242 S SatelliteTracking setSatelliteTracking, getSatelliteTracking sst, gst, 111 SatelliteUsage setSatelliteUsage, getSatelliteUsage ssu, gsu, 141 **SBASCorrections** setSBASCorrections, getSBASCorrections ssbc, gsbc, 142 SBASService setSBASService, getSBASService sssc, gssc, 144 SBFCloudIt setSBFCloudIt, getSBFCloudIt ssci, gsci, 285 **SBFFTP** setSBFFTP, getSBFFTP ssfp, gsfp, 275



```
SBFGroups
    setSBFGroups, getSBFGroups
      ssgp, gsgp, 215
SBFOnce
    exeSBFOnce, getSBFOnce
      esoc, gsoc, 216
SBFOutput
    setSBFOutput, getSBFOutput
      sso, gso, 219
SignalTracking
    setSignalTracking, getSignalTracking
      snt, gnt, 113
SignalUsage
    setSignalUsage, getSignalUsage
      snu, gnu, 145
SmoothingInterval
    setSmoothingInterval, getSmoothingInterval
      ssi, gsi, 115
StandbyMonitoring
    setStandbyMonitoring, getStandbyMonitoring
      ssm, gsm, 99
StaticPosCartesian
    setStaticPosCartesian, getStaticPosCartesian
      sspc, gspc, 146
StaticPosGeodetic
    setStaticPosGeodetic, getStaticPosGeodetic
      sspg, gspg, 148
Т
TimeLabParameters
    setTimeLabParameters, getTimeLabParameters
      stmp, gtmp, 174
TimingSystem
    setTimingSystem, getTimingSystem
      sts, gts, 166
TrackingLoopParameters
    setTrackingLoopParameters, getTrackingLoopParameters
      stlp, gtlp, 117
TroposphereModel
    set Troposphere Model, get Troposphere Model\\
      stm, gtm, 149
TroposphereParameters
    setTroposphereParameters, getTroposphereParameters
      stp, gtp, 151
U
USBInternetAccess
    set USB Internet Access, get USB Internet Access\\
      suia, guia, 96
UserAccessLevel
    setUserAccessLevel, getUserAccessLevel
      sual, gual, 106
```



UserDatum
setUserDatum, getUserDatum
sud, gud, 157
UserDatumVel
setUserDatumVel, getUserDatumVel
sudv, gudv, 158
UserEllipsoid
setUserEllipsoid, getUserEllipsoid
sue, gue, 159

W

WakeUpInterval
setWakeUpInterval, getWakeUpInterval
swui, gwui, 100
WBIMitigation
setWBIMitigation, getWBIMitigation
swbi, gwbi, 122
WiFiAccessPoint
setWiFiAccessPoint, getWiFiAccessPoint
swfa, gwfa, 205
WiFiAccessPoints
lstWiFiAccessPoints
lwa, 206
WiFiMode
setWiFiMode, getWiFiMode
swfm, gwfm, 207



Index of SBF Blocks

ASCIIIn, 481 BaseStation, 438 BaseVectorCart, 415 BaseVectorGeod, 418 BBSamples, 480 **BDSAlm**, 359 **BDSCNav2**, 357 BDSIon, 360 BDSNav, 355 **BDSRaw**, 325 BDSRawB1C, 326 BDSRawB2a, 327 BDSRawB2b, 328 BDSUtc, 361 ChannelStatus, 445 Commands, 478 Comment, 479 CosmosStatus, 472 DiffCorrIn, 436 DiskStatus, 467 **DOP**, 397 DynDNSStatus, 464 EndOfMeas, 314 EndOfPVT, 422 ExtEvent, 426 ExtEventBaseVectGeod, 433 ExtEventPVTCartesian, 427 ExtEventPVTGeodetic, 430 **GALAlm**, 350 **GALAuthStatus**, 473 GALGstGps, 353 GALIon, 351 GALNav, 347 GALRawCNAV, 322 GALRawFNAV, 320 GALRawINAV, 321

GALSARRLM, 354



GALUtc, 352 GEOAlm, 375 GEOClockEphCovMatrix, 380 **GEOCorrections**, 413 **GEODegrFactors**, 373 **GEOFastCorr**, 369 GEOFastCorrDegr, 371 **GEOIGPMask**, 376 **GEOIntegrity**, 370 **GEOIonoDelay**, 378 **GEOLongTermCorr**, 377 **GEOMT00**, 367 **GEONav**, 372 **GEONetworkTime**, 374 **GEOPRNMask**, 368 GEORawL1, 323 GEORawL5, 324 **GEOServiceLevel**, 379 **GLOAlm**, 345 **GLONav**, 344 GLORawCA, 319 GLOTime, 346 **GPSAlm**, 339 **GPSCNav**, 342 GPSIon, 340 **GPSNav**, 337 GPSRawCA, 315 GPSRawL1C, 318 GPSRawL2C, 316 GPSRawL5, 317 GPSUtc, 341 InputLink, 453 IPStatus, 461 LBandBeams, 444 LBandTrackerStatus, 440 LBAS1DecoderStatus, 441 LBAS1Messages, 443 LogStatus, 468 Meas3CNOHiRes, 310 Meas3Doppler, 311 **Meas3MP**, 313 **Meas3PP**, 312 Meas3Ranges, 309 MeasEpoch, 302 MeasExtra, 307 NavICLNav, 365 NAVICRaw, 336

NTRIPClientStatus, 459 NTRIPServerStatus, 460



OutputLink, 456

P2PPStatus, 471

PosCart, 398

PosCovCartesian, 389

PosCovGeodetic, 391

PosLocal, 402

PosProjected, 404

PowerStatus, 465

PVTCartesian, 381

PVTGeodetic, 385

PVTResiduals, 408

PVTSatCartesian, 406

PVTSupport, 420

PVTSupportA, 421

QualityInd, 466

QZSAlm, 364

QZSNav, 362

QZSRawL1C, 333

QZSRawL1CA, 329

QZSRawL1S, 334

QZSRawL2C, 330

QZSRawL5, 331

QZSRawL5S, 335

QZSRawL6, 332

RAIMStatistics, 412

ReceiverSetup, 474

ReceiverStatus, 448

ReceiverTime, 423

RFStatus, 470

RTCMDatum, 439

RxComponents, 476

RxMessage, 477

SatVisibility, 452

SystemInfo, 482

VelCovCartesian, 393

VelCovGeodetic, 395

WiFiAPStatus, 462

WiFiClientStatus, 463

xPPSOffset, 424